Table of Contents

Natural Language Processing: Python and NLTK Natural Language Processing: Python and NLTK Credits Preface What this learning path covers What you need for this learning path Who this learning path is for Reader feedback Customer support Downloading the example code Errata Piracy Questions <u>1. Module 1</u> 1. Introduction to Natural Language Processing Why learn NLP? Let's start playing with Python! Lists Helping yourself **Regular** expressions Dictionaries Writing functions **Diving into NLTK** Your turn **Summary** 2. Text Wrangling and Cleansing What is text wrangling? Text cleansing Sentence splitter Tokenization Stemming Lemmatization Stop word removal Rare word removal Spell correction Your turn Summary 3. Part of Speech Tagging What is Part of speech tagging Stanford tagger Diving deep into a tagger Sequential tagger N-gram tagger

Regex tagger Brill tagger Machine learning based tagger Named Entity Recognition (NER) NER tagger Your Turn **Summary** 4. Parsing Structure in Text Shallow versus deep parsing The two approaches in parsing Why we need parsing Different types of parsers A recursive descent parser A shift-reduce parser A chart parser A regex parser Dependency parsing Chunking Information extraction Named-entity recognition (NER) **Relation extraction Summary** 5. NLP Applications Building your first NLP application Other NLP applications Machine translation Statistical machine translation Information retrieval **Boolean** retrieval Vector space model The probabilistic model Speech recognition Text classification Information extraction Question answering systems Dialog systems Word sense disambiguation Topic modeling Language detection Optical character recognition Summary 6. Text Classification Machine learning Text classification Sampling Naive Bayes Decision trees

Stochastic gradient descent Logistic regression Support vector machines The Random forest algorithm Text clustering K-means Topic modeling in text Installing gensim References **Summary** 7. Web Crawling Web crawlers Writing your first crawler Data flow in Scrapy The Scrapy shell Items The Sitemap spider The item pipeline External references Summary 8. Using NLTK with Other Python Libraries NumPy ndarray Indexing **Basic operations** Extracting data from an array Complex matrix operations **Reshaping and stacking** Random numbers SciPy Linear algebra eigenvalues and eigenvectors The sparse matrix Optimization pandas Reading data Series data Column transformation Noisy data <u>matplotlib</u> **Subplot** Adding an axis A scatter plot <u>A bar plot</u> <u>3D plots</u> External references **Summary**

9. Social Media Mining in Python Data collection Twitter Data extraction Trending topics Geovisualization Influencers detection Facebook Influencer friends Summary 10. Text Mining at Scale Different ways of using Python on Hadoop Python streaming Hive/Pig UDF Streaming wrappers NLTK on Hadoop A UDF Python streaming Scikit-learn on Hadoop **PySpark Summary** 2. Module 2 1. Tokenizing Text and WordNet Basics Introduction Tokenizing text into sentences Getting ready How to do it... How it works... There's more... Tokenizing sentences in other languages See also Tokenizing sentences into words How to do it... How it works... There's more... Separating contractions PunktWordTokenizer WordPunctTokenizer See also Tokenizing sentences using regular expressions Getting ready How to do it... How it works... There's more... Simple whitespace tokenizer See also Training a sentence tokenizer

Getting ready How to do it... How it works... There's more... See also Filtering stopwords in a tokenized sentence Getting ready How to do it... How it works... There's more... See also Looking up Synsets for a word in WordNet Getting ready How to do it... How it works... There's more... Working with hypernyms Part of speech (POS) See also Looking up lemmas and synonyms in WordNet How to do it... How it works... There's more... All possible synonyms Antonyms See also Calculating WordNet Synset similarity How to do it... How it works... There's more... Comparing verbs Path and Leacock Chordorow (LCH) similarity See also **Discovering word collocations** Getting ready How to do it... How it works... There's more Scoring functions Scoring ngrams See also 2. Replacing and Correcting Words Introduction Stemming words How to do it... How it works... There's more...

The LancasterStemmer class The RegexpStemmer class The SnowballStemmer class See also Lemmatizing words with WordNet Getting ready How to do it... How it works... There's more... Combining stemming with lemmatization See also Replacing words matching regular expressions Getting ready How to do it... How it works... There's more... Replacement before tokenization See also Removing repeating characters Getting ready How to do it... How it works... There's more... See also Spelling correction with Enchant Getting ready How to do it... How it works... There's more... The en GB dictionary Personal word lists See also Replacing synonyms Getting ready How to do it... How it works... There's more... CSV synonym replacement YAML synonym replacement See also Replacing negations with antonyms How to do it... How it works... There's more... See also 3. Creating Custom Corpora Introduction

Setting up a custom corpus Getting ready How to do it... How it works... There's more... Loading a YAML file See also Creating a wordlist corpus Getting ready How to do it... How it works... There's more... Names wordlist corpus English words corpus See also Creating a part-of-speech tagged word corpus Getting ready How to do it... How it works... There's more... Customizing the word tokenizer Customizing the sentence tokenizer Customizing the paragraph block reader Customizing the tag separator Converting tags to a universal tagset See also Creating a chunked phrase corpus Getting ready How to do it... How it works... There's more... Tree leaves Treebank chunk corpus CoNLL2000 corpus See also Creating a categorized text corpus Getting ready How to do it... How it works... There's more... Category file Categorized tagged corpus reader Categorized corpora See also Creating a categorized chunk corpus reader Getting ready How to do it ...

How it works... There's more... Categorized CoNLL chunk corpus reader See also Lazy corpus loading How to do it... How it works... There's more... Creating a custom corpus view How to do it... How it works... There's more... Block reader functions Pickle corpus view Concatenated corpus view See also Creating a MongoDB-backed corpus reader Getting ready How to do it... How it works... There's more... See also Corpus editing with file locking Getting ready How to do it... How it works... 4. Part-of-speech Tagging Introduction Default tagging Getting ready How to do it... How it works... There's more... **Evaluating accuracy Tagging sentences** Untagging a tagged sentence See also Training a unigram part-of-speech tagger How to do it... How it works... There's more... Overriding the context model Minimum frequency cutoff See also Combining taggers with backoff tagging How to do it... How it works...

There's more... Saving and loading a trained tagger with pickle See also Training and combining ngram taggers Getting ready How to do it... How it works... There's more... Ouadgram tagger See also Creating a model of likely word tags How to do it... How it works... There's more... See also Tagging with regular expressions Getting ready How to do it... How it works... There's more See also Affix tagging How to do it... How it works... There's more... Working with min stem length See also Training a Brill tagger How to do it... How it works... There's more... Tracing See also Training the TnT tagger How to do it... How it works... There's more... Controlling the beam search Significance of capitalization See also Using WordNet for tagging Getting ready How to do it... How it works... See also Tagging proper names How to do it...

How it works... See also **Classifier-based** tagging How to do it... How it works... There's more... Detecting features with a custom feature detector Setting a cutoff probability Using a pre-trained classifier See also Training a tagger with NLTK-Trainer How to do it... How it works... There's more... Saving a pickled tagger Training on a custom corpus Training with universal tags Analyzing a tagger against a tagged corpus Analyzing a tagged corpus See also 5. Extracting Chunks Introduction Chunking and chinking with regular expressions Getting ready How to do it ... How it works... There's more... Parsing different chunk types Parsing alternative patterns Chunk rule with context See also Merging and splitting chunks with regular expressions How to do it... How it works... There's more... Specifying rule descriptions See also Expanding and removing chunks with regular expressions How to do it... How it works... There's more... See also Partial parsing with regular expressions How to do it... How it works... There's more... The ChunkScore metrics

Looping and tracing chunk rules See also Training a tagger-based chunker How to do it... How it works... There's more... Using different taggers See also Classification-based chunking How to do it... How it works... There's more... Using a different classifier builder See also Extracting named entities How to do it... How it works... There's more... Binary named entity extraction See also Extracting proper noun chunks How to do it... How it works... There's more... See also Extracting location chunks How to do it... How it works... There's more... See also Training a named entity chunker How to do it... How it works... There's more... See also Training a chunker with NLTK-Trainer How to do it... How it works... There's more... Saving a pickled chunker Training a named entity chunker Training on a custom corpus Training on parse trees Analyzing a chunker against a chunked corpus Analyzing a chunked corpus See also 6. Transforming Chunks and Trees

Introduction Filtering insignificant words from a sentence Getting ready How to do it... How it works... There's more... See also Correcting verb forms Getting ready How to do it... How it works... See also Swapping verb phrases How to do it... How it works... There's more... See also Swapping noun cardinals How to do it... How it works... See also Swapping infinitive phrases How to do it... How it works... There's more... See also Singularizing plural nouns How to do it... How it works... See also Chaining chunk transformations How to do it... How it works... There's more... See also Converting a chunk tree to text How to do it... How it works... There's more... See also Flattening a deep tree Getting ready How to do it... How it works... There's more... The cess esp and cess cat treebank See also

Creating a shallow tree How to do it... How it works... See also Converting tree labels Getting ready How to do it... How it works... See also 7. Text Classification Introduction Bag of words feature extraction How to do it... How it works... There's more... Filtering stopwords Including significant bigrams See also Training a Naive Bayes classifier Getting ready How to do it... How it works... There's more... Classification probability Most informative features Training estimator Manual training See also Training a decision tree classifier How to do it... How it works... There's more... Controlling uncertainty with entropy cutoff Controlling tree depth with depth cutoff Controlling decisions with support cutoff See also Training a maximum entropy classifier Getting ready How to do it... How it works... There's more... Megam algorithm See also Training scikit-learn classifiers Getting ready How to do it... How it works...

There's more... **Comparing Naive Bayes algorithms** Training with logistic regression Training with LinearSVC See also Measuring precision and recall of a classifier How to do it... How it works... There's more... F-measure See also Calculating high information words How to do it... How it works... There's more... The MaxentClassifier class with high information words The DecisionTreeClassifier class with high information words The SklearnClassifier class with high information words See also Combining classifiers with voting Getting ready How to do it... How it works... See also Classifying with multiple binary classifiers Getting ready How to do it... How it works... There's more... See also Training a classifier with NLTK-Trainer How to do it... How it works... There's more... Saving a pickled classifier Using different training instances The most informative features The Maxent and LogisticRegression classifiers **SVMs Combining classifiers** High information words and bigrams Cross-fold validation Analyzing a classifier See also 8. Distributed Processing and Handling Large Datasets Introduction Distributed tagging with execnet

Getting ready How to do it... How it works... There's more... Creating multiple channels Local versus remote gateways See also Distributed chunking with execnet Getting ready How to do it... How it works... There's more... Python subprocesses See also Parallel list processing with execnet How to do it... How it works... There's more... See also Storing a frequency distribution in Redis Getting ready How to do it... How it works... There's more... See also Storing a conditional frequency distribution in Redis Getting ready How to do it... How it works... There's more... See also Storing an ordered dictionary in Redis Getting ready How to do it... How it works... There's more... See also Distributed word scoring with Redis and execnet Getting ready How to do it... How it works... There's more... See also 9. Parsing Specific Data Types Introduction Parsing dates and times with dateutil Getting ready

How to do it... How it works... There's more... See also Timezone lookup and conversion Getting ready How to do it... How it works... There's more... Local timezone Custom offsets See also Extracting URLs from HTML with lxml Getting ready How to do it... How it works... There's more... Extracting links directly Parsing HTML from URLs or files Extracting links with XPaths See also Cleaning and stripping HTML Getting ready How to do it... How it works... There's more... See also Converting HTML entities with BeautifulSoup Getting ready How to do it... How it works... There's more... Extracting URLs with BeautifulSoup See also Detecting and converting character encodings Getting ready How to do it... How it works... There's more... Converting to ASCII UnicodeDammit conversion See also A. Penn Treebank Part-of-speech Tags 3. Module 3 1. Working with Strings Tokenization Tokenization of text into sentences

Tokenization of text in other languages Tokenization of sentences into words Tokenization using TreebankWordTokenizer Tokenization using regular expressions Normalization Eliminating punctuation Conversion into lowercase and uppercase Dealing with stop words Calculate stopwords in English Substituting and correcting tokens Replacing words using regular expressions Example of the replacement of a text with another text Performing substitution before tokenization Dealing with repeating characters Example of deleting repeating characters Replacing a word with its synonym Example of substituting word a with its synonym Applying Zipf's law to text Similarity measures Applying similarity measures using Ethe edit distance algorithm Applying similarity measures using Jaccard's Coefficient Applying similarity measures using the Smith Waterman distance Other string similarity metrics Summary 2. Statistical Language Modeling Understanding word frequency Develop MLE for a given text Hidden Markov Model estimation Applying smoothing on the MLE model Add-one smoothing Good Turing Kneser Ney estimation Witten Bell estimation Develop a back-off mechanism for MLE Applying interpolation on data to get mix and match Evaluate a language model through perplexity Applying metropolis hastings in modeling languages Applying Gibbs sampling in language processing **Summary** 3. Morphology – Getting Our Feet Wet Introducing morphology Understanding stemmer Understanding lemmatization Developing a stemmer for non-English language Morphological analyzer Morphological generator Search engine

Summary

4. Parts-of-Speech Tagging – Identifying Words Introducing parts-of-speech tagging Default tagging Creating POS-tagged corpora Selecting a machine learning algorithm Statistical modeling involving the n-gram approach Developing a chunker using pos-tagged corpora Summary 5. Parsing – Analyzing Training Data Introducing parsing Treebank construction Extracting Context Free Grammar (CFG) rules from Treebank Creating a probabilistic Context Free Grammar from CFG CYK chart parsing algorithm Earley chart parsing algorithm **Summary** 6. Semantic Analysis – Meaning Matters Introducing semantic analysis Introducing NER A NER system using Hidden Markov Model Training NER using Machine Learning Toolkits NER using POS tagging Generation of the synset id from Wordnet Disambiguating senses using Wordnet Summarv 7. Sentiment Analysis – I Am Happy Introducing sentiment analysis Sentiment analysis using NER Sentiment analysis using machine learning Evaluation of the NER system **Summary** 8. Information Retrieval - Accessing Information Introducing information retrieval Stop word removal Information retrieval using a vector space model Vector space scoring and query operator interaction Developing an IR system using latent semantic indexing Text summarization Question-answering system **Summary** 9. Discourse Analysis – Knowing Is Believing Introducing discourse analysis Discourse analysis using Centering Theory Anaphora resolution **Summary** 10. Evaluation of NLP Systems – Analyzing Performance

The need for evaluation of NLP systemsEvaluation of NLP tools (POS taggers, stemmers, and morphological analyzers)Parser evaluation using gold dataEvaluation of IR systemMetrics for error identificationMetrics based on lexical matchingMetrics based on syntactic matchingMetrics using shallow semantic matchingSummaryB. BibliographyIndex

Learn to build expert NLP and machine learning projects using NLTK and other Python libraries

A course in three modules



BIRMINGHAM - MUMBAI

Copyright © 2016 Packt Publishing

All rights reserved. No part of this course may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, without the prior written permission of the publisher, except in the case of brief quotations embedded in critical articles or reviews.

Every effort has been made in the preparation of this course to ensure the accuracy of the information presented. However, the information contained in this course is sold without warranty, either express or implied. Neither the authors, nor Packt Publishing, and its dealers and distributors will be held liable for any damages caused or alleged to be caused directly or indirectly by this course.

Packt Publishing has endeavored to provide trademark information about all of the companies and products mentioned in this course by the appropriate use of capitals. However, Packt Publishing cannot guarantee the accuracy of this information.

Published on: November 2016

Published by Packt Publishing Ltd.

Livery Place

35 Livery Street

Birmingham B3 2PB, UK.

ISBN 978-1-78728-510-1

www.packtpub.com

Credits

Authors

Nitin Hardeniya

Jacob Perkins

Deepti Chopra

Nisheeth Joshi

Iti Mathur

Reviewers

Afroz Hussain

Sujit Pal

Kumar Raj

Patrick Chan

Mohit Goenka

Lihang Li

Maurice HT Ling

Jing (Dave) Tian

Arturo Argueta

Content Development Editor

Aishwarya Pandere

Production Coordinator

Arvindkumar Gupta

Preface

NLTK is one of the most popular and widely used library in the natural language processing (NLP) community. The beauty of NLTK lies in its simplicity, where most of the complex NLP tasks can be implemented using a few lines of code. Start off by learning how to tokenize text into component words. Explore and make use of the WordNet language dictionary. Learn how and when to stem or lemmatize words. Discover various ways to replace words and perform spelling correction. Create your own custom text corpora and corpus readers, including a MongoDB backed corpus. Use part-of-speech taggers to annotate words with their parts of speech. Create and transform chunked phrase trees using partial parsing. Dig into feature extraction for text classification and sentiment analysis. Learn how to do parallel and distributed text processing, and to store word distributions in Redis.

This learning path will teach you all that and more, in a hands-on learn-by-doing manner. Become an expert in using NLTK for Natural Language Processing with this useful companion.

What this learning path covers

<u>Module 1</u>, *NLTK Essentials*, talks about all the preprocessing steps required in any text mining/NLP task. In this module, we discuss tokenization, stemming, stop word removal, and other text cleansing processes in detail and how easy it is to implement these in NLTK.

<u>Module 2</u>, *Python 3 Text Processing with NLTK 3 Cookbook*, explains how to use corpus readers and create custom corpora. It also covers how to use some of the corpora that come with NLTK. It covers the chunking process, also known as partial parsing, which can identify phrases and named entities in a sentence. It also explains how to train your own custom chunker and create specific named entity recognizers.

<u>Module 3</u>, *Mastering Natural Language Processing with Python*, covers how to calculate word frequencies and perform various language modeling techniques. It also talks about the concept and application of Shallow Semantic Analysis (that is, NER) and WSD using Wordnet.

It will help you understand and apply the concepts of Information Retrieval and text summarization.

What you need for this learning path

Module 1:

We need the following software for this module:

Chapter number	Software required (with version)	Free/ Proprietary	Download links to the software	Hardware specifications	OS required
1-5	Python/Anaconda NLTK	Free	https://www.python.org/ http://continuum.io/downloads http://www.nltk.org/	Common Unix Printing System	any
6	scikit-learn and gensim	Free	http://scikit-learn.org/stable/ https://radimrehurek.com/ gensim/	Common Unix Printing System	any
7	Scrapy	Free	http://scrapy.org/	Common Unix Printing System	any
8	NumPy, SciPy, pandas, and matplotlib	Free	http://www.numpy.org/ http://www.scipy.org/ http://pandas.pydata.org/ http://matplotlib.org/	Common Unix Printing System	any
9	Twitter Python APIs and Facebook python APIs	Free	https://dev.twitter.com/ overview/api/twitter-libraries https://developers.facebook.com	Common Unix Printing System	any

Module 2:

You will need Python 3 and the listed Python packages. For this learning path, the author used Python 3.3.5. To install the packages, you can use pip (<u>https://pypi.python.org/pypi/pip/</u>). The following is the

list of the packages in requirements format with the version number used while writing this learning path:

- NLTK>=3.0a4
- pyenchant>=1.6.5
- lockfile>=0.9.1
- numpy>=1.8.0
- scipy>=0.13.0
- scikit-learn>=0.14.1
- execnet>=1.1
- pymongo>=2.6.3
- redis>=2.8.0
- lxml>=3.2.3
- beautifulsoup4>=4.3.2
- python-dateutil>=2.0
- charade>=1.0.3

You will also need NLTK-Trainer, which is available at <u>https://github.com/japerk/nltk-trainer</u>.

Beyond Python, there are a couple recipes that use MongoDB and Redis, both NoSQL databases. These can be downloaded at <u>http://www.mongodb.org/</u> and <u>http://redis.io/</u>, respectively.

Module 3:

For all the chapters, Python 2.7 or 3.2+ is used. NLTK 3.0 must be installed either on 32-bit machine or 64-bit machine. Operating System required is Windows/Mac/Unix.

Who this learning path is for

If you are an NLP or machine learning enthusiast and an intermediate Python programmer who wants to quickly master NLTK for natural language processing, then this Learning Path will do you a lot of good. Students of linguistics and semantic/sentiment analysis professionals will find it invaluable.

Reader feedback

Feedback from our readers is always welcome. Let us know what you think about this course—what you liked or disliked. Reader feedback is important for us as it helps us develop titles that you will really get the most out of.

To send us general feedback, simply e-mail < feedback@packtpub.com>, and mention the course's title in the subject of your message.

If there is a topic that you have expertise in and you are interested in either writing or contributing to a course, see our author guide at <u>www.packtpub.com/authors</u>.

Customer support

Now that you are the proud owner of a Packt course, we have a number of things to help you to get the most from your purchase.

Downloading the example code

You can download the example code files for this course from your account at <u>http://www.packtpub.com</u>. If you purchased this course elsewhere, you can visit <u>http://www.packtpub.com/support</u> and register to have the files e-mailed directly to you.

You can download the code files by following these steps:

- 1. Log in or register to our website using your e-mail address and password.
- 2. Hover the mouse pointer on the SUPPORT tab at the top.
- 3. Click on Code Downloads & Errata.
- 4. Enter the name of the course in the **Search** box.
- 5. Select the course for which you're looking to download the code files.
- 6. Choose from the drop-down menu where you purchased this course from.
- 7. Click on Code Download.

You can also download the code files by clicking on the **Code Files** button on the course's webpage at the Packt Publishing website. This page can be accessed by entering the course's name in the **Search** box. Please note that you need to be logged in to your Packt account.

Once the file is downloaded, please make sure that you unzip or extract the folder using the latest version of:

- WinRAR / 7-Zip for Windows
- Zipeg / iZip / UnRarX for Mac
- 7-Zip / PeaZip for Linux

The code bundle for the course is also hosted on GitHub at <u>https://github.com/PacktPublishing/Natural-Language-Processing-Python-and-NLTK</u>. We also have other code bundles from our rich catalog of books, videos and courses available at <u>https://github.com/PacktPublishing/</u>. Check them out!

Errata

Although we have taken every care to ensure the accuracy of our content, mistakes do happen. If you find a mistake in one of our books—maybe a mistake in the text or the code—we would be grateful if you could report this to us. By doing so, you can save other readers from frustration and help us improve subsequent versions of this course. If you find any errata, please report them by visiting http://www.packtpub.com/submit-errata, selecting your course, clicking on the Errata Submission Form link, and entering the details of your errata. Once your errata are verified, your submission will be accepted and the errata will be uploaded to our website or added to any list of existing errata under the Errata section of that title.

To view the previously submitted errata, go to <u>https://www.packtpub.com/books/content/support</u> and enter the name of the book in the search field. The required information will appear under the **Errata** section.

Piracy

Piracy of copyrighted material on the Internet is an ongoing problem across all media. At Packt, we take the protection of our copyright and licenses very seriously. If you come across any illegal copies of our works in any form on the Internet, please provide us with the location address or website name immediately so that we can pursue a remedy.

Please contact us at <<u>copyright@packtpub.com</u>> with a link to the suspected pirated material.

We appreciate your help in protecting our authors and our ability to bring you valuable content.

Questions

If you have a problem with any aspect of this course, you can contact us at <<u>questions@packtpub.com</u>>, and we will do our best to address the problem.

Part 1. Module 1

NLTK Essentials

Build cool NLP and machine learning applications using NLTK and other Python libraries

Chapter 1. Introduction to Natural Language Processing

I will start with the introduction to **Natural Language Processing** (**NLP**). Language is a central part of our day to day life, and it's so interesting to work on any problem related to languages. I hope this book will give you a flavor of NLP, will motivate you to learn some amazing concepts of NLP, and will inspire you to work on some of the challenging NLP applications.

In my own language, the study of language processing is called NLP. People who are deeply involved in the study of language are linguists, while the term 'computational linguist' applies to the study of processing languages with the application of computation. Essentially, a computational linguist will be a computer scientist who has enough understanding of languages, and can apply his computational skills to model different aspects of the language. While computational linguists address the theoretical aspect of language, NLP is nothing but the application of computational linguistics.

NLP is more about the application of computers on different language nuances, and building real-world applications using NLP techniques. In a practical context, NLP is analogous to teaching a language to a child. Some of the most common tasks like understanding words, sentences, and forming grammatically and structurally correct sentences, are very natural to humans. In NLP, some of these tasks translate to tokenization, chunking, part of speech tagging, parsing, machine translation, speech recognition, and most of them are still the toughest challenges for computers. I will be talking more on the practical side of NLP, assuming that we all have some background in NLP. The expectation for the reader is to have minimal understanding of any programming language and an interest in NLP and Language.

By end of the chapter we want readers

- A brief introduction to NLP and related concepts.
- Install Python, NLTK and other libraries.
- Write some very basic Python and NLTK code snippets.

If you have never heard the term NLP, then please take some time to read any of the books mentioned here—just for an initial few chapters. A quick reading of at least the Wikipedia page relating to NLP is a must:

- Speech and Language Processing by Daniel Jurafsky and James H. Martin
- Statistical Natural Language Processing by Christopher D. Manning and Hinrich Schütze

Why learn NLP?

I start my discussion with the Gartner's new hype cycle and you can clearly see NLP on top of the cycle. Currently, NLP is one of the rarest skill sets that is required in the industry. After the advent of big data, the major challenge is that we need more people who are good with not just structured, but also with semi or unstructured data. We are generating **petabytes** of Weblogs, tweets, Facebook feeds, chats, emails, and reviews. Companies are collecting all these different kind of data for better customer targeting and meaningful insights. To process all these unstructured data source we need people who understand NLP. We are in the age of information; we can't even imagine our life without Google. We use Siri for the most of basic stuff. We use spam filters for filtering spam emails. We need spell checker on our Word document. There are many examples of real world NLP applications around us.



Image is taken from http://www.gartner.com/newsroom/id/2819918

Let me also give you some examples of the amazing NLP applications that you can use, but are not aware that they are built on NLP:

- Spell correction (MS Word/ any other editor)
- Search engines (Google, Bing, Yahoo, wolframalpha)
- Speech engines (Siri, Google Voice)
- Spam classifiers (All e-mail services)
- News feeds (Google, Yahoo!, and so on)
- Machine translation (Google Translate, and so on)
- IBM Watson

Building these applications requires a very specific skill set with a great understanding of language and tools to process the language efficiently. So it's not just hype that makes NLP one of the most niche areas, but it's the kind of application that can be created using NLP that makes it one of the most unique skills to have.

To achieve some of the above applications and other basic NLP preprocessing, there are many open source tools available. Some of them are developed by organizations to build their own NLP applications, while some of them are open-sourced. Here is a small list of available NLP tools:

• GATE

- Mallet
- Open NLP
- UIMA
- Stanford toolkit
- Genism
- Natural Language Tool Kit (NLTK)

Most of the tools are written in Java and have similar functionalities. Some of them are robust and have a different variety of NLP tools available. However, when it comes to the ease of use and explanation of the concepts, NLTK scores really high. NLTK is also a very good learning kit because the learning curve of Python (on which NLTK is written) is very fast. NLTK has incorporated most of the NLP tasks, it's very elegant and easy to work with. For all these reasons, NLTK has become one of the most popular libraries in the NLP community:

I am assuming all you guys know Python. If not, I urge you to learn Python. There are many basic tutorials on Python available online. There are lots of books also available that give you a quick overview of the language. We will also look into some of the features of Python, while going through the different topics. But for now, even if you only know the basics of Python, such as lists, strings, regular expressions, and basic I/O, you should be good to go.

Note

Python can be installed from the following website:

https://www.python.org/downloads/

http://continuum.io/downloads

https://store.enthought.com/downloads/

I would recommend using Anaconda or Canopy Python distributions. The reason being that these distributions come with bundled libraries, such as scipy, numpy, scikit, and so on, which are used for data analysis and other applications related to NLP and related fields. Even NLTK is part of this distribution.

Note

Please follow the instructions and install NLTK and NLTK data:

http://www.nltk.org/install.html

Let's test everything.

Open the terminal on your respective operating systems. Then run:

\$ python

This should open the Python interpreter:

```
Python 2.6.6 (r266:84292, Oct 15 2013, 07:32:41)
[GCC 4.4.7 20120313 (Red Hat 4.4.7-4)] on linux2
Type "help", "copyright", "credits" or "license" for more
information.
>>>
```

I hope you got a similar looking output here. There is a chance that you will have received a different looking output, but ideally you will get the latest version of Python (I recommend that to be 2.7), the compiler GCC, and the operating system details. I know the latest version of Python will be in 3.0+ range, but as with any other open source systems, we should tries to hold back to a more stable version as opposed to jumping on to the latest version. If you have moved to Python 3.0+, please have a look at the link below to gain an understanding about what new features have been added:

https://docs.python.org/3/whatsnew/3.4.html.

UNIX based systems will have Python as a default program. Windows users can set the path to get Python working. Let's check whether we have installed NLTK correctly:

```
>>>import nltk
>>>print "Python and NLTK installed successfully"
Python and NLTK installed successfully
```

Hey, we are good to go!
Let's start playing with Python!

We'll not be diving too deep into Python; however, we'll give you a quick tour of Python essentials. Still, I think for the benefit of the audience, we should have a quick five minute tour. We'll talk about the basics of data structures, some frequently used functions, and the general construct of Python in the next few sections.

Note

I highly recommend the two hour Google Python class. <u>https://developers.google.com/edu/python</u> should be good enough to start. Please go through the Python website <u>https://www.python.org/</u> for more tutorials and other resources.

Lists

Lists are one of the most commonly used data structures in Python. They are pretty much comparable to arrays in other programming languages. Let's start with some of the most important functions that a Python list provide.

Try the following in the Python console:

```
>>> lst=[1,2,3,4]
>>> # mostly like arrays in typical languages
>>>print lst
[1, 2, 3, 4]
```

Python lists can be accessed using much more flexible indexing. Here are some examples:

>>>print 'First element' +1st[0]

You will get an error message like this:

TypeError: cannot concatenate 'str' and 'int' objects

The reason being that Python is an interpreted language, and checks for the type of the variables at the time it evaluates the expression. We need not initialize and declare the type of variable at the time of declaration. Our list has integer object and cannot be concatenated as a print function. It will only accept a string object. For this reason, we need to convert list elements to string. The process is also known as type casting.

```
>>>print 'First element :' +str(lst[0])
>>>print 'last element :' +str(lst[-1])
>>>print 'first three elements :' +str(lst[0:2])
>>>print 'last three elements :'+str(lst[-3:])
First element :1
last element :4
```

```
first three elements : [1, 2,3] last three elements : [2, 3, 4]
```

Helping yourself

The best way to learn more about different data types and functions is to use help functions like help() and dir(lst).

The dir (python object) command is used to list all the given attributes of the given Python object. Like if you pass a list object, it will list all the cool things you can do with lists:

```
>>>dir(lst)
```

```
>>>' , '.join(dir(lst))
'__add__ , __class__ , __contains__ , __delattr__ , __delitem__ ,
__delslice__ , __doc__ , __eq__ , __format__ , __ge__ ,
__getattribute__ , __getitem__ , __getslice__ , __gt__ , __hash__ ,
__iadd_ , __imul__ , __init__ , __iter__ , __le__ , __len__ ,
__lt__ , __mul__ , __ne__ , __new_ , __reduce__ , __reduce_ex__ ,
__repr__ , __reversed_ , __rmul__ , __setattr__ , __setitem__ ,
__setslice__ , __sizeof__ , __str__ , __subclasshook__ , append ,
count , extend , index , insert , pop , remove , reverse , sort'
```

With the help (python object) command, we can get detailed documentation for the given Python object, and also give a few examples of how to use the Python object:

```
>>>help(lst.index)
Help on built-in function index:
index(...)
    L.index(value, [start, [stop]]) -> integer -- return first index
of value.
This function raises a ValueError if the value is not present.
```

So help and dir can be used on any Python data type, and are a very nice way to learn about the function and other details of that object. It also provides you with some basic examples to work with, which I found useful in most cases.

Strings in Python are very similar to other languages, but the manipulation of strings is one of the main features of Python. It's immensely easy to work with strings in Python. Even something very simple, like splitting a string, takes effort in Java / C, while you will see how easy it is in Python.

Using the help function that we used previously, you can get help for any Python object and any function. Let's have some more examples with the other most commonly used data type strings:

• **Split**: This is a method to split the string based on some delimiters. If no argument is provided it assumes whitespace as delimiter.

```
>>> mystring="Monty Python ! And the holy Grail ! \n"
>>> print mystring.split()
['Monty', 'Python', '!', 'and', 'the', 'holy', 'Grail', '!']
```

• Strip: This is a method that can remove trailing whitespace, like '\n', '\n\r' from the string:

>>> print mystring.strip()
>>>Monty Python ! and the holy Grail !

If you notice the '\n' character is stripped off. There are also methods like rstrip() and lstrip() to strip trailing whitespaces to the right and left of the string.

• Upper/Lower: We can change the case of the string using these methods:

>>> print (mystring.upper()
>>>MONTY PYTHON !AND THE HOLY GRAIL !

• **Replace**: This will help you substitute a substring from the string:

```
>>> print mystring.replace('!','''')
>>> Monty Python and the holy Grail
```

There are tons of string functions. I have just talked about some of the most frequently used.

Note

Please look the following link for more functions and examples:

https://docs.python.org/2/library/string.html.

Regular expressions

One other important skill for an NLP enthusiast is working with regular expression. Regular expression is effectively pattern matching on strings. We heavily use pattern extrication to get meaningful information from large amounts of messy text data. The following are all the regular expressions you need. I haven't used any regular expressions beyond these in my entire life:

- (a period): This expression matches any single character except newline \n.
- \w: This expression will match a character or a digit equivalent to [a-z A-Z 0-9]
- \W (*upper case W*) matches any non-word character.
- \s: This expression (*lowercase s*) matches a single whitespace character space, newline, return, tab, form [\n\r\t\f].
- \S: This expression matches any non-whitespace character.
- \t: This expression performs a tab operation.
- \n: This expression is used for a newline character.
- \r: This expression is used for a return character.
- \d: Decimal digit [0-9].
- ^: This expression is used at the start of the string.
- \$: This expression is used at the end of the string.

• \: This expression is used to nullify the specialness of the special character. For example, you want to match the \$ symbol, then add \ in front of it.

Let's search for something in the running example, where mystring is the same string object, and we will try to look for some patterns in that. A substring search is one of the common use-cases of the re module. Let's implement this:

```
>>># We have to import re module to use regular expression
>>>import re
>>>if re.search('Python',mystring):
>>> print "We found python "
>>>else:
>>> print "NO "
```

Once this is executed, we get the message as follows:

We found python

We can do more pattern finding using regular expressions. One of the common functions that is used in finding all the patterns in a string is findall. It will look for the given patterns in the string, and will give you a list of all the matched objects:

```
>>>import re
>>>print re.findall('!',mystring)
['!', '!']
```

As we can see there were two instances of the "!" in the mystring and findall return both object as a list.

Dictionaries

The other most commonly used data structure is dictionaries, also known as **associative arrays/memories** in other programming languages. Dictionaries are data structures that are indexed by keys, which can be any immutable type; such as strings and numbers can always be keys.

Dictionaries are handy data structure that used widely across programming languages to implement many algorithms. Python dictionaries are one of the most elegant implementations of hash tables in any programming language. It's so easy to work around dictionary, and the great thing is that with few nuggets of code you can build a very complex data structure, while the same task can take so much time and coding effort in other languages. This gives the programmer more time to focus on algorithms rather than the data structure itself.

I am using one of the very common use cases of dictionaries to get the frequency distribution of words in a given text. With just few lines of the following code, you can get the frequency of words. Just try the same task in any other language and you will understand how amazing Python is:

```
>>># declare a dictionary
>>>word_freq={}
>>> for tok in string.split():
>>> if tok in word_freq:
>>> word_freq [tok]+=1
>>> else:
>>> word_freq [tok]=1
>>>print word_freq
{'!': 2, 'and': 1, 'holy': 1, 'Python': 1, 'Grail': 1, 'the': 1,
'Monty': 1}
```

Writing functions

As any other programming langauge Python also has its way of writing functions. Function in Python start with keyword def followed by the function name and parentheses (). Similar to any other programming language any arguments and the type of the argument should be placed within these parentheses. The actual code starts with (:) colon symbol. The initial lines of the code are typically doc string (comments), then we have code body and function ends with a return statement. For example in the given example the function wordfreq start with def keyword, there is no argument to this function and the function ends with a return statement.

```
>>>import sys
>>>def wordfreq (mystring):
           1 1 1
>>>
>>>
           Function to generated the frequency distribution of the
given text
           . . .
>>>
           print mystring
>>>
           word freq={}sep
>>>
           for tok in mystring.split():
>>>
                   if tok in word freq:
>>>
>>>
                            word freq [tok]+=1
>>>
                   else:
                            word freq [tok]=1
>>>
>>>
           print word freq
>>>def main():
>>>
           str="This is my fist python program"
>>>
           wordfreq(str)
>>>if name == ' main ':
>>>
           main()
```

This was the same code that we wrote in the previous section the idea of writing in a form of function is to make the code re-usable and readable. The interpreter style of writing Python is also very common but for writing big programes it will be a good practice to use function/classes and one of the programming paradigm. We also wanted the user to write and run first Python program. You need to follow these steps to achive this.

- 1. Open an empty python file mywordfreq.py in your prefered text editor.
- 2. Write/Copy the code above in the code snippet to the file.
- 3. Open the command prompt in your Operating system.
- 4. Run following command prompt:

```
$ python mywordfreq,py "This is my fist python program !!"
```

5. Output should be:

```
{'This': 1, 'is': 1, 'python': 1, 'fist': 1, 'program': 1,
'my': 1}
```

Now you have a very basic understanding about some common data-structures that python provides. You can write a full Python program and able to run that. I think this is good enough I think with this much of an introduction to Python you can manage for the initial chapters.

Note

Please have a look at some Python tutorials on the following website to learn more commands on Python:

https://wiki.python.org/moin/BeginnersGuide

Diving into NLTK

Instead of going further into the theoretical aspects of natural language processing, let's start with a quick dive into NLTK. I am going to start with some basic example use cases of NLTK. There is a good chance that you have already done something similar. First, I will give a typical Python programmer approach, and then move on to NLTK for a much more efficient, robust, and clean solution.

We will start analyzing with some example text content. For the current example, I have taken the content from Python's home page.

```
>>>import urllib2
>>># urllib2 is use to download the html content of the web link
>>>response = urllib2.urlopen('http://python.org/')
>>># You can read the entire content of a file using read() method
>>>html = response.read()
>>>print len(html)
47020
```

We don't have any clue about the kind of topics that are discussed in this URL, so let's start with an **exploratory data analysis (EDA)**. Typically in a text domain, EDA can have many meanings, but will go with a simple case of what kinds of terms dominate the document. What are the topics? How frequent they are? The process will involve some level of preprocessing steps. We will try to do this first in a pure Python way, and then we will do it using NLTK.

Let's start with cleaning the html tags. One ways to do this is to select just the tokens, including numbers and character. Anybody who has worked with regular expression should be able to convert html string into list of tokens:

```
>>># Regular expression based split the string
>>>tokens = [tok for tok in html.split()]
>>>print "Total no of tokens :"+ str(len(tokens))
>>># First 100 tokens
>>>print tokens[0:100]
Total no of tokens :2860
['<!doctype', 'html>', '<!--[if', 'lt', 'IE', '7]>', '<html',
'class="no-js', 'ie6', 'lt-ie7', 'lt-ie8', 'lt-ie9">',
'class="no-js', 'ie6', 'lt-ie7', 'lt-ie8', 'lt-ie9">',
'<![endif]-->', '<!--[if', 'IE', '7]>', '<html', 'class="no-js',
'ie7', 'lt-ie8', 'lt-ie9">', '<![endif]-->', ''type="text/css"',
'media="not', 'print,', 'braille,' ...]
```

As you can see, there is an excess of html tags and other unwanted characters when we use the preceding method. A cleaner version of the same task will look something like this:

```
>>>import re
>>># using the split function
>>>#https://docs.python.org/2/library/re.html
```

```
>>>tokens = re.split('\W+',html)
>>>print len(tokens)
>>>print tokens[0:100]
5787
['', 'doctype', 'html', 'if', 'lt', 'IE', '7', 'html', 'class',
'no', 'js', 'ie6', 'lt', 'ie7', 'lt', 'ie8', 'lt', 'ie9', 'endif',
'if', 'IE', '7', 'html', 'class', 'no', 'js', 'ie7', 'lt', 'ie8',
'lt', 'ie9', 'endif', 'if', 'IE', '8', 'msapplication', 'tooltip',
'content', 'The', 'official', 'home', 'of', 'the', 'Python',
'Programming', 'Language', 'meta', 'name', 'apple' ...]
```

This looks much cleaner now. But still you can do more; I leave it to you to try to remove as much noise as you can. You can clean some HTML tags that are still popping up, You probably also want to look for word length as a criteria and remove words that have a length one—it will remove elements like 7, 8, and so on, which are just noise in this case. Now instead writing some of these preprocessing steps from scratch let's move to NLTK for the same task. There is a function called clean_html() that can do all the cleaning that we were looking for:

```
>>>import nltk
>>># http://www.nltk.org/api/nltk.html#nltk.util.clean_html
>>>clean = nltk.clean_html(html)
>>># clean will have entire string removing all the html noise
>>>tokens = [tok for tok in clean.split()]
>>>print tokens[:100]
['Welcome', 'to', 'Python.org', 'Skip', 'to', 'content', '▼',
'Close', 'Python', 'PSF', 'Docs', 'PyPI', 'Jobs', 'Community',
'▲', 'The', 'Python', 'Network', '≡', 'Menu', 'Arts',
'Business' ...]
```

Cool, right? This definitely is much cleaner and easier to do.

Let's try to get the frequency distribution of these terms. First, let's do it the Pure Python way, then I will tell you the NLTK recipe.

```
>>>import operator
>>>freq dis={}
>>>for tok in tokens:
>>> if tok in freq dis:
>>>
           freq dis[tok]+=1
>>>
    else:
>>>
           freq dis[tok]=1
>>># We want to sort this dictionary on values ( freq in this case )
>>>sorted freq dist= sorted(freq dis.items(),
key=operator.itemgetter(1), reverse=True)
>>> print sorted freq dist[:25]
[('Python', 55), ('>>>', 23), ('and', 21), ('to', 18), (',', 18),
('the', 14), ('of', 13), ('for', 12), ('a', 11), ('Events', 11),
```

```
('News', 11), ('is', 10), ('2014-', 10), ('More', 9), ('#', 9),
('3', 9), ('=', 8), ('in', 8), ('with', 8), ('Community', 7),
('The', 7), ('Docs', 6), ('Software', 6), (':', 6), ('3:', 5),
('that', 5), ('sum', 5)]
```

Naturally, as this is Python's home page, Python and the (>>>) interpreter symbol are the most common terms, also giving a sense of the website.

A better and more efficient approach is to use NLTK's FreqDist() function. For this, we will take a look at the same code we developed before:

```
>>>import nltk
>>>Freq dist nltk=nltk.FreqDist(tokens)
>>>print Freq dist nltk
>>>for k,v in Freq dist nltk.items():
       print str(k)+':'+str(v)
>>>
<FreqDist: 'Python': 55, '>>>': 23, 'and': 21, ',': 18, 'to': 18,
'the': 14, 'of': 13, 'for': 12, 'Events': 11, 'News': 11, ...>
Python:55
>>>:23
and:21
,:18
to:18
the:14
of:13
for:12
Events:11
News:11
```

Tip

Downloading the example code

You can download the example code files from your account at <u>http://www.packtpub.com</u> for all the Packt Publishing books you have purchased. If you purchased this book elsewhere, you can visit <u>http://www.packtpub.com/support</u> and register to have the files e-mailed directly to you.

Let's now do some more funky things. Let's plot this:

```
>>>Freq_dist_nltk.plot(50, cumulative=False)
>>># below is the plot for the frequency distributions
```



We can see that the cumulative frequency is growing, and at some point the curve is going into long tail. Still, there is some noise, there are words like the, of, for, and =. These are useless words, and there is a terminology for them. These words are stop words; words like the, a, an, and so on. Article pronouns are generally present in most of the documents, hence they are not discriminative enough to be informative. In most of the NLP and information retrieval tasks, people generally remove stop words. Let's go back again to our running example:

```
>>>stopwords=[word.strip().lower() for word in open("PATH/
english.stop.txt")]
>>>clean_tokens=[tok for tok in tokens if len(tok.lower())>1 and
(tok.lower() not in stopwords)]
>>>Freq_dist_nltk=nltk.FreqDist(clean_tokens)
>>>Freq_dist_nltk.plot(50, cumulative=False)
```



Note

Please go to <u>http://www.wordle.net/advanced</u> for more word clouds.

Looks much cleaner now! After finishing this much, you can go to **wordle** and put the distribution in a form of a CSV and you should be able to get something like this word cloud:



Your turn

- Please try the same exercise for different URLs.
- Try to reach the word cloud.

Summary

To summarize, this chapter was intended to give you a brief introduction to Natural Language Processing. The book does assume some background in NLP and programming in Python, but we have tried to give a very quick head start to Python and NLP. We have installed all the related packages that are require for us to work with NLTK. We wanted to give you, with a few simple lines of code, an idea of how to use NLTK. We were able to deliver an amazing word cloud, which is a great way of visualizing the topics in a large amount of unstructured text, and is quite popular in the industry for text analytics. I think the goal was to set up everything around NLTK, and to get Python working smoothly on your system. You should also be able to write and run basic Python programs. I wanted the reader to feel the power of the NLTK library, and build a small running example that will involve a basic application around word cloud. If the reader is able to generate the word cloud, I think we were successful.

In the next few chapters, we will learn more about Python as a language, and its features related to process natural language. We will explore some of the basic NLP preprocessing steps and learn about some of basic concepts related to NLP.

Chapter 2. Text Wrangling and Cleansing

The previous chapter was all about you getting a head start on Python as well as **NLTK**. We learned about how we can start some meaningful **EDA** with any corpus of text. We did all the pre-processing part in a very crude and simple manner. In this chapter, will go over preprocessing steps like **tokenization**, **stemming**, **lemmatization**, and **stop word** removal in more detail. We will explore all the tools in NLTK for text wrangling. We will talk about all the pre-processing steps used in modern NLP applications, the different ways to achieve some of these tasks, as well as the general do's and don'ts. The idea is to give you enough information about these tools so that you can decide what kind of pre-processing tool you need for your application. By the end of this chapter, readers should know :

- About all the data wrangling, and to perform it using NLTK
- What is the importance of text cleansing and what are the common tasks that can be achieved using NLTK

What is text wrangling?

It's really hard to define the term text/data wrangling. I will define it as all the pre-processing and all the heavy lifting you do before you have a machine readable and formatted text from raw data. The process involves **data munging**, **text cleansing**, **specific preprocessing**, **tokenization**, **stemming** or **lemmatization** and **stop word removal**. Let's start with a basic example of parsing a csv file:

```
>>>import csv
>>>with open('example.csv','rb') as f:
>>> reader = csv.reader(f,delimiter=',',quotechar='"')
>>> for line in reader :
>>> print line[1]  # assuming the second field is the raw
sting
```

Here we are trying to parse a CSV, in above code line will be a list of all the column elements of the CSV. We can customize this to work on any delimiter and quoting character. Now once we have the raw string, we can apply different kinds of text wrangling that we learned in the last chapter. The point here is to equip you with enough detail to deal with any day to day CSV files.

A clear process flow for some of the most commonly accepted document types is shown in the following block diagram:

Data Sources	CSV	HTML	XML	Databases	Json	PDF	NoSQL
Python parsers	import csv	Import HTMLparser SAX Parser DOM Parser	import XMLParser	PYODBC https://code.google, com/p/pyodbc/wki/ GettingStarted	import json	PDFminer https://bpi.python, org/pyp/pdfminer/	http: //stackoverflow. comparations/5832 531/nasgl-db-for python
				Raw text	_	Г	
				Tokenization		Text cleansing	
			S	top word ramoval		Love Crock Love B	
			Stem	ming / Lemmatizatio	n		

I have listed most common data sources in the first stack of the diagram. In most cases, the data will be residing in one of these data formats. In the next step, I have listed the most commonly used Python wrappers around those data formats. For example, in the case of a csv file, Python's csv module is the most robust way of handling the csv file. It allows you to play with different splitters, different quote characters, and so on.

The other most commonly used files are json.

For example, json looks like:

```
{
   "array": [1,2,3,4],
   "boolean": True,
   "object": {
        "a": "b"
   },
    "string": "Hello World"
}
```

Let's say we want to process the string. The parsing code will be:

```
>>>import json
>>>jsonfile = open('example.json')
>>>data = json.load(jsonfile)
>>>print data['string']
"Hello World"
```

We are just loading a json file using the json module. Python allows you to choose and process it to a raw string form. Please have a look at the diagram to get more details about all the data sources, and their parsing packages in Python. I have only given pointers here; please feel free to search the web for more details about these packages.

So before you write your own parser to parse these different document formats, please have a look at the second row for available parsers in Python. Once you reach a raw string, all the pre-processing steps can be applied as a pipeline, or you might choose to ignore some of them. We will talk about tokenization, stemmers, and lemmatizers in the next section in detail. We will also talk about the variants, and when to use one case over the other.

Note

Now that you have an idea of what text wrangling is, try to connect to any one of the databases using one of the Python modules described in the preceding image.

Text cleansing

Once we have parsed the text from a variety of data sources, the challenge is to make sense of this raw data. Text cleansing is loosely used for most of the cleaning to be done on text, depending on the data source, parsing performance, external noise and so on. In that sense, what we did in <u>Chapter 1</u>, *Introduction to Natural Language Processing* for cleaning the html using html_clean, can be labeled as text cleansing. In another case, where we are parsing a PDF, there could be unwanted noisy characters, non ASCII characters to be removed, and so on. Before going on to next steps we want to remove these to get a clean text to process further. With a data source like xml, we might only be interested in some specific elements of the tree, with databases we may have to manipulate splitters, and sometimes we are only interested in specific columns. In summary, any process that is done with the aim to make the text cleaner and to remove all the noise surrounding the text can be termed as text cleansing. There are no clear boundaries between the terms data munging, text cleansing, and data wrangling they can be used interchangeably in a similar context. In the next few sections, we will talk about some of the most common pre-processing steps while doing any NLP task.

Sentence splitter

Some of the NLP applications require splitting a large raw text into sentences to get more meaningful information out. Intuitively, a sentence is an acceptable unit of conversation. When it comes to computers, it is a harder task than it looks. A typical sentence splitter can be something as simple as splitting the string on (.), to something as complex as a predictive classifier to identify sentence boundaries:

```
>>>inputstring = ' This is an example sent. The sentence splitter
will split on sent markers. Ohh really !!'
>>>from nltk.tokenize import sent_tokenize
>>>all_sent = sent_tokenize(inputstring)
>>>print all_sent
[' This is an example sent', 'The sentence splitter will split on
markers.','Ohh really !!']
```

We are trying to split the raw text string into a list of sentences. The preceding function, sent_tokenize, internally uses a sentence boundary detection algorithm that comes pre-built into NLTK. If your application requires a custom sentence splitter, there are ways that we can train a sentence splitter of our own:

```
>>>import nltk.tokenize.punkt
>>>tokenizer = nltk.tokenize.punkt.PunktSentenceTokenizer()
```

The preceding sentence splitter is available in all the 17 languages. You just need to specify the respective pickle object. In my experience, this is good enough to deal with a variety of the text corpus, and there is a lesser chance that you will have to build your own.

Tokenization

A word (*Token*) is the minimal unit that a machine can understand and process. So any text string cannot be further processed without going through tokenization. Tokenization is the process of splitting the raw string into meaningful tokens. The complexity of tokenization varies according to the need of the NLP application, and the complexity of the language itself. For example, in English it can be as simple as choosing only words and numbers through a regular expression. But for Chinese and Japanese, it will be a very complex task.

```
>>>s = "Hi Everyone !
                         hola gr8" # simplest tokenizer
>>>print s.split()
['Hi', 'Everyone', '!', 'hola', 'gr8']
>>>from nltk.tokenize import word tokenize
>>>word tokenize(s)
['Hi', 'Everyone', '!', 'hola', 'gr8']
>>>from nltk.tokenize import regexp tokenize, wordpunct tokenize,
blankline tokenize
>>>regexp tokenize(s, pattern='\w+')
['Hi', 'Everyone', 'hola', 'gr8']
>>regexp tokenize(s, pattern='\d+')
['8']
>>>wordpunct tokenize(s)
['Hi', ',', 'Everyone', '!!', 'hola', 'gr8']
>>>blankline tokenize(s)
['Hi, Everyone !! hola gr8']
```

In the preceding code we have used various tokenizers. To start with we used the simplest: the <code>split()</code> method of Python strings. This is the most basic tokenizer, that uses white space as delimiter. But the <code>split()</code> method itself can be configured for some more complex tokenization. In the preceding example, you will find hardly a difference between the <code>s.split()</code> and <code>word_tokenize</code> methods.

The word_tokenize method is a generic and more robust method of tokenization for any kind of text corpus. The word_tokenize method comes pre-built with NLTK. If you are not able to access it, you made some mistakes in installing NLTK data. Please refer to <u>Chapter 1</u>, *Introduction to Natural Language Processing* for installation.

There are two most commonly used tokenizers. The first is word_tokenize, which is the default one, and will work in most cases. The other is regex_tokenize, which is more of a customized tokenizer for the specific needs of the user. Most of the other tokenizers can be derived from regex tokenizers. You can also build a very specific tokenizer using a different pattern. In line 8 of the preceding code, we split the same string with the regex tokenizer. We use $\w +$ as a regular expression, which means we need all the words and digits from the string, and other symbols can be used as a splitter, same as what we do in line 10 where we specify $\d +$ as regex. The result will produce only digits from the string.

Can you build a regex tokenizer that will only select words that are either small, capitals, numbers, or money symbols?

Hint: Just look for the regular expression for the preceding query and use a regex_tokenize.

Tip

You can also have a look at some of the demos available online: <u>http://text-processing.com/demo</u>.

Stemming

Stemming, in literal terms, is the process of cutting down the branches of a tree to its stem. So effectively, with the use of some basic rules, any token can be cut down to its stem. Stemming is more of a crude rule-based process by which we want to club together different variations of the token. For example, the word *eat* will have variations like eating, eaten, eats, and so on. In some applications, as it does not make sense to differentiate between eat and eaten, we typically use stemming to club both grammatical variances to the root of the word. While stemming is used most of the time for its simplicity, there are cases of complex language or complex NLP tasks where it's necessary to use lemmatization instead. Lemmatization is a more robust and methodical way of combining grammatical variations to the root of a word.

In the following snippet, we show a few stemmers:

```
>>>from nltk.stem import PorterStemmer # import Porter stemmer
>>>from nltk.stem.lancaster import LancasterStemmer
>>>from nltk.stem.Snowball import SnowballStemmer
>>>pst = PorterStemmer() # create obj of the PorterStemmer
>>>lst = LancasterStemmer() # create obj of LancasterStemmer
>>>lst.stem("eating")
eat
>>>pst.stem("shopping")
shop
```

A basic rule-based stemmer, like removing *-s/es* or *-ing* or *-ed* can give you a precision of more than 70 percent, while **Porter stemmer** also uses more rules and can achieve very good accuracies.

We are creating different stemmer objects, and applying a stem() method on the string. As you can see, there is not much of a difference when you look at a simple example, however there are many stemming algorithms around, and the precision and performance of them differ. You may want to have a look at <u>http://www.nltk.org/api/nltk.stem.html</u> for more details. I have used Porter Stemmer most often, and if you are working with English, it's good enough. There is a family of **Snowball stemmers** that can be used for Dutch, English, French, German, Italian, Portuguese, Romanian, Russian, and so on. I also came across a light weight stemmer for Hindi on <u>http://research.variancia.com/hindi_stemmer</u>.

Tip

I would suggest a study of all the stemmers for those who want to explore more about stemmers on <u>http://en.wikipedia.org/wiki/Stemming</u>.

But most users can live with Porter and Snowball stemmer for a large number of use cases. In modern NLP applications, sometimes people even ignore stemming as a pre-processing step, so it typically depends on your domain and application. I would also like to tell you the fact that if you want to use some NLP taggers, like Part of Speech tagger (POS), NER or dependency parser, you should avoid stemming, because stemming will modify the token and this can result in a different result. We will go into this further when we talk about taggers in general.

Lemmatization

Lemmatization is a more methodical way of converting all the grammatical/inflected forms of the root of the word. Lemmatization uses context and part of speech to determine the inflected form of the word and applies different normalization rules for each part of speech to get the root word (*lemma*):

```
>>>from nltk.stem import WordNetLemmatizer
>>>wlem = WordNetLemmatizer()
>>>wlem.lemmatize("ate")
eat
```

Here, WordNetLemmatizer is using wordnet, which takes a word and searches wordnet, a semantic dictionary. It also uses a morph analysis to cut to the root and search for the specific lemma (variation of the word). Hence, in our example it is possible to get *eat* for the given variation *ate*, which was never possible with stemming.

- Can you explain what the difference is between Stemming and lemmatization?
- Can you come up with a Porter stemmer (Rule-based) for your native language?
- Why would it be harder to implement a stemmer for languages like Chinese?

Stop word removal

Stop word removal is one of the most commonly used preprocessing steps across different NLP applications. The idea is simply removing the words that occur commonly across all the documents in the corpus. Typically, articles and pronouns are generally classified as stop words. These words have no significance in some of the NLP tasks like information retrieval and classification, which means these words are not very discriminative. On the contrary, in some NLP applications stop word removal will have very little impact. Most of the time, the stop word list for the given language is a well hand-curated list of words that occur most commonly across corpuses. While the stop word lists for most languages are available online, these are also ways to automatically generate the stop word list for the given corpus. A very simple way to build a stop word list is based on word's document frequency (Number of documents the word presents), where the words present across the corpus can be treated as stop words. Enough research has been done to get the optimum list of stop words for some specific corpus. NLTK comes with a pre-built list of stop words for around 22 languages.

To implement the process of stop word removal, below is code that uses NLTK stop word. You can also create a dictionary on a lookup based approach like we did in <u>Chapter 1</u>, *Introduction to Natural Language Processing*.

```
>>>from nltk.corpus import stopwords
>>>stoplist = stopwords.words('english') # config the language name
# NLTK supports 22 languages for removing the stop words
>>>text = "This is just a test"
>>>cleanwordlist = [word for word in text.split() if word not in
stoplist]
# apart from just and test others are stopwords
['test']
```

In the preceding code snippet, we have deployed a cleaner version of the same stop word removal we did in <u>Chapter 1</u>, *Introduction to Natural Language Processing*. Previously, we were using a lookup based approach. Even in this case, NLTK internally did a very similar approach. I would recommend using the NLTK list of stop words, because this is more of a standardized list, and this is robust when compared to any other implementation. We also have a way to use similar methods for other languages by just passing the language name as a parameter to the stop words constructor.

- What's the math behind removing stop words?
- Can we perform other NLP operations after stop word removal?

Rare word removal

This is very intuitive, as some of the words that are very unique in nature like names, brands, product names, and some of the noise characters, such as html leftouts, also need to be removed for different NLP tasks. For example, it would be really bad to use names as a predictor for a text classification problem, even if they come out as a significant predictor. We will talk about this further in subsequent chapters. We definitely don't want all these noisy tokens to be present. We also use length of the words as a criteria for removing words with very a short length or a very long length:

```
>>># tokens is a list of all tokens in corpus
>>>freq_dist = nltk.FreqDist(token)
>>>rarewords = freq_dist.keys()[-50:]
>>>after_rare_words = [ word for word in token not in rarewords]
```

We are using the FreqDist() function to get the distribution of the terms in the corpus, selecting the rarest one into a list, and then filtering our original corpus. We can also do it for individual documents, as well.

Spell correction

It is not a necessary to use a spellchecker for all NLP applications, but some use cases require you to use a basic spellcheck. We can create a very basic spellchecker by just using a dictionary lookup. There are some enhanced string algorithms that have been developed for fuzzy string matching. One of the most commonly used is edit-distance. NLTK also provides you with a variety of metrics module that has edit distance.

>>>from nltk.metrics import edit_distance >>>edit_distance("rain","shine") 3

We will cover this module in more detail in advanced chapters. We also have one of the most elegant codes for spellchecker from Peter Norvig, which is quite easy to understand and written in pure Python.

Tip

I would recommend that anyone who works with natural language processing visit the following link for spellcheck: <u>http://norvig.com/spell-correct.html</u>

Your turn

Here are the answers to the open-ended questions:

• Try to connect any of the data base using pyodbc.

https://code.google.com/p/pyodbc/wiki/GettingStarted

• Can you build a regex tokenizer that will only select words that are either small, capitals, numbers or money symbols?

 $[\w+]$ selects all the words and numbers [a-z A-Z 0-9] and $[\\$]$ will match money symbol.

• What's the difference between Stemming and lemmatization?

Stemming is more of a rule-based approach to get the root of the word's grammatical forms, while lemmatization also considers context and the POS of the given word, then applies rules specific to grammatical variants. Stemmers are easier to implement and the processing time is faster than lemmatizer.

• Can you come up with a Porter stemmer (Rule-based) for your native language?

Hint: http://tartarus.org/martin/PorterStemmer/python.txt

http://Snowball.tartarus.org/algorithms/english/stemmer.html

• Can we perform other NLP operations after stop word removal?

No; never. All the typical NLP applications like POS tagging, chunking, and so on will need context to generate the tags for the given text. Once we remove the stop word, we lose the context.

• Why would it be harder to implement a stemmer for languages like Hindi or Chinese?

Indian languages are morphologically rich and it's hard to token the Chinese; there are challenges with the normalization of the symbols, so it's even harder to implement steamer. We will talk about these challenges in advanced chapters.

Summary

In this chapter we talked about all the data wrangling/munging in the context of text. We went through some of the most common data sources, and how to parse them with Python packages. We talked about tokenization in depth, from a very basic string method to a custom regular expression based tokenizer.

We talked about stemming and lemmatization, and the various types of stemmers that can be used, as well as the pros and cons of each of them. We also discussed the stop word removal process, why it's important, when to remove stop words, and when it's not needed. We also briefly touched upon removing rare words and why it's important in text cleansing—both stop word and rare word removal are essentially removing outliers from the frequency distribution. We also referred to spell correction. There is no limit to what you can do with text wrangling and text cleansing. Every text corpus has new challenges, and a new kind of noise that needs to be removed. You will get to learn over time what kind of pre-processing works best for your corpus, and what can be ignored.

In the next chapter will see some of the NLP related pre-processing, like POS tagging, chunking, and NER. I am leaving answers or hints for some of the open questions that we asked in the chapter.

Chapter 3. Part of Speech Tagging

In previous chapters, we talked about all the preprocessing steps we need, in order to work with any text corpus. You should now be comfortable about parsing any kind of text and should be able to clean it. You should be able to perform all text preprocessing, such as Tokenization, Stemming, and Stop Word removal on any text. You can perform and customize all the preprocessing tools to fit your needs. So far, we have mainly discussed generic preprocessing to be done with text documents. Now let's move on to more intense NLP preprocessing steps.

In this chapter, we will discuss what part of speech tagging is, and what the significance of POS is in the context of NLP applications. We will also learn how to use NLTK to extract meaningful information using tagging and various taggers used for NLP intense applications. Lastly, we will learn how NLTK can be used to tag a named entity. We will discuss in detail the various NLP taggers and also give a small snippet to help you get going. We will also see the best practices, and where to use what kind of tagger. By the end of this chapter, readers will learn:

- What is Part of speech tagging and how important it is in context of NLP
- What are the different ways of doing POS tagging using NLTK
- How to build a custom POS tagger using NLTK

What is Part of speech tagging

In your childhood, you may have heard the term **Part of Speech** (**POS**). It can really take good amount of time to get the hang of what adjectives and adverbs actually are. What exactly is the difference? Think about building a system where we can encode all this knowledge. It may look very easy, but for many decades, coding this knowledge into a machine learning model was a very hard NLP problem. I think current state of the art POS tagging algorithms can predict the POS of the given word with a higher degree of precision (that is approximately 97 percent). But still lots of research going on in the area of POS tagging.

Languages like English have many tagged corpuses available in the news and other domains. This has resulted in many state of the art algorithms. Some of these taggers are generic enough to be used across different domains and varieties of text. But in specific use cases, the POS might not perform as expected. For these use cases, we might need to build a POS tagger from scratch. To understand the internals of a POS, we need to have a basic understanding of some of the machine learning techniques. We will talk about some of these in <u>Chapter 6</u>, *Text Classification*, but we have to discuss the basics in order to build a custom POS tagger to fit our needs.

First, we will learn some of the pertained POS taggers available, along with a set of tokens. You can get the POS of individual words as a **tuple**. We will then move on to the internal workings of some of these taggers, and we will also talk about building a custom tagger from scratch.

When we talk about POS, the most frequent POS notification used is Penn Treebank:

Tag	Description
NNP	Proper noun, singular
NNPS	Proper noun, plural
PDT	Pre determiner
POS	Possessive ending
PRP	Personal pronoun
PRP\$	Possessive pronoun
RB	Adverb
RBR	Adverb, comparative
RBS	Adverb, superlative
RP	Particle
SYM	Symbol (mathematical or scientific)
то	to
υн	Interjection
VB	Verb, base form
VBD	Verb, past tense
VBG	Verb, gerund/present participle

Tag	Description				
VBN	Verb, past				
WP	Wh-pronoun				
WP\$	Possessive wh-pronoun				
WRB	Wh-adverb				
#	Pound sign				
\$	Dollar sign				
•	Sentence-final punctuation				
,	Comma				
:	Colon, semi-colon				
(Left bracket character				
)	Right bracket character				
	Straight double quote				
,	Left open single quote				
	Left open double quote				
۲	Right close single quote				
"	Right open double quote				

Looks pretty much like what we learned in primary school English class, right? Now once we have an understanding about what these tags mean, we can run an experiment:

```
>>>import nltk
>>>from nltk import word_tokenize
>>>s = "I was watching TV"
>>>print nltk.pos_tag(word_tokenize(s))
[('I', 'PRP'), ('was', 'VBD'), ('watching', 'VBG'), ('TV', 'NN')]
```

If you just want to use POS for a corpus like news or something similar, you just need to know the preceding three lines of code. In this code, we are tokenizing a piece of text and using NLTK's pos_tag method to get a tuple of (word, pos-tag). This is one of the pre-trained POS taggers that comes with NLTK.

Note

It's internally using the maxent classifier (will discuss these classifiers in advanced chapters) trained model to predict to which class of tag a particular word belongs.

To get more details you can use the following link:

https://github.com/nltk/nltk/blob/develop/nltk/tag/ init .py

NLTK has used python's powerful data structures efficiently, so we have a lot more flexibility in terms of use of the results of NLTK outputs.

You must be wondering what could be a typical use of POS in a real application. In a typical preprocessing, we might want to look for all the nouns. Now this code snippet will give us all the nouns in the given sentence:

```
>>>tagged = nltk.pos_tag(word_tokenize(s))
>>>allnoun = [word for word,pos in tagged if pos in ['NN','NNP'] ]
```

Try to answer the following questions:

- Can we remove stop words before POS tagging?
- How can we get all the verbs in the sentence?

Stanford tagger

Another awesome feature of NLTK is that it also has many wrappers around other pre-trained taggers, such as **Stanford tools**. A common example of a POS tagger is shown here:

```
>>>from nltk.tag.stanford import POSTagger
>>>import nltk
>>>stan_tagger = POSTagger('models/
english-bidirectional-distdim.tagger','standford-postagger.jar')
>>>tokens = nltk.word_tokenize(s)
>>>stan_tagger.tag(tokens)
```

Tip

To use the above code, you need to download the Stanford tagger from <u>http://nlp.stanford.edu/software/</u> <u>stanford-postagger-full-2014-08-27.zip</u>. Extract both the jar and model into a folder, and give an absolute path in argument for the POSTagger.

Summarizing this, there are mainly two ways to achieve any tagging task in NLTK:

- 1. Using NLTK's or another lib's pre-trained tagger, and applying it on the test data. Both preceding taggers should be sufficient to deal with any POS tagging task that deals with plain English text, and the corpus is not very domain specific.
- 2. Building or Training a tagger to be used on test data. This is to deal with a very specific use case and to develop a customized tagger.

Let's dig deeper into what goes on inside a typical POS tagger.

Diving deep into a tagger

A typical tagger uses a lot of trained data, with sentences tagged for each word that will be the POS tag attached to it. Tagging is purely manual and looks like this:

Well/UH what/WP do/VBP you/PRP think/VB about/IN the/DT idea/NN of/ IN ,/, uh/UH ,/, kids/NNS having/VBG to/TO do/VB public/JJ service/ NN work/NN for/IN a/DT year/NN ?/.Do/VBP you/PRP think/VBP it/PRP 's/ BES a/DT ,/,

The preceding sample is taken from the Penn Treebank switchboard corpus. People have done lot of manual work tagging large corpuses. There is a **Linguistic Data Consortium (LDC)** where people have dedicated so much time to tagging for different languages, different kinds of text and different kinds of tagging like POS, dependency parsing, and discourse (will talk about these later).

Note

You can get all these resources and more information about them at <u>https://www.ldc.upenn.edu/</u>. (LDC provides a fraction of data for free but you can also purchase the entire tagged corpus. NLTK has approximately 10 percent of the PTB.)

If we also want to train our own POS tagger, we have to do the tagging exercise for our specific domain. This kind of tagging will require domain experts.

Typically, tagging problems like POS tagging are seen as sequence labeling problems or a classification problem where people have tried generative and discriminative models to predict the right tag for the given token.

Instead of jumping directly in to more sophisticated examples, let's start with some simple approaches for tagging.

The following snippet gives us the frequency distribution of POS tags in the Brown corpus:

```
>>>from nltk.corpus import brown
>>>import nltk
>>>tags = [tag for (word, tag) in
brown.tagged_words(categories='news')]
>>>print nltk.FreqDist(tags)
<FreqDist: 'NN': 13162, 'IN': 10616, 'AT': 8893, 'NP': 6866, ',':
5133, 'NNS': 5066, '.': 4452, 'JJ': 4392 >
```

We can see NN comes as the most frequent tag, so let's start building a very naïve POS tagger, by assigning NN as a tag to all the test words. NLTK has a DefaultTagger function that can be used for this. DefaultTagger function is part of the Sequence tagger, which will be discussed next. There is a function called evaluate() that gives the accuracy of the correctly predicted POS of the words. This is used to benchmark the tagger against the brown corpus. In the default_tagger case, we are getting approximately 13 percent of the predictions correct. We will use the same benchmark for all the taggers moving forward.

```
>>>brown_tagged_sents = brown.tagged_sents(categories='news')
>>>default_tagger = nltk.DefaultTagger('NN')
>>>print default_tagger.evaluate(brown_tagged_sents)
0.130894842572
```

Sequential tagger

Not surprisingly, the above tagger performed poorly. The DefaultTagger is part of a base class SequentialBackoffTagger that serves tags based on the Sequence. Tagger tries to model the tags based on the context, and if it is not able to predict the tag correctly, it consults a BackoffTagger. Typically, the DefaultTagger parameter could be used as a BackoffTagger.

Let's move on to more sophisticated sequential taggers.

N-gram tagger

N-gram tagger is a subclass of SequentialTagger, where the tagger takes previous *n* words in the context, to predict the POS tag for the given token. There are variations of these taggers where people have tried it with UnigramsTagger, BigramsTagger, and TrigramTagger:

```
>>>from nltk.tag import UnigramTagger
>>>from nltk.tag import DefaultTagger
>>>from nltk.tag import BigramTagger
>>>from nltk.tag import TrigramTagger
# we are dividing the data into a test and train to evaluate our
taggers.
>>>train_data = brown_tagged_sents[:int(len(brown_tagged_sents) *
0.9)]
>>>test data = brown tagged sents[int(len(brown tagged sents) *
```

```
0.9):]
>>>unigram_tagger = UnigramTagger(train_data,backoff=default_tagger)
>>>print unigram_tagger.evaluate(test_data)
0.826195866853
>>>bigram_tagger = BigramTagger(train_data, backoff=unigram_tagger)
>>>print bigram_tagger.evaluate(test_data)
0.835300351655
>>>trigram_tagger = TrigramTagger(train_data,backoff=bigram_tagger)
>>>print trigram_tagger.evaluate(test_data)
0.83327713281
```

Unigram just considers the conditional frequency of tags and predicts the most frequent tag for the every given token. The bigram_tagger parameter will consider the tags of the given word and the previous word, and tag as tuple to get the given tag for the test word. The TrigramTagger parameter looks for the previous two words with a similar process.

It's very evident that coverage of the TrigramTagger parameter will be less and the accuracy of that instance will be high. On the other hand, UnigramTagger will have better coverage. To deal with this tradeoff between precision/recall, we combine the three taggers in the preceding snippet. First it will look for the trigram of the given word sequence for predicting the tag; if not found it Backoff to BigramTagger parameter and to a UnigramTagger parameter and in end to a NN tag.

Regex tagger

There is one more class of sequential tagger that is a regular expression based taggers. Here, instead of looking for the exact word, we can define a regular expression, and at the same time we can define the corresponding tag for the given expressions. For example, in the following code we have provided some of the most common regex patterns to get the different parts of speech. We know some of the patterns related to each POS category, for example we know the articles in English and we know that anything that ends with *ness* will be an adjective. Instead, we will write a bunch of regex and a pure python code, and the NLTK RegexpTagger parameter will provide an elegant way of building a pattern based POS. This can also be used to induce domain related POS patterns.

```
>>>from nltk.tag.sequential import RegexpTagger
>>>regexp tagger = RegexpTagger(
```

```
[( r'^-?[0-9]+(.[0-9]+)?$', 'CD'), # cardinal numbers
          (r'(The|the|A|a|An|an)$', 'AT'),
                                             # articles
          ( r'.*able$', 'JJ'),
                                             # adjectives
                                   # nouns formed from adj
          ( r'.*ness$', 'NN'),
          ( r'.*ly$', 'RB'),
                                     # adverbs
          ( r'.*s$', 'NNS'),
                                     # plural nouns
          ( r'.*ing$', 'VBG'),
                                   # gerunds
          (r'.*ed$', 'VBD'),
                                     # past tense verbs
          (r'.*', 'NN')
                                     # nouns (default)
         1)
>>>print regexp tagger.evaluate(test data)
0.303627342358
```

We can see that by just using some of the obvious patterns for POS we are able to reach approximately 30 percent in terms of accuracy. If we combine regex taggers, such as the BackoffTagger, we might improve the performance. The other use case for regex tagger is in the preprocessing step, where instead of using a raw Python function string.sub(), we can use this tagger to tag date patterns, money patterns, location patterns and so on.

- Can you modify the code of a hybrid tagger in the N-gram tagger section to work with Regex tagger? Does that improve performance?
- Can you write a tagger that tags Date and Money expressions?

Brill tagger

Brill tagger is a transformation based tagger, where the idea is to start with a guess for the given tag and, in next iteration, go back and fix the errors based on the next set of rules the tagger learned. It's also a supervised way of tagging, but unlike N-gram tagging where we count the N-gram patterns in training data, we look for transformation rules.

If the tagger starts with a Unigram / Bigram tagger with an acceptable accuracy, then brill tagger, instead looking for a trigram tuple, will be looking for rules based on tags, position and the word itself.

An example rule could be:

Replace NN with VB when the previous word is TO.

After we already have some tags based on UnigramTagger, we can refine if with just one simple rule. This is an interactive process. With a few iterations and some more optimized rules, the brill tagger can outperform some of the N-gram taggers. The only piece of advice is to look out for over-fitting of the tagger for the training set.

Note

You can also look at the work here for more example rules.

http://stp.lingfil.uu.se/~bea/publ/megyesi-BrillsPoSTagger.pdf

- Can you try to write more rules based on your observation?
- Try to combine brill tagger with UnigramTagger.

Machine learning based tagger

Until now we have just used some of the pre-trained taggers from NLTK or Stanford. While we have used them in the examples in previous section, the internals of the taggers are still a black box to us. For example, pos_tag internally uses a **Maximum Entropy Classifier** (MEC). While StanfordTagger also uses a modified version of Maximum Entropy. These are discriminatory models. While there are many **Hidden Markov Model** (HMM) and **Conditional Random Field** (CRF) based taggers, these are generative models.

Covering all of these topics is beyond the scope of the book. I would highly recommend the NLP class for a great understanding of these concepts. We will cover some of the classification techniques in

<u>Chapter 6</u>, *Text Classification*, but some of these are very advanced topics in NLP, and will need more attention.

If I have to explain in short, the way to categorize POS tagging problem is either as a classification problem where given a word and the features like previous word, context, morphological variation, and so on. We classify the given word into a POS category, while the others try to model it as a generative model using the similar features. It's for the reader's reference to go over some of these topics using links in the tips.

Note

NLP CLASS: <u>https://www.coursera.org/course/nlp</u>

HMM: http://mlg.eng.cam.ac.uk/zoubin/papers/ijprai.pdf

MEC: https://web.stanford.edu/class/cs124/lec/Maximum_Entropy_Classifiers.pdf

http://nlp.stanford.edu/software/tagger.shtml
Named Entity Recognition (NER)

Aside from POS, one of the most common labeling problems is finding entities in the text. Typically NER constitutes name, location, and organizations. There are NER systems that tag more entities than just three of these. The problem can be seen as a sequence, labeling the Named entities using the context and other features. There is a lot more research going on in this area of NLP where people are trying to tag Biomedical entities, product entities in retail, and so on. Again, there are two ways of tagging the NER using NLTK. One is by using the pre-trained NER model that just scores the test data, the other is to build a Machine learning based model. NLTK provides the ne_chunk() method and a wrapper around Stanford NER tagger for Named Entity Recognition.

NER tagger

NLTK provides a method for Named Entity Extraction: ne_chunk. We have shown a small snippet to demonstrate how to use it for tagging any sentence. This method will require you to preprocess the text to tokenize for sentences, tokens, and POS tags in the same order to be able to tag for Named entities. NLTK used ne_chunking, where chunking is nothing but tagging multiple tokens to a call it a meaningful entity.

NE chunking is loosely used in the same way as Named entity:

```
>>import nltk
>>>from nltk import ne_chunk
>>>Sent = "Mark is studying at Stanford University in California"
>>>print(ne_chunk(nltk.pos_tag(word_tokenize(sent)), binary=False))
(S
    (PERSON Mark/NNP)
    is/VBZ
    studying/VBG
    at/IN
    (ORGANIZATION Stanford/NNP University/NNP)
    in/IN
    NY(GPE California/NNP)))
```

The ne_chunking method recognizes people (names), places (location), and organizations. If binary is set to True then it provides the output for the entire sentence tree and tags everything. Setting it to False will give us detailed person, location and organizations information, as with the preceding example using the Stanford NER Tagger.

Similar to the POS tagger, NLTK also has a wrapper around Stanford NER. This NER tagger has better accuracy. The code following snippet will let you use the tagger. You can see in the given example that we are able to tag all the entities with just three lines of code:

```
>>>from nltk.tag.stanford import NERTagger
>>>st = NERTagger('<PATH>/stanford-ner/classifiers/
all.3class.distsim.crf.ser.gz',...
```

```
'<PATH>/stanford-ner/stanford-ner.jar')
>>>st.tag('Rami Eid is studying at Stony Brook University in
NY'.split()) [('Rami', 'PERSON'), ('Eid', 'PERSON'), ('is', 'O'),
('studying', 'O'), ('at', 'O'), ('Stony', 'ORGANIZATION'), ('Brook',
'ORGANIZATION'), ('University', 'ORGANIZATION'), ('in', 'O'), ('NY',
'LOCATION')]
```

If you observe closely, even with a very small test sentence, we can say Stanford Tagger outperformed the NLTK ne chunk tagger.

Now, these kinds of NER taggers are a nice solution for a generic kind of entity tagging, but we have to train our own tagger, when it comes, to tag domain specific entities like biomedical and product names, so we have to build our own NER system. I would also recommend an NER Calais. It has ways of tagging not just typical NER, but also some more entities. The performance of this tagger is also very good:

https://code.google.com/p/python-calais/

Your Turn

Here are the answers to the questions posed in the above sections:

• Can we remove stop words before POS tagging?

No; If we remove the stop words, we will lose the context, and some of the POS taggers (Pre-Trained model) use word context as features to give the POS of the given word.

• How can we get all the verbs in the sentence?

We can get all the verbs in the sentence by using pos_tag

```
>>>tagged = nltk.pos_tag(word_tokenize(s))
>>>allverbs = [word for word,pos in tagged if pos in
['VB','VBD','VBG'] ]
```

• Can you modify the code of the hybrid tagger in the N-gram tagger section to work with Regex tagger? Does that improve performance?

Yes. We can modify the code of the hybrid tagger in the N-gram tagger section to work with the Regex tagger:

```
>>>print unigram_tagger.evaluate(test_data,backoff=
regexp_tagger)
>>>bigram_tagger = BigramTagger(train_data,
backoff=unigram_tagger)
>>>print bigram_tagger.evaluate(test_data)
>>>trigram_tagger=TrigramTagger(train_data,backoff=bigram_tagger)
)
>>>print trigram_tagger.evaluate(test_data)
0.857122212053
0.866708415627
0.863914446746
```

The performance improves as we add some basic pattern-based rules, instead of predicting the most frequent tag.

• Can you write a tagger that tags Date and Money expressions?

Yes, we can write a tagger that tags Date and Money expressions. Following is the code:

```
>>>date_regex =
RegexpTagger([(r'(\d{2})[/.-](\d{2})[/.-](\d{4})$','DATE'),(r'\$
','MONEY')])
>>>test_tokens = "I will be flying on sat 10-02-2014 with
around 10M $ ".split()
>>>print date_regex.tag(test_tokens)
```

Note

The last two questions haven't been answered.

There can be many rules according to the reader's observation, so there is no Right / Wrong answer here.

Can you try a similar word cloud to what we did in <u>Chapter 1</u>, *Introduction to Natural Language Processing* with only nouns and verbs now?

References:

https://github.com/japerk/nltk-trainer

http://en.wikipedia.org/wiki/Part-of-speech_tagging

http://en.wikipedia.org/wiki/Named-entity_recognition

http://www.inf.ed.ac.uk/teaching/courses/icl/nltk/tagging.pdf

http://www.nltk.org/api/nltk.tag.html

Summary

This chapter was intended to expose the reader to some of the most useful NLP pre-processing steps of tagging. We have talked about the Part of Speech problem in general, including the significance of POS in the context of NLP. We also discussed the different ways we can use a pre-trained POS tagger in NLTK, how simple it is to use, and how to create wonderful applications. We then talked about all the available POS tagging options, like N-gram tagging, Regex based tagging, etc. We have developed a mix of these taggers that can be built for domain specific corpuses. We briefly talked about how a typical pre-trained tagger is built. We discussed the possible approaches to address tagging problems. We also talked about NER taggers, and how it works with NLTK. I think if, by the end of this chapter, the user understands the importance of POS and NER in general in the context of NLP, as well as how to run the snippet of codes using NLTK, I will consider this chapter successful. But the journey does not end here. We know some of the shallow NLP preprocessing steps now, and in most of the practical application POS, the NER predominantly used. In more complex NLP applications such as the Q/A system, Summarization, and Speech we need deeper NLP techniques like Chunking, Parsing, Semantics. We will talk about these in the next chapter.

Chapter 4. Parsing Structure in Text

This chapter involves a better understanding of deep structure in text and also how to deep parse text and use it in various NLP applications. Now, we are equipped with various NLP preprocessing steps. Let's move to some deeper aspect of the text. The structure of language is so complex that we can describe it by various layers of structural processing. In this chapter we will touch upon all these structures in text, differentiate between them, and provide you with enough details about the usage of one of these. We will talk about **context-free grammar** (**CFG**) and how it can be implemented with NLTK. We will also look at the various parsers and how we can use some of the existing parsing methods in NLTK. We will also provide details about some options that exist in NLTK to do deep structural analysis. We will also try to give you some real-world use cases of information extraction and how it can be achieved by using some of the topics that you will learn in this chapter. We want you to have an understanding of these topics by the end of this chapter.

In this chapter:

- We will also see what parsing is and what is the relevance of parsing in NLP.
- We will then explore different parsers and see how we can use NLTK for parsing.
- Finally, we will see how parsing can be used for information extraction.

Shallow versus deep parsing

In deep or full parsing, typically, grammar concepts such as CFG, and **probabilistic context-free grammar** (**PCFG**), and a search strategy is used to give a complete syntactic structure to a sentence. Shallow parsing is the task of parsing a limited part of the syntactic information from the given text. While deep parsing is required for more complex NLP applications, such as dialogue systems and summarization, shallow parsing is more suited for information extraction and text mining varieties of applications. I will talk about these in the next few sections with more details about their pros and cons and how we can use them for our NLP application.

The two approaches in parsing

There are mainly two views/approaches used to deal with parsing, which are as follows:

The rule-based approach	The probabilistic approach
This approach is based on rules/grammar	In this approach, you learn rules/grammar by using probabilistic models
Manual grammatical rules are coded down in CFG, and so on, in this approach	This uses observed probabilities of linguistic features
This has a top-down approach	This has a bottom-up approach
This approach includes CFG and Regex- based parser	This approach includes PCFG and the Stanford parser

Why we need parsing

I again want to take you guys back to school, where we learned grammar. Now tell me why you learnt grammar Do you really need to learn grammar? The answer is definitely yes! When we grow, we learn our native languages. Now, when we typically learn languages, we learn a small set of vocabulary. We learn to combine small chunks of phrases and then small sentences. By learning each example sentence, we learn the structure of the language. Your mom might have corrected you many times when you uttered an incorrect sentence. We apply a similar process when we try to understand the sentence, but the process is so common that we never actually pay attention to it or think about it in detail. Maybe the next time you correct someone's grammar, you will understand.

When it comes to writing a parser, we try to replicate the same process here. If we come up with a set of rules that can be used as a template to write the sentences in a proper order. We also need the words that can fit into these categories. We already talked about this process. Remember POS tagging, where we knew the category of the given word?

Now, if you've understood this, you have learned the rules of the game and what moves are valid and can be taken for a specific step. We essentially follow a very natural phenomenon of the human brain and try to emulate it. One of the simplest grammar concepts to start with is CFG, where we just need a set of rules and a set of terminal tokens.

Let's write our first grammar with very limited vocabulary and very generic rules:

```
# toy CFG
>>>from nltk import CFG
>>>toy grammar =
nltk.CFG.fromstring(
......
  S -> NP VP
                           # S indicate the entire sentence
                           # VP is verb phrase the
  VP \rightarrow V NP
  V -> "eats" | "drinks" # V is verb
  NP -> Det N
                # NP is noun phrase (chunk that has noun in it)
  Det -> "a" | "an" | "the" # Det is determiner used in the
sentences
  N -> "president" | "Obama" | "apple" | "coke" # N some example nouns
    """)
>>>toy grammar.productions()
```

Now, this grammar concept can generate a finite amount of sentences. Think of a situation where you just know how to combine a noun with a verb and the only verbs and nouns you knew were the ones we used in the preceding code. Some of the example sentences we can form from these are:

- · President eats apple
- Obama drinks coke

Now, understand what's happening here. Our mind has created a grammar concept to parse based on the preceding rules and substitutes whatever vocabulary we have. If we are able to parse correctly, we understand the meaning.

So, effectively, the grammar we learnt at school constituted the useful rules of English. We still use those and also keep enhancing them and these are the same rules we use to understand all English sentences. However, today's rules do not apply to William Shakespeare's body of work.

On the other hand, the same grammar can construct meaningless sentences such as:

- Apple eats coke
- President drinks Obama

When it comes to a **syntactic parser**, there is a chance that a syntactically formed sentence could be meaningless. To get to the semantics, we need a deeper understanding of semantics structure of the sentence. I encourage you to look for a semantic parser in case you are interested in these aspects of language.

Different types of parsers

A parser processes an input string by using a set of grammatical rules and builds one or more rules that construct a grammar concept. Grammar is a declarative specification of a well-formed sentence. A parser is a procedural interpretation of grammar. It searches through the space of a variety of trees and finds an optimal tree for the given sentence. We will go through some of the parsers available and briefly touch upon their workings in detail for awareness, as well as for practical purposes.

A recursive descent parser

One of the most straightforward forms of parsing is recursive descent parsing. This is a top-down process in which the parser attempts to verify that the syntax of the input stream is correct, as it is read from left to right. A basic operation necessary for this involves reading characters from the input stream and matching them with the terminals from the grammar that describes the syntax of the input. Our recursive descent parser will look ahead one character and advance the input stream reading pointer when it gets a proper match.

A shift-reduce parser

The shift-reduce parser is a simple kind of bottom-up parser. As is common with all bottom-up parsers, a shift-reduce parser tries to find a sequence of words and phrases that correspond to the right-hand side of a grammar production and replaces them with the left-hand side of the production, until the whole sentence is reduced.

A chart parser

We will apply the algorithm design technique of dynamic programming to the parsing problem. Dynamic programming stores intermediate results and reuses them when appropriate, achieving significant efficiency gains. This technique can be applied to syntactic parsing. This allows us to store partial solutions to the parsing task and then allows us to look them up when necessary in order to efficiently arrive at a complete solution. This approach to parsing is known as chart parsing.

Note

For a better understanding of the parsers, you can go through an example at

http://www.nltk.org/howto/parse.html.

A regex parser

A regex parser uses a regular expression defined in the form of grammar on top of a POS-tagged string. The parser will use these regular expressions to parse the given sentences and generate a parse tree out of this. A working example of the regex parser is given here:

```
# Regex parser
>>>chunk_rules=ChunkRule("<.*>+","chunk everything")
>>>import nltk
```

```
>>>from nltk.chunk.regexp import *
>>>reg parser = RegexpParser('''
        NP: {<DT>? <JJ>* <NN>* }
                                     # NP
         P: {<IN>}
                                     # Preposition
         V: {<V.*>}
                                     # Verb
        PP: {<P> <NP>}
                                     # PP -> P NP
        VP: {<V> <NP | PP>* }
                                     \# VP -> V (NP|PP)*
  ''')
>>>test sent="Mr. Obama played a big role in the Health insurance
bill"
>>>test sent pos=nltk.pos tag(nltk.word tokenize(test sent))
>>>paresed out=reg_parser.parse(test_sent_pos)
>>> print paresed out
Tree('S', [('Mr.', 'NNP'), ('Obama', 'NNP'), Tree('VP', [Tree('V',
[('played', 'VBD')]), Tree('NP', [('a', 'DT'), ('big', 'JJ'),
('role', 'NN')])]), Tree('P', [('in', 'IN')]), ('Health', 'NNP'),
Tree('NP', [('insurance', 'NN'), ('bill', 'NN')])])
```

The following is a graphical representation of the tree for the preceding code:



In the current example, we define the kind of patterns (a regular expression of the POS) we think will make a phrase, for example, anything that $\{ \text{DT} > ? \text{JJ} > * \text{NN} > * \}$ has a starting determiner followed by an adjective and then a noun is mostly a noun phrase. Now, this is more of a linguistic rule that we have defined to get the rule-based parse tree.

Dependency parsing

Dependency parsing (DP) is a modern parsing mechanism. The main concept of DP is that each linguistic unit (*words*) is connected with each other by a directed link. These links are called **dependencies** in linguistics. There is a lot of work going on in the current parsing community. While **phrase structure parsing** is still widely used for free word order languages (Czech and Turkish), dependency parsing has turned out to be more efficient.

A very clear distinction can be made by looking at the parse tree generated by phrase structure grammar and dependency grammar for a given example, as the sentence "The big dog chased the cat". The parse tree for the preceding sentence is:



If we look at both parse trees, the phrase structures try to capture the relationship between words and phrases and then eventually between phrases. While a dependency tree just looks for a dependency between words, for example, *big* is totally dependent on *dog*.

NLTK provides a couple of ways to do dependency parsing. One of them is to use a **probabilistic**, **projective dependency parser**, but it has the restriction of training with a limited set of training data. One of the state of the art dependency parsers is a Stanford parser. Fortunately, NLTK has a wrapper around it and in the following example, I will talk about how to use a Stanford parser with NLTK:

```
cop(test-6, is-2)
det(test-6, the-3)
amod(test-6, english-4)
compound(test-6, parser-5)
root(ROOT-0, test-6)
Universal dependencies, enhanced
nsubj(test-6, this-1)
cop(test-6, is-2)
det(test-6, is-2)
det(test-6, the-3)
amod(test-6, english-4)
compound(test-6, parser-5)
root(ROOT-0, test-6)
```

The output looks quite complex but, in reality, it's not. The output is a list of three major outcomes, where the first is just the POS tags and the parsed tree of the given sentences. The same is plotted in a more elegant way in the following figure. The second is the dependency and positions of the given words. The third is the enhanced version of dependency:



Tip

For a better understanding of how to use a Stanford parser, refer to

http://nlpviz.bpodgursky.com/home and

http://nlp.stanford.edu:8080/parser/index.jsp.

Chunking

Chunking is shallow parsing where instead of reaching out to the deep structure of the sentence, we try to club some chunks of the sentences that constitute some meaning.

A chunk can be defined as the minimal unit that can be processed. So, for example, the sentence "the President speaks about the health care reforms" can be broken into two chunks, one is "the President", which is noun dominated, and hence is called a **noun phrase** (**NP**). The remaining part of the sentence is dominated by a verb, hence it is called a **verb phrase** (**VP**). If you see, there is one more sub-chunk in the part "speaks about the health care reforms". Here, one more NP exists that can be broken down again in "speaks about" and "health care reforms", as shown in the following figure:



This is how we broke the sentence into parts and that's what we call chunking. Formally, chunking can also be described as a processing interface to identify non-overlapping groups in unrestricted text.

Now, we understand the difference between shallow and deep parsing. When we reach the syntactic structure of the sentences with the help of CFG and understand the syntactic structure of the sentence. Some cases we need to go for semantic parsing to understand the meaning of the sentence. On the other hand, there are cases where, we don't need analysis this deep. Let's say, from a large portion of unstructured text, we just want to extract the key phrases, named entities, or specific patterns of the entities. For this, we will go for shallow parsing instead of deep parsing because deep parsing involves processing the sentence against all the grammar rules and also the generation of a variety of syntactic tree till the parser generates the best tree by using the process of backtracking and reiterating. This entire process is time consuming and cumbersome and, even after all the processing, you might not get the right parse tree. Shallow parsing guarantees the shallow parse structure in terms of chunks which is relatively faster.

So, let's write some code snippets to do some basic chunking:

```
# Chunking
```

```
>>>from nltk.chunk.regexp import *
>>>test_sent="The prime minister announced he had asked the chief
government whip, Philip Ruddock, to call a special party room
meeting for 9am on Monday to consider the spill motion."
>>>test_sent_pos=nltk.pos_tag(nltk.word_tokenize(test_sent))
>>>rule_vp = ChunkRule(r'(<VB.*>)?(<VB.*>)+(<PRP>)?', 'Chunk VPs')
```

```
>>>parser vp = RegexpChunkParser([rule vp],chunk label='VP')
>>>print parser vp.parse(test sent pos)
>>>rule np =
ChunkRule(r'(<DT>?<RB>?)?<JJ|CD>*(<JJ|CD><,>)*(<NN.*>)+', 'Chunk
NPs')
>>>parser np = RegexpChunkParser([rule np],chunk label="NP")
>>>print parser np.parse(test sent pos)
(S
  The/DT
  prime/JJ
  minister/NN
  (VP announced/VBD he/PRP)
  (VP had/VBD asked/VBN)
  the/DT
  chief/NN
  government/NN
whip/NN
···· •
.....
... .
(VP consider/VB)
  the/DT
  spill/NN
  motion/NN
  ./.)
(S
  (NP The/DT prime/JJ minister/NN)
                                                           # 1st noun
phrase
  announced/VBD
  he/PRP
  had/VBD
  asked/VBN
  (NP the/DT chief/NN government/NN whip/NN)
                                                              # 2nd
noun phrase
  ,/,
  (NP Philip/NNP Ruddock/NNP)
  ,/,
  to/TO
  call/VB
  (NP a/DT special/JJ party/NN room/NN meeting/NN) # 3rd noun
phrase
  for/IN
  9am/CD
  on/IN
  (NP Monday/NNP)
                                            # 4th noun phrase
  to/TO
```

```
consider/VB
 (NP the/DT spill/NN motion/NN)
phrase
 ./.)
```

5th noun

The preceding code is good enough to do some basic chunking of verb and noun phrases. A conventional pipeline in chunking is to tokenize the POS tag and the input string before they are ed to any chunker. Here, we use a regular chunker, as rule NP / VP defines different POS patterns that can be called a verb/noun phrase. For example, the NP rule defines anything that starts with the determiner and then there is a combination of an adverb, adjective, or cardinals that can be chunked in to a noun phrase. Regular expression-based chunkers rely on chunk rules defined manually to chunk the string. So, if we are able to write a universal rule that can incorporate most of the noun phrase patterns, we can use regex chunkers. Unfortunately, it's hard to come up with those kind of generic rules; the other approach is to use a machine learning way of doing chunking. We briefly touched upon ne_chunk() and the Stanford NER tagger that both use a pre-trained model to tag noun phrases.

Information extraction

We learnt about taggers and parsers that we can use to build a basic information extraction engine. Let's jump directly to a very basic IE engine and how a typical IE engine can be developed using NLTK.

Any sort of meaningful information can be drawn only if the given input stream goes to each of the following NLP steps. We already have enough understanding of sentence tokenization, word tokenization, and POS tagging. Let's discuss NER and relation extraction as well.

A typical information extraction pipeline looks very similar to that shown in the following figure:



Note

Some of the other preprocessing steps, such as stop word removal and stemming, are generally ignored and do not add any value to an IE engine.

Named-entity recognition (NER)

We already briefly discussed NER generally in the last chapter. Essentially, NER is a way of extracting some of the most common entities, such as names, organizations, and locations. However, some of the modified NER can be used to extract entities such as product names, biomedical entities, author names, brand names, and so on.

Let's start with a very generic example where we are given a text file of the content and we need to extract some of the most insightful named entities from it:

```
# NP chunking (NER)
>>>f=open(# absolute path for the file of text for which we want NER)
>>>text=f.read()
>>>sentences = nltk.sent_tokenize(text)
>>>tokenized_sentences = [nltk.word_tokenize(sentence) for sentence
in sentences]
>>>tagged_sentences = [nltk.pos_tag(sentence) for sentence in
tokenized_sentences]
>>>for sent in tagged_sentences:
>>>print nltk.ne_chunk(sent)
```

In the preceding code, we just followed the same pipeline provided in the preceding figure. We took all the preprocessing steps, such as sentence tokenization, tokenization, POS tagging, and NLTK. NER (pre-trained models) can be used to extract all NERs.

Relation extraction

Relation extraction is another commonly used information extraction operation. Relation extraction as it sound is the process of extracting the different relationships between different entities. There are variety of the relationship that exist between the entities. We have seen relationship like inheritance/ synonymous/analogous. The definition of the relation can be dependent on the Information need. For example in the case where we want to look from unstructured text data who is the writer of which book then authorship could be a relation between the author name and book name. With NLTK the idea is to use the same IE pipeline that we used till NER and extend it with a relation pattern based on the NER tags.

So, in the following code, we used an inbuilt corpus of ieer, where the sentences are tagged till NER and the only thing we need to specify is the relation pattern we want and the kind of NER we want the relation to define. In the following code, a relationship between an organization and a location has been defined and we want to extract all the combinations of these patterns. This can be applied in various ways, for example, in a large corpus of unstructured text, we will be able to identify some of the organizations of our interest with their corresponding location:

```
>>>import re
>>>IN = re.compile(r'.*\bin\b(?!\b.+ing)')
>>>for doc in nltk.corpus.ieer.parsed_docs('NYT_19980315'):
>>> for rel in nltk.sem.extract_rels('ORG', 'LOC', doc,
corpus='ieer', pattern = IN):
>>>print(nltk.sem.rtuple(rel))
[ORG: u'WHYY'] u'in' [LOC: u'Philadelphia']
[ORG: u'McGlashan & Sarrail'] u'firm in' [LOC: u'San Mateo']
[ORG: u'Freedom Forum'] u'in' [LOC: u'Arlington']
[ORG: u'Brookings Institution'] u', the research group in' [LOC:
u'Washington']
[ORG: u'Idealab'] u', a self-described business incubator
based in' [LOC: u'Los Angeles']
..
```

Summary

We moved beyond the basic preprocessing steps in this chapter. We looked deeper at NLP techniques, such as parsing and information extraction. We discussed parsing in detail, which parsers are available, and how to use NLTK to do any NLP parsing. You understood the concept of CFG and PCFG and how to learn from a tree bank and build a parser. We talked about shallow and deep parsing and what the difference is between them.

We also talked about some of the information extraction essentials, such as entity extraction and relation extraction. We talked about a typical information extraction engine pipeline. We saw a very small and simple IE engine that can be built in less than 100 lines of code. Think about this kind of system running on an entire Wikipedia dump or an entire web content related to an organization. Cool, isn't it?

We will use some of the topics we've learnt in this chapter in further chapters to build some useful NLP applications.

Chapter 5. NLP Applications

This chapter discusses NLP applications. Here, we will put all the learning from the previous chapters into action and will see what kind of application can be developed using the concepts we have learned. This will be a complete hands-on chapter. In the last few chapters we have learned most of the preprocessing steps that are required for any NLP application. We know how to use tokenizer, POS tag, and NER and how to perform parsing. This chapter will give you an idea how we can developed some of the complex NLP application using the concepts we have learned.

There are so many applications of NLP in the real world. Some of the most exciting and common examples you can observe are Google Search, Siri, machine translation, Google News, Jeopardy, and spell check. Some of these took many years for researchers to reach this level and bring these applications to their current state. NLP is complicated too; we have seen in the previous chapters that most of the processing steps, such as POS and NER, are still research problems. But with the use of NLTK, we have solved many of these problems with reasonable accuracy. We will not cover the more sophisticated applications such as machine translation or speech recognition in this book. But at this point in time, you should have enough background knowledge to understand some of the basic blocks of these applications. As a NLP enthusiast we should have a basic understanding of these NLP applications. I urge you to try and look for some of these NLP applications on the web and try to understand them.

By the end of this chapter :

- We will introduce reader to few common NLP applications.
- We will develop a NLP application (News summarizer) using what we have learnt so far.
- The importance of different NLP applications and essential details about each of them.

Building your first NLP application

Let's start with one of the very complex NLP applications, which is **summarization**. The concept of summarization is quite simple. We are given an article/passage/story and you will have to generate a summary of the content automatically. Summarization actually requires deep knowledge of NLP because we need to understand not just the structure of the sentence but also the structure of the entire text. We also need to know about genre of the text and the theme of the content.

Since it all looks very complex to us, let's try a very intuitive approach. We will assume that summarization is nothing but ranking of the sentences based on their importance and significance to you. We will create a few rules based on the understanding and the preprocessing tools we have learned so far and will try to come up with an acceptable summary of the news article.

I have scraped an article from the *New York Times* in a text file nyt.txt, in the following example. The idea here is to summarize this news article for us. Let's build a version of Google News for our personal use.

To start off, we need to keep in mind that, typically, a sentence that has more entities and nouns has greater importance than other sentences. We will try to normalize the same logic while calculating an

importance score, using the following code. To get the top-n sentence, we can choose a threshold for the importance score.

Let's read the content of the news article. You can choose any news article with only contents of the news dumped into a text file. The content will look like this:

```
>>>import sys
>>>f=open('nyt.txt','r')
>>>news_content=f.read()
""" President Obama on Monday will ban the federal provision of some
types of military-style equipment to local police departments and
sharply restrict the availability of others, administration
officials said.
The ban is part of Mr. Obama's push to ease tensions between law
enforcement and minority communities in reaction to the crises in
Baltimore; Ferguson, Mo.; and other cities.
- - -
blic." It contains dozens of recommendations for agencies throughout
```

```
the country."""
```

Once we parse the contents of the news we will need to split the entire news article into a list of sentences. We will go back to our old sentence tokenizer to break the entire news snippet into sentences. Let's also provide some form of sentence number so that we can identify and rank a sentence. Once we have the sentence, we will pass it through a word tokenizer and eventually through the NER tagger and POS tagger.

```
>>>import nltk
>>>results=[]
>>>for sent no, sentence in
enumerate(nltk.sent tokenize(news content)):
>>>
       no of tokens=len(nltk.word tokenize(sentence))
       #print no of toekns
>>>
       # Let's do POS tagging
>>>
       tagged=nltk.pos tag(nltk.word tokenize(sentence))
>>>
>>>
       # Count the no of Nouns in the sentence
       no of nouns=len([word for word, pos in tagged if pos in
>>>
["NN","NNP"] ])
>>>
       #Use NER to tag the named entities.
>>>
ners=nltk.ne chunk(nltk.pos tag(nltk.word tokenize(sentence)),
binary=False)
>>>
       no of ners= len([chunk for chunk in ners if hasattr(chunk,
'node')])
       score=(no of ners+no of nouns)/float(no of toekns)
>>>
>>>
```

>>> results.append((sent_no,no_of_tokens,no_of_ners,\ no_of_nouns,score,sentence))

In the preceding code, we are iterating over a list of sentences calculating a score based on a formula that is nothing but the fraction of tokens being entities as compared to a normal token. We are creating a tuple of all these as the results.

Now, the result is a tuple with all the scores, such as the number of nouns, entities, and so on. We can sort it based on the score in descending order, as shown in the following example:

>>>for sent in sorted(results,key=lambda x: x[4],reverse=True): >>> print sent[5]

Now, the result of this will be sorted by the rank of the sentence. You will be amazed by the kind of results we get for the news article.

Once we have a list of no_of_nouns and no_of_ners scores, we can actually create some more complex rules around this. For example, a typical news article will start with very important details about the topic, and the last sentence will be a conclusion to the story.

Can we modify the same snippet to incorporate this logic?

The other theory of this kind of summarization is that the important sentences generally contain important words and that most of the the discriminatory words across the corpus will be important. The sentences that has very discriminatory words are important. A very simple measure of that is to calculate the **TF-IDF** (**term frequency–inverse document frequency**) score of each and every word and then look for an average score normalized by the words that are important; this can then be used as the criteria to choose sentences for our summary.

For explaining the concepts instead of the entire article, just take the first three sentences of the article. Let's see how you can implement something this complex using very few lines of code:

Note

This code require installing scikit. If you have installed anaconda or canopy you should be fine otherwise install scikit using this link.

http://scikit-learn.org/stable/install.html

```
>>>import nltk
>>>from sklearn.feature_extraction.text import TfidfVectorizer
>>>results=[]
>>>news_content="Mr. Obama planned to promote the effort on Monday
during a visit to Camden, N.J. The ban is part of Mr. Obama's push
to ease tensions between law enforcement and minority \communities
in reaction to the crises in Baltimore; Ferguson, Mo. We are,
```

without a doubt, sitting at a defining moment in American policing, Ronald L. Davis, the director of the Office of Community Oriented

```
Policing Services at the Department of Justice, told reporters in a
conference call organized by the White House"
>>>sentences=nltk.sent_tokenize(news_content)
>>>vectorizer = TfidfVectorizer(norm='l2',min_df=0, use_idf=True,
smooth_idf=False, sublinear_tf=True)
>>>sklearn_binary=vectorizer.fit_transform(sentences)
>>>print countvectorizer.get_feature_names()
>>>print sklearn_binary.toarray()
>>>for i in sklearn_binary.toarray():
>>> results.append(i.sum()/float(len(i.nonzero()[0]))
```

In the preceding code, I am using some unknown methods, such as TfidfVectorizer, which is a scoring method that will calculate a vector of TF-IDF scores for each sentence in a given list of sentences. Don't worry, we will talk about this in more detail. For this chapter, consider it as a black-box function that, for a given list of sentences/documents, will give you the score corresponding to each sentence and will also provide the ability to build a term-doc matrix that will look just like our output.

We got a dictionary of all the words present across all the sentences and then we have a list of lists where each element assigns each word its individual TF-IDF score. If you got that right, then you can see some of the stop words will get a near-zero score while some discriminatory words like ban and Obama will get a very high score. Now once we have this in the code, I will look for the average TF-IDF score by using only non-zero TF-IDF words. This will give us a similar kind of score as we got in our first approach.

You will be amazed by the kind of results a simple algorithm can give. I think now you are all set to write your own news summarizer that summarizes any given news article with the two preceding algorithms and the summary will look quite decent. While this kind of approach will give you a decent summarization, it's actually very poor when you compare it with the current state of summarization research. I would recommend looking for some literature relating to summarization. I would also like you to try and combine both the approaches for summarization.

Other NLP applications

Some of the other NLP applications are text classification, machine translation, speech recognition, information retrieval, information extraction, topic segmentation, and discourse analysis. Some of these problems are actually very difficult NLP tasks and a lot of research is still going on in these areas. We will discuss some of these in depth in the next chapter, but as NLP students, we should have a basic understanding of these applications.

Machine translation

The easiest way to understand machine translation is to know how we translate from one language to other. Our mind parses the sentence structure and tries to understand the sentence. Once we understand the sentence, we will try to substitute the words from the original language with those from the target language. While substituting, we use the grammar rules of the target sentence and finally achieve the correct translation.



Loosely, the process can be translated to something like the pyramid in the preceding figure. If we start from the source language text, we have to tokenize the sentences that we will parse the tree (for syntactic structure in easy words) to make sure the sentences are correctly formulated. Semantic structure holds the meaning of the sentences, and at the next level, we reach the state of Interlingua, which is an abstract state that is independent from any language. There are multiple ways in which people have developed methods of translation. The more you go on towards the root of the pyramid, the more intense is the NLP processing required. So, based on these levels of transfer, there are a variety of methods that are available. I have listed two of them here:

- **Direct translation**: This will be more of a dictionary-based machine translation while you have huge corpora of source and target language words. This kind of transfer is possible for applications where we have a large corpus of languages available. It's popular because of its simplicity.
- **Syntactic transfer**: Here you will try to build a parser of the source language. There are varieties of ways in which people have approached the problem of parsing. There are deep parsers that actually take care of some parts of semantics too. Once you have a parser, target word substitution happens and the target parser can generate the final sentence in the target language.

Statistical machine translation

Statistical machine translation (**SMT**) is one of the latest approach of machine translation, where people have come up with a variety of ways to apply statistical methods to almost all the aspects of machine translation. The idea behind this kind of algorithm is that we have a huge volume of corpora, parallel text, and language models that can help us predict the language translation in the target language. Google Translate is a great example of SMT, where it learns from the corpora of different language pairs and builds an SMT around it.

Information retrieval

Information retrieval (**IR**) is also one of the most popular and widely used applications. The best exmple of IR is Google Search, where—given an input query from the user—the information retrieval algorithm will try to retrieve the information which is relevant to the user's query.

In simple words, IR is the process of obtaining the most relevant information that is needed by the user. There are a variety of ways in which the information needs can be addressed to the system, but the system eventually retrieves the most relevant infromation.

The way a typical IR system works is that it generates an indexing mechanism, also known as **inverted index**. This is very similar to the indexing schemes used in books, where you will have an index of the words present throughout the book on the last pages of the book. Similarly, an IR system will create an inverted index poslist. A typical posting list will look like this:

```
< Term , DocFreq, [DocId1,DocId2] >
{"the",2 --->[1,2] }
{"US",1 --->[2] }
{"president",2 --->[1,2] }
```

So if any word occurs in both document 1 and document 2, the posting list will be a list of documents pointing to terms. Once you have this kind of data structure, there are different retrieval models that can been introduced. There are different retrieval models that work on different types of data. A few are listed in the following sections.

Boolean retrieval

In the Boolean model, we just need to run a Boolean operation on the poslist. For example, if we are looking for a search query like "US president", the system should look for an intersection of the postlist of "US" and "president".

{US} {president} => [2]

Here, the second document turns out to be the relevant document.

Vector space model

The concept of **vector space model** (**VSM**) derives from geometry. The way to visualize the documents in the high dimension space of vocabulary is to represent it as a vector. So each and every document is represented as a vector in that space. We can represent the vector in various ways, but one of the most useful and efficient ways is using TF-IDF.

Given a term and a corpus, we can calculate the **term frequency** (**TF**) and **inverse document frequency** (**IDF**) using the following formula:

$$\operatorname{tf}(t,d) = 0.5 + \frac{0.5 \times f(t,d)}{\max\left\{f(w,d) : w \in d\right\}}$$

The TF is nothing but the frequency in the document. While the IDF is the inverse of document frequency, which is the count of documents in the corpus where the term occurs:

$$\operatorname{idf}(t, D) = \log \frac{N}{\left| \{d \in D : t \in d\} \right|}$$

There are various normalization variants of these, but we can incorporate both of these to create a more robust scoring mechanism to get the scoring of each term in the document. To get to a TF-IDF score, we need to multiply these two scores as follows:

$$\operatorname{tfidf}(t,d,D) = \operatorname{tf}(t,d) \times \operatorname{idf}(t,D)$$

In TF-IDF, we are scoring a term for how much it is present in the current document and how much it is spread across the corpus. This gives us an idea of the terms that are not common across corpora and where ever they are present have a high frequency. It becomes discriminatory to retrieve these

documents. We have also used TF-IDF in the previous section, where we describe our summarizer. The same scoring can be used to represent the document as a vector. Once we have all the documents represented in a vectorized form, the vector space model can be formulated.

In VSM, the search query of the user is also considered as a document and represented as a vector. Intuitively, a dot product between these two vectors can be used to get the cosine similarity between the document and the user query.



In the preceding diagram, we see that these same documents can be represented using each term as an axis and the query Obama will have as much relevance to D1 as compared to D2. The scoring of the query for relevant documents can be formulated as follows:

$$\sin(d_{j},q) = \frac{d_{j} \cdot q}{\|d_{j}\|\|q\|} = \frac{\sum_{i=1}^{N} w_{i,j}, w_{i,q}}{\sqrt{\sum_{i=1}^{N} w_{i,j}^{2}} \sqrt{\sum_{i=1}^{N} w_{i,q}^{2}}}$$

The probabilistic model

The probabilistic model tries to estimate the probability of the user's need for the document. This model assumes that the probability of the relevance depends on the user query and document representation. The main idea is that a document that is in the relevant set will not be present in the non-relevant set. We denote dj as the document and q as user query; R represents the relevant set of documents, while P represents the non-relevant set. The scoring can be done like this:

$$\sin\left(d_{j},q\right) = \frac{P\left(R \mid \vec{d}_{j}\right)}{P\left(\overline{R} \mid \vec{d}_{j}\right)}$$

Note

For more topics on IR, I would recommend that you read from the following link:

http://nlp.stanford.edu/IR-book/html/htmledition/irbook.html

Speech recognition

Speech recognition is a very old NLP problem. People have been trying to address this since the era of World War I, and it still is one of the hottest topics in the area of computing. The idea here is really intuitive. Given the speech uttered by a human can we convert it to text? The problem with speech is that we produce a sequence of sounds, called **phonemes**, that are hard to process, so speech segmentation itself is a big problem. Once the speech is processable, the next step is to go through some of the constraints (models) that are built using training data available. This involves heavy machine learning. If you see the figure representing the modeling as one box of applying constraints, it's actually one of the most complex components of the entire system. While acoustic modeling involves building modes based on phonemes, lexical models will try to address the modeling on smaller segments of sentences, associating a meaning to each segment. Separately language models are built on unigrams and bigrams of words.

Once we build these models, an utterence of the sentences is passed through the process. Once processed for initial preprocessing, the sentence is passed through these acoustic, lexical, and language models for generating the token as output.



Text classification

Text classification is a very interesting and common application of NLP. In your daily work, you interact with many text classifiers. We use a spam filter, a priority inbox, news aggregators, and so on. All of these are in fact applications built using text classification.

Text classification is a well-defined and somewhat solved problem, and it has been applied across many domains. Typically, any text classification is the process of classifying text documents using words and the combination of words. While it's a typical machine learning problem, many of the preprocessing steps used in text classification are from NLP.

An abstract diagram of text classification is shown here:



Here we have a bunch of documents for a set of classes. For simplicity, we will use just binary 1/0 as the class. Now let's assume it's a spam detection problem where 1 represents spam and 0 represents normal text which is not to be considered as spam.

The process involves some of the preprocessing steps we learned in previous chapters. While some of these are essential, it depends on the kind of text classification problem we are trying to solve. So in few cases, it's more a case of feature engineering while we drop some of the preprocessing steps. The final goal of feature engineering is to generate a **Term doc matrix** (**TDM**), which holds the vocabulary of the entire corpus: columns and rows are the documents, while the matrix represents a scoring mechanism to show the **Bag of word** (**BOW**) representation. The weighting scheme can be varied to TF, TF-IDF, Bernoulli, and other variations of term frequency.

There are also ways to induce features such as the POS of a given feature, contextual POS, and others, to make our feature space more NLP intense. Once the TDM is generated, the text classification problem becomes a typical supervised/unsupervised classification problem, where given a set of samples, we need to predict what sample belongs to what class. The next chapter is dedicated entirely to this topic. This is definitely a splendid application of NLP/ML and is used quite often for commercial purposes.

Some of the most common use cases in day-to-day scenarios are sentiment analysis, spam classification, e-mail categorization, news categorization, patent classification, and so on. We will talk about text classification in more detail in the next chapter.

Information extraction

Information extraction (IE) is a process of extracting meaningful information from unstructured text. IE is yet another widely popular and highly important application. In general, an information extraction engine harnesses huge numbers of unstructured documents and generates some sort of structured/semistructured **knowledge base (KB)** that can be deployed to build an application around it. A simple example is that of generating a very good ontology using a huge set of unstructured text documents. A similar project in this line is DBpedia, where all the Wikipedia articles are used to generate the ontology of artifacts that are interrelated or have some other relationship.

There are mainly two ways of extracting information:

- **Rule-based extraction**: This method is where one uses a template filling mechanism. The idea is to look for some kind predefined use cases for expected outcomes and try to mine the unstructured text for that specific template. For example, building a knowledge base of football will involve getting information on all the players and their profiles, the statistics, some personal information, and so on. All that can be well defined and extracted using either pattern-based rules or POS tags, NERs and relation extraction.
- Machine learning based: The other approach involves deeper NLP-based methods such as building a parser specific to the need of our knowledge base. Some of the KBs will require mining the entities that can't be extracted using a pre-trained NER, so we have to build a custom NER. We might want to develop a relation extraction algorithm specific to the KB we are trying to build. This is a more NLP-intensive approach, where we are developing a NLP-based parser or tagger to use for heavy machine learning.

Question answering systems

Question answering (**QA**) systems are intelligent systems that can address any question based on their knowledge base. One of the major examples of this is IBM Watson, which took part in the TV show *Jeopardy* and won over human opponents. A QA system can be broken down to building components from speech recognition for querying the knowledge base while the knowledge base is generated using information retrieval and extraction.

Once you have a question for the system, one big problem is to classify/categorize the question in different ways. The other aspect is to search the knowledge base effectively and retrieve the most precise document. Even after that, we have to generate the answer in a natural way using some of the other applications, such as summarization and parsing.

Dialog systems

Dialog systems are considered the dream application, where given a speech in source language, the system will perform speech recognition and transcribe it to text. This text will then go to a machine translation system that can translate the speech into the target language and then a text-to-speech system will convert it into speech in the target language. This is one of the most desirable applications of NLP, where we can talk to a computer in any language and the computer will reply in the same language. This kind of application can actually destroy the language barrier that exists in the world.

Apple Siri and Google Voice are examples of some of the commercial applications in the line of dialog systems intelligent enough to understand our information needs, try to address them in a set of actions or information, and respond in a human-like manner.

Word sense disambiguation

Word sense disambiguation (**WSD**) is also one of the difficult challenges not solved even after years of research and one of the major causes of application problems, such as question answering, summarization, search, and so on. A simple way to understand the concept is that many words have different meanings when used in different contexts. For example, "cold" in the following example:

- The ice-cream is really cold
- That was cold blooded!

Here the word "cold "has two different senses, and it's really hard for computers to understand this concept. Some of the other NLP processing options, such as POS tagging and NER, are used to resolve some of these problems.

Topic modeling

Topic modeling, in the context of a large amount of unstructured text content, is really an amazing application, where the primary task is to identify the emerging topics in the corpus and then categorize the documents in the corpus as per these topics. We will discuss this briefly in the next chapter.

Topic modeling uses the same NLP preprocessing, for example, sentence split, tokenization, stemming, and so on. The beauty of the algorithms is that we have an unsupervised way of categorizing the document; also, topics are generated without explicitly mentioning anything prior to the process. I encourage you to look at topic modeling in more detail. Try reading about **latent dirichlet allocation** (LDA) and **latent semantics indexing** (LSI) for more detail.

Language detection

Given a snippet of text, the detection of language is also a problem. The application of language detection is very important for some of the other NLP applications, such as search, machine translation, speech, and so on. The main concept is learning from the text as features what the language is. A variety of machine learning and NLP techniques are used for feature engineering in the process.

Optical character recognition

Optical character recognition (**OCR**) is an application of NLP and computer vision, where given a handwritten document/ non-digital document, the system can recognize the text and extract it into digital format. This has also been widely researched in the area of machine learning for many years. Some of the big OCR projects are Google Books, where they use OCR to convert non-digital books into a centralized library.

Summary

In conclusion, there are many NLP applications around us that we interact with in our day-to-day routines. NLP is difficult and complex, and some of these problems are still unsolved or do not yet have perfect solutions. So anybody who is looking for problems in NLP, try exploring the literature around that. It's a great time to be an NLP researcher. In the era of Big Data, NLP applications are very popular. Many research labs and organizations are currently working on NLP applications such as speech recognition, search, and text classification.

I believe we have learned a lot up until this chapter. For the next couple of chapters, we will delve deeply into some of the applications described here. We have reached a point where we know enough NLP related preprocessing tools and also have a basic understanding about some of the most popular NLP applications. I hope you leverage some of this learning to build a version of an NLP application.

In the next chapter, we will start with some of the important NLP applications, such as text classification, text clustering, and topic modeling. We will move slightly away from the pure NLTK applications on to how NLTK can be used in conjunction with other libraries.

Chapter 6. Text Classification

We were talking about some of the most common NLP tools and preprocessing steps in the last chapter. This is the chapter where we will get to use most of the stuff we learnt in the previous chapters, and build one of the most sophisticated NLP applications. We will give you a generic approach about text classification and how you can build a text classifier from scratch with very few lines of code. We will give you a cheat sheet of all the classification algorithms in the context of text classification.

While we will talk about some of the most common text classification algorithms, this is just a brief introduction and to get to a detailed understanding and mathematical background, there are many online resources and books available that you can refer to. We will try to give you all you need to know to get you started with some working code snippets. Text classification is a great use case of NLP, but in this chapter, instead of using NLTK, we will use **scikit-learn** that has a wider range of classification algorithms and its library is much more memory efficient for text mining.

By the end of this chapter:

- You will learn and understand all text classification algorithms
- You will learn end-to-end pipeline to build a text classifier and how to implement it with scikitlearn and NLTK



The following is the scikit-learn cheat sheet for machine learning:

credit : scikit-learn

Now, as you travel along the process shown in the cheat sheet. We have a clear guideline about what kind of algorithm is required for which problem? When we should move from one classifier to another

depending on the size of the tagged sample? It's a good place to start following this for building practical application, and in most cases this will work. We will focus mostly on text data while the scikit-learn can work with other types of data as well. We will explore text classification, text clustering, and topic detection in text (**dimensionality reduction**) with examples in this chapter and build some cool NLP applications. I will not go in to more detail about the concepts of machine learning, classification, and clustering in this chapter, as there are enough resources available on the Web for you. We will provide you with more details of all these concepts in the context of a text corpus. Still, let me give you a refresher.

Machine learning

There are two types of machine learning techniques—supervised learning and Unsupervised learning:

- **Supervised learning**: Based on some historic prelabeled samples, machines learn how to predict the future test sample, based on the following categories:
 - **Classification**: This is used when we need to predict whether a test sample belongs to one of the classes. If there are only two classes, it's a binary classification problem; otherwise, it's a multiclass classification.
 - **Regression**: This is used when we need to predict a continuous variable, such as a house price and stock index.
- Unsupervised learning: When we don't have any labeled data and we still need to predict the class label, this kind of learning is called unsupervised learning. When we need to group items based on similarity between items, this is called a clustering problem. While if we need to represent high-dimensional data in lower dimensions, this is more of a dimensionality reduction problem.
- Semi-supervised learning: This is a class of supervised learning tasks and techniques that also make use of unlabeled data for training. As the name suggests, it's more of a middle ground for supervised and unsupervised learning, where we use small amount of labeled data and large amount of unlabeled data to build a predictive machine learning model.
- **Reinforcement learning**: This is a form of machine learning where an agent can be programmed by a reward and punishment, without specifying how the task is to be achieved.

If you understood the different machine learning algorithms, I want you to guess what kind of machine learning problems the following are:

- You need to predict the values of weather for the next month
- Detection of a fraud in millions of transactions
- Google's priority inbox
- Amazon's recommendations
- Google news
- Self-driving cars

Text classification

The simplest definition of text classification is that it is a classification of text based on the content of that text. Now, in general, all the machine learning methods and algorithms are written for numeric features/variables. One of the most important problems with text corpus is how to represent text as numeric features. There are different transformations prescribed in the literature. Let's start with one of the simplest and most widely used transformations.

Now, to understand the processes of text classification, let's take a real word problem of spams. In the world of WhatsApp and SMS, you get many spam messages. Let's start by solving this real problem of spam detection with the help of text classification. We will be using this running example across the chapter.

Here are a few real examples of SMS's that we asked people to manually tag for us:

SMS001 ['spam', 'Had your mobile 11 months or more? U R entitled to Update to the latest colour mobiles with camera for Free! Call The Mobile Update Co FREE on 08002986030'] SMS002 ['ham', "I'm gonna be home soon and i don't want to talk about this stuff anymore tonight, k? I've cried enough today."]

Note

A similar tagged dataset can be downloaded from link here. Make sure you create a CSV like the one show in the example. 'SMSSpamCollection' in the following code which will correspond to this file.

https://archive.ics.uci.edu/ml/datasets/SMS+Spam+Collection

The first thing you want to do here is what we learnt in the last few chapters about data cleaning, tokenization, and stemming to get much cleaner content out of the SMS. I wrote a basic function to clean the text. Let's go over the following code:

```
>>>import nltk
>>>from nltk.corpus import stopwords
>>>from nltk.stem import WordNetLemmatizer
>>>import csv
>>>def preprocessing(text):
      text = text.decode("utf8")
>>>
>>>
       # tokenize into words
       tokens = [word for sent in nltk.sent tokenize(text) for word
>>>
in nltk.word tokenize(sent)]
       # remove stopwords
>>>
       stop = stopwords.words('english')
>>>
>>>
       tokens = [token for token in tokens if token not in stop]
       # remove words less than three letters
>>>
```
```
tokens = [word for word in tokens if len(word) >= 3]
>>>
>>>
       # lower capitalization
>>>
       tokens = [word.lower() for word in tokens]
       # lemmatize
>>>
       lmtzr = WordNetLemmatizer()
>>>
>>>
       tokens = [lmtzr.lemmatize(word) for word in tokens]
       preprocessed text= ' '.join(tokens)
>>>
       return preprocessed text
>>>
```

We have talked about tokenization, lemmatization, and stop words in <u>Chapter 3</u>, *Part of Speech Tagging*. In the following code, I am just parsing the SMS file and cleaning the content to get cleaner text of the SMS. In the next few lines, I created two lists to get all the cleaned content of the SMS and class label. In **ML** (**Machine learning**) terms all the X and Y:

Before moving any further we need to make sure we have scikit-learn installed on the system.

>>>import sklearn

Note

If there is an error you made some error installing scikit. Please go to below link and install scikit:

http://scikit-learn.org/stable/install.html

Sampling

Once we have the entire corpus in the form of lists, we need to perform some form of sampling. Typically, the way to sample the entire corpus in development train sets, dev-test sets, and test sets is similar to the sampling shown in the following figure.

The idea behind the whole exercise is to avoid overfitting. If we feed all the data points to the model, then the algorithm will learn from the entire corpus, but the real test of these algorithms is to perform on unseen data. In very simplistic terms, if we are using the entire data in the model learning process the classifier will perform very good on this data, but it will not be robust. The reason being, we have to tune it to perform the best on the given data, but it doesn't learn how to deal with unknown data.



To solve this kind of a problem, the best way is to divide the entire corpus into two major sets. The development set and test set are kept away for the modeling exercise. We just use the dev set to build and tune the model. Once we are done with the entire modeling exercise, the results are projected based on the test set that we put aside. Now, if the model performs well on this set, we are sure that it's accurate and robust for any new data sample.

Sampling itself is a very complicated and well-researched stream in the machine learning community, and it's a remedy for many data **skewness** and overfitting issues. For simplicity, will use the basic sampling, where we just divide the corpus into a split of 70:30:

```
>>>trainset_size = int(round(len(sms_data)*0.70))
>>># i chose this threshold for 70:30 train and test split.
>>>print 'The training set size for this classifier is ' +
str(trainset_size) + '\n'
>>>x_train = np.array([''.join(el) for el in
sms_data[0:trainset_size]])
>>>y_train = np.array([el for el in sms_labels[0:trainset_size]])
```

```
>>>x_test = np.array([''.join(el) for el in
sms_data[trainset_size+1:len(sms_data)]])
>>>y_test = np.array([el for el in
sms_labels[trainset_size+1:len(sms_labels)]])or el in
sms_labels[trainset_size+1:len(sms_labels)]])
>>>print x_train
>>>print y_train
```

- So what do you think will happen if we use the entire data as training data?
- What will happen when we have a very unbalanced sample?

Note

To understand more about the available sampling techniques, go through

http://scikit-learn.org/stable/modules/classes.html#module-sklearn.cross_validation.

Let's jump to one of the most important things, where we transform the entire text into a vector form. The form is referred to as the **term-document matrix**. If we have to create a term-document matrix for the given example, it will look somewhat like this:

TDM	anymore	call	camera	color	cried	enough	entitled	free	gon	had	latest	mobile
SMS1	0	1	1	1	0	0	1	2	0	1	0	3
SMS2	1	0	0	0	1	1	0	0	1	0	0	0

The representation here of the text document is also known as the **BOW** (**Bag of Word**) representation. This is one of the most commonly used representation in text mining and other applications. Essentially, we are not considering any context between the words to generate this kind of representation.

To generate a similar term-document matrix in Python, we use scikit vectorizers:

```
>>>from sklearn.feature extraction.text import CountVectorizer
>>>sms exp=[ ]
>>>for line in sms list:
>>>
           sms exp.append(preprocessing(line[1]))
>>>vectorizer = CountVectorizer(min df=1)
>>>X exp = vectorizer.fit transform(sms exp)
>>>print "||".join(vectorizer.get feature names())
>>>print X exp.toarray()
                                   1,
                                                     1,
array([[
           1,
                 0,
                       1,
                             1,
                                         0,
                                               0,
                                                           2,
                                   Ο,
                                                     1,
0,
     1,
            0,
                 1,
                       3,
                             1,
                                         0,
                                               0,
                                                           0,
0,
                 0],[ 0, 1, 0, 0,
                                                 Ο,
                                                        1,
     2,
           0,
                                                              1,
                                         Ο,
                                                           1,
0,
     0,
           1,
                 0,
                       1,
                             Ο,
                                   Ο,
                                               1,
                                                     1,
                       1,
Ο,
     1,
           1,
                 0,
                             1,
                                   11)
```

The count vectorizer is a good start, but there is an issue that you will face while using it: longer documents will have higher average count values than shorter documents, even though they might talk about the same topics.

Tip

To avoid these potential discrepancies, it suffices to divide the number of occurrences of each word in a document by the total number of words in the document. This new feature is called **tf** (**Term frequencies**).

Another refinement on top of tf is to downscale weights for words that occur in many documents in the corpus, and are therefore less informative than those that occur only in a smaller portion of the corpus.

This downscaling is called **tf-idf** (**term frequency-inverse document frequency**). Fortunately, scikit also provides a way to achieve the following:

```
>>>from sklearn.feature_extraction.text import TfidfVectorizer
>>>vectorizer = TfidfVectorizer(min_df=2, ngram_range=(1, 2), stop_
words='english', strip_accents='unicode', norm='12')
>>>X_train = vectorizer.fit_transform(x_train)
>>>X_test = vectorizer.transform(x_test)
```

We now have the text in a matrix format the same as we have in any machine learning exercise. Now, X_train and X_test can be used for classification using any machine learning algorithm. Let's talk about some of the most commonly used machine learning algorithms in context of text classification.

Naive Bayes

Let's build your first text classifier. Let's start with a Naive Bayes classifier. Naive Bayes relies on the Bayes algorithm and essentially, is a model of assigning a class label to the sample based on the conditional probability class given by features/attributes. Here we deal with frequencies/bernoulli to estimate prior and posterior probabilities.

 $posterior = \frac{prior \times likelihood}{evidence}.$

The naive assumption here is that all features are independent of each other, which looks counter intuitive in the case of text. However, surprisingly, Naive Bayes performs quite well in most of the real-world use cases.

Another great thing about NB is that it's too simple and very easy to implement and score. We need to store the frequencies and calculate the probabilities. It's really fast in case of training as well as test (scoring). For all these reasons, in most of the cases of text classification, it serves as a benchmark.

Let's write some code to achieve this classifier:



The way to read the confusion matrix is that from all the 1,392 samples in the test set, there were 1205 true positives and 156 true negative cases. However, we also predicted 5 false negatives and 26 false positives. There are different ways of measuring a typical binary classification.

We have given definitions of some of the most common measures used in classification measures:



Here is the classification report:

	Precision	recall	f1-score	support
ham	0.97	1.00	0.98	1210
spam	1.00	0.77	0.87	182
avg / total	0.97	0.97	0.97	1392

With the preceding definition, we can now understand the results clearly. So, effectively, all the preceding metrics look good, which means that our classifier is performing accurately, and is robust. I would highly recommend that you look into the module metrics for more options to analyze the results of the classifier. The most important and balanced metric is the f1 measure (which is nothing but the harmonic mean of precision and recall), which is used widely because it gives a better picture of the coverage and the quality of the classification algorithms. Accuracy intuitively tells us how many true samples have been covered from all the samples. Precision and recall both have significance, while precision talks about how many true positives it got and what else got covered, hand recall gives us details about how accurate we are from the pool of true positives and false negatives.

Note

For more information on various scikit classes visit the following link:

http://scikit-learn.org/stable/modules/classes.html#module-sklearn.metrics

The other more important process we follow to understand our model is to really look deep into the model by looking at the actual features that contribute to the positive and negative classes. I just wrote a very small snippet to generate the top n features and print them. Let's have a look at them:

```
>>>feature_names = vectorizer.get_feature_names()
>>>coefs = clf.coef_
>>>intercept = clf.intercept_
>>>coefs_with_fns = sorted(zip(clf.coef_[0], feature_names))
>>>n = 10
>>>top = zip(coefs_with_fns[:n], coefs_with_fns[:-(n + 1):-1])
```

```
>>>for (coef 1, fn 1), (coef 2, fn 2) in top:
>>>
       print('\t%.4f\t%-15s\t\t%.4f\t%-15s' % (coef 1, fn 1, coef 2,
fn 2))
-9.1602
           10 den
                                    -6.0396
                                                free
-9.1602
           15
                                    -6.3487
                                                txt
-9.1602
                                    -6.5067
           1hr
                                                text
                                    -6.5393
-9.1602
           1st ur
                                                claim
-9.1602
                                    -6.5681
           200
                                                reply
-9.1602
           2marrow
                                    -6.5808
                                               mobile
-9.1602
                                    -6.5858
           2morrow
                                                stop
-9.1602
                                    -6.6124
           2mrw
                                                ur
-9.1602
           2nd innings
                                    -6.6245
                                               prize
-9.1602
                                    -6.7856
           2nd ur
                                                www
```

In the preceding code, I just read all the feature names from the vectorizer, got the coefficients related to the given feature, and then printed the first-10 features. If you want more features, just modify the value of *n*. If we look closely just at the features, we get a lot of information about the model as well as more suggestions about our feature selection and other parameters, such as preprocessing, unigrams/bigrams, stemming, tokenizations, and so on. For example, if you look at the top features of ham you can see that 2morrow, 2nd innings, and some of the digits are coming very significantly. We can see on the positive class (spam) term "free" comes out a very significant term which is intuitive while many spam messages will be about some free offers and deal. Some of the other terms to note are prize, www, claim.

Note

For more details, refer to http://scikitlearn.org/stable/modules/naive_bayes.html.

Decision trees

Decision trees are one of the oldest predictive modeling techniques, where for the given features and target, the algorithm tries to build a logic tree. There are multiple algorithms that exist for decision trees. One of the most famous and widely used algorithm is **CART**.

CART constructs binary trees using this feature, and constructs a threshold that yields the large amount of information from each node. Let's write the code to get a CART classifier:

```
>>>from sklearn import tree
>>>clf = tree.DecisionTreeClassifier().fit(X_train.toarray(),
y_train)
>>>y_tree_predicted = clf.predict(X_test.toarray())
>>>print y_tree_predicted
>>>print ' \n Here is the classification report:'
>>>print classification report(y test, y tree predicted)
```

The only difference is in the input format of the training set. We need to modify the sparse matrix format to a **NumPy** array because the scikit tree module takes only a NumPy array.

Generally, trees are good when the number of features are very less. So, although our results look good here, people hardly use trees in text classification. On the other hand, trees have some really positive sides to them. It is still one the most intuitive algorithms and is very easy to explain and implement. There are many implementations of tree-based algorithms, such as ID3, C4.5, and C5. scikit-learn uses an optimized version of the CART algorithm.

Stochastic gradient descent

Stochastic gradient descent (SGD) is a simple, yet very efficient approach that fits linear models. It is particularly useful when the number of samples (and the number of features) is very large. If you follow the cheat sheet, you will find SGD to be the one-stop solution for many text classification problems. Since it also takes care of regularization and provides different losses, it turns out to be a great choice when experimenting with linear models.

SGD, also known as **Maximum entropy** (**MaxEnt**), provides functionality to fit linear models for classification and regression using different (convex) loss functions and penalties. For example, with loss = log, fits a logistic regression model, while with loss = hinge, it fits a linear support vector machine (SVM).

An example of SGD is as follows:

```
>>>from sklearn.linear_model import SGDClassifier
>>>from sklearn.metrics import confusion_matrix
>>>clf = SGDClassifier(alpha=.0001, n_iter=50).fit(X_train, y_train)
>>>y_pred = clf.predict(X_test)
>>>print '\n Here is the classification report:'
>>>print classification_report(y_test, y_pred)
>>>print ' \n confusion_matrix \n '
>>>cm = confusion_matrix(y_test, y_pred)
>>>print cm
```

Here is the classification report:

	precision	recall	f1-score	support
ham	0.99	1.00	0.99	1210
spam	0.96	0.91	0.93	182
avg / total	0.98	0.98	0.98	1392

Most informative features:

-1.0002	sir	2.3815	ringtoneking
-0.5239	bed	2.0481	filthy
-0.4763	said	1.8576	service
-0.4763	happy	1.7623	story
-0.4763	might	1.6671	txt
-0.4287	added	1.5242	new
-0.4287	list	1.4765	ringtone
-0.4287	morning	1.3813	reply

-0.4287	always	1.3337	message
-0.4287	and	1.2860	call
-0.4287	plz	1.2384	chat
-0.3810	people	1.1908	text
-0.3810	actually	1.1908	real
-0.3810	urgnt	1.1431	video

Logistic regression

Logistic regression is a linear model for classification. It's also known in the literature as logit regression, maximum-entropy classification (MaxEnt), or the log-linear classifier. In this model, the probabilities describing the possible outcomes of a single trial are modeled using a logit function.

As an optimization problem, the L2 binary class' penalized logistic regression minimizes the following cost function:

$$\min_{w,c} \frac{1}{2} w^{T} w + C \sum_{i=1}^{n} \log \left(\exp \left(-y_{i} \left(X_{i}^{T} w + c \right) \right) + 1 \right)$$

Similarly, L1 the binary class' regularized logistic regression solves the following optimization problem:

$$\min_{w,c} \frac{1}{2} \|w\|_{1} + C \sum_{i=1}^{n} \log \left(\exp \left(-y_{i} \left(X_{i}^{T} w + c \right) \right) + 1 \right)$$

Support vector machines

Support vector machines (SVM) is currently the-state-of-art algorithm in the field of machine learning.

SVM is a non-probabilistic classifier. SVM constructs a set of hyperplanes in an infinite-dimensional space, which can be used for classification, regression, or other tasks. Intuitively, a good separation is achieved by a hyperplane that has the largest distance to the nearest training data point of any class (the so-called functional margin), since in general, the larger the margin, the lower the size of classifier.

Let's build one of the most sophisticated supervised learning algorithms with scikit:

```
>>>from sklearn.svm import LinearSVC
>>>svm_classifier = LinearSVC().fit(X_train, y_train)
>>>y_svm_predicted = svm_classifier.predict(X_test)
>>>print '\n Here is the classification report:'
>>>print classification_report(y_test, y_svm_predicted)
```

>>>cm = confusion_matrix(y_test, y_pred) >>>print cm

Here is the classification report for the same:

	precision	recall	f1-score	support
ham	0.99	1.00	0.99	1210
spam	0.97	0.90	0.93	182
avg / total	0.98	0.98	0.98	1392

[[1204

The most informative features:

confusion matrix

-0.9657	road	2.3724	txt
-0.7493	mail	2.0720	claim
-0.6701	morning	2.0451	service
-0.6691	home	2.0008	uk
-0.6191	executive	1.7909	150p
-0.5984	said	1.7374	www
-0.5978	lol	1.6997	mobile
-0.5876	kate	1.6736	50
-0.5754	got	1.5882	ringtone
-0.5642	darlin	1.5629	video
-0.5613	fullonsms	1.4816	tone
-0.5613	fullonsms com	1.4237	prize

These are definitely the best results so far from all the supervised algorithms we have tried. Now with this, I will stop with supervised classifiers. There are millions of books available related to the different machine learning algorithms; even for individual algorithms, there are many books that are available for you. I would highly recommend you to have a deep understanding of any of the preceding algorithms before you use them for any of the real-world applications.

6] [17 165]]

The Random forest algorithm

A random forest is an ensemble classifier that estimates based on the combination of different decision trees. Effectively, it fits a number of decision tree classifiers on various subsamples of the dataset. Also, each tree in the forest built on a random best subset of features. Finally, the act of enabling these trees gives us the best subset of features among all the random subsets of features. Random forest is currently one of best performing algorithms for many classification problems.

An example of Random forest is as follows:

```
>>>from sklearn.ensemble import RandomForestClassifier
>>>RF_clf = RandomForestClassifier(n_estimators=10)
>>>predicted = RF_clf.predict(X_test)
>>>print '\n Here is the classification report:'
>>>print classification_report(y_test, predicted)
>>>cm = confusion_matrix(y_test, y_pred)
>>>print cm
```

Note

People who still want to work with NLTK for text classification. Please go through the following link:

http://www.nltk.org/howto/classify.html

Text clustering

The other family of problems that can come with text is unsupervised classification. One of the most common problem statements you can get is "I have these millions of documents (unstructured data). Is there a way I can group them into some meaningful categories?". Now, once you have some samples of tagged data, we could build a supervised algorithm that we talked about, but here, we need to use an unsupervised way of grouping text documents.

Text clustering is one of the most common ways of unsupervised grouping, also known as, clustering. There are a variety of algorithms available using clustering. I mostly used **k-means** or **hierarchical** clustering. I will talk about both of them and how to use them with a text corpus.

K-means

Very intuitively, as the name suggest, we are trying to find k groups around the mean of the data points. So, the algorithm starts with picking up some random data points as the centroid of all the data points. Then, the algorithm assigns all the data points to it's nearest centroid. Once this iteration is done, recalculation of the centroid happens and these iterations continue until we reach a state where the centroids don't change (algorithm saturate).

There is a variant of the algorithm that uses mini batches to reduce the computation time, while still attempting to optimize the same objective function.

Tip

Mini batches are subsets of the input data randomly sampled in each training iteration. These options should always be tried once your dataset is really huge and you want less training time.

An example of K-means is as follows:

```
>>>from sklearn.cluster import KMeans, MiniBatchKMeans
>>>true k=5
>>>km = KMeans(n clusters=true k, init='k-means++', max iter=100,
n init=1)
>>>kmini = MiniBatchKMeans(n clusters=true k, init='k-means++',
n init=1, init size=1000, batch size=1000, verbose=opts.verbose)
>>># we are using the same test, train data in TFIDF form as we did
in text classification
>>>km model=km.fit(X train)
>>>kmini model=kmini.fit(X train)
>>>print "For K-mean clustering "
>>>clustering = collections.defaultdict(list)
>>>for idx, label in enumerate(km model.labels ):
           clustering[label].append(idx)
>>>
>>>print "For K-mean Mini batch clustering "
>>>clustering = collections.defaultdict(list)
```

>>>for idx, label in enumerate(kmini_model.labels_): >>> clustering[label].append(idx)

In the preceding code, we just imported scikit-learn's kmeans / minibatchkmeans and fitted the same training data that we were using in the running examples. We can also print a cluster for each sample using the last three lines of the code.

Topic modeling in text

The other famous problem in the context of the text corpus is finding the topics of the given document. The concept of topic modeling can be addressed in many different ways. We typically use **LDA** (Latent **Dirichlet allocation**) and LSI (Latent semantic indexing) to apply topic modeling text documents.

Typically, in most of the industries, we have huge volumes of unlabeled text documents. In case of an unlabeled corpus to get the initial insights of the corpus, a topic model is a great option, as it not only gives us topics of relevance, but also categorizes the entire corpus into number of topics given to the algorithm.

We will use a new Python library "gensim" that implements these algorithms for us. So, let's jump to the implementation of LDA and LSI for the same running SMS dataset. Now, the only change to the problem is that we want to model different topics in the SMS data and also want to know which document belongs to which topic. A better and more realistic use case could be to run topic modeling on the entire Wikipedia dump to find different kinds of topics that have been discussed there, or to run topic modeling on billions of reviews/complaints from customers to get an insight of the topics that people discuss.

Installing gensim

One of the easiest ways to install gensim is using a package manager:

```
>>>easy_install -U gensim
```

Otherwise, you can install it using:

>>>pip install gensim

Once you're done with the installation, run the following command:

>>>import gensim

Note

If there is any error, go to

https://radimrehurek.com/gensim/install.html.

Now, let's look at the following code:

```
>>>from gensim import corpora, models, similarities
>>>from itertools import chain
>>>import nltk
>>>from nltk.corpus import stopwords
>>>from operator import itemgetter
>>>import re
```

```
>>>documents = [document for document in sms_data]
>>>stoplist = stopwords.words('english')
>>>texts = [[word for word in document.lower().split() if word not
in stoplist] \ for document in documents]
```

We are just reading the document in our SMS data and removing the stop words. We could use the same method that we did in the previous chapters to do this. Here, we are using a library-specific way of doing things.

Note

Gensim has all the typical NLP features as well provides some great way to create different corpus formats, such as TFIDF, libsvm, market matrix. It also provides conversion of one to another.

In the following code, we are converting the list of documents to a BOW model and then, to a typical **TF-IDF** corpus:

```
>>>dictionary = corpora.Dictionary(texts)
>>>corpus = [dictionary.doc2bow(text) for text in texts]
>>>tfidf = models.TfidfModel(corpus)
>>>corpus_tfidf = tfidf[corpus]
```

Once you have a corpus in the required format, we have the following two methods, where given the number of topics, the model tries to take all the documents from the corpus to build a LDA/LSI model:

```
>>>si = models.LsiModel(corpus_tfidf, id2word=dictionary,
num_topics=100)
>>>#lsi.print_topics(20)
>>>n_topics = 5
>>>lda = models.LdaModel(corpus_tfidf, id2word=dictionary,
num_topics=n_topics)
```

Once the model is built, we need to understand the different topics, what kind of terms represent that topic, and we need to print some top terms related to that topic:

```
>>>for i in range(0, n topics):
           temp = lda.show topic(i, 10)
>>>
           terms = []
>>>
>>>
           for term in temp:
               terms.append(term[1])
>>>
               print "Top 10 terms for topic #" + str(i) + ": "+ ",
>>>
".join(terms)
Top 10 terms for topic #0: week, coming, get, great, call, good,
day, txt, like, wish
Top 10 terms for topic #1: call, ..., later, sorry, 'll, lor, home,
min, free, meeting
Top 10 terms for topic #2: ..., n't, time, got, come, want, get,
wat, need, anything
```

Top 10 terms for topic #3: get, tomorrow, way, call, pls, 're, send, pick, ..., text Top 10 terms for topic #4: ..., good, going, day, know, love, call, yup, get, make

Now, if you look at the output, we have five different topics with clearly different intent. Think about the same exercise for Wikipedia or a huge corpus of web pages, and you will get some meaningful topics that represent the corpus.

References

- <u>http://scikit-learn.org/</u>
- <u>https://radimrehurek.com/gensim/</u>
 <u>https://en.wikipedia.org/wiki/Document_classification</u>

Summary

The idea behind this chapter was to introduce you to the world of text mining. We want to give you a basic introduction to some of the most common algorithms available with text classification and clustering .We know how some of these concept will help you to build really great NLP applications, such as spam filters, domain centric news feeds, web page taxonomy, and so on. Though we have not used NLTK to classify the module in our code snippets, we used NLTK for all the preprocessing steps. We highly recommend you to use scikit-learn over NLTK for any classification problem. In this chapter, we started with machine learning and the types of problems that it can address. We discussed some of the specifics of ML problems in the context of text. We talked about some of the most common classification algorithms that are used for text classification, clustering, and topic modeling. We also give you enough implementation details to get the job done. I still think you need to read a lot about each and every algorithm separately to understand the theory and to gain in-depth understanding of them.

We also provided you an entire pipeline of the process that you need to follow in case of any text mining problem. We covered most of the practical aspects of machine learning, such as sampling, preprocessing, model building, and model evaluation.

The next chapter will also not be directly related to NLTK/NLP, but it will be a great tool for a data scientist/NLP enthusiast. In most of NLP problems, we deal with unstructured text data, and the Web is one of the richest and biggest data sources available for this. Let's learn how to gather data from the Web and how to efficiently use it to build some amazing NLP applications.

Chapter 7. Web Crawling

The largest repository of unstructured text is the Web, and if you know how to crawl it, then you have all the data you need readily available for your experiments. Hence, web crawling is something worth learning for people who are interested in NLTK. This chapter is all about gathering data from the Web.

In this chapter we will use an amazing Python library called **Scrapy** to write our web crawlers. We will provide you all the details to configure different settings that are required. We will write some of the most common spider strategies and many use cases. Scrapy also requires some understanding about **XPath**, crawling, scraping, and some concepts related to the Web in general. We will touch upon these topics and make sure you understand their practical aspects, before really getting in to their implementation. By the end of this chapter, you will have a better understand of web crawler.

- How we can write our own crawler using Scrapy
- Understanding about all the major Scrapy functionality

Web crawlers

One of the biggest web crawler is Google that crawls the entire **World Wide Web** (**WWW**). Google has to traverse every page that exists on the Web and scrape/crawl the entire content.

A web crawler is a computer program that systematically browses the web page by page and also scrapes/crawls the content of the pages. A web crawler can also parse the next set of URLs to be visited from the crawled content. So, if these processes run indefinitely over the entire Web, we can crawl through all the web pages. Web crawlers are interchangeably also called spiders, bots, and scrapers. They all mean the same.

There are a few main points we need to think about before writing our first crawler. Now, every time a web crawler traverses a page, we must decide what kind of content we want to select and what content we want to ignore. For applications such as a search engine, we should ignore all the images, js files, css files, and other files and should concentrate only on HTML content that can be indexed and exposed to the search. In some information extraction engines, we select specific tags or parts of a web page. We also need to extract the URLs if we want to do the crawling recursively. This brings us to the topic of crawling strategy. Here, we need to decide whether we want to go recursively in depth first manner or breadth first manner. We want to follow all the URLs on the next page and then go in depth first manner till we get the URLs, or we should go to all the URLs in the next page and do this recursively.

We also need to make sure that we are not going in the self loop stage because essentially, we traverse a graph in most of the cases. We need to make sure we have a clear revisit strategy for a page. One of the most talked about crawled policies is focused crawling, where we know what kind of domains/topics we are looking for, and the ones that need to be crawled. Some of these issues will be discussed in more detail in the spider section.

Note

Take a look at the video on Udacity at https://www.youtube.com/watch?v=CDXOcvUNBaA.

Writing your first crawler

Let's start with a very basic crawler that will crawl the entire content of a web page. To write the crawlers, we will use Scrapy. Scrapy is a one of the best crawling solutions using Python. We will explore all the different features of Scrapy in this chapter. First, we need to install Scrapy for this exercise.

To do this, type in the following command:

\$ pip install scrapy

This is the easiest way of installing Scrapy using a package manager. Let's now test whether we got everything right or not. (Ideally, Scrapy should now be part of sys.path):

>>> import scrapy

Tip

If there is any error, then take a look at http://doc.scrapy.org/en/latest/intro/install.html.

At this point, we have Scrapy working for you. Let's start with an example spider app with Scrapy:

\$ scrapy startproject tutorial

Once you write the preceding command, the directory structure should look like the following:

```
tutorial/
scrapy.cfg #the project configuration file
tutorial/ #the project's python module, you'll later
import your code from here.
______init___.py
items.py #the project's items file.
pipelines.py #the project's pipelines file.
settings.py # the project's settings file.
spiders/ #a directory where you'll later put your spiders.
_____init___.py
```

The top folder will be given the name of the example tutorial in this case. Then, there is the project configuration file (scrapy.cfg) that will define the kind of setting file that should be used for the project. It also provides the deploy URLs for the project.

Another important part of tutorial setting.py is where we can decide what kind of item pipeline and spider will be used. The item.py and pipline.py are the files that define the data and kind of preprocessing we need to do on the parsed item. The spider folder will contain the different spiders you wrote for the specific URLs.

For our first test spider, we will dump the contents of a news in a local file. We need to create a file named NewsSpider.py, and put it in the path /tutorial/spiders. Let's write the first spider:

```
>>>from scrapy.spider import BaseSpider
>>>class NewsSpider(BaseSpider):
       name = "news"
>>>
>>>
       allowed domains = ["nytimes.com"]
       start URLss = [
>>>
           'http://www.nytimes.com/'
>>>
>>>
        1
>>>def parse(self, response):
>>>
           filename = response.URLs.split("/")[-2]
           open(filename, 'wb').write(response.body)
>>>
```

Once we have this spider ready, we can start crawling using the following command:

\$ scrapy crawl news

After you enter the preceding command, you should see some logs like this:

```
[scrapy] INFO: Scrapy 0.24.5 started (bot: tutorial)
[scrapy] INFO: Optional features available: ssl, http11, boto
[scrapy] INFO: Overridden settings: {'NEWSPIDER_MODULE':
'tutorial.spiders', 'SPIDER_MODULES': ['tutorial.spiders'],
'BOT_NAME': 'tutorial'}
[scrapy] INFO: Enabled extensions: LogStats, TelnetConsole,
CloseSpider, WebService, CoreStats, SpiderState
```

If you don't see logs like the ones shown in the preceding snippet, you have missed something. Check the location of the spider and other Scrapy-related settings, such as the name of the spider matching to the crawl command, and whether setting.py is configured for the same spider and item pipeline or not.

Now, if you are successful, there should be a file in your local folder with the name www.nytimes.com that has the entire web content of the <u>www.nytimes.com</u> page.

Let's see some of the terms that we used in the spider code in more detail:

- name: This is the name of the spider that works as an identifier for Scrapy to look for the spider class. So, the crawl command argument and this name should always match. Also make sure that it's unique and case sensitive.
- start_urls: This is a list of URLs where the spider will begin to crawl. The crawler with start from a seed URL and using the parse() method, it will parse and look for the next URL to crawl. Instead of just a single seed URL, we can provide a list of URLs that can start the crawl.
- parse(): This method is called to parse the data from start URLs. The logic of what kind of element is to be selected for specific attributes of item. This could be as simple as dumping the

entire content of HTML to as complex as many parse methods callable from parse, and different selectors for individual item attributes.

So, the code does nothing but starts with the given URLs (in this case, <u>www.nytimes.com</u>) and crawls the entire content of the page. Typically, a crawler is more complex and will do much more than this; now, let's take a step back and understand what happened behind the scenes. For this, take a look at the following figure:



credit :Scrapy

Data flow in Scrapy

The data flow in Scrapy is controlled by the execution engine and goes like this:

- 1. The process starts with locating the chosen spider and opening the first URL from the list of start_urls.
- 2. The first URL is then scheduled as a request in a scheduler. This is more of an internal to Scrapy.
- 3. The Scrapy engine then looks for the next set of URLs to crawl.
- 4. The scheduler then sends the next URLs to the engine and the engine then forwards it to the downloader using the downloaded middleware. These middlewares are where we place different proxies and user-agent settings.
- 5. The downloader downloads the response from the page and passes it to the spider, where the parse method selects specific elements from the response.
- 6. Then, the spider sends the processed item to the engine.
- 7. The engine sends the processed response to the item pipeline, where we can add some post processing.
- 8. The same process continues for each URL until there are no remaining requests.

The Scrapy shell

The best way to understand Scrapy is to use it through a shell and to get your hands dirty with some of the initial commands and tools provided by Scrapy. It allows you to experiment and develop your XPath expressions that you can put into your spider code.

Tip

To experiment with the Scrapy shell, I would recommend you to install one of the developer tools (**Chrome**) and Firebug (**Mozilla Firefox**) as a plugin. This tool will help us dig down to the very specific part that we want from the web page.

Now, let's start with a very interesting use case where we want to capture the trending topics from Google news (<u>https://news.google.com/</u>).

The steps to follow here are:

- 1. Open <u>https://news.google.com/</u> in your favorite browser.
- 2. Go to the trending topic section on Google news. Then, right-click on and select **Inspect Element** for the first topic, as shown in the following screenshot:



- 3. The moment you open this, there will be a side window that will pop up and you will get a view.
- 4. Search and select the div tag. For this example, we are interested in <div class="topic">.
- 5. Once this is done, you will come to know that we have actually parsed the specific part of the web page, as shown in the following screenshot:



Now, what we actually did manually in the preceding steps can be done in an automated way. Scrapy uses an XML path language called XPath. XPath can be used to achieve this kind of functionality. So, let's see how we can implement the same example using Scrapy.

To use Scrapy, put the following command in you cmd:

\$scrapy shell https://news.google.com/

The moment you hit enter, the response of the Google news page is loaded in the Scrapy shell. Now, let's move to the most important aspect of Scrapy where we want to understand how to look for a specific HTML element of the page. Let's start and run the example of getting topics from Google news that are shown in the preceding image:

In [1]: sel.xpath('//div[@class="topic"]').extract()

The output to this will be as follows:

```
Out[1]:
[<Selector xpath='//div[@class="topic"]' data=u'<div
class="topic"><a href="/news/sectio'>,
<Selector xpath='//div[@class="topic"]' data=u'<div class="topic"><a
href="/news/sectio'>,
<Selector xpath='//div[@class="topic"]' data=u'<div class="topic"><a
href="/news/sectio'>]
```

Now, we need to understand some of the functions that Scrapy and XPath provide to experiment with the shell and then, we need to update our spider to do more sophisticated stuff. Scrapy selectors are built with the help of the lxml library, which means that they're very similar in terms of speed and parsing accuracy.

Let's have a look at some of the most frequently used methods provided for selectors:

- xpath(): This returns a list of selectors, where each of the selectors represents the nodes selected by the XPath expression given as an argument.
- css(): This returns a list of selectors. Here, each of the selectors represent the nodes selected by the CSS expression given as an argument.
- extract():This returns content as a string with the selected data.
- re(): This returns a list of unicode strings extracted by applying the regular expression given as an argument.

I am giving you a cheat sheet of these top 10 selector patterns that can cover most of your work for you. For a more complex selector, if you search the Web, there should be an easy solution that you can use. Let's start with extracting the title of the web page that is very generic for all web pages:

```
In [2] :sel.xpath('//title/text()')
Out[2]: [<Selector xpath='//title/text()' data=u' Google News'>]
```

Now, once you have selected any element, you also want to extract for more processing. Let's extract the selected content. This is a generic method that works with any selector:

```
In [3]: sel.xpath('//title/text()').extract()
Out[3]: [u' Google News']
```

The other very generic requirement is to look for all the elements in the given page. Let's achieve this with this selector:

```
In [4]: sel.xpath('//ul/li')
Out [4] : list of elements (divs and all)
```

We can extract all the titles in the page with this selector:

```
In [5]: sel.xpath('//ul/li/a/text()').extract()
Out [5]: [ u'India',
u'World',
u'Business',
u'Technology',
u'Entertainment',
u'More Top Stories']
```

With this selector, you can extract all the hyperlinks in the web page:

```
In [6]:sel.xpath('//ul/li/a/@href').extract()
Out [6] : List of urls
```

Let's select all the and div elements:

```
In [7]:sel.xpath('td'')
In [8]:divs=sel.xpath("//div")
```

This will select all the divs elements and then, you can loop it:

```
In [9]: for d in divs:
    printd.extract()
```

This will print the entire content of each div in the entire page. So, in case you are not able to get the exact div name, you can also look at the regex-based search.

Now, let's select all div elements that contain the attribute class="topic":

```
In [10]:sel.xpath('/div[@class="topic"]').extract()
In [11]: sel.xpath("//h1").extract()  # this includes the h1
tag
```

This will select all the elements in the page and get the class of those elements:

```
In [12 ] for node in sel.xpath("//p"):
print node.xpath("@class").extract()
Out[12] print all the 
In [13]: sel.xpath("//li[contains(@class, 'topic')]")
Out[13]:
[<Selector xpath="//li[contains(@class, 'topic')]" data=u'<li
class="nav-item nv-FRONTPAGE selecte'>,
<Selector xpath="//li[contains(@class, 'topic')]" data=u'<li
class="nav-item nv-FRONTPAGE selecte'>]
```

Let's write some selector nuggets to get the data from a css file. If we just want to extract the title from the css file, typically, everything works the same, except you need to modify the syntax:

```
In [14] :sel.css('title::text').extract()
Out[14]: [u'Google News']
```

Use the following command to list the names of all the images used in the page:

```
In[15]: sel.xpath('//a[contains(@href, "image")]/img/@src').extract()
Out [15] : Will list all the images if the web developer has put the
images in /img/src
```

Let's see a regex-based selector:

```
In [16 ]sel.xpath('//title').re('(\w+)')
Out[16]: [u'title', u'Google', u'News', u'title']
```

In some cases, removing the namespaces can help us get the right pattern. A selector has an inbuilt remove_namespaces() function to make sure that the entire document is scanned and all the namespaces are removed. Make sure before using it whether we want some of these namespaces to be part of the pattern or not. The following is example of remove_namespaces() function:

```
In [17] sel.remove_namespaces()
sel.xpath("//link")
```

Now that we have more understanding about the selectors, let's modify the same old news spider that we built previously:

```
>>>from scrapy.spider import BaseSpider
>>>class NewsSpider(BaseSpider):
>>> name = "news"
>>> allowed_domains = ["nytimes.com"]
>>> start_URLss = [
>>> 'http://www.nytimes.com/'
>>> ]
>>>def parse(self, response):
>>> sel = Selector(response)
```

```
>>> sites = sel.xpath('//ul/li')
>>> for site in sites:
>>> title = site.xpath('a/text()').extract()
>>> link = site.xpath('a/@href').extract()
>>> desc = site.xpath('text()').extract()
>>> print title, link, desc
```

Here, we mainly modified the parse method, which is one of the core of our spider. This spider can now crawl through the entire page, but we do a more structured parsing of the title, description, and URLs.

Now, let's write a more robust crawler using all the capabilities of Scrapy.

Items

Until now, we were just printing the crawled content on stdout or dumping it in a file. A better way to do this is to define items.py every time we write a crawler. The advantage of doing this is that we can consume these items in our parse method, and this can also give us output in any data format, such as XML, JSON, or CSV. So, if you go back to your old crawler, the items class will have a function like this:

```
>>>fromscrapy.item import Item, Field
>>>class NewsItem(scrapy.Item):
>>>  # define the fields for your item here like:
>>>  # name = scrapy.Field()
>>>  pass
```

Now, let's make it like the following by adding different fields:

```
>>>from scrapy.item import Item, Field
>>>class NewsItem(Item):
>>> title = Field()
>>> link = Field()
>>> desc = Field()
```

Here, we added field() to title, link, and desc. Once we have a field in place, our spider parse method can be modified to parse_news_item, where instead dumping the parsed fields to a file now it can be consumed by an item object.

A Rule method is a way of specifying what kind of URL needs to be crawled after the current one. A Rule method provides SgmlLinkExtractor, which is a way of defining the URL pattern that needs to be extracted from the crawled page. A Rule method also provides a callback method, which is typically a pointer for a spider to look for the parsing method, which in this case is parse_news_item. In case we have a different way to parse, then we can have multiple rules and parse methods. A Rule method also has a Boolean parameter to follow, which specifies whether links should be followed by each response extracted with this rule. If the callback is None, follow defaults to *True*: otherwise, it default to *False*.

One important point to note is that the Rule method does not use parse. This is because the name of the default callback method is parse() and if we use it, we are actually overriding it, and that can stop the functionality of the crawl spider. Now, let's jump on to the following code to understand the preceding methods and parameters:

```
>>>from scrapy.contrib.spiders import CrawlSpider, Rule
>>>from scrapy.contrib.linkextractors.sqml import SqmlLinkExtractor
>>>from scrapy.selector import Selector
>>>from scrapy.item import NewsItem
>>>class NewsSpider(CrawlSpider):
>>>
       name = 'news'
>>>
       allowed domains = ['news.google.com']
       start urls = ['https://news.google.com']
>>>
       rules = (
>>>
>>>
           # Extract links matching cnn.com
>>>
           Rule(SgmlLinkExtractor(allow=('cnn.com', ),
deny=(http://edition.cnn.com/', ))),
          # Extract links matching 'news.google.com'
>>>
          Rule(SgmlLinkExtractor(allow=('news.google.com', )),
>>>
callback='parse news item'),
>>>
       )
       def parse news item(self, response):
>>>
           sel = Selector(response)
>>>
>>>
           item = NewsItem()
           item['title'] = sel.xpath('//title/text()').extract()
>>>
           item[topic] = sel.xpath('/div[@class="topic"]').extract()
>>>
>>>
           item['desc'] = sel.xpath('//td//text()').extract()
>>>
           return item
```

The Sitemap spider

If the site provides sitemap.xml, then a better way to crawl the site is to use SiteMapSpider instead.

Here, given sitemap.xml, the spider parses the URLs provided by the site itself. This is a more polite way of crawling and good practice:

```
>>>from scrapy.contrib.spiders import SitemapSpider
>>>class MySpider(SitemapSpider):
>>>
       sitemap URLss = ['http://www.example.com/sitemap.xml']
       sitemap rules = [('/electronics/', 'parse electronics'),
>>>
('/apparel/', 'parse apparel'),]
       def 'parse electronics'(self, response):
>>>
>>>
           # you need to create an item for electronics,
>>>
           return
       def 'parse apparel'(self, response):
>>>
>>>
           #you need to create an item for apparel
>>>
           return
```

In the preceding code, we wrote one parse method for each product category. It's a great use case if you want to build a price aggregator/comparator. You might want to parse different attributes for different products, for example, for electronics, you might want to scrape the tech specification, accessory, and price; while for apparels, you are more concerned about the size and color of the item. Try your hand at using one of the retailer sites and use shell to get the patterns to scrape the size, color, and price of different items. If you do this, you should be in a good shape to write your first industry standard spider.

In some cases, you want to crawl a website that needs you to log in before you can enter some parts of the website. Now, Scrapy has a workaround that too. They implemented FormRequest, which is more of a **POST** call to the HTTP server and gets the response. Let's have a deeper look into the following spider code:

```
>>>class LoginSpider(BaseSpider):
>>>
       name = 'example.com'
       start URLss = ['http://www.example.com/users/login.php']
>>>
       def parse(self, response):
>>>
           return [FormRequest.from response(response,
>>>
formdata={'username': 'john', 'password': 'secret'},
callback=self.after login)]
       def after login(self, response):
>>>
           # check login succeed before going on
>>>
          if "authentication failed" in response.body:
>>>
               self.log("Login failed", level=log.ERROR)
>>>
>>>
             return
```

For a website that requires just the username and password without any captcha, the preceding code should work just by adding the specific login details. This is the part of the parse method since you need to log in the first page in the most of the cases. Once you log in, you can write your own after login callback method with items and other details.

The item pipeline

Let's talk about some more item postprocessing. Scrapy provides a way to define a pipeline for items as well, where you can define the kind of post processing an item has to go through. This is a very methodical and good program design.

We need to build our own item pipeline if we want to post process scraped items, such as removing noise and case conversion, and in other cases, where we want to derive some values from the object, for example, to calculate the age from DOB or to calculate the discount price from the original price. In the end, we might want to dump the item separately into a file.

The way to achieve this will be as follows:

1. We need to define an item pipeline in setting.py:

```
ITEM_PIPELINES = {
    'myproject.pipeline.CleanPipeline': 300,
    'myproject.pipeline.AgePipeline': 500,
    'myproject.pipeline.DuplicatesPipeline: 700,
    'myproject.pipeline.JsonWriterPipeline': 800,
}
```

2. Let's write a class to clean the items:

```
>>>from scrapy.exceptions import Item
>>>import datetime
>>>class AgePipeline(object):
>>> def process_item(self, item, spider):
>>> if item['DOB']:
>>> item['Age'] =
(datetime.datetime.strptime(item['DOB'],
'%d-%m-%y').date()-datetime.datetime.strptime('currentdate,
'%d-%m-%y').date()).days/365
>>> return item
```

3. We need to derive the age from DOB. We used Python's date functions to achieve this:

```
>>>from scrapy import signals
>>>from scrapy.exceptions import Item
>>>class DuplicatesPipeline(object):
>>> def __init__(self):
>>> self.ids_seen = set()
>>> def process_item(self, item, spider):
>>> if item['id'] in self.ids_seen:
>>> raise DropItem("Duplicate item found: %s" % item)
>>> else:
```

>>> self.ids_seen.add(item['id'])
>>> return item

4. We also need to remove the duplicates. Python has the set() data structure that only contains unique values, we can create a pipline DuplicatesPipeline.py like below using Scrapy :

```
>>>from scrapy import signals
>>>from scrapy.exceptions import Item
>>>class DuplicatesPipeline(object):
       def __init__(self):
>>>
>>>
           self.ids seen = set()
       def process item(self, item, spider):
>>>
           if item['id'] in self.ids seen:
>>>
               raise DropItem("Duplicate item found: %s" % item)
>>>
>>>
           else:
>>>
               self.ids seen.add(item['id'])
>>>
               return item
```

5. Let's finally write the item in the JSON file using JsonWriterPipeline.py pipeline:

```
>>>import json
>>>class JsonWriterPipeline(object):
>>> def __init__(self):
>>> self.file = open('items.txt', 'wb')
>>> def process_item(self, item, spider):
>>> line = json.dumps(dict(item)) + "\n"
>>> self.file.write(line)
>>> return item
```

External references

I encourage you to follow some simple spiders and try building some cool applications using these spiders. I would also like you to look at the following links for reference:

- <u>http://doc.scrapy.org/en/latest/intro/tutorial.html</u>
- <u>http://doc.scrapy.org/en/latest/intro/overview.html</u>

Summary

In this chapter, you learned about another great Python library and now, you don't need help from anybody for your data needs. You learned how you can write a very sophisticated crawling system, and now you know how to write a focused spider. In this chapter, we saw how to abstract the item logic from the main system and how to write some specific spider for the most common use cases. We know some of the most common settings that need to be taken care of in order to implement our own spider and we wrote some complex parse methods that can be reused. We understand selectors very well and know a hands-on way of figuring out what kind of elements we want for specific item attributes, and we also went through Firebug to get more of a practical understanding of selectors. Last but not least, very importantly, make sure that you follow the security guidelines of the websites you crawl.

In the next chapter, we will explore some essential Python libraries that can be used for natural language processing and machine learning.

Chapter 8. Using NLTK with Other Python Libraries

In this chapter, we will explore some of the backbone libraries of Python for machine learning and natural language processing. Until now, we have used NLTK, Scikit, and genism, which had very abstract functions, and were very specific to the task in hand. Most of statistical NLP is heavily based on the vector space model, which in turn depends on basic linear algebra covered by NumPy. Also many NLP tasks, such as POS or NER tagging, are really classifiers in disguise. Some of the libraries we will discuss are heavily used in all these tasks.

The idea behind this chapter is to give you a quick overview of some the most fundamental Python libraries. This will help us understand more than just the data structure, design, and math behind some of the coolest libraries, such as NLTK and Scikit, which we have discussed in the previous chapters.

We will look at the following four libraries. I have tried to keep it short, but I highly encourage you to read in more detail about these libraries if you want Python to be a one-stop solution to most of your data science needs.

- NumPy (Numeric Python)
- SciPy (Scientific Python)
- Pandas (Data manipulation)
- Matplotlib (Visualization)

NumPy

NumPy is a Python library for dealing with numerical operations, and it's really fast. NumPy provides some of the highly optimized data structures, such as ndarrays. NumPy has many functions specially designed and optimized to perform some of the most common numeric operations. This is one of the reasons NLTK, scikit-learn, pandas, and other libraries use NumPy as a base to implement some of the algorithms. This section will give you a brief summary with running examples of NumPy. This will not just help us understand the fundamental data structures beneath NLTK and other libraries, but also give us the ability to customize some of these functionalities to our needs.

Let's start with discussion on ndarrays, how they can be used as matrices, and how easy and efficient it is to deal with matrices in NumPy.

ndarray

An ndarray is an array object that represents a multidimensional, homogeneous array of fixed-size items.

We will start with building an ndarray using an ordinary Python list:

```
>>>x=[1,2,5,7,3,11,14,25]
>>>import numpy as np
>>>np_arr=np.array(x)
>>>np arr
```
As you can see, this is a linear 1D array. The real power of Numpy comes with 2D arrays. Let's move to 2D arrays. We will create one using a Python list of lists.

```
>>>arr=[[1,2],[13,4],[33,78]]
>>>np_2darr= np.array(arr)
>>>type(np_2darr)
numpy.ndarray
```

Indexing

The ndarray is indexed more like Python containers. NumPy provides a slicing method to get different views of the ndarray.

```
>>>np 2darr.tolist()
[[1, 2], [13, 4], [33, 78]]
>>>np 2darr[:]
array([[1, 2], [13, 4], [33, 78]])
>>>np 2darr[:2]
array([[1, 2], [13, 4]])
>>>np 2darr[:1]
array([[1, 2]])
>>>np 2darr[2]
array([33, 78])
     np 2darr[2][0]
>>>
>>>33
     np 2darr[:-1]
>>>
array([[1, 2], [13, 4]])
```

Basic operations

NumPy also has some other operations that can be used in various numeric processing. In this example, we want to get an array with values ranging from 0 to 10 with a step size of 0.1. This is typically required for any optimization routine. Some of the most common libraries, such as Scikit and NLTK, actually use these NumPy functions.

>>>import numpy as np
>>>>np.arange(0.0, 1.0, 0.1)
array([0. , 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9,
1]

We can do something like this, and generate a array with all ones and all zeros:

```
>>>np.ones([2, 4])
array([[1., 1., 1., 1.], [1., 1., 1., 1.]])
>>>np.zeros([3,4])
array([[0., 0., 0., 0.], [0., 0., 0., 0.], [0., 0., 0., 0.]])
```

Wow!

If you have done higher school math, you know that we need all these matrixes to perform many algebraic operations. And guess what, most of the Python machine learning libraries also do that!

>>>np.linspace(0, 2, 10)
array([0., 0.22222222, 0.44444444, 0.666666667,
0.88888889, 1.11111111, 1.33333333, 1.55555556,
1.77777778, 2,])

The linespace function returns number samples which are evenly spaced, calculated over the interval from the start and end values. In the given example we were trying to get 10 sample in the range of 0 to 2.

Similarly, we can do this at the log scale. The function here is:

>>>np.logsp	ace	(0,1)			
array([1.,	1	.04811313,	1.09854114,	1.1513954,
7.90604321,		8.28	642773,	8.68511374,	9.10298178,
9.54095476,		10.,])		

You can still execute Python's help function to get more details about the parameter and the return values.

```
>>>help(np.logspace)
Help on function logspace in module NumPy.core.function_base:
```

```
logspace(start, stop, num=50, endpoint=True, base=10.0)
Return numbers spaced evenly on a log scale.
```

In linear space, the sequence starts at ``base ** start`` (`base` to the power of `start`) and ends with ``base ** stop`` (see `endpoint` below).

Parameters ----start : float

So we have to provide the start and end and the number of samples we want on the scale; in this case, we also have to provide a base.

Extracting data from an array

We can do all sorts of manipulation and filtering on the ndarrays. Let's start with a new Ndarray, A:

```
>>>A = array([[0, 0, 0], [0, 1, 2], [0, 2, 4], [0, 3, 6]])
>>>B = np.array([n for n in range n for n in range(4)])
```

>>>B array([0, 1, 2, 3])

We can do this kind of conditional operation, and it's very elegant. We can observe this in the following example:

```
>>>less_than_3 = B<3 # we are filtering the items that are less than
3.
>>>less_than_3
array([ True, True, True, False], dtype=bool)
>>>B[less_than_3]
array([0, 1, 2])
```

We can also assign a value to all these values, as follows:

>>>B[less_than_3] = 0
>>>: B
array([0, 0, 0, 3])

There is a way to get the diagonal of the given matrix. Let's get the diagonal for our matrix A:

>>>np.diag(A) array([0, 1, 4])

Complex matrix operations

One of the common matrix operations is element-wise multiplication, where we will multiply one element of a matrix by an element of another matrix. The shape of the resultant matrix will be same as the input matrix, for example:

>>>A = np.array([[1,2],[3,4]])
>>>A * A
array([[1, 4], [9, 16]])

Note

However, we can't perform the following operation, which will throw an error when executed:

>>>A * B
-----ValueError Traceback (most recent call last)
<ipython-input-53-e2f71f566704> in <module>()
----> 1 A*B

ValueError: Operands could not be broadcast together with shapes (2,2) (4,).

Simply, the numbers of columns of the first operand have to match the number of rows in the second operand for matrix multiplication to work.

Let's do the dot product, which is the backbone of many optimization and algebraic operations. I still feel doing this in a traditional environment was not very efficient. Let's see how easy it is in NumPy, and how super-efficient it is in terms of memory.

```
>>>np.dot(A, A)
array([[ 7, 10], [15, 22]])
```

We can do operations like add, subtract, and transpose, as shown in the following example:

```
>>A - A
array([[0, 0], [0, 0]])
>>>A + A
array([[2, 4], [6, 8]])
>>>np.transpose(A)
array([[1, 3], [2, 4]])
>>>A
array([[1, 2], [2, 3]])
```

The same transpose operations can be performed using an alternative operation, such as this:

>>>A.T array([[1, 3], [2, 4]])

We can also cast these ndarrays into a matrix and perform matrix operations, as shown in the following example:

```
>>>M = np.matrix(A)
>>>M
matrix([[1, 2], [3, 4]])
>>> np.conjugate(M)
matrix([[1, 2], [3, 4]])
>>> np.invert(M)
matrix([[-2, -3], [-4, -5]])
```

We can perform all sorts of complex matrix operations with NumPy, and they are pretty simple to use too! Please have a look at documentation for more information on NumPy.

Let's switch back to some of the common mathematics operations, such as min, max, mean, and standard deviation, for the given array elements. We have generated the normal distributed random numbers. Let's see how these things can be applied there:

```
>>>N = np.random.randn(1,10)
>>>N
array([[ 0.59238571, -0.22224549, 0.6753678,
0.48092087, -0.37402105, -0.54067842, 0.11445297,
```

```
-0.02483442, -0.83847935, 0.03480181, ]])
>>>N.mean()
-0.010232957191371551
>>>N.std()
0.47295594072935421
```

This was an example demonstrating how NumPy can be used to perform simple mathematic and algebraic operations of finding out the mean and standard deviation of a set of numbers.

Reshaping and stacking

In case of some of the numeric, algebraic operations we do need to change the shape of resultant matrix based on the input matrices. NumPy has some of the easiest ways of reshaping and stacking the matrix in whichever way you want.

>>>A array([[1, 2], [3, 4]])

If we want a flat matrix, we just need to reshape it using NumPy's reshape() function:

```
>>>(r, c) = A.shape # r is rows and c is columns
>>>r,c
(2L, 2L)
>>>A.reshape((1, r * c))
array([[1, 2, 3, 4]])
```

This kind of reshaping is required in many algebraic operations. To flatten the ndarray, we can use the flatten() function:

>>>A.flatten() array([1, 2, 3, 4])

There is a function to repeat the same elements of the given array. We need to just specify the number of times we want the element to repeat. To repeat the ndarray, we can use the repeat () function:

```
>>>np.repeat(A, 2)
array([1, 1, 2, 2, 3, 3, 4, 4])
>>>>A
array([[1, 2],[3, 4]])
```

In the preceding example, each element is repeated twice in sequence. A similar function known as tile() is used for for repeating the matrix, and is shown here:

>>>np.tile(A, 4) array([[1, 2, 1, 2, 1, 2, 1, 2], [3, 4, 3, 4, 3, 4, 3, 4]])

There are also ways to add a row or a column to the matrix. If we want to add a row, we use the concatenate() function shown here:

```
>>>B = np.array([[5, 6]])
>>>np.concatenate((A, B), axis=0)
array([[1, 2], [3, 4], [5, 6]])
```

This can also be achieved using the Vstack() function shown here:

```
>>>np.vstack((A, B))
array([[1, 2], [3, 4], [5, 6]])
```

Also, if you want to add a column, you can use the concatenate () function in the following manner:

```
>>>np.concatenate((A, B.T), axis=1)
array([[1, 2, 5], [3, 4, 6]])
```

Tip

Alternatively, the hstack() function can be used to add columns. This is used very similarly to the vstack() function in the example shown above.

Random numbers

Random number generation is also used across many tasks involving NLP and machine learning tasks. Let's see how easy it is to get a random sample:

```
>>>from numpy import random
>>>#uniform random number from [0,1]
>>>random.rand(2, 5)
array([[ 0.82787406, 0.21619509, 0.24551583, 0.91357419,
0.39644969], [ 0.91684427, 0.34859763, 0.87096617, 0.31916835,
0.09999382]])
```

There is one more function called random.randn(), which generates normally distributed random numbers in the given range. So, in the following example, we want random numbers between 2 and 5.

```
>>>random.randn(2, 5)
array([[-0.59998393, -0.98022613, -0.52050449, 0.73075943,
-0.62518516], [ 1.00288355, -0.89613323, 0.59240039, -0.89803825,
0.11106479]])
```

This is achieved by using the function random.randn(2,5).

SciPy

Scientific Python or SciPy is a framework built on top of NumPy and ndarray and was essentially developed for advanced scientific operations such as optimization, integration, algebraic operations, and Fourier transforms.

The concept was to efficiently use ndarrays to provide some of these common scientific algorithms in a memory-efficient manner. Because of NumPy and SciPy, we are in a state where we can focus on writing libraries such as scikit-learn and NLTK, which focus on domain-specific problems, while NumPy / SciPy do the heavy lifting for us. We will give you a brief overview of the data structures and common operations provided in SciPy. We get the details of some of the black-box libraries, such as scikit-learn and understand what goes on behind the scenes.

>>>import scipy as sp

This is how you import SciPy. I am using sp as an alias but you can import everything.

Let's start with something we are more familiar with. Let's see how integration can be achieved here, using the quad() function.

```
>>>from scipy.integrate import quad, dblquad, tplquad
>>>def f(x):
>>> return x
>>>x_lower == 0 # the lower limit of x
>>>x_upper == 1 # the upper limit of x
>>>val, abserr = = quad(f, x_lower, x_upper)
>>>print val,abserr
>>> 0.5 , 5.55111512313e-15
```

If we integrate the x, it will be $x^{2/2}$, which is 0.5. There are other scientific functions, such as these:

- Interpolation (scipy.interpolate)
- Fourier transforms (scipy.fftpack)
- Signal processing (scipy.signal)

But we will focus on only linear algebra and optimization because these are more relevant in the context of machine learning and NLP.

Linear algebra

The linear algebra module contains a lot of matrix-related functions. Probably the best contribution of SciPy is sparse matrix (CSR matrix), which is used heavily in other packages for manipulation of matrices.

SciPy provides one of the best ways of storing sparse matrices and doing data manipulation on them. It also provides some of the common operations, such as linear equation solving. It has a great way of solving eigenvalues and eigenvectors, matrix functions (for example, matrix exponentiation), and more

complex operations such as decompositions (SVD). Some of these are the behind-the-scenes optimization in our ML routines. For example, SVD is the simplest form of LDA (topic modeling) that we used in <u>Chapter 6</u>, *Text Classification*.

The following is an example showing how the linear algebra module can be used:

```
>>>A = = sp.rand(2, 2)
>>>B = = sp.rand(2, 2)
>>>import Scipy
>>>X = = solve(A, B)
>>>from Scipy import linalg as LA
>>>X = = LA.solve(A, B)
>>>LA.dot(A, B)
```

Note

Detailed documentation is available at http://docs.scipy.org/doc/scipy/reference/linalg.html.

eigenvalues and eigenvectors

In some of the NLP and machine learning applications, we represent the documents as term document matrices. Eigenvalues and eigenvectors are typically calculated for many different mathematical formulations. Say A is our matrix, and there exists a vector v such that $Av = \lambda v$.

In this case, λ will be our eigenvalue and v will be our eigenvector. One of the most commonly used operation, the **singular value decomposition** (**SVD**)will require some calculus functionality. It's quite simple to achieve this in SciPy.

```
>>>evals = LA.eigvals(A)
>>>evals
array([-0.32153198+0.j, 1.40510412+0.j])
```

And eigen vectors are as follows:

>>>evals, evect = LA.eig(A)

We can perform other matrix operations, such as inverse, transpose, and determinant:

```
>>>LA.inv(A)
array([[-1.24454719, 1.97474827], [ 1.84807676, -1.15387236]])
>>>LA.det(A)
-0.4517859060209965
```

The sparse matrix

In a real-world scenario, when we use a typical matrix, most of the elements of this matrix are zeroes. It is highly inefficient to go over all these non-zero elements for any matrix operation. As a solution to this

kind of problem, a sparse matrix format has been introduced, with the simple idea of storing only non-zero items.

A matrix in which most of the elements are non-zeroes is called a dense matrix, and the matrix in which most of the elements are zeroes is called a sparse matrix.

A matrix is typically a 2D array with an index of row and column will provide the value of the element. Now there are different ways in which we can store sparse matrices:

- **DOK** (**Dictionary of keys**): Here, we store the dictionary with keys in the format (*row*, *col*) and the values are stored as dictionary values.
- LOL (list of list): Here, we provide one list per row, with only an index of the non-zero elements.
- COL (Coordinate list): Here, a list (row, col, value) is stored as a list.
- CRS/CSR (Compressed row Storage): A CSR matrix reads values first by column; a row index is stored for each value, and column pointers are stored (*val*, *row_ind*, *col_ptr*). Here, *val* is an array of the non-zero values of the matrix, *row_ind* represents the row indices corresponding to the values, and *col_ptr* is the list of *val* indexes where each column starts. The name is based on the fact that column index information is compressed relative to the COO format. This format is efficient for arithmetic operations, column slicing, and matrix-vector products.

Note

See <u>http://docs.scipy.org/doc/scipy-0.15.1/reference/generated/scipy.sparse.csr_matrix.html</u> for more information.

• CSC (sparse column): This is similar to CSR, except that the values are read first by column; a row index is stored for each value, and column pointers are stored. In otherwords, CSC is (*val*, *row_ind*, *col_ptr*).

Note

Have a look at the documentation at:

http://docs.scipy.org/doc/scipy-0.15.1/reference/generated/scipy.sparse.csc_matrix.html

Let's have some hands-on experience with CSR matrix manipulation. We have a sparse matrix A:

```
>>>from scipy import sparse as s
>>>A = array([[1,0,0],[0,2,0],[0,0,3]])
>>>A
array([[1, 0, 0], [0, 2, 0], [0, 0, 3]])
>>>from scipy import sparse as sp
>>>C = = sp.csr_matrix(A);
>>>C
<3x3 sparse matrix of type '<type 'NumPy.int32'>'
with 3 stored elements in Compressed Sparse Row format>
```

If you read very carefully, the CSR matrix stored just three elements. Let's see what it stored:

```
>>>C.toarray()
array([[1, 0, 0], [0, 2, 0], [0, 0, 3]])
>>>C * C.todense()
matrix([[1, 0, 0], [0, 4, 0], [0, 0, 9]])
```

This is exactly what we are looking for. Without going over all the zeroes, we still got the same results with the CSR matrix.

```
>>>dot(C, C).todense()
```

Optimization

I hope you understand that every time we have built a classifier or a tagger in the background, all these are some sort of optimization routine. Let's have some basic understanding about the function provided in SciPy. We will start with getting a minima of the given polynomial. Let's jump to one of the example snippets of the optimization routine provided by SciPy.

```
>>>def f(x):
>>> returnx return x**2-4
>>>optimize.fmin_bfgs(f,0)
Optimization terminated successfully.
Current function value: -4.000000
Iterations: 0
Function evaluations: 3
Gradient evaluations: 1
array([0])
```

Here, the first argument is the function you want the minima of, and the second is the initial guess for the minima. In this example, we already knew that zero will be the minima. To get more details, use the function help(), as shown here:

To summarize, we now have enough knowledge about SciPy's most basic data structures, and some of the most common optimization techniques. The intention was to motivate you to not just run black-box machine learning or natural language processing, but to go beyond that and get the mathematical context about the ML algorithms you are using and also have a look at the source code and try to understand it.

Implementing this will not just help your understanding about the algorithm, but also allow you to optimize/customize the implementation to your need.

pandas

Let's talk about pandas, which is one of the most exciting Python libraries, especially for people who love \mathbf{R} and want to play around with the data in a more vectorized manner. We will devote this part of the chapter only to pandas; we will discuss some basic data manipulation and handling in pandas frames.

Reading data

Let's start with one of the most important tasks in any data analysis to parse the data from a CSV/other file.

Tip

I am using https://archive.ics.uci.edu/ml/machine-learning-databases/adult/adult.data

https://archive.ics.uci.edu/ml/machine-learning-databases/iris/iris.names

Feel free to use any other CSV file.

To begin, please download the data to your local storage from the preceding links, and load it into a pandas data-frame, as shown here:

```
>>>import pandas as pd
>>># Please provide the absolute path of the input file
>>>data = pd.read_csv("PATH\\iris.data.txt",header=0")
>>>data.head()
```

	4.9	3.0	1.4	0.2	Iris-setosa
0	4.7	3.2	1.3	0.2	Iris-setosa
1	4.6	3.1	1.5	0.2	Iris-setosa
2	5.0	3.6	1.4	0.2	Iris-setosa

This will read a CSV file and store it in a DataFrame. Now, there are many options you have while reading a CSV file. One of the problems is that we read the first line of the data in this DataFrame as a header; to use the actual header, we need to set the option header to None, and pass a list of names as column names. If we already have the header in perfect form in the CSV, we don't need to worry about the header as pandas, by default, assumes the first line to be the header. The header 0 in the preceding code is actually the row number that will be treated as the header.

So let's use the same data, and add the header into the frame:

>>>data = pd.read_csv("PATH\\iris.data.txt", names=["sepal length",
"sepal width", "petal length", "petal width", "Cat"], header=None)
>>>data.head()

	sepal length	sepal width	petal length	petal width	Cat
0	4.9	3.0	1.4	0.2	Iris-setosa
1	4.7	3.2	1.3	0.2	Iris-setosa
2	4.6	3.1	1.5	0.2	Iris-setosa

This has created temporary column names for the frame so that, in case you have headers in the file as a first row, you can drop the header option, and pandas will detect the first row of the file as the header. The other common options are Sep/Delimiter, where you want to specify the delimiter used to separate the columns. There are at least 20 different options available, which can be used to optimize the way we read and cleanse our data, for example removing Na's, removing blank lines, and indexing based on the specific column. Please have a look at the different type of files:

- read csv: reading a CSV file.
- read_excel: reading a XLS file.
- read_hdf: reading a HDFS file.
- read_sql: reading a SQL file.
- read_json: reading a JSON file.

These can be the substitutes for all the different parsing methods we discussed in <u>Chapter 2</u>, *Text Wrangling and Cleansing*. The same numbers of options are available to write files too.

Now let's see the power of pandas frames. If you are an R programmer, you would love to see the summary and header option we have in R.

>>>data.describe()

The describe() function will give you a brief summary of each column and the unique values.

>>sepal_len_cnt=data['sepal length'].value_counts() >>>sepal_len_cnt

5.0 10 6.3 9 6.7 8 5.7 8 5.1 8 dtype: int64

```
>>>data['Iris-setosa'].value_counts()
Iris-versicolor 50
Iris-virginica 50
Iris-setosa 48
dtype: int64
```

Again for R lovers, we are now dealing with vectors, so that we can look for each value of the column by using something like this:

```
>>>data['Iris-setosa'] == 'Iris-setosa'
0 True
1 True
147 False
148 False
Name: Iris-setosa, Length: 149, dtype: bool
```

Now we can filter the DataFrame in place. Here the setosa will have only entries related to Irissetosa.

```
>>>sntsosa=data[data['Cat'] == 'Iris-setosa']
>>>sntsosa[:5]
```

This is our typical SQL Group By function. We have all kinds of aggregate functions as well.

Note

You can browse through the following link to look at Dow Jones data:

https://archive.ics.uci.edu/ml/machine-learning-databases/00312/

Series data

Pandas also have a neat way of indexing by date, and then using the frame for all sorts of time series kind of analysis. The best part is that once we have indexed the data by date some of the most painful operations on the dates will be a command away from us. Let's take a look at series data, such as stock price data for a few stocks, and how the values of the opening and closing stock change weekly.

```
>>>import pandas as pd
>>>stockdata =
pd.read_csv("dow_jones_index.data",parse_dates=['date'],
index_col=['date'], nrows=100)
>>>stockdata.head()
```

date	quarter	stock	open	high	low	close	volume	percent_change_price
01/07/2011	1	AA	\$15.82	\$16.72	\$15.78	\$16.42	239655616	3.79267
01/14/2011	1	AA	\$16.71	\$16.71	\$15.64	\$15.97	242963398	-4.42849
01/21/2011	1	AA	\$16.19	\$16.38	\$15.60	\$15.79	138428495	-2.47066

```
>>max(stockdata['volume'])
    1453438639
>>>max(stockdata['percent_change_price'])
    7.621739999999991
>>>stockdata.index
<class 'pandas.tseries.index.DatetimeIndex'>
[2011-01-07, ..., 2011-01-28]
Length: 100, Freq: None, Timezone: None
>>>stockdata.index.day
array([ 7, 14, 21, 28, 4, 11, 18, 25, 4, 11, 18, 25, 7, 14, 21, 28,
4,11, 18, 25, 4, 11, 18, 25, 7, 14, 21, 28, 4])
```

The preceding command gives the day of the week for each date.

>>>stockdata.index.month

The preceding command lists different values by month.

>>>stockdata.index.year

The preceding command lists different values by year.

You can aggregate the data using a resample with whatever aggregation you want. It could be sum, mean, median, min, or max.

```
>>>import numpy as np
>>>stockdata.resample('M', how=np.sum)
```

Column transformation

Say we want to filter out columns or to add a column. We can achieve this by just by providing a list of columns as an argument to axis 1. We can drop the columns from a data frame like this:

>>>stockdata.drop(["percent_change_volume_over_last_wk"],axis=1)

Let's filter out some of the unwanted columns, and work with a limited set of columns. We can create a new DataFrame like this:

```
>>>stockdata_new = pd.DataFrame(stockdata,
columns=["stock","open","high","low","close","volume"])
>>>stockdata_new.head()
```

We can also run R-like operations on the columns. Say I want to rename the columns. I can do something like this:

>>stockdata["previous_weeks_volume"] = 0

This will change all the values in the column to 0. We can do it conditionally and create derived variables in place.

Noisy data

A typical day in the life of a data scientist starts with data cleaning. Removing noise, cleaning unwanted files, making sure that date formats are correct, ignoring noisy records, and dealing with missing values. Typically, the biggest chunk of time is spent on data cleansing rather than on any other activity.

In a real-world scenario, the data is messy in most cases, and we have to deal with missing values, null values, Na's, and other formatting issues. So one of the major features of any data library is to deal with all these problems and address them in an efficient way. pandas provide some amazing features to deal with some of these problems.

>>>stockdata.head() >>>stockdata.dropna().head(2)

Using the preceding command we get rid of all the Na's from our data.

date	quarter	Stock	open	high	low	close	volume	percent_change_price
01/14/2011	1	AA	\$16.71	\$16.71	\$15.64	\$15.97	242963398	-4.42849
01/21/2011	1	AA	\$16.19	\$16.38	\$15.60	\$15.79	138428495	-2.47066
01/28/2011	1	AA	\$15.87	\$16.63	\$15.82	\$16.13	151379173	1.63831

You also noticed that we have a \$ symbol in front of the value, which makes the numeric operation hard. Let's get rid of that, as it will give us noisy results otherwise (for example. \$43.86 is not among the top values here).

>>>import numpy
>>>stockdata_new.open.describe()
count 100
unique 99
top \$43.86
freq 2
Name: open, dtype: object

We can perform some operations on two columns, and derive a new variable out of this:

```
>>>stockdata_new.open = stockdata new.open.str.replace('$',
'').convert objects(convert numeric=True)
>>>stockdata new.close = stockdata new.close.str.replace('$',
'').convert objects(convert numeric=True)
>>>(stockdata new.close -
stockdata new.open).convert objects(convert numeric=True)
>>stockdata new.open.describe()
count
         100.000000
mean
          51.286800
          32.154889
std
          13.710000
min
          17.705000
25%
50%
          46.040000
75%
          72.527500
max
         106.900000
Name: open, dtype: float64
```

We can also perform some arithmetic operations, and create new variables out of it.

>>>stockdata_new['newopen'] = stockdata_new.open.apply(lambda x: 0.8 * x) >>>stockdata new.newopen.head(5)

We can filter the data on the value of a column in this way too. For example, let's filter out a dataset for one of the companies among all those that we have the stock values for.

>>>stockAA = stockdata_new.query('stock=="AA"') >>>stockAA.head()

To summarize, we have seen some useful functions related to data reading, cleaning, manipulation, and aggregation in this section of pandas. In the next section, will try to use some of these data frames to generate visualization out of this data.

matplotlib

matplotlib is a very popular visualization library written in Python. We will cover some of the most commonly used visualizations. Let's start by importing the library:

```
>>>import matplotlib
>>>import matplotlib.pyplot as plt
>>>import numpy
```

We will use the same running data set from the Dow Jones index for some of the visualizations now. We already have stock data for company "AA". Let's make one more frame for a new company CSCO, and plot some of these:

```
>>>stockCSCO = stockdata_new.query('stock=="CSCO"')
>>>stockCSCO.head()
>>>from matplotlib import figure
>>>plt.figure()
>>>plt.scatter(stockdata_new.index.date,stockdata_new.volume)
>>>plt.xlabel('day') # added the name of the x axis
>>>plt.ylabel('stock close value') # add label to y-axis
>>>plt.title('title') # add the title to your graph
>>>plt.savefig("matplot1.jpg") # savefig in local
```

You can also save the figure as a JPEG/PNG file. This can be done using the savefig() function shown here:

```
>>>plt.savefig("matplot1.jpg")
```

Subplot

Subplot is the best way to layout your plots. This works as a canvas, where we can add not just one plot but multiple plots. In this example, we have tried to put four plots with the parameters numrow, numcol which will define the canvas and the next argument in the plot number.

```
>>>plt.subplot(2, 2, 1)
>>>plt.plot(stockAA.index.weekofyear, stockAA.open, 'r--')
>>>plt.subplot(2, 2, 2)
>>>plt.plot(stockCSCO.index.weekofyear, stockCSCO.open, 'g-*')
>>>plt.subplot(2, 2, 3)
>>>plt.plot(stockAA.index.weekofyear, stockAA.open, 'g--')
>>>plt.subplot(2, 2, 4)
>>>plt.plot(stockCSCO.index.weekofyear, stockCSCO.open, 'r-*')
>>>plt.subplot(2, 2, 3)
>>>plt.subplot(2, 2, 4)
```

```
>>>plt.plot(x, y, 'r-*')
>>>fig.savefig("matplot2.png")
```



We can do something more elegant for plotting many plots at one go!

```
>>>fig, axes = plt.subplots(nrows=1, ncols=2)
>>>for ax in axes:
>>> ax.plot(x, y, 'r')
>>> ax.set_xlabel('x')
>>> ax.set_ylabel('y')
>>> ax.set_title('title');
```

As you case see, there are ways to code a lot more like in typical Python to handle different aspects of the plots you want to achieve.

Adding an axis

We can add an axis to the figure by using addaxis(). By adding an axis to the figure, we can define our own drawing area. addaxis() takes the following arguments:

```
*rect* [*left*, *bottom*, *width*, *height*]
>>>fig = plt.figure()
>>>axes = fig.add_axes([0.1, 0.1, 0.8, 0.8]) # left, bottom, width,
```

height (range 0 to 1)
>>>axes.plot(x, y, 'r')

Let' plot some of the most commonly used type of plots. The great thing is that most of the parameters, such as title and label, still work in the same way. Only the kind of plot will change.

If you want to add an x label, a y label, and a title with the axis; the commands are as follows:

```
>>>fig = plt.figure()
>>>ax = fig.add_axes([0.1, 0.1, 0.8, 0.8])
>>>ax.plot(stockAA.index.weekofyear,stockAA.open,label="AA")
>>>ax.plot(stockAA.index.weekofyear,stockCSCO.open,label="CSCO")
>>>ax.set_xlabel('weekofyear')
>>>ax.set_ylabel('stock value')
>>>ax.set_title('Weekly change in stock price')
>>>ax.legend(loc=2); # upper left corner
>>>plt.savefig("matplot3.jpg")
```

Try writing the preceding code and observe the output!



A scatter plot

One of the simplest forms of plotting is to plot the y-axis point for different x-axis values. In the following example, we have tried to capture the variation of the stock price weekly in a scatter plot:

```
>>>import matplotlib.pyplot as plt
>>>plt.scatter(stockAA.index.weekofyear,stockAA.open)
>>>plt.savefig("matplot4.jpg")
>>>plt.close()
```

A bar plot

Intuitively, the distribution of the y axis is shown against the x axis in the following bar chart. In the following example, we have used a bar plot to display data on a graph.

```
>>>n = 12
>>>X = np.arange(n)
>>>Y1 = np.random.uniform(0.5, 1.0, n)
>>>Y2 = np.random.uniform(0.5, 1.0, n)
>>>plt.bar(X, +Y1, facecolor='#9999ff', edgecolor='white')
>>>plt.bar(X, -Y2, facecolor='#ff9999', edgecolor='white')
```

3D plots

We can also build some spectacular 3D visualizations in matplotlib. The following example shows how one can create a 3D plot using matplotlib:

```
>>>from mpl_toolkits.mplot3d import Axes3D
>>>fig = plt.figure()
>>>ax = Axes3D(fig)
>>>X = np.arange(-4, 4, 0.25)
>>>Y = np.arange(-4, 4, 0.25)
>>>X, Y = np.meshgrid(X, Y)
>>>R = np.sqrt(X**2+ + Y**2)
>>>Z = np.sin(R)
>>>ax.plot_surface(X, Y, Z, rstride=1, cmap='hot')
```

External references

I like to encourage readers to go over some of the following links for more details about the individual libraries, and for more resources:

- <u>http://www.NumPy.org/</u>
- http://www.Scipy.org/
- http://pandas.pydata.org/
- http://matplotlib.org/

Summary

This chapter was a brief summary of some of the most fundamental libraries of Python that do a lot of heavy lifting for us when we deal with text and other data. NumPy helps us in dealing with numeric operations and the kind of data structure required for some of these. SciPy has many scientific operations that are used in various Python libraries. We learned how to use these functions and data structures.

We have also touched upon pandas, which is a very efficient library for data manipulation, and has been getting a lot of mileage in recent times. Finally, we gave you a quick view of one of Python's most commonly used visualization libraries, matplotlib.

In the next chapter, we will focus on social media. We will see how to capture data from some of the common social networks and produce meaningful insights around social media.

Chapter 9. Social Media Mining in Python

This chapter is all about social media. Though it's not directly related to NLTK / NLP, social data is also a very rich source of unstructured text data. So, as NLP enthusiasts, we should have the skill to play with social data. We will try to explore how to gather relevant data from some of the most popular social media platforms. We will cover how to gather data from Twitter, Facebook, and so on using Python APIs. We will explore some of the most common use cases in the context of social media mining, such as trending topics, sentiment analysis, and so on.

You already learned a lot of topics under the concepts of natural language processing and machine learning in the last few chapters. We will try to build some of the applications around social data in this chapter. We will also provide you with some of the best practices to deal with social data, and look at social data from the context of graph visualization.

There is a graph that underlies social media and most of the graph-based problems can be formulated as information flow problems and finding out the busiest node in the graph. Some of the problems such as trending topics, influencer detection, and sentiment analysis are examples of these. Let's take some of these use cases, and build some cool applications around these social networks.

By the end of this chapter,:

- You should be able to collect data from any social media using APIs.
- You will also learn to formulate the data in a structured format and how to build some amazing applications.
- Lastly, we will be able to visualize and gain meaningful insight out of social media.

Data collection

The most important objective of this chapter is to gather data across some of the most common social networks. We will look mainly at Twitter and Facebook and try to give you enough details about the API and how to effectively use them to get relevant data. We will also talk about the data dictionary for scrapped data, and how we can build some cool apps using some of the stuff we learned so far.

Twitter

We will start with one of the most popular and open social media that is completely public. This means that practically, you can gather entire Twitter stream, which is payable, while you can capture one percent of the stream for free. In the context of business, Twitter is a very rich resource of information such as public sentiments and emerging topics.

Let's get directly to face the main challenge of getting the tweets relevant to your use case.

Note

The following is the repository of many Twitter libraries. These libraries are not verified by Twitter, but run on the Twitter API.

https://dev.twitter.com/overview/api/twitter-libraries

There are more than 10 Python libraries there. So pick and choose the one you like. I generally use Tweepy and we will use it to run the examples in this book. Most of the libraries are wrappers around the Twitter API, and the parameters and signatures of all these are roughly the same.

The simplest way to install Tweepy is to install it using pip:

\$ pip install tweepy

Note

The hard way is to build it from source. The GitHub link to Tweepy is:

https://github.com/tweepy/tweepy.

To get Tweepy to work, you have to create a developer account with Twitter and get the access tokens for your application. Once you complete this, you will get your credentials and below these, the keys. Go through <u>https://apps.twitter.com/app/new</u> for registration and access tokens. The following snapshot shows the access tokens:

OAuth settings	
Your application's OAuth setti	ngs. Keep the "Consumer secret" a secret. This key should never be human-readable in your application.
Access level	Read, write, and direct messages About the application permission model
Consumer key	PHG9tkvOpVdCLHaluiQFAA
Consumer secret	dqpNZnLTwteX1YGnQ0VQ3Pv2up6ensEFeaS8MnQDE
Request token URL	https://api.twitter.com/oauth/request_token
Authorize URL	https://api.twitter.com/oauth/authorize
Access token URL	https://api.twitter.com/oauth/access_token
Caliback URL	None
Your access token Use the access token string a account. Do not share your or	s your "cauch_coken," and the access token secret as your "cauch_coken_secret," to sign requests with your own Twitter work_coken_secret with anyone
Access token	38744894-0TBISZIcuDE6Sm1Vi6VqZXGVYH9Yjn63e92M8v7ei
Access token secret	g6ElhezIPulcrPzM1jDyqqjXMH25EDeJncHaxxQeu0
Access level	Read, write, and direct messages
Recreate my access tok	an a

We will start with a very simple example to gather data using Twitter's streaming API. We are using Tweepy to capture the Twitter stream to gather all the tweets related to the given keywords:

```
tweetdump.py
>>>from tweepy.streaming import StreamListener
>>>from tweepy import OAuthHandler
>>>from tweepy import Stream
>>>import sys
>>>consumer key = 'ABCD012XXXXXXXX'
>>>consumer secret = 'xyz123xxxxxxxxxx'
>>>access token secret ='XXXXXXXXqaw2KYz0VcqC00F3U4'
>>>class StdOutListener(StreamListener):
      def on data(self, data):
>>>
>>>
          with open(sys.argv[1], 'a') as tf:
              tf.write(data)
>>>
>>>
          return
>>>
      def on error(self, status):
>>>
          print(status)
>>>if name == ' main ':
      1 = StdOutListener()
>>>
      auth = OAuthHandler(consumer key, consumer secret)
>>>
      auth.set access token (access token, access token secret)
>>>
>>>
      stream = Stream(auth, 1)
>>>
      stream.filter(track=['Apple watch'])
```

In the preceding code, we used the same code given in the example of Tweepy, with a little modification. This is an example where we use the streaming API of Twitter, where we track **Apple Watch**. Twitter's streaming API provides you the facility of conducting a search on the actual Twitter stream and you can consume a maximum of one percent of the stream using this API.

In the preceding code, the main parts that you need to understand are the first and last four lines. In the initial lines, we are specifying the access tokens and other keys that we generated in the previous section. In the last four lines, we create a listener to consume the stream. In the last line, we use stream.filter to filter Twitter for keywords that we have put in the track. We can specify multiple keywords here. This will result in all the tweets that contain the term Apple Watch for our running example.

In the following example, we will load the tweets we have collected, and have a look at the tweet structure and how to extract meaningful information from it. A typical tweet JSON structure looks similar to:

```
{
    "created_at":"Wed May 13 04:51:24 +0000 2015",
    "id":598349803924369408,
    "id_str":"598349803924369408",
    "text":"Google launches its first Apple Watch app with News &
Weather http:\/\/t.co\/o1XMBmhnH2",
    "source":"\u003ca href=\"http:\/\/ifttt.com\"
rel=\"nofollow\"\u003eIFTTT\u003c\/a\u003e",
```

```
"truncated":false,
"in reply to status id":null,
"user":{
"id":1461337266,
"id str":"1461337266",
"name": "vestihitech \u0430\u0432\u0442\u043e\u043c\u0430\u0442",
"screen name": "vestihitecha",
"location":"",
"followers count":20,
"friends count":1,
"listed count":4,
""statuses count":7442,
"created at": "Mon May 27 05:51:27 +0000 2013",
"utc offset":14400,
},
"geo":{ "latitude" : 51.4514285, "longitude"=-0.99
}
"place": "Reading, UK",
"contributors":null,
"retweet count":0,
"favorite count":0,
"entities":{
"hashtags":["apple watch", "google"
],
"trends":[
],
"urls":[
{
"url":"http:\/\/t.co\/o1XMBmhnH2",
"expanded url":"http:\/\/ift.tt\/1HfqhCe",
"display url":"ift.tt\/1HfqhCe",
"indices":[
66,
88
1
}
],
"user mentions":[
],
"symbols":[
]
},
"favorited":false,
"retweeted":false,
"possibly sensitive":false,
"filter level":"low",
```

```
"lang":"en",
"timestamp_ms":"1431492684714"
}
]
```

Data extraction

Some of the most commonly used fields of interest in data extraction are:

- text: This is the content of the tweet provided by the user
- user: These are some of the main attributes about the user, such as username, location, and photos
- Place: This is where the tweets are posted, and also the geo coordinates
- Entities: Effectively, these are the hashtags and topics that a user attaches to his / her tweets

Every attribute in the previous figure can be a good use case for some of the social mining exercises done in practice. Let's jump onto the topic of how we can get to these attributes and convert them to a more readable form, or how we can process some of these:

The output of the preceding code will give you, as expected, four lists in which all the tweet content is in tweet_texts and the location of the tweets and hashtags.

Tip

In the code, we are just loading a JSON output generated using json.loads(). I would recommend you to use an online tool such as Json Parser (<u>http://json.parser.online.fr/</u>) to get an idea of what your JSON looks like and what are its attributes (key and value).

Next, if you look, there are different levels in the JSON, where some of the attributes such as text have a direct value, while some of them have more nested information. This is the reason you see, where when we are looking at hashtags, we have to iterate one more level, while in case of text, we just fetch the values. Since our file actually has a list of tweets, we have to iterate that list to get all the tweets, while each tweet object will look like the example tweet structure.

Trending topics

Now, if we look for trending topics in this kind of a setup. One of the simplest ways to find them could be to look for frequency distribution of words across tweets. We already have a list of tweet_text that contains the tweets:

```
>>>import nltk
>>>from nltk import word_tokenize,sent_tokenize
>>>from nltk import FreqDist
>>>tweets_tokens = []
>>>for tweet in tweet_text:
>>> tweets_tokens.append(word_tokenize(tweet))
>>>Topic_distribution = nltk.FreqDist(tweets_tokens)
>>>Freq dist nltk.plot(50, cumulative=False)
```

One other more complex way of doing this could be the use of the part of speech tagger that you learned in <u>Chapter 3</u>, *Part of Speech Tagging*. The theory is that most of the time, topics will be nouns or entities. So, the same exercise can be done like this. In the preceding code, we read every tweet and tokenize it, and then use POS as a filter to only select nouns as topics:

```
>>>import nltk
>>>Topics = []
>>>for tweet in tweet_text:
>>> tagged = nltk.pos_tag(word_tokenize(tweet))
>>> Topics_token = [word for word,pos in ] in tagged if pos in
['NN','NNP']
>>> print Topics token
```

If we want to see a much cooler example, we can gather tweets across time and then generate plots. This will give us a very clear idea of the trending topics. For example, the data we are looking for is "Apple Watch". This word should peak on the day when Apple launched Apple Watch and the day they started selling it. However, it will be interesting to see what kind of topics emerged apart from those, and how they trended over time.

Geovisualization

One of the other common application of social media is geo-based visualization. In the tweet structure, we saw attributes named geo, longitude, and latitude. Once you have access to these values, it is very easy to use some of the common visualization libraries, such as **D3**, to come up with something like this:



This is just an example of what we can achieve with these kind of visualizations; this was the visualization of a tweet in the U.S. We can clearly see the areas of increased intensity in eastern places such as New York. Now, a similar analysis done by a company on the customers can give a clear insight about which are some of the most popular places liked by our customer base. We can text mine these tweets for sentiment, and then we can infer insights about customers as to in which states they are not happy with the company and so on.

Influencers detection

Detection of important nodes in the social graph that has a lot of importance is another great problem in the context of social graphs. So, if we have millions of tweets streaming about our company, then one important use case would be to gather the most influential customers in the social media, and then target them for branding, marketing, or improving customer engagement.

In the case of Twitter, this goes back to the graph theory and concept of PageRank, where in a given node, if the ratio of outdegree and indegree is high, then that node is an influencer. This is very intuitive since people who have more followers than the number of people they follow are typically, influencers. One company, **KLOUT**, (<u>https://klout.com/</u>) has been focusing on a similar problem. Let's write a very basic and intuitive algorithm to calculate Klout's score:

```
>>>klout_scores = [ (tweet['user']['followers_count]/
tweet['user']['friends_count'],tweet['user']) for tweet in tweets ]
```

Some of the examples where we worked on Twitter will hold exactly the same modification of content field. We can build a trending topic example with Facebook posts. We can also visualize Facebook users and post on the **geomap** and influencer kind of use cases. In fact, in the next section, we will see a variation of this in the context of Facebook.

Facebook

Facebook is a bit more personal, and somewhat private social network. Facebook does not allow you to gather the feeds/posts of the user simply for security and privacy reasons. So, Facebook's graph API has a limited way of accessing the feeds of the given page. I would recommend you to go to https://developers.facebook.com/docs/graph-api/using-graph-api/v2.3 for better understanding.

The next question is how to access the Graph API using Python and how to get started with it. There are many wrappers written over Facebook's API, and we will use one the most common Facebook SDK:

\$ pip install facebook-sdk

Tip

You can also install it through:

```
https://github.com/Pythonforfacebook/facebook-sdk.
```

The next step is to get the access token for the application while Facebook treats every API call as an application. Even for this data collection step, we will pretend to be an application.

Note

To get your token, go to:

```
https://developers.facebook.com/tools/explorer.
```

We are all set now! Let's start with one of the most widely used Facebook graph APIs. In this API, Facebook provides a graph-based search for pages, users, events, places, and so on. So, the process of getting to the post becomes a two-stage process, where we have to look for a specific pageid / userid related to our topic of interest, and then we will be able to access the feeds of that page. One simple use case for this kind of an exercise could be to use the official page of a company and look for customer complaints. The way to go about this is:

```
>>>import facebook
>>>import json
>>>fo = open("fdump.txt",'w')
>>>ACCESS_TOKEN = 'XXXXXXXXXX' # https://developers.facebook.com/
tools/explorer
```

```
>>>fb = facebook.GraphAPI(ACCESS_TOKEN)
>>>company_page = "326249424068240"
>>>content = fb.get_object(company_page)
>>>fo.write(json.dumps(content))
```

The code will attach the token to the Facebook Graph API and then we will make a REST call to Facebook. The problem with this is that we have to have the ID of the given page with us beforehand. The code which will attach the token is as follows:

```
"website":"www.dimennachildrenshistorymuseum.org",
"can post":true,
"category list":[
{
"id":"244600818962350",
"name": "History Museum"
},
{
"id":"187751327923426",
"name": "Educational Organization"
}
],
"likes":1793,
},
"id":"326249424068240",
"category": "Museum/art gallery",
"has added app":false,
"talking about count":8,
"location":{
"city":"New York",
"zip":"10024",
"country": "United States",
"longitude":-73.974413,
"state":"NY",
"street": "170 Central Park W",
"latitude":40.779236
},
"is community page":false,
"username": "nyhistorykids",
"description":"The first-ever museum bringing American history to
life through the eyes of children, where kids plus history equals
serious fun! Kids of all ages can practice their History Detective
skills at the DiMenna Children's History Museum and:\n\n\u2022
discover the past through six historic figure pavilions\n\n\u2022!",
"hours":{
""thu 1 close":"18:00"
},
"phone":"(212) 873-3400",
```

```
"link": "https://www.facebook.com/nyhistorykids",
"price range":"$ (0-10)",
"checkins":1011,
"about":"The DiMenna Children' History Museum is the first-ever
museum bringing American history to life through the eyes of
children. Visit it inside the New-York Historical Society!",
"name": "New-York Historical Society DiMenna Children's History
Museum",
"cover":{
"source":"https://scontent.xx.fbcdn.net/hphotos-xpf1/t31.0-8/
s720x720/1049166 672951706064675 339973295 o.jpg",
"cover id":"672951706064675",
"offset x":0,
"offset y":54,
"id":"672951706064675"
},
"were here count":1011,
"is published":true
},
```

Here, we showed a similar schema for the Facebook data as we did for Twitter, and now we can see what kind of information is required for our use case. In most of the cases, the user post, category, name, about, and likes are some of the important fields. In this example, we are showing a page of a museum, but in a more business-driven use case, a company page has a long list of posts and other useful information that can give some great insights about it.

Let's say I have a Facebook page for my organization xyz.org and I want to know about the users who complained about me on the page; this is good for a use case such as complaint classification. The way to achieve the application now is simple enough. You need to look for a set of keywords in fdump.txt, and it can be as complex as scoring using a text classification algorithm we learned in <u>Chapter 6</u>, *Text Classification*.

The other use case could be to look for a topic of interest, and then to look for the resulting pages for open posts and comments. This is exactly analogous to searching using the graph search bar on your Facebook home page. However, the power of doing this programmatically is that we can conduct these searches and then each page can be recursively parsed for use comments. The code for searching user data is as follows:

User search

```
>>>fb.request("search", {'q' : 'nitin', 'type' : 'user'})
Place based on the nearest location.
>>>fb.request("search", {'q' : 'starbucks', 'type' : 'place'})
Look for open pages.
>>>fb.request("search", {'q' : 'Stanford university', 'type' : page})
Look for event matching to the key word.
>>>fb.request("search", {'q' : 'beach party', 'type' : 'event'})
```

Once we have dumped all the relevant data into a structured format, we can apply some of the concepts we learned when we went through the topics of NLP and machine learning. Let's pick the same use case of finding posts, that will mostly be complaints on a Facebook page.

I assume that we now have the data in the following format:

Userid	FB Post
XXXX0001	The product was pathetic and I tried reaching out to your customer care, but nobody responded
XXXX002	Great work guys
XXXX003	Where can I call to get my account activated ??? Really bad service

We will go back to the same example we had in <u>Chapter 6</u>, *Text Classification*, where we built a text classifier to detect whether the **SMS** (text message) was spam. Similarly, we can create training data using this kind of data, where from the given set of posts, we will ask manual taggers to tag the comments that are complaints and the ones that are not. Once we have significant training data, we can build the same text classifier:

```
fb_classification.py
```

```
>>>from sklearn.feature_extraction.text import TfidfVectorizer
>>>vectorizer = TfidfVectorizer(min_df=2, ngram_range=(1, 2),
stop_words='english', strip_accents='unicode', norm='12')
>>>X_train = vectorizer.fit_transform(x_train)
>>>X_test = vectorizer.transform(x_test)
```

```
>>>from sklearn.linear_model import SGDClassifier
>>>clf = SGDClassifier(alpha=.0001, n_iter=50).fit(X_train, y_train)
>>>y_pred = clf.predict(X_test)
```

Let's assume that these three are the only samples. We can tag 1st and 3rd to be classified as complaints, while 2nd will not be a complaint. Although we will build a vectorizer of unigram and bigram in the same way, we can actually build a classifier using the same process. I ignored some of the preprocessing steps here. You can use the same process as discussed in <u>Chapter 6</u>, *Text Classification*. In some of the cases, it will be hard/expensive to get training data like this. In some of these cases, we can apply either an unsupervised algorithm, such as text clustering or topic modeling. The other way is to use some different dataset that is openly available and build model on that and apply it here. For example, in the same use case, we can crawl some of the customer complaints available on the Web and use that as training data for our model. This can work as a good proxy for labeled data.

Influencer friends

One other use case of social media could be finding out the most influencer in your social graph. In our case, it could be finding out a clear node that has a vast amount of inlinks and outlinks will be the influencer in the graph.

The same problem in the context of business can be finding out the most influential customers, and targeting them to market our products.

The code for the Influencer friends is as follows:

```
>>>friends = fb.get_connections("me", "friends")["data"]
>>>print friends
>>>for frd in friends:
>>> print fb.get_connections(frd["id"],"friends")
```

Once you have a list of all your friends and mutual friends, you can create a data structure like this:

source node	destination node	link_exist
Friend 1	Friend 2	1
Friend 1	Friend 3	1
Friend 2	Friend 3	0
Friend 1	Friend 4	1

This a kind of data structure that can be used to generate a network, and is a very good way of visualizing the social graph. I used D3 here, but python also has a library called **NetworkX** (<u>https://networkx.github.io/</u>) that can be used to generate graph visualization, as shown in the following graph. To generate a visualization, you need to arrive at a adjacency matrix that can be created based on the bases of the preceding information about who is the friend of whom.


Visualization of a sample network in D3

Summary

In this chapter, we touched upon some of the most popular social networks. You learned how to get data using Python. You understood the structure and kind of attributes data has. We explored different options provided by the API.

We explored some of the most common use cases in the context of social media mining. We touched upon the use cases about trending topics, influencer detection, information flow, and so on. We visualized some of these use cases. We also applied some of the learnings from the previous chapter, where we used NLTK to get some of the topic and entity extraction, while in scikit-learn we classified some of the complaints.

In conclusion, I would suggest that you look for some of the same use cases in context of some other social networks and try to explore them. The great part of these social networks is that all of them have a data API, and most of them are open enough to do some interesting analysis. If you apply the same learning you did in this chapter, you need to understand the API, how to get the data, and then how to apply some of the concepts we learned in the previous chapters. I hope that after learning all this, you will come up with more use cases, and some interesting analysis of social media.

Chapter 10. Text Mining at Scale

In this chapter, we will go back to some of the libraries we learned about in the previous chapters, but this time, we want to learn to learn how these libraries will scale up with bigdata. We assume that you have a fair bit of an idea about big data, **Hadoop** and **Hive**. We will explore how some of the Python libraries, such as NLTK, scikit-learn, and pandas can be used on a Hadoop cluster with a large amount of unstructured data.

We will cover some of the most common use cases in the context of NLP and text mining, and we will also provide a code snippet that will be helpful for you to get your job done. We will look at three major examples that can capture the vast majority of your text mining problems. We will tell you how to run NLTK at scale to perform some of the NLP tasks that we completed in the initial chapters. We will give you a few examples of some of the text classification tasks that can be done on Big Data.

One other aspect of doing machine learning and NLP at a very high scale is to understand whether the problem is parallelizable or not. We will talk in brief about some of the problems discussed in the previous chapter, and whether these problems are big data problems or not. Or in some case is it even possible to solve this using Big Data.

Since most of the libraries we learned so far are written in Python, let's deal with one of the main questions of how to get Python on Big Data (Hadoop).

By end of the chapter we like reader to have :

- Good understanding about big data related technologies such as Hadoop, Hive and how it can be done using python.
- Step by step tutorial to work with NLTK, Scikit & PySpark on Big Data.

Different ways of using Python on Hadoop

There are many ways to run a Python process on Hadoop. We will talk about some of the most popular ways through which we can run Python on Hadoop as a streaming MapReduce job, Python UDF in Hive, and Python hadoop wrappers.

Python streaming

Typically a Hadoop job has to be written in form of a map and reduce function. User has to write an implementation of map and reduce function for the given task. Commonly these mappers and reducers are implemented in JAVA. At the same time Hadoop provide streaming, you where a user can write a Python mapper and reducer function similar to Java in any other language. I am assuming that you have run a word count example using Python. We will also use the same example using NLTK later in this chapter.

Note

In case you have not, have a look at

http://www.michael-noll.com/tutorials/writing-an-hadoop-mapreduce-program-in-python/ to know more about MapReduce in Python.

Hive/Pig UDF

Other way to use Python is by writing a **UDF** (**User Defined Function**) in Hive/Pig. The idea here is that most of the operations we are performing in NLTK are highly parallelizable. For example, POS tagging, Tokenization, Lemmatization, Stop Word removal, and NER can be highly distributable. The reason being the content of each row is independent from the other row, and we don't need any context while doing some of these operations.

So, if we have NLTK and other Python libraries on each node of the cluster, we can write a **user defined function** (**UDF**) in Python, using libraries such as NLTK and scikit. This is one of the easiest way of doing NLTK, especially for scikit on a large scale. We will give you a glimpse of both of these in this chapter.

Streaming wrappers

There is a long list of wrappers that different organizations have implemented to get Python running on the cluster. Some of them are actually quite easy to use, but all of them suffer from performance bias. I have listed some of them as follows, but you can go through the project page in case you want to know more about them:

- Hadoopy
- Pydoop
- Dumbo
- mrjob

Note

For the exhaustive list of options available for the usage of Python on Hadoop, go through the article at

http://blog.cloudera.com/blog/2013/01/a-guide-to-python-frameworks-for-hadoop/.

NLTK on Hadoop

We talked enough about NLTK as a library, and what are some of the most-used functions it gives us. Now, NLTK can solve many NLP problems from which many are highly parallelizable. This is the reason why we will try to use NLTK on Hadoop.

The best way of running NLTK on Hadoop is to get it installed on all the nodes of the cluster. This is probably not that difficult to achieve. There are ways in which you can do this, such as sending the resource files as a streaming argument. However, we will rather prefer the first option.

A UDF

There are a variety of ways in which we can make NLTK run on Hadoop. Let's talk about one example of using NLTK by doing tokenization in parallel using a Hive UDF.

For this use case, we have to follow these steps:

1. We have chosen a small dataset where only two columns exist. We have to create the same schema in Hive:

ID	Content
UA0001	"I tried calling you. The service was not up to the mark"
UA0002	"Can you please update my phone no"
UA0003	"Really bad experience"
UA0004	"I am looking for an iPhone"

2. Create the same schema in Hive. The following Hive script will do this for you:

Hive script

```
CREATE TABLE $InputTableName (
ID String,
Content String
)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY '\t';
```

3. Once we have the schema, essentially, we want to get something like tokens of the content in a separate column. So, we just want another column in the *\$outTable* with the same schema, and the added column of tokens:

Hive script

```
CREATE TABLE $OutTableName (
ID String,
Content String,
Tokens String
)
```

4. Now, we have the schemas ready. We have to write the UDF in Python to read the table line by line and then apply a tokenize method. This is very similar to what we did in <u>Chapter 3</u>, *Part of Speech Tagging*. This is the piece of function that is analogous to all the examples in <u>Chapter 3</u>, *Part of Speech Tagging*. Now, if you want to get POS tags, Lemmatization, and HTML, you just need to modify this UDF. Let's see how the UDF will look for our tokenizer:

```
>>>import sys
>>>import datetime
>>>import pickle
>>>import nltk
>>>nltk.download('punkt')
>>>for line in sys.stdin:
     line = line.strip()
>>>
     print>>sys.stderr, line
>>>
      id, content= line.split('\t')
>>>
>>>
      print>>sys.stderr,tok.tokenize(content)
      tokens =nltk.word tokenize(concat all text)
>>>
>>>
      print '\t'.join([id,content,tokens])
```

- 5. Just name this UDF something like: nltk scoring.py.
- 6. Now, we have to run the insert hive query with the TRANSFORM function to apply the UDF on the given content and to do tokenization and dump the tokens in the new column:

Hive script

```
add FILE nltk_scoring.py;
add FILE english.pickle; #Adding file to DistributedCache
INSERT OVERWRITE TABLE $OutTableName
SELECT
TRANSFORM (id, content)
USING 'PYTHONPATH nltk_scoring.py'
AS (id string, content string, tokens string )
FROM $InputTablename;
```

7. If you are getting an error like this, you have not installed the NLTK and NLTK data correctly:

```
use the NLTK Downloader to obtain the resource: >>>
nltk.download()
```

Searched in:

- '/home/nltk_data'
- '/usr/share/nltk_data'
- '/usr/local/share/nltk_data'
- '/usr/lib/nltk_data'
- '/usr/local/lib/nltk_data'
- 8. If you are able to run this Hive job successfully, you will get a table named OutTableName, that will look something like this:

ID	Content	
UA0001	"I tried calling you, The service was not up to the mark"	[" I", " tried", "calling", "you", "The", "service" "was", "not", "up", "to", "the", "mark"]
UA0002	"Can you please update my phone no"	["Can", "you", "please" "update", " my", "phone" "no"]
UA0003	"Really bad experience"	["Really"," bad" "experience"]
UA0004	"I am looking for an iphone"	["I", "am", "looking", "for", "an", "iPhone"]

Python streaming

Let's try the second option of Python streaming. We have Hadoop streaming, where we can write our own mapper and reducer functions, and then use Python streaming with mapper.py, as it looks quite similar to our Hive UDF. Here we are using the same example with map-reduce python streaming this will give us a option of choosing a Hive table or using a HDFS file directly. We will just go over the content of the file and tokenize it. We will not perform any reduce operation here, but for learning, I included a dummy reducer, which just dumps it. So now, we can ignore the reducer from the execution command completely.

Here is the code for the Mapper.py:

Mapper.py

```
>>>import sys
>>>import pickle
>>>import nltk
>>>for line in sys.stdin:
>>> line = line.strip()
>>> id, content = line.split('\t')
```

>>> tokens =nltk.word_tokenize(concat_all_text)
>>> print '\t'.join([id,content,topics])

Here is the code for the Reducer.py:

Reducer.py

```
>>>import sys
>>>import pickle
>>>import nltk
>>>for line in sys.stdin:
>>>
    line = line.strip()
>>> id, content,tokens = line.split('\t')
>>> print '\t'.join([id,content,tokens])
```

The following is the Hadoop command to execute a Python stream: Hive script

```
hadoop jar <path>/hadoop-streaming.jar \
-D mapred.reduce.tasks=1 -file <path>/mapper.py \
-mapper <path>/mapper.py \
-file <path>/reducer.py \
-reducer <path>/reducer.py \
-input /hdfspath/infile \
-output outfile
```

Scikit-learn on Hadoop

The other important use case for big data is machine learning. Specially with Hadoop, scikit-learn is more important, as this is one of the best options we have to score a machine learning model on big data. Large-scale machine learning is currently one of the hottest topics, and doing this in a big data environment such as Hadoop is all the more important. Now, the two aspects of machine learning models are building a model on big data and to build model on a significantly large amount of data and scoring a significantly large amount of data.

To understand more, let's take the same example data we used in the previous table, where we have some customer comments. Now, we can build, let's say, a text classification mode using a significant training sample, and use some of the learnings from <u>Chapter 6</u>, *Text Classification* to build a Naive Bayes, SVM, or a logistic regression model on the data. While scoring, we might need to score a huge amount of data, such as customer comments. On the other hand building the model itself on big data is not possible with scikit-learn, we will require tool like spark/Mahot for that. We will take the same step-by-step approach of scoring using a pre-trained model as we did with NLTK. While building the mode on big data will be covered in the next section. For scoring using a pre-trained model specifically when we are working on a text mining kind of problem. We need two main objects (a vectorizer and modelclassifier) to be stored as a serialized pickle object.

Note

Here, pickle is a Python module to achieve serialization by which the object will be saved in a binary state on the disk and can be consumed by loading again.

https://docs.python.org/2/library/pickle.html

Build an offline model using scikit on your local machine and make sure you pickle objects. For example, if I use the Naive Bayes example from <u>Chapter 6</u>, *Text Classification*, we need to store vectorizer and clf as pickle objects:

```
>>>vectorizer = TfidfVectorizer(sublinear_tf=True, min_df=in_min_df,
stop_words='english', ngram_range=(1,2), max_df=in_max_df)
>>>joblib.dump(vectorizer, "vectorizer.pkl", compress=3)
>>>clf = GaussianNB().fit(X_train,y_train)
>>>joblib.dump(clf, "classifier.pkl")
```

The following are the steps for creating a output table which will have all the customer comments for the entire history:

1. Create the same schema in Hive as we did in the previous example. The following Hive script will do this for you. This table can be huge; in our case, let's assume that it contains all the customer comments about the company in the past:

Hive script

```
CREATE TABLE $InputTableName (
ID String,
Content String
)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY '\t';
```

2. Build an output table with the output column like the predict and probability score:

Hive script

```
CREATE TABLE $OutTableName (
ID String,
Content String,
predict String,
predict_score double
)
```

3. Now, we have to load these pickle objects to the distributed cache using the addFILE command in Hive:

add FILE vectorizer.pkl; add FILE classifier.pkl;

4. The next step is to write the Hive UDF, where we are loading these pickle objects. Now, they start behaving the same as they were on the local. Once we have the classifier and vectorizer object, we can use our test sample, which is nothing but a string, and generate the TFIDF vector out of this. The vectorizer object can be used now to predict the class as well as the probability of the class:

Classification.py

```
>>>import sys
>>>import pickle
>>>import sklearn
>>>from sklearn.externals import joblib
>>>clf = joblib.load('classifier.pkl')
>>vectorizer = joblib.load('vectorizer.pkl')
>>>for line in sys.stdin:
>>>
      line = line.strip()
>>>
      id, content= line.split('\t')
      X test = vectorizer.transform([str(content)])
>>>
      prob = clf.predict proba(X test)
>>>
>>>
      pred = clf.predict(X test)
      prob_score =prob[:,1]
>>>
>>>
      print '\t'.join([id, content,pred,prob score])
```

5. Once we have written the classification.py UDF, we have to also add this UDF to the distributed cache and then effectively, run this UDF as a TRANSFORM function on each and every row of the table. The Hive script for this will look like this:

Hive script

add FILE classification.py; INSERT OVERWRITE TABLE \$OutTableName SELECT TRANSFORM (id, content) USING 'python2.7 classification.py' AS (id string, scorestringscore string) FROM \$Tablename;

6. If everything goes well, then we will have the output table with the output schema as:

ID	Content	Predict	Prob_score
UA0001	"I tried calling you, The service was not up to the mark"	Complaint	0.98
UA0002	"Can you please update my phone no "	No	0.23
UA0003	"Really bad experience"	Complaint	097
UA0004	"I am looking for an iPhone "	No	0.01

So, our output table will have all the customer comments for the entire history, scores for whether they were complaints or not, and also a confidence score. We have choosen a Hive UDF for our example, but the similar process can be done through the Pig and Python steaming in a similar way as we did in NLTK.

This example was to give you a hands-on experience of how to score a machine learning model on Hive. In the next example, we will talk about how to build a machine learning/NLP model on big data.

PySpark

Let's go back to the same discussion we had of building a machine learning/NLP model on Hadoop and the other where we score a ML model on Hadoop. We discussed second option of scoring in depth in the last section. Instead sampling a smaller data-set and scoring let's use a larger data-set and build a large-scale machine learning model step-by-step using PySpark. I am again using the same running data with the same schema:

ID	Comment	Class
UA0001	I tried calling you, The service was not up to the mark	1
UA0002	Can you please update my phone no	0
UA0003	Really bad experience	1
UA0004	I am looking for an iPhone	0
UA0005	Can somebody help me with my password	1
UA0006	Thanks for considering my request for	0

Consider the schema for last 10 years worth of comments of the organization. Now, instead of using a small sample to build a classification model, and then using a pretrained model to score all the comments, let me give you a step-by-step example of how to build a text classification model using PySpark.

The first thing that we need to do is we need to import some of the modules. Starting with SparkContext, which is more of a configuration, you can provide more parameters, such as app names and others for this.

```
>>>from pyspark import SparkContext
>>>sc = SparkContext(appName="comment_classifcation")
```

Note

For more information, go through the article at

http://spark.apache.org/docs/0.7.3/api/pyspark/pyspark.context.SparkContext-class.html.

The next thing is reading a tab delimited text file. Reading the file should be on HDFS. This file could be huge (~Tb/Pb):

```
>>>lines = sc.textFile("testcomments.txt")
```

The lines are now a list of all the rows in the corpus:

```
>>>parts = lines.map(lambda l: l.split("\t"))
>>>corpus = parts.map(lambda row: Row(id=row[0], comment=row[1],
class=row[2]))
```

The part is a list of fields as we have each field in the line delimited on "\t".

Let's break the corpus that has [ID, comment, class (0,1)] in the different RDD objects:

```
>>>comment = corpus.map(lambda row: " " + row.comment)
>>>class var = corpus.map(lambda row:row.class)
```

Once we have the comments, we need to do a process very similar to what we did in <u>Chapter 6</u>, *Text Classification*, where we used scikit to do tokenization, hash vectorizer and calculate TF, IDF, and tf-idf using a vectorizer.

The following is the snippet of how to create tokenization, term frequency, and inverse document frequency:

```
>>>from pyspark.mllib.feature import HashingTF
>>>from pyspark.mllib.feature import IDF
# https://spark.apache.org/docs/1.2.0/mllib-feature-extraction.html
>>>comment_tokenized = comment.map(lambda line: line.strip().split("
"))
>>>hashingTF = HashingTF(1000) # to select only 1000 features
>>>comment_tf = hashingTF.transform(comment_tokenized)
>>>comment_idf = IDF().fit(comment_tf)
>>>comment_tfidf = comment_idf.transform(comment_tf)
```

We will merge the class with the tfidf RDD like this:

```
>>>finaldata = class_var.zip(comment_tfidf)
```

We will do a typical test, and train sampling:

```
>>>train, test = finaldata.randomSplit([0.8, 0.2], seed=0)
```

Let's perform the main classification commands, which are quite similar to scikit. We are using a logistic regression, which is widely used classifier. The pyspark.mllib provides you with a variety of algorithms.

Note

For more information on pyspark.mllib visit <u>https://spark.apache.org/docs/latest/api/python/</u>pyspark.mllib.html

The following is an example of Naive bayes classifier:

```
>>>from pyspark.mllib.regression import LabeledPoint
>>>from pyspark.mllib.classification import NaiveBayes
>>>train_rdd = train.map(lambda t: LabeledPoint(t[0], t[1]))
>>>test_rdd = test.map(lambda t: LabeledPoint(t[0], t[1]))
>>>nb = NaiveBayes.train(train_rdd,lambda = 1.0)
>>>nb_output = test_rdd.map(lambda point:
(NB.predict(point.features), point.label))
>>>print nb output
```

The nb_output command contains the final predictions for the test sample. The great thing to understand is that with just less than 50 lines, we built a snippet code for an industry-standard text classification with even petabytes of the training sample.

Summary

To summarize this chapter, our objective was to apply the concepts that we learned so far in the context of big data. In this chapter, you learned how to use some Python libraries, such as NLTK and scikit with Hadoop. We talked about scoring a machine learning model, or an NLP-based operation.

We also saw three major examples of the most-common use cases. On understanding these examples, you can apply most of the NLTK, scikit and PySpark functions.

This chapter was a quick and brief introduction to NLP and text mining on big data. This is one of the hottest topics, and each term and tool which I talked about in the example snippet could be a book in itself. I tried to give you a hacker's approach, to give you an introduction to big data and text mining on a large scale. I encourage you to read more about some of these big data technologies such as Hadoop, Hive, Pig, and Spark and try to explore some of the examples we gave in this chapter.

Part 2. Module 2

Python 3 Text Processing with NLTK 3 Cookbook

Over 80 practical recipes on natural language processing techniques using Python's NTLK 3.0

Chapter 1. Tokenizing Text and WordNet Basics

In this chapter, we will cover the following recipes:

- Tokenizing text into sentences
- · Tokenizing sentences into words
- Tokenizing sentences using regular expressions
- Training a sentence tokenizer
- Filtering stopwords in a tokenized sentence
- Looking up Synsets for a word in WordNet
- · Looking up lemmas and synonyms in WordNet
- Calculating WordNet Synset similarity
- Discovering word collocations

Introduction

Natural Language ToolKit (NLTK) is a comprehensive Python library for natural language processing and text analytics. Originally designed for teaching, it has been adopted in the industry for research and development due to its usefulness and breadth of coverage. NLTK is often used for rapid prototyping of text processing programs and can even be used in production applications. Demos of select NLTK functionality and production-ready APIs are available at <u>http://text-processing.com</u>.

This chapter will cover the basics of tokenizing text and using WordNet. **Tokenization** is a method of breaking up a piece of text into many pieces, such as sentences and words, and is an essential first step for recipes in the later chapters. **WordNet** is a dictionary designed for programmatic access by natural language processing systems. It has many different use cases, including:

- Looking up the definition of a word
- · Finding synonyms and antonyms
- Exploring word relations and similarity
- Word sense disambiguation for words that have multiple uses and definitions

NLTK includes a WordNet corpus reader, which we will use to access and explore WordNet. A corpus is just a body of text, and corpus readers are designed to make accessing a corpus much easier than direct file access. We'll be using WordNet again in the later chapters, so it's important to familiarize yourself with the basics first.

Tokenizing text into sentences

Tokenization is the process of splitting a string into a list of pieces or tokens. A token is a piece of a whole, so a word is a token in a sentence, and a sentence is a token in a paragraph. We'll start with sentence tokenization, or splitting a paragraph into a list of sentences.

Getting ready

Installation instructions for NLTK are available at <u>http://nltk.org/install.html</u> and the latest version at the time of writing this is Version 3.0b1. This version of NLTK is built for Python 3.0 or higher, but it is backwards compatible with Python 2.6 and higher. In this book, we will be using Python 3.3.2. If you've used earlier versions of NLTK (such as version 2.0), note that some of the APIs have changed in Version 3 and are not backwards compatible.

Once you've installed NLTK, you'll also need to install the data following the instructions at http://nltk.org/data.html. I recommend installing everything, as we'll be using a number of corpora and pickled objects. The data is installed in a data directory, which on Mac and Linux/Unix is usually /usr/share/nltk_data, or on Windows is C:\nltk_data. Make sure that tokenizers/ punkt.zip is in the data directory and has been unpacked so that there's a file at tokenizers/ punkt/PY3/english.pickle.

Finally, to run the code examples, you'll need to start a Python console. Instructions on how to do so are available at <u>http://nltk.org/install.html</u>. For Mac and Linux/Unix users, you can open a terminal and type python.

How to do it...

Once NLTK is installed and you have a Python console running, we can start by creating a paragraph of text:

>>> para = "Hello World. It's good to see you. Thanks for buying this book."

Tip

Downloading the example code

You can download the example code files for all Packt books you have purchased from your account at http://www.packtpub.com. If you purchased this book elsewhere, you can visit http://www.packtpub.com. If you purchased this book elsewhere, you can visit http://www.packtpub.com. If you purchased this book elsewhere, you can visit

Now we want to split the paragraph into sentences. First we need to import the sentence tokenization function, and then we can call it with the paragraph as an argument:

```
>>> from nltk.tokenize import sent_tokenize
>>> sent tokenize(para)
```

['Hello World.', "It's good to see you.", 'Thanks for buying this book.']

So now we have a list of sentences that we can use for further processing.

How it works...

The sent_tokenize function uses an instance of PunktSentenceTokenizer from the nltk.tokenize.punkt module. This instance has already been trained and works well for many European languages. So it knows what punctuation and characters mark the end of a sentence and the beginning of a new sentence.

There's more...

The instance used in sent_tokenize() is actually loaded on demand from a pickle file. So if you're going to be tokenizing a lot of sentences, it's more efficient to load the PunktSentenceTokenizer class once, and call its tokenize() method instead:

```
>>> import nltk.data
>>> tokenizer = nltk.data.load('tokenizers/punkt/PY3/english.pickle')
>>> tokenizer.tokenize(para)
['Hello World.', "It's good to see you.", 'Thanks for buying this
book.']
```

Tokenizing sentences in other languages

If you want to tokenize sentences in languages other than English, you can load one of the other pickle files in tokenizers/punkt/PY3 and use it just like the English sentence tokenizer. Here's an example for Spanish:

```
>>> spanish_tokenizer = nltk.data.load('tokenizers/punkt/PY3/
spanish.pickle')
>>> spanish_tokenizer.tokenize('Hola amigo. Estoy bien.')
['Hola amigo.', 'Estoy bien.']
```

You can see a list of all the available language tokenizers in /usr/share/nltk_data/ tokenizers/punkt/PY3 (or C:\nltk_data\tokenizers\punkt\PY3).

See also

In the next recipe, we'll learn how to split sentences into individual words. After that, we'll cover how to use regular expressions to tokenize text. We'll cover how to train your own sentence tokenizer in an upcoming recipe, *Training a sentence tokenizer*.

Tokenizing sentences into words

In this recipe, we'll split a sentence into individual words. The simple task of creating a list of words from a string is an essential part of all text processing.

How to do it...

Basic word tokenization is very simple; use the word_toke nize() function:

```
>>> from nltk.tokenize import word_tokenize
>>> word_tokenize('Hello World.')
['Hello', 'World', '.']
```

How it works...

The word_tokenize() function is a wrapper function that calls tokenize() on an instance of the TreebankWordTokenizer class. It's equivalent to the following code:

```
>>> from nltk.tokenize import TreebankWordTokenizer
>>> tokenizer = TreebankWordTokenizer()
>>> tokenizer.tokenize('Hello World.')
['Hello', 'World', '.']
```

It works by separating words using spaces and punctuation. And as you can see, it does not discard the punctuation, allowing you to decide what to do with it.

There's more...

Ignoring the obviously named WhitespaceTokenizer and SpaceTokenizer, there are two other word tokenizers worth looking at: PunktWordTokenizer and WordPunctTokenizer. These differ from TreebankWordTokenizer by how they handle punctuation and contractions, but they all inherit from TokenizerI. The inheritance tree looks like what's shown in the following diagram:



Separating contractions

The TreebankWordTokenizer class uses conventions found in the Penn Treebank corpus. This corpus is one of the most used corpora for natural language processing, and was created in the 1980s by annotating articles from the *Wall Street Journal*. We'll be using this later in <u>Chapter 4</u>, *Part-of-speech Tagging*, and <u>Chapter 5</u>, *Extracting Chunks*.

One of the tokenizer's most significant conventions is to separate contractions. For example, consider the following code:

>>> word_tokenize("can't")
['ca', "n't"]

If you find this convention unacceptable, then read on for alternatives, and see the next recipe for tokenizing with regular expressions.

PunktWordTokenizer

An alternative word tokenizer is PunktWordTokenizer. It splits on punctuation, but keeps it with the word instead of creating separate tokens, as shown in the following code:

```
>>> from nltk.tokenize import PunktWordTokenizer
>>> tokenizer = PunktWordTokenizer()
```

```
>>> tokenizer.tokenize("Can't is a contraction.")
['Can', "'t", 'is', 'a', 'contraction.']
```

WordPunctTokenizer

Another alternative word tokenizer is WordPunctTokenizer. It splits all punctuation into separate tokens:

```
>>> from nltk.tokenize import WordPunctTokenizer
>>> tokenizer = WordPunctTokenizer()
>>> tokenizer.tokenize("Can't is a contraction.")
['Can', "'", 't', 'is', 'a', 'contraction', '.']
```

See also

For more control over word tokenization, you'll want to read the next recipe to learn how to use regular expressions and the RegexpTokenizer for tokenization. And for more on the Penn Treebank corpus, visit <u>http://www.cis.upenn.edu/~treebank/</u>.

Tokenizing sentences using regular expressions

Regular expressions can be used if you want complete control over how to tokenize text. As regular expressions can get complicated very quickly, I only recommend using them if the word tokenizers covered in the previous recipe are unacceptable.

Getting ready

First you need to decide how you want to tokenize a piece of text as this will determine how you construct your regular expression. The choices are:

- Match on the tokens
- Match on the separators or gaps

We'll start with an example of the first, matching alphanumeric tokens plus single quotes so that we don't split up contractions.

How to do it...

We'll create an instance of RegexpTokenizer, giving it a regular expression string to use for matching tokens:

```
>>> from nltk.tokenize import RegexpTokenizer
>>> tokenizer = RegexpTokenizer("[\w']+")
>>> tokenizer.tokenize("Can't is a contraction.")
["Can't", 'is', 'a', 'contraction']
```

There's also a simple helper function you can use if you don't want to instantiate the class, as shown in the following code:

```
>>> from nltk.tokenize import regexp_tokenize
>>> regexp_tokenize("Can't is a contraction.", "[\w']+")
["Can't", 'is', 'a', 'contraction']
```

Now we finally have something that can treat contractions as whole words, instead of splitting them into tokens.

How it works...

The RegexpTokenizer class works by compiling your pattern, then calling re.findall() on your text. You could do all this yourself using the re module, but RegexpTokenizer implements the TokenizerI interface, just like all the word tokenizers from the previous recipe. This means it can be used by other parts of the NLTK package, such as corpus readers, which we'll cover in detail in <u>Chapter 3</u>, *Creating Custom Corpora*. Many corpus readers need a way to tokenize the text they're reading, and can take optional keyword arguments specifying an instance of a TokenizerI subclass. This way, you have the ability to provide your own tokenizer instance if the default tokenizer is unsuitable.

There's more...

RegexpTokenizer can also work by matching the gaps, as opposed to the tokens. Instead of using re.findall(), the RegexpTokenizer class will use re.split(). This is how the BlanklineTokenizer class in nltk.tokenize is implemented.

Simple whitespace tokenizer

The following is a simple example of using RegexpT okenizer to tokenize on whitespace:

```
>>> tokenizer = RegexpTokenizer('\s+', gaps=True)
>>> tokenizer.tokenize("Can't is a contraction.")
["Can't", 'is', 'a', 'contraction.']
```

Notice that punctuation still remains in the tokens. The gaps=True parameter means that the pattern is used to identify gaps to tokenize on. If we used gaps=False, then the pattern would be used to identify tokens.

See also

For simpler word tokenization, see the previous recipe.

Training a sentence tokenizer

NLTK's default sentence tokenizer is general purpose, and usually works quite well. But sometimes it is not the best choice for your text. Perhaps your text uses nonstandard punctuation, or is formatted in a unique way. In such cases, training your own sentence tokenizer can result in much more accurate sentence tokenization.

Getting ready

For this example, we'll be using the webtext corpus, specifically the overheard.txt file, so make sure you've downloaded this corpus. The text in this file is formatted as dialog that looks like this:

```
White guy: So, do you have any plans for this evening?
Asian girl: Yeah, being angry!
White guy: Oh, that sounds good.
```

As you can see, this isn't your standard paragraph of sentences formatting, which makes it a perfect case for training a sentence tokenizer.

How to do it...

NLTK provides a PunktSentenceTokenizer class that you can train on raw text to produce a custom sentence tokenizer. You can get raw text either by reading in a file, or from an NLTK corpus using the raw() method. Here's an example of training a sentence tokenizer on dialog text, using overheard.txt from the webtext corpus:

```
>>> from nltk.tokenize import PunktSentenceTokenizer
>>> from nltk.corpus import webtext
>>> text = webtext.raw('overheard.txt')
>>> sent tokenizer = PunktSentenceTokenizer(text)
```

Let's compare the results to the default sentence tokenizer, as follows:

```
>>> sents1 = sent_tokenizer.tokenize(text)
>>> sents1[0]
'White guy: So, do you have any plans for this evening?'
>>> from nltk.tokenize import sent_tokenize
>>> sents2 = sent_tokenize(text)
>>> sents2[0]
'White guy: So, do you have any plans for this evening?'
>>> sents1[678]
'Girl: But you already have a Big Mac...'
>>> sents2[678]
'Girl: But you already have a Big Mac...\\nHobo: Oh, this is all
theatrical.'
```

While the first sentence is the same, you can see that the tokenizers disagree on how to tokenize sentence 679 (this is the first sentence where the tokenizers diverge). The default tokenizer includes the next line of dialog, while our custom tokenizer correctly thinks that the next line is a separate sentence. This difference is a good demonstration of why it can be useful to train your own sentence tokenizer, especially when your text isn't in the typical paragraph-sentence structure.

How it works...

The PunktSentenceTokenizer class uses an unsupervised learning algorithm to learn what constitutes a sentence break. It is unsupervised because you don't have to give it any labeled training data, just raw text. You can read more about these kinds of algorithms at https://en.wikipedia.org/wiki/Unsupervised_learning. The specific technique used in this case is called sentence boundary detection and it works by counting punctuation and tokens that commonly end a sentence, such as a period or newline, then using the resulting frequencies to decide what the sentence boundaries should actually look like.

This is a simplified description of the algorithm—if you'd like more details, take a look at the source code of the nltk.tokenize.punkt.PunktTrainer class, which can be found online at http://www.nltk.org/_modules/nltk/tokenize/punkt.html#PunktSentenceTokenizer.

There's more...

The PunktSentenceTokenizer class learns from any string, which means you can open a text file and read its content. Here is an example of reading overheard.txt directly instead of using the raw() corpus method. This assumes that the webtext corpus is located in the standard directory at /usr/share/nltk_data/corpora. We also have to pass a specific encoding to the open() function, as follows, because the file is not in ASCII:

```
>>> with open('/usr/share/nltk_data/corpora/webtext/overheard.txt',
encoding='ISO-8859-2') as f:
... text = f.read()
>>> sent_tokenizer = PunktSentenceTokenizer(text)
>>> sents = sent_tokenizer.tokenize(text)
>>> sents[0]
'White guy: So, do you have any plans for this evening?'
>>> sents[678]
'Girl: But you already have a Big Mac...'
```

Once you have a custom sentence tokenizer, you can use it for your own corpora. Many corpus readers accept a sent_tokenizer parameter, which lets you override the default sentence tokenizer object with your own sentence tokenizer. Corpus readers are covered in more detail in <u>Chapter 3</u>, *Creating Custom Corpora*.

See also

Most of the time, the default sentence tokenizer will be sufficient. This is covered in the first recipe, *Tokenizing text into sentences*.

Filtering stopwords in a tokenized sentence

Stopwords are common words that generally do not contribute to the meaning of a sentence, at least for the purposes of information retrieval and natural language processing. These are words such as *the* and *a*. Most search engines will filter out stopwords from search queries and documents in order to save space in their index.

Getting ready

NLTK comes with a stopwords corpus that contains word lists for many languages. Be sure to unzip the data file, so NLTK can find these word lists at nltk data/corpora/stopwords/.

How to do it...

We're going to create a set of all English stopwords, then use it to filter stopwords from a sentence with the help of the following code:

```
>>> from nltk.corpus import stopwords
>>> english_stops = set(stopwords.words('english'))
>>> words = ["Can't", 'is', 'a', 'contraction']
>>> [word for word in words if word not in english_stops]
["Can't", 'contraction']
```

How it works...

The stopwords corpus is an instance of nltk.corpus.reader.WordListCorpusReader. As such, it has a words () method that can take a single argument for the file ID, which in this case is 'english', referring to a file containing a list of English stopwords. You could also call stopwords.words() with no argument to get a list of all stopwords in every language available.

There's more...

You can see the list of all English stopwords using stopwords.words('english') or by examining the word list file at nltk_data/corpora/stopwords/english. There are also stopword lists for many other languages. You can see the complete list of languages using the fileids method as follows:

```
>>> stopwords.fileids()
['danish', 'dutch', 'english', 'finnish', 'french', 'german',
'hungarian', 'italian', 'norwegian', 'portuguese', 'russian',
'spanish', 'swedish', 'turkish']
```

Any of these fileids can be used as an argument to the words () method to get a list of stopwords for that language. For example:

```
>>> stopwords.words('dutch')
['de', 'en', 'van', 'ik', 'te', 'dat', 'die', 'in', 'een', 'hij',
'het', 'niet', 'zijn', 'is', 'was', 'op', 'aan', 'met', 'als',
'voor', 'had', 'er', 'maar', 'om', 'hem', 'dan', 'zou', 'of', 'wat',
'mijn', 'men', 'dit', 'zo', 'door', 'over', 'ze', 'zich', 'bij',
'ook', 'tot', 'je', 'mij', 'uit', 'der', 'daar', 'haar', 'naar',
'heb', 'hoe', 'heeft', 'hebben', 'deze', 'u', 'want', 'nog', 'zal',
'me', 'zij', 'nu', 'ge', 'geen', 'omdat', 'iets', 'worden', 'toch',
'al', 'waren', 'veel', 'meer', 'doen', 'toen', 'moet', 'ben',
'zonder', 'kan', 'hun', 'dus', 'alles', 'onder', 'ja', 'eens',
'hier', 'wie', 'werd', 'altijd', 'doch', 'wordt', 'wezen', 'kunnen',
'ons', 'zelf', 'tegen', 'na', 'reeds', 'wil', 'kon', 'niets', 'uw',
'iemand', 'geweest', 'andere']
```

See also

If you'd like to create your own stopwords corpus, see the *Creating a wordlist corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*, to learn how to use WordListCorpusReader. We'll also be using stopwords in the *Discovering word collocations* recipe later in this chapter.

Looking up Synsets for a word in WordNet

WordNet is a lexical database for the English language. In other words, it's a dictionary designed specifically for natural language processing.

NLTK comes with a simple interface to look up words in WordNet. What you get is a list of **Synset** instances, which are groupings of synonymous words that express the same concept. Many words have only one Synset, but some have several. In this recipe, we'll explore a single Synset, and in the next recipe, we'll look at several in more detail.

Getting ready

Be sure you've unzipped the wordnet corpus at nltk_data/corpora/wordnet. This will allow WordNetCorpusReader to access it.

How to do it...

Now we're going to look up the Synset for cookbook, and explore some of the properties and methods of a Synset using the following code:

```
>>> from nltk.corpus import wordnet
>>> syn = wordnet.synsets('cookbook')[0]
>>> syn.name()
'cookbook.n.01'
>>> syn.definition()
'a book of recipes and cooking directions'
```

How it works...

You can look up any word in WordNet using wordnet.synsets (word) to get a list of Synsets. The list may be empty if the word is not found. The list may also have quite a few elements, as some words can have many possible meanings, and, therefore, many Synsets.

There's more...

Each Synset in the list has a number of methods you can use to learn more about it. The name () method will give you a unique name for the Synset, which you can use to get the Synset directly:

```
>>> wordnet.synset('cookbook.n.01')
Synset('cookbook.n.01')
```

The definition () method should be self-explanatory. Some Synsets also have an examples () method, which contains a list of phrases that use the word in context:

```
>>> wordnet.synsets('cooking')[0].examples()
['cooking can be a great art', 'people are needed who have
```

experience in cookery', 'he left the preparation of meals to his wife']

Working with hypernyms

Synsets are organized in a structure similar to that of an inheritance tree. More abstract terms are known as **hypernyms** and more specific terms are **hyponyms**. This tree can be traced all the way up to a root hypernym.

Hypernyms provide a way to categorize and group words based on their similarity to each other. The *Calculating WordNet Synset similarity* recipe details the functions used to calculate the similarity based on the distance between two words in the hypernym tree:

```
>>> syn.hypernyms()
[Synset('reference_book.n.01')]
>>> syn.hypernyms()[0].hyponyms()
[Synset('annual.n.02'), Synset('atlas.n.02'),
Synset('cookbook.n.01'), Synset('directory.n.01'),
Synset('encyclopedia.n.01'), Synset('handbook.n.01'),
Synset('instruction_book.n.01'), Synset('source_book.n.01'),
Synset('wordbook.n.01')]
>>> syn.root_hypernyms()
[Synset('entity.n.01')]
```

As you can see, reference_book is a hypernym of cookbook, but cookbook is only one of the many hyponyms of reference_book. And all these types of books have the same root hypernym, which is entity, one of the most abstract terms in the English language. You can trace the entire path from entity down to cookbook using the hypernym_paths() method, as follows:

```
>>> syn.hypernym_paths()
[[Synset('entity.n.01'), Synset('physical_entity.n.01'),
Synset('object.n.01'), Synset('whole.n.02'),
Synset('artifact.n.01'), Synset('creation.n.02'),
Synset('product.n.02'), Synset('work.n.02'),
Synset('publication.n.01'), Synset('book.n.01'),
Synset('reference book.n.01'), Synset('cookbook.n.01')]]
```

The hypernym_paths() method returns a list of lists, where each list starts at the root hypernym and ends with the original Synset. Most of the time, you'll only get one nested list of Synsets.

Part of speech (POS)

You can also look up a simplified part-of-speech tag as follows:

```
>>> syn.pos()
'n'
```

There are four common part-of-speech tags (or POS tags) found in WordNet, as shown in the following table:

Part of speech	Tag	
Noun	n	
Adjective	a	
Adverb	r	
Verb	v	

These POS tags can be used to look up specific Synsets for a word. For example, the word 'great' can be used as a noun or an adjective. In WordNet, 'great' has 1 noun Synset and 6 adjective Synsets, as shown in the following code:

```
>>> len(wordnet.synsets('great'))
7
>>> len(wordnet.synsets('great', pos='n'))
1
>>> len(wordnet.synsets('great', pos='a'))
6
```

These POS tags will be referenced more in the Using WordNet for tagging recipe in Chapter 4, Part-of-speech Tagging.

See also

In the next two recipes, we'll explore lemmas and how to calculate Synset similarity. And in <u>Chapter 2</u>, *Replacing and Correcting Words*, we'll use WordNet for lemmatization, synonym replacement, and then explore the use of antonyms.

Looking up lemmas and synonyms in WordNet

Building on the previous recipe, we can also look up lemmas in WordNet to find synonyms of a word. A **lemma** (in linguistics), is the canonical form or morphological form of a word.

How to do it ...

In the following code, we'll find that there are two lemmas for the cookbook Synset using the lemmas () method:

```
>>> from nltk.corpus import wordnet
>>> syn = wordnet.synsets('cookbook')[0]
>>> lemmas = syn.lemmas()
>>> len(lemmas)
2
>>> lemmas[0].name()
'cookbook'
>>> lemmas[1].name()
'cookery_book'
>>> lemmas[0].synset() == lemmas[1].synset()
True
```

How it works...

As you can see, cookery_book and cookbook are two distinct lemmas in the same Synset. In fact, a lemma can only belong to a single Synset. In this way, a Synset represents a group of lemmas that all have the same meaning, while a lemma represents a distinct word form.

There's more...

Since all the lemmas in a Synset have the same meaning, they can be treated as synonyms. So if you wanted to get all synonyms for a Synset, you could do the following:

```
>>> [lemma.name() for lemma in syn.lemmas()]
['cookbook', 'cookery_book']
```

All possible synonyms

As mentioned earlier, many words have multiple Synsets because the word can have different meanings depending on the context. But, let's say you didn't care about the context, and wanted to get all the possible synonyms for a word:

```
>>> synonyms = []
>>> for syn in wordnet.synsets('book'):
... for lemma in syn.lemmas():
... synonyms.append(lemma.name())
```

>>> len(synonyms)
38

As you can see, there appears to be 38 possible synonyms for the word 'book'. But in fact, some synonyms are verb forms, and many synonyms are just different usages of 'book'. If, instead, we take the set of synonyms, there are fewer unique words, as shown in the following code:

```
>>> len(set(synonyms))
25
```

Antonyms

Some lemmas also have antonyms. The word good, for example, has 27 Synsets, five of which have lemmas with antonyms, as shown in the following code:

```
>>> gn2 = wordnet.synset('good.n.02')
>>> qn2.definition()
'moral excellence or admirableness'
>>> evil = gn2.lemmas()[0].antonyms()[0]
>>> evil.name
'evil'
>>> evil.synset().definition()
'the quality of being morally wrong in principle or practice'
>>> ga1 = wordnet.synset('good.a.01')
>>> gal.definition()
'having desirable or positive qualities especially those suitable
for a thing specified'
>>> bad = gal.lemmas()[0].antonyms()[0]
>>> bad.name()
'bad'
>>> bad.synset().definition()
'having undesirable or negative gualities'
```

The antonyms () method returns a list of lemmas. In the first case, as we can see in the previous code, the second Synset for good as a noun is defined as moral excellence, and its first antonym is evil, defined as morally wrong. In the second case, when good is used as an adjective to describe positive qualities, the first antonym is bad, which describes negative qualities.

See also

In the next recipe, we'll learn how to calculate Synset similarity. Then in <u>Chapter 2</u>, *Replacing and Correcting Words*, we'll revisit lemmas for lemmatization, synonym replacement, and antonym replacement.

Calculating WordNet Synset similarity

Synsets are organized in a *hypernym* tree. This tree can be used for reasoning about the similarity between the Synsets it contains. The closer the two Synsets are in the tree, the more similar they are.

How to do it...

If you were to look at all the hyponyms of reference_book (which is the hypernym of cookbook), you'd see that one of them is instruction_book. This seems intuitively very similar to a cookbook, so let's see what WordNet similarity has to say about it with the help of the following code:

So they are over 91% similar!

How it works...

The wup_similarity method is short for **Wu-Palmer Similarity**, which is a scoring method based on how similar the word senses are and where the Synsets occur relative to each other in the hypernym tree. One of the core metrics used to calculate similarity is the shortest path distance between the two Synsets and their common hypernym:

```
>>> ref = cb.hypernyms()[0]
>>> cb.shortest_path_distance(ref)
1
>>> ib.shortest_path_distance(ref)
1
>>> cb.shortest_path_distance(ib)
2
```

So cookbook and instruction_book must be very similar, because they are only one step away from the same reference_book hypernym, and, therefore, only two steps away from each other.

There's more...

Let's look at two dissimilar words to see what kind of score we get. We'll compare dog with cookbook, two seemingly very different words.

```
>>> dog = wordnet.synsets('dog')[0]
>>> dog.wup_similarity(cb)
0.38095238095238093
```

Wow, dog and cookbook are apparently 38% similar! This is because they share common hypernyms further up the tree:

```
>>> sorted(dog.common_hypernyms(cb))
[Synset('entity.n.01'), Synset('object.n.01'),
Synset('physical_entity.n.01'), Synset('whole.n.02')]
```

Comparing verbs

The previous comparisons were all between nouns, but the same can be done for verbs as well:

The previous Synsets were obviously handpicked for demonstration, and the reason is that the hypernym tree for verbs has a lot more breadth and a lot less depth. While most nouns can be traced up to the hypernym object, thereby providing a basis for similarity, many verbs do not share common hypernyms, making WordNet unable to calculate the similarity. For example, if you were to use the Synset for bake.v.01 in the previous code, instead of bake.v.02, the return value would be None. This is because the root hypernyms of both the Synsets are different, with no overlapping paths. For this reason, you also cannot calculate the similarity between words with different parts of speech.

Path and Leacock Chordorow (LCH) similarity

Two other similarity comparisons are the path similarity and the LCH similarity, as shown in the following code:

As you can see, the number ranges are very different for these scoring methods, which is why I prefer the wup similarity method.

See also

The recipe on *Looking up Synsets for a word in WordNet* has more details about hypernyms and the hypernym tree.

Discovering word collocations

Collocations are two or more words that tend to appear frequently together, such as United States. Of course, there are many other words that can come after United, such as United Kingdom and United Airlines. As with many aspects of natural language processing, context is very important. And for collocations, context is everything!

In the case of collocations, the context will be a document in the form of a list of words. Discovering collocations in this list of words means that we'll find common phrases that occur frequently throughout the text. For fun, we'll start with the script for *Monty Python and the Holy Grail*.

Getting ready

The script for *Monty Python and the Holy Grail* is found in the webtext corpus, so be sure that it's unzipped at nltk_data/corpora/webtext/.

How to do it...

We're going to create a list of all lowercased words in the text, and then produce BigramCollocationFinder, which we can use to find bigrams, which are pairs of words. These bigrams are found using association measurement functions in the nltk.metrics package, as follows:

```
>>> from nltk.corpus import webtext
>>> from nltk.collocations import BigramCollocationFinder
>>> from nltk.metrics import BigramAssocMeasures
>>> words = [w.lower() for w in webtext.words('grail.txt')]
>>> bcf = BigramCollocationFinder.from_words(words)
>>> bcf.nbest(BigramAssocMeasures.likelihood_ratio, 4)
[("'", 's'), ('arthur', ':'), ('#', '1'), ("'", 't')]
```

Well, that's not very useful! Let's refine it a bit by adding a word filter to remove punctuation and stopwords:

```
>>> from nltk.corpus import stopwords
>>> stopset = set(stopwords.words('english'))
>>> filter_stops = lambda w: len(w) < 3 or w in stopset
>>> bcf.apply_word_filter(filter_stops)
>>> bcf.nbest(BigramAssocMeasures.likelihood_ratio, 4)
[('black', 'knight'), ('clop', 'clop'), ('head', 'knight'),
('mumble', 'mumble')]
```

Much better, we can clearly see four of the most common bigrams in *Monty Python and the Holy Grail*. If you'd like to see more than four, simply increase the number to whatever you want, and the collocation finder will do its best.
How it works...

BigramCollocationFinder constructs two frequency distributions: one for each word, and another for bigrams. A frequency distribution, or FreqDist in NLTK, is basically an enhanced Python dictionary where the keys are what's being counted, and the values are the counts. Any filtering functions that are applied reduce the size of these two FreqDists by eliminating any words that don't pass the filter. By using a filtering function to eliminate all words that are one or two characters, and all English stopwords, we can get a much cleaner result. After filtering, the collocation finder is ready to accept a generic scoring function for finding collocations.

There's more...

In addition to BigramCollocationFinder, there's also TrigramCollocationFinder, which finds triplets instead of pairs. This time, we'll look for trigrams in Australian singles advertisements with the help of the following code:

```
>>> from nltk.collocations import TrigramCollocationFinder
>>> from nltk.metrics import TrigramAssocMeasures
>>> words = [w.lower() for w in webtext.words('singles.txt')]
>>> tcf = TrigramCollocationFinder.from_words(words)
>>> tcf.apply_word_filter(filter_stops)
>>> tcf.apply_freq_filter(3)
>>> tcf.nbest(TrigramAssocMeasures.likelihood_ratio, 4)
[('long', 'term', 'relationship')]
```

Now, we don't know whether people are looking for a long-term relationship or not, but clearly it's an important topic. In addition to the stopword filter, I also applied a frequency filter, which removed any trigrams that occurred less than three times. This is why only one result was returned when we asked for four because there was only one result that occurred more than two times.

Scoring functions

There are many more scoring functions available besides <code>likelihood_ratio()</code>. But other than <code>raw_freq()</code>, you may need a bit of a statistics background to understand how they work. Consult the NLTK API documentation for <code>NgramAssocMeasures</code> in the <code>nltk.metrics</code> package to see all the possible scoring functions.

Scoring ngrams

In addition to the nbest () method, there are two other ways to get ngrams (a generic term used for describing bigrams and trigrams) from a collocation finder:

- above_score(score_fn, min_score): This can be used to get all ngrams with scores that are at least min_score. The min_score value that you choose will depend heavily on the score_fn you use.
- score_ngrams (score_fn): This will return a list with tuple pairs of (ngram, score). This
 can be used to inform your choice for min_score.

See also

The nltk.metrics module will be used again in the *Measuring precision and recall of a classifier* and *Calculating high information words* recipes in <u>Chapter 7</u>, *Text Classification*.

Chapter 2. Replacing and Correcting Words

In this chapter, we will cover the following recipes:

- Stemming words
- · Lemmatizing words with WordNet
- Replacing words matching regular expressions
- Removing repeating characters
- Spelling correction with Enchant
- Replacing synonyms
- Replacing negations with antonyms

Introduction

In this chapter, we will go over various word replacement and correction techniques. The recipes cover the gamut of linguistic compression, spelling correction, and text normalization. All of these methods can be very useful for preprocessing text before search indexing, document classification, and text analysis.

Stemming words

Stemming is a technique to remove affixes from a word, ending up with the stem. For example, the stem of cooking is cook, and a good stemming algorithm knows that the ing suffix can be removed. Stemming is most commonly used by search engines for indexing words. Instead of storing all forms of a word, a search engine can store only the stems, greatly reducing the size of index while increasing retrieval accuracy.

One of the most common stemming algorithms is the **Porter stemming algorithm** by Martin Porter. It is designed to remove and replace well-known suffixes of English words, and its usage in NLTK will be covered in the next section.

Note

The resulting stem is not always a valid word. For example, the stem of cookery is cookeri. This is a feature, not a bug.

How to do it...

NLTK comes with an implementation of the Porter stemming algorithm, which is very easy to use. Simply instantiate the PorterStemmer class and call the stem() method with the word you want to stem:

```
>>> from nltk.stem import PorterStemmer
>>> stemmer = PorterStemmer()
>>> stemmer.stem('cooking')
'cook'
>>> stemmer.stem('cookery')
'cookeri'
```

How it works...

The PorterStemmer class knows a number of regular word forms and suffixes and uses this knowledge to transform your input word to a final stem through a series of steps. The resulting stem is often a shorter word, or at least a common form of the word, which has the same root meaning.

There's more...

There are other stemming algorithms out there besides the Porter stemming algorithm, such as the **Lancaster stemming algorithm**, developed at Lancaster University. NLTK includes it as the LancasterStemmer class. At the time of writing this book, there is no definitive research demonstrating the superiority of one algorithm over the other. However, Porter stemming algorithm is generally the default choice.

All the stemmers covered next inherit from the StemmerI interface, which defines the stem() method. The following is an inheritance diagram that explains this:



The LancasterStemmer class

The functions of the LancasterStemmer class are just like the functions of the PorterStemmer class, but can produce slightly different results. It is known to be slightly more aggressive than the PorterStemmer functions:

```
>>> from nltk.stem import LancasterStemmer
>>> stemmer = LancasterStemmer()
>>> stemmer.stem('cooking')
'cook'
>>> stemmer.stem('cookery')
'cookery'
```

The RegexpStemmer class

You can also construct your own stemmer using the RegexpStemmer class. It takes a single regular expression (either compiled or as a string) and removes any prefix or suffix that matches the expression:

```
>>> from nltk.stem import RegexpStemmer
>>> stemmer = RegexpStemmer('ing')
>>> stemmer.stem('cooking')
'cook'
>>> stemmer.stem('cookery')
'cookery'
>>> stemmer.stem('ingleside')
'leside'
```

A RegexpStemmer class should only be used in very specific cases that are not covered by the PorterStemmer or the LancasterStemmer class because it can only handle very specific patterns and is not a general-purpose algorithm.

The SnowballStemmer class

The SnowballStemmer class supports 13 non-English languages. It also provides two English stemmers: the original porter algorithm as well as the new English stemming algorithm. To use the SnowballStemmer class, create an instance with the name of the language you are using and then call the stem() method. Here is a list of all the supported languages and an example using the Spanish SnowballStemmer class:

```
>>> from nltk.stem import SnowballStemmer
>>> SnowballStemmer.languages('danish', 'dutch', 'english',
'finnish', 'french', 'german', 'hungarian', 'italian', 'norwegian',
'porter', 'portuguese', 'romanian', 'russian', 'spanish', 'swedish')
>>> spanish_stemmer = SnowballStemmer('spanish')
>>> spanish_stemmer.stem('hola')
u'hol'
```

See also

In the next recipe, we will cover Lemmatization, which is quite similar to stemming, but subtly different.

Lemmatizing words with WordNet

Lemmatization is very similar to stemming, but is more akin to synonym replacement. A lemma is a root word, as opposed to the root stem. So unlike stemming, you are always left with a valid word that means the same thing. However, the word you end up with can be completely different. A few examples will explain this.

Getting ready

Make sure that you have unzipped the wordnet corpus in nltk_data/corpora/wordnet. This will allow the WordNetLemmatizer class to access WordNet. You should also be familiar with the part-of-speech tags covered in the *Looking up Synsets for a word in WordNet* recipe of <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*.

How to do it...

We will use the WordNetLemmatizer class to find lemmas:

```
>>> from nltk.stem import WordNetLemmatizer
>>> lemmatizer = WordNetLemmatizer()
>>> lemmatizer.lemmatize('cooking')
'cooking'
>>> lemmatizer.lemmatize('cooking', pos='v')
'cook'
>>> lemmatizer.lemmatize('cookbooks')
'cookbook'
```

How it works...

The WordNetLemmatizer class is a thin wrapper around the wordnet corpus and uses the morphy() function of the WordNetCorpusReader class to find a lemma. If no lemma is found, or the word itself is a lemma, the word is returned as is. Unlike with stemming, knowing the part of speech of the word is important. As demonstrated previously, cooking does not return a different lemma unless you specify that the POS is a verb. This is because the default POS is a noun, and as a noun, cooking is its own lemma. On the other hand, cookbooks is a noun with its singular form, cookbook, as its lemma.

There's more...

Here's an example that illustrates one of the major differences between stemming and lemmatization:

```
>>> from nltk.stem import PorterStemmer
>>> stemmer = PorterStemmer()
>>> stemmer.stem('believes')
'believ'
```

```
>>> lemmatizer.lemmatize('believes')
'belief'
```

Instead of just chopping off the es like the PorterStemmer class, the WordNetLemmatizer class finds a valid root word. Where a stemmer only looks at the form of the word, the lemmatizer looks at the meaning of the word. By returning a lemma, you will always get a valid word.

Combining stemming with lemmatization

Stemming and lemmatization can be combined to compress words more than either process can by itself. These cases are somewhat rare, but they do exist:

```
>>> stemmer.stem('buses')
'buse'
>>> lemmatizer.lemmatize('buses')
'bus'
>>> stemmer.stem('bus')
'bu'
```

In this example, stemming saves one character, lemmatization saves two characters, and stemming the lemma saves a total of three characters out of five characters. That is nearly a 60% compression rate! This level of word compression over many thousands of words, while unlikely to always produce such high gains, can still make a huge difference.

See also

In the previous recipe, we covered the basics of stemming and WordNet was introduced in the *Looking up* Synsets for a word in WordNet and Looking up lemmas and synonyms in WordNet recipes of <u>Chapter</u> <u>1</u>, *Tokenizing Text and WordNet Basics*. Looking forward, we will cover the *Using WordNet for tagging* recipe in <u>Chapter 4</u>, *Part-of-speech Tagging*.

Replacing words matching regular expressions

Now, we are going to get into the process of replacing words. If stemming and lemmatization are a kind of linguistic compression, then word replacement can be thought of as error correction or text normalization.

In this recipe, we will replace words based on regular expressions, with a focus on expanding contractions. Remember when we were tokenizing words in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, and it was clear that most tokenizers had trouble with contractions? This recipe aims to fix this by replacing contractions with their expanded forms, for example, by replacing "can't" with "cannot" or "would've" with "would have".

Getting ready

Understanding how this recipe works will require a basic knowledge of regular expressions and the remodule. The key things to know are matching patterns and the re.sub() function.

How to do it...

First, we need to define a number of replacement patterns. This will be a list of tuple pairs, where the first element is the pattern to match with and the second element is the replacement.

Next, we will create a RegexpReplacer class that will compile the patterns and provide a replace() method to substitute all the found patterns with their replacements.

The following code can be found in the replacers.py module in the book's code bundle and is meant to be imported, not typed into the console:

```
import re
replacement patterns = [
  (r'won\'t', 'will not'),
  (r'can\'t', 'cannot'),
  (r'i\'m', 'i am'),
  (r'ain\'t', 'is not'),
  (r'(\w+)\'ll', '\g<1> will'),
  (r'(\lambda +)n\lambda't', \lambda < 1 > not'),
  (r'(\w+)\'ve', '\g<1> have'),
  (r'(\w+)\'s', '\g<1> is'),
  (r'(\w+)\'re', '\q<1> are'),
  (r'(\w+)\'d', '\q<1> would')
1
class RegexpReplacer(object):
  def init (self, patterns=replacement patterns):
    self.patterns = [(re.compile(regex), repl) for (regex, repl) in
```

```
patterns]

def replace(self, text):
   s = text
   for (pattern, repl) in self.patterns:
      s = re.sub(pattern, repl, s)
   return s
```

How it works...

Here is a simple usage example:

```
>>> from replacers import RegexpReplacer
>>> replacer = RegexpReplacer()
>>> replacer.replace("can't is a contraction")
'cannot is a contraction'
>>> replacer.replace("I should've done that thing I didn't do")
'I should have done that thing I did not do'
```

The RegexpReplacer.replace() function works by replacing every instance of a replacement pattern with its corresponding substitution pattern. In replacement patterns, we have defined tuples such as $r'(\langle w+ \rangle \langle ve' and \langle g<1 \rangle$ have'. The first element matches a group of ASCII characters followed by 've. By grouping the characters before 've in parenthesis, a match group is found and can be used in the substitution pattern with the $\langle g<1 \rangle$ reference. So, we keep everything before 've, then replace 've with the word have. This is how should've can become should have.

There's more...

This replacement technique can work with any kind of regular expression, not just contractions. So, you can replace any occurrence of & with and, or eliminate all occurrences of – by replacing it with an empty string. The RegexpReplacer class can take any list of replacement patterns for whatever purpose.

Replacement before tokenization

Let's try using the RegexpReplacer class as a preliminary step before tokenization:

```
>>> from nltk.tokenize import word_tokenize
>>> from replacers import RegexpReplacer
>>> replacer = RegexpReplacer()
>>> word_tokenize("can't is a contraction")
['ca', "n't", 'is', 'a', 'contraction']
>>> word_tokenize(replacer.replace("can't is a contraction"))
['can', 'not', 'is', 'a', 'contraction']
```

Much better! By eliminating the contractions in the first place, the tokenizer will produce cleaner results. Cleaning up the text before processing is a common pattern in natural language processing.

See also

For more information on tokenization, see the first three recipes in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*. For more replacement techniques, continue reading the rest of this chapter.

Removing repeating characters

In everyday language, people are often not strictly grammatical. They will write things such as I loooooove it in order to emphasize the word love. However, computers don't know that "loooooove" is a variation of "love" unless they are told. This recipe presents a method to remove these annoying repeating characters in order to end up with a *proper* English word.

Getting ready

As in the previous recipe, we will be making use of the $r \in$ module, and more specifically, backreferences. A **backreference** is a way to refer to a previously matched group in a regular expression. This will allow us to match and remove repeating characters.

How to do it...

We will create a class that has the same form as the RegexpReplacer class from the previous recipe. It will have a replace () method that takes a single word and returns a more correct version of that word, with the dubious repeating characters removed. This code can be found in replacers.py in the book's code bundle and is meant to be imported:

```
import re

class RepeatReplacer(object):
    def __init__(self):
        self.repeat_regexp = re.compile(r'(\w*)(\w)\2(\w*)')
        self.repl = r'\1\2\3'

    def replace(self, word):
        repl_word = self.repeat_regexp.sub(self.repl, word)

        if repl_word != word:
        return self.replace(repl_word)
        else:
        return repl_word
```

And now some example use cases:

```
>>> from replacers import RepeatReplacer
>>> replacer = RepeatReplacer()
>>> replacer.replace('looooove')
'love'
>>> replacer.replace('oooooh')
'oh'
>>> replacer.replace('goose')
'gose'
```

How it works...

The RepeatReplacer class starts by compiling a regular expression to match and define a replacement string with backreferences. The repeat_regexp pattern matches three groups:

- 0 or more starting characters (\w*)
- A single character (\w) that is followed by another instance of that character $(\2)$
- 0 or more ending characters $(\backslash w^*)$

The replacement string is then used to keep all the matched groups, while discarding the backreference to the second group. So, the word loooove gets split into (looo) (o)o(ve) and then recombined as loooove, discarding the last o. This continues until only one o remains, when repeat_regexp no longer matches the string and no more characters are removed.

There's more...

In the preceding examples, you can see that the RepeatReplacer class is a bit too greedy and ends up changing goose into gose. To correct this issue, we can augment the replace() function with a WordNet lookup. If WordNet recognizes the word, then we can stop replacing characters. Here is the WordNet-augmented version:

```
import re
from nltk.corpus import wordnet
class RepeatReplacer(object):
    def __init__(self):
        self.repeat_regexp = re.compile(r'(\w*)(\w)\2(\w*)')
        self.repl = r'\1\2\3'
    def replace(self, word):
        if wordnet.synsets(word):
            return word
        repl_word = self.repeat_regexp.sub(self.repl, word)
        if repl_word != word:
            return self.replace(repl_word)
        else:
            return repl word
```

Now, goose will be found in WordNet, and no character replacement will take place. Also, oooooh will become ooh instead of oh because ooh is actually a word in WordNet, defined as an expression of admiration or pleasure.

See also

Read the next recipe to learn how to correct misspellings. For more information on WordNet, refer to the WordNet recipes in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*. We will also be using WordNet for antonym replacement later in this chapter.

Spelling correction with Enchant

Replacing repeating characters is actually an extreme form of spelling correction. In this recipe, we will take on the less extreme case of correcting minor spelling issues using **Enchant**—a spelling correction API.

Getting ready

You will need to install Enchant and a dictionary for it to use. Enchant is an offshoot of the AbiWord open source word processor, and more information on it can be found at <u>http://www.abisource.com/</u><u>projects/enchant/</u>.

For dictionaries, **Aspell** is a good open source spellchecker and dictionary that can be found at <u>http://aspell.net/</u>.

Finally, you will need the **PyEnchant** library, which can be found at the following link: <u>http://pythonhosted.org/pyenchant/</u>

You should be able to install it with the <code>easy_install</code> command that comes with Python setuptools, such as by typing <code>sudo easy_install</code> pyenchant on Linux or Unix. On a Mac machine, PyEnchant may be difficult to install. If you have difficulties, consult http://pythonhosted.org/pyenchant/download.html.

How to do it...

We will create a new class called SpellingReplacer in replacers.py, and this time, the replace() method will check Enchant to see whether the word is valid. If not, we will look up the suggested alternatives and return the best match using nltk.metrics.edit_distance():

```
import enchant
from nltk.metrics import edit_distance

class SpellingReplacer(object):
    def __init__(self, dict_name='en', max_dist=2):
        self.spell_dict = enchant.Dict(dict_name)
        self.max_dist = max_dist

    def replace(self, word):
        if self.spell_dict.check(word):
            return word
        suggestions = self.spell_dict.suggest(word)

    if suggestions and edit_distance(word, suggestions[0]) <=
        self.max_dist:
        return suggestions[0]</pre>
```

```
else:
return word
```

The preceding class can be used to correct English spellings, as follows:

```
>>> from replacers import SpellingReplacer
>>> replacer = SpellingReplacer()
>>> replacer.replace('cookbok')
'cookbook'
```

How it works...

The SpellingReplacer class starts by creating a reference to an Enchant dictionary. Then, in the replace() method, it first checks whether the given word is present in the dictionary. If it is, no spelling correction is necessary and the word is returned. If the word is not found, it looks up a list of suggestions and returns the first suggestion, as long as its edit distance is less than or equal to max_dist. The edit distance is the number of character changes necessary to transform the given word into the suggested word. The max_dist value then acts as a constraint on the Enchant suggest function to ensure that no unlikely replacement words are returned. Here is an example showing all the suggestions for language, a misspelling of language:

```
>>> import enchant
>>> d = enchant.Dict('en')
>>> d.suggest('languege')
['language', 'languages', 'languor', "language's"]
```

Except for the correct suggestion, language, all the other words have an edit distance of three or greater. You can try this yourself with the following code:

```
>>> from nltk.metrics import edit_distance
>>> edit_distance('language', 'languege')
1
>>> edit_distance('language', 'languo')
3
```

There's more...

You can use language dictionaries other than en, such as en_GB, assuming the dictionary has already been installed. To check which other languages are available, use enchant.list_languages():

```
>>> enchant.list_languages()
['en', 'en CA', 'en GB', 'en US']
```

Tip

If you try to use a dictionary that doesn't exist, you will get enchant.DictNotFoundError. You can first check whether the dictionary exists using enchant.dict_exists(), which will return True if the named dictionary exists, or False otherwise.

The en_GB dictionary

Always ensure that you use the correct dictionary for whichever language you are performing spelling correction on. The en_US dictionary can give you different results than en_GB, such as for the word theater. The word theater is the American English spelling whereas the British English spelling is theatre:

```
>>> import enchant
>>> dUS = enchant.Dict('en_US')
>>> dUS.check('theater')
True
>>> dGB = enchant.Dict('en_GB')
>>> dGB.check('theater')
False
>>> from replacers import SpellingReplacer
>>> us_replacer = SpellingReplacer('en_US')
>>> us_replacer.replace('theater')
'theater'
>>> gb_replacer = SpellingReplacer('en_GB')
>>> gb_replacer.replace('theater')
'theatre'
```

Personal word lists

Enchant also supports personal word lists. These can be combined with an existing dictionary, allowing you to augment the dictionary with your own words. So, let's say you had a file named mywords.txt that had nltk on one line. You could then create a dictionary augmented with your personal word list as follows:

```
>>> d = enchant.Dict('en_US')
>>> d.check('nltk')
False
>>> d = enchant.DictWithPWL('en_US', 'mywords.txt')
>>> d.check('nltk')
True
```

To use an augmented dictionary with our SpellingReplacer class, we can create a subclass in replacers.py that takes an existing spelling dictionary:

```
class CustomSpellingReplacer(SpellingReplacer):
    def init (self, spell dict, max dist=2):
```

```
self.spell_dict = spell_dict
self.max dist = max dist
```

This CustomSpellingReplacer class will not replace any words that you put into mywords.txt:

```
>>> from replacers import CustomSpellingReplacer
>>> d = enchant.DictWithPWL('en_US', 'mywords.txt')
>>> replacer = CustomSpellingReplacer(d)
>>> replacer.replace('nltk')
'nltk'
```

See also

The previous recipe covered an extreme form of spelling correction by replacing repeating characters. You can also perform spelling correction by simple word replacement as discussed in the next recipe.

Replacing synonyms

It is often useful to reduce the vocabulary of a text by replacing words with common synonyms. By compressing the vocabulary without losing meaning, you can save memory in cases such as *frequency analysis* and *text indexing*. More details about these topics are available at https://en.wikipedia.org/wiki/Frequency_analysis and https://en.wikipedia.org/wiki/Frequency_analysis and https://en.wikipedia.org/wiki/Full_text_search. Vocabulary reduction can also increase the occurrence of significant collocations, which was covered in the *Discovering word collocations* recipe of Chapter 1, *Tokenizing Text and WordNet Basics*.

Getting ready

You will need a defined mapping of a word to its synonym. This is a simple controlled vocabulary. We will start by hardcoding the synonyms as a Python dictionary, and then explore other options to store synonym maps.

How to do it...

We'll first create a WordReplacer class in replacers.py that takes a word replacement mapping:

```
class WordReplacer(object):
    def __init__(self, word_map):
        self.word_map = word_map
    def replace(self, word):
        return self.word map.get(word, word)
```

Then, we can demonstrate its usage for simple word replacement:

```
>>> from replacers import WordReplacer
>>> replacer = WordReplacer({'bday': 'birthday'})
>>> replacer.replace('bday')
'birthday'
>>> replacer.replace('happy')
'happy'
```

How it works...

The WordReplacer class is simply a class wrapper around a Python dictionary. The replace() method looks up the given word in its word_map dictionary and returns the replacement synonym if it exists. Otherwise, the given word is returned as is.

If you were only using the word_map dictionary, you wouldn't need the WordReplacer class and could instead call word_map.get() directly. However, WordReplacer can act as a base class for other classes that construct the word_map dictionary from various file formats. Read on for more information.

There's more...

Hardcoding synonyms in a Python dictionary is not a good long-term solution. Two better alternatives are to store the synonyms in a CSV file or in a YAML file. Choose whichever format is easiest for those who maintain your synonym vocabulary. Both of the classes outlined in the following section inherit the replace() method from WordReplacer.

CSV synonym replacement

The CsvWordReplacer class extends WordReplacer in replacers.py in order to construct the word map dictionary from a CSV file:

```
import csv
class CsvWordReplacer(WordReplacer):
    def __init__(self, fname):
        word_map = {}
        for line in csv.reader(open(fname)):
            word, syn = line
            word_map[word] = syn
        super(CsvWordReplacer, self).__init__(word_map)
```

Your CSV file should consist of two columns, where the first column is the word and the second column is the synonym meant to replace it. If this file is called synonyms.csv and the first line is bday, birthday, then you can perform the following:

```
>>> from replacers import CsvWordReplacer
>>> replacer = CsvWordReplacer('synonyms.csv')
>>> replacer.replace('bday')
'birthday'
>>> replacer.replace('happy')
'happy'
```

YAML synonym replacement

If you have PyYAML installed, you can create YamlWordReplacer in replacers.py as shown in the following:

```
import yaml
class YamlWordReplacer(WordReplacer):
    def __init__ (self, fname):
        word_map = yaml.load(open(fname))
        super(YamlWordReplacer, self).__init__ (word_map)
```

Note

Download and installation instructions for PyYAML are located at <u>http://pyyaml.org/wiki/PyYAML</u>. You can also type pip install pyyaml on the command prompt

Your YAML file should be a simple mapping of word: synonym, such as bday: birthday. Note that the YAML syntax is very particular, and the space after the colon is required. If the file is named synonyms.yaml, then you can perform the following:

```
>>> from replacers import YamlWordReplacer
>>> replacer = YamlWordReplacer('synonyms.yaml')
>>> replacer.replace('bday')
'birthday'
>>> replacer.replace('happy')
'happy'
```

See also

You can use the WordReplacer class to perform any kind of word replacement, even spelling correction for more complicated words that can't be automatically corrected, as we did in the previous recipe. In the next recipe, we will cover antonym replacement.

Replacing negations with antonyms

The opposite of synonym replacement is **antonym replacement**. An **antonym** is a word that has the opposite meaning of another word. This time, instead of creating custom word mappings, we can use WordNet to replace words with unambiguous antonyms. Refer to the *Looking up lemmas and synonyms in WordNet* recipe in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, for more details on antonym lookups.

How to do it...

Let's say you have a sentence like let's not uglify our code. With antonym replacement, you can replace not uglify with beautify, resulting in the sentence let's beautify our code. To do this, we will create an AntonymReplacer class in replacers.py as follows:

```
from nltk.corpus import wordnet
class AntonymReplacer (object):
  def replace(self, word, pos=None):
    antonyms = set()
    for syn in wordnet.synsets(word, pos=pos):
      for lemma in syn.lemmas():
        for antonym in lemma.antonyms():
          antonyms.add(antonym.name())
    if len(antonyms) == 1:
      return antonyms.pop()
    else:
      return None
  def replace negations(self, sent):
    i, l = 0, len(sent)
    words = []
    while i < l:
      word = sent[i]
      if word == 'not' and i+1 < 1:
        ant = self.replace(sent[i+1])
        if ant:
          words.append(ant)
          i += 2
          continue
      words.append(word)
      i += 1
    return words
```

Now, we can tokenize the original sentence into ["let's", 'not', 'uglify', 'our', 'code'] and pass this to the replace negations () function. Here are some examples:

```
>>> from replacers import AntonymReplacer
>>> replacer = AntonymReplacer()
>>> replacer.replace('good')
>>> replacer.replace('uglify')
'beautify'
>>> sent = ["let's", 'not', 'uglify', 'our', 'code']
>>> replacer.replace_negations(sent)
["let's", 'beautify', 'our', 'code']
```

How it works...

The AntonymReplacer class has two methods: replace() and replace_negations(). The replace() method takes a single word and an optional part-of-speech tag, then looks up the Synsets for the word in WordNet. Going through all the Synsets and every lemma of each Synset, it creates a set of all antonyms found. If only one antonym is found, then it is an unambiguous replacement. If there is more than one antonym, which can happen quite often, then we don't know for sure which antonym is correct. In the case of multiple antonyms (or no antonyms), replace() returns None as it cannot make a decision.

In replace_negations(), we look through a tokenized sentence for the word not. If not is found, then we try to find an antonym for the next word using replace(). If we find an antonym, then it is appended to the list of words, replacing not and the original word. All other words are appended as is, resulting in a tokenized sentence with unambiguous negations replaced by their antonyms.

There's more...

As unambiguous antonyms aren't very common in WordNet, you might want to create a custom antonym mapping in the same way we did for synonyms. This AntonymWordReplacer can be constructed by inheriting from both WordReplacer and AntonymReplacer:

```
class AntonymWordReplacer(WordReplacer, AntonymReplacer):
    pass
```

The order of inheritance is very important, as we want the initialization and replace function of WordReplacer combined with the replace_negations function from AntonymReplacer. The result is a replacer that can perform the following:

```
>>> from replacers import AntonymWordReplacer
>>> replacer = AntonymWordReplacer({'evil': 'good'})
>>> replacer.replace_negations(['good', 'is', 'not', 'evil'])
['good', 'is', 'good']
```

Of course, you can also inherit from CsvWordReplacer or YamlWordReplacer instead of WordReplacer if you want to load the antonym word mappings from a file.

See also

The previous recipe covers the WordReplacer from the perspective of synonym replacement. In <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, WordNet usage is covered in detail in the *Looking up Synsets for a word in WordNet* and *Looking up lemmas and synonyms in WordNet* recipes.

Chapter 3. Creating Custom Corpora

In this chapter, we will cover the following recipes:

- Setting up a custom corpus
- Creating a wordlist corpus
- Creating a part-of-speech tagged word corpus
- Creating a chunked phrase corpus
- Creating a categorized text corpus
- Creating a categorized chunk corpus reader
- Lazy corpus loading
- Creating a custom corpus view
- Creating a MongoDB-backed corpus reader
- Corpus editing with file locking

Introduction

In this chapter, we'll cover how to use corpus readers and create custom corpora. If you want to train your own model, such as a part-of-speech tagger or text classifier, you will need to create a custom corpus to train on. Model training is covered in the subsequent chapters.

Now you'll learn how to use the existing corpus data that comes with NLTK. This information is essential for future chapters when we'll need to access the corpora as training data. You've already accessed the WordNet corpus in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*. This chapter will introduce you to many more corpora.

We'll also cover creating custom corpus readers, which can be used when your corpus is not in a file format that NLTK already recognizes, or if your corpus is not located in files at all, but instead is located in a database such as MongoDB. It is essential to be familiar with tokenization, which was covered in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*.

Setting up a custom corpus

A **corpus** is a collection of text documents, and **corpora** is the plural of corpus. This comes from the Latin word for body; in this case, a body of text. So a **custom corpus** is really just a bunch of text files in a directory, often alongside many other directories of text files.

Getting ready

You should already have the NLTK data package installed, following the instructions at http://www.nltk.org/data. We'll assume that the data is installed to C:\nltk_data on Windows, and /usr/share/nltk data on Linux, Unix, and Mac OS X.

How to do it...

NLTK defines a list of data directories, or paths, in nltk.data.path. Our custom corpora must be within one of these paths so it can be found by NLTK. In order to avoid conflict with the official data package, we'll create a custom nltk_data directory in our home directory. The following is some Python code to create this directory and verify that it is in the list of known paths specified by nltk.data.path:

```
>>> import os, os.path
>>> path = os.path.expanduser('~/nltk_data')
>>> if not os.path.exists(path):
... os.mkdir(path)
>>> os.path.exists(path)
True
>>> import nltk.data
>>> path in nltk.data.path
True
```

If the last line, path in nltk.data.path, is True, then you should now have a nltk_data directory in your home directory. The path should be %UserProfile%\nltk_data on Windows, or ~/nltk_data on Unix, Linux, and Mac OS X. For simplicity, I'll refer to the directory as ~/nltk_data.

Note

If the last line does not return True, try creating the nltk_data directory manually in your home directory, then verify that the absolute path is in nltk.data.path. It's essential to ensure that this directory exists and is in nltk.data.path before continuing. You can see a list of the directories by running python -c "import nltk.data; print(nltk.data.path)". Once you have your nltk_data directory, the convention is that corpora resides in a corpora subdirectory. Create this corpora directory within the nltk_data directory, so that the path is ~/nltk_data/ corpora. Finally, we'll create a subdirectory in corpora to hold our custom corpus. Let's call it cookbook, giving us the full path, which is ~/nltk_data/corpora/cookbook. So on Unix, Linux, and Mac OS X, you could run the following to create the directory:

mkdir -p ~/nltk_data/corpora/cookbook

Now, we can create a simple wordlist file and make sure it loads. In the *Spelling correction with Enchant* recipe in <u>Chapter 2</u>, *Replacing and Correcting Words*, we created a wordlist file called mywords.txt. Put this file into ~/nltk_data/corpora/cookbook/. Now we can use nltk.data.load(), as shown in the following code, to load the file:

```
>>> import nltk.data
>>> nltk.data.load('corpora/cookbook/mywords.txt', format='raw')
b'nltk\n'
```

Note

We need to specify format='raw' since nltk.data.load() doesn't know how to interpret .txt files. As we'll see, it does know how to interpret a number of other file formats.

How it works...

The nltk.data.load() function recognizes a number of formats, such as 'raw', 'pickle', and 'yaml'. If no format is specified, then it tries to guess the format based on the file's extension. In the previous case, we have a .txt file, which is not a recognized extension, so we have to specify the 'raw' format. But, if we used a file that ended in .yaml, then we would not need to specify the format.

Filenames passed into nltk.data.load() can be *absolute* or *relative* paths. Relative paths must be relative to one of the paths specified in nltk.data.path. The file is found using nltk.data.find(path), which searches all known paths combined with the relative path. Absolute paths do not require a search, and are used as is. When using relative paths, be sure to use choose unambiguous names for your files so as not to conflict with any existing NLTK data.

There's more...

For most corpora access, you won't actually need to use nltk.data.load, as that will be handled by the CorpusReader classes covered in the following recipes. But it's a good function to be familiar with for loading pickle files and .yaml files, and it also introduces the idea of putting all of your data files into a path known by NLTK.

Loading a YAML file

If you put the synonyms.yaml file from the *Replacing synonyms* recipe in <u>Chapter 2</u>, *Replacing and Correcting Words* into ~/nltk_data/corpora/cookbook (next to mywords.txt), you can use nltk.data.load() to load it without specifying a format:

```
>>> import nltk.data
>>> nltk.data.load('corpora/cookbook/synonyms.yaml')
{'bday': 'birthday'}
```

This assumes that PyYAML is installed. If not, you can find download and installation instructions at <u>http://pyyaml.org/wiki/PyYAML</u>.

See also

In the next recipes, we'll cover various corpus readers, and then in the *Lazy corpus loading* recipe, we'll use the LazyCorpusLoader class, which expects corpus data to be in a corpora subdirectory of one of the paths specified by nltk.data.path.

Creating a wordlist corpus

The WordListCorpusReader class is one of the simplest CorpusReader classes. It provides access to a file containing a list of words, one word per line. In fact, you've already used it when we used the stopwords corpus in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, in the *Filtering stopwords in a tokenized sentence* and *Discovering word collocations* recipes.

Getting ready

We need to start by creating a wordlist file. This could be a single column CSV file, or just a normal text file with one word per line. Let's create a file named wordlist that looks like this:

nltk corpus corpora wordnet

How to do it...

Now we can instantiate a WordListCorpusReader class that will produce a list of words from our file. It takes two arguments: the directory path containing the files, and a list of filenames. If you open the Python console in the same directory as the files, then '.' can be used as the directory path. Otherwise, you must use a directory path such as nltk_data/corpora/cookbook:

```
>>> from nltk.corpus.reader import WordListCorpusReader
>>> reader = WordListCorpusReader('.', ['wordlist'])
>>> reader.words()
['nltk', 'corpus', 'corpora', 'wordnet']
>>> reader.fileids()
['wordlist']
```

How it works...

The WordListCorpusReader class inherits from CorpusReader, which is a common base class for all corpus readers. The CorpusReader class does all the work of identifying which files to read, while WordListCorpusReader reads the files and tokenizes each line to produce a list of words. The following is an inheritance diagram:



When you call the words () function, it calls nltk.tokenize.line_tokenize() on the raw file data, which you can access using the raw() function as follows:

```
>>> reader.raw()
'nltk\ncorpus\ncorpora\nwordnet\n'
>>> from nltk.tokenize import line_tokenize
>>> line_tokenize(reader.raw())
['nltk', 'corpus', 'corpora', 'wordnet']
```

There's more...

The stopwords corpus is a good example of a multifile WordListCorpusReader. In the *Filtering stopwords in a tokenized sentence* recipe in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, we saw that it had one wordlist file for each language, and you could access the words for that language by calling stopwords.words(fileid). If you want to create your own multifile wordlist corpus, this is a great example to follow.

Names wordlist corpus

Another wordlist corpus that comes with NLTK is the names corpus that is shown in the following code. It contains two files: female.txt and male.txt, each containing a list of a few thousand common first names organized by gender as follows:

```
>>> from nltk.corpus import names
>>> names.fileids()
['female.txt', 'male.txt']
>>> len(names.words('female.txt'))
5001
```

```
>>> len(names.words('male.txt'))
2943
```

English words corpus

NLTK also comes with a large list of English words. There's one file with 850 basic words, and another list with over 200,000 known English words, as shown in the following code:

```
>>> from nltk.corpus import words
>>> words.fileids()
['en', 'en-basic']
>>> len(words.words('en-basic'))
850
>>> len(words.words('en'))
234936
```

See also

The *Filtering stopwords in a tokenized sentence* recipe in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, has more details on using the stopwords corpus. In the following recipes, we'll cover more advanced corpus file formats and corpus reader classes.

Creating a part-of-speech tagged word corpus

Part-of-speech tagging is the process of identifying the part-of-speech tag for a word. Most of the time, a tagger must first be trained on a training corpus. How to train and use a tagger is covered in detail in <u>Chapter 4</u>, *Part-of-speech Tagging*, but first we must know how to create and use a training corpus of part-of-speech tagged words.

Getting ready

The simplest format for a tagged corpus is of the form *word/tag*. The following is an excerpt from the brown corpus:

```
The/at-tl expense/nn and/cc time/nn involved/vbn are/ber astronomical/jj ./.
```

Each word has a tag denoting its part-of-speech. For example, nn refers to a noun, while a tag that starts with vb is a verb.

Note

Different corpora can use different tags to mean the same thing. For example, the treebank corpus uses different tags as compared to the brown corpus, even though both are English text. But both sets of tags can be converted into a universal tagset, described at the end of this recipe.

How to do it...

If you were to put the previous excerpt into a file called brown.pos, you could then create a TaggedCorpusReader class using the following code:

```
>>> from nltk.corpus.reader import TaggedCorpusReader
>>> reader = TaggedCorpusReader('.', r'.*\.pos')
>>> reader.words()
['The', 'expense', 'and', 'time', 'involved', 'are', ...]
>>> reader.tagged words()
[('The', 'AT-TL'), ('expense', 'NN'), ('and', 'CC'), ...]
>>> reader.sents()
[['The', 'expense', 'and', 'time', 'involved', 'are',
'astronomical', '.']]
>>> reader.tagged sents()
[[('The', 'AT-TL'), ('expense', 'NN'), ('and', 'CC'), ('time',
'NN'), ('involved', 'VBN'), ('are', 'BER'), ('astronomical', 'JJ'),
('.', '.')]]
>>> reader.paras()
[[['The', 'expense', 'and', 'time', 'involved', 'are',
'astronomical', '.']]]
>>> reader.tagged paras()
```

```
[[[('The', 'AT-TL'), ('expense', 'NN'), ('and', 'CC'), ('time',
'NN'), ('involved', 'VBN'), ('are', 'BER'), ('astronomical', 'JJ'),
('.', '.')]]]
```

How it works...

This time, instead of naming the file explicitly, we use a regular expression, r'.*\.pos', to match all the files whose names end with .pos. We could have done the same thing as we did with the WordListCorpusReader class, and pass ['brown.pos'] as the second argument, but this way you can see how to include multiple files in a corpus without naming each one explicitly.

The TaggedCorpusReader class provides a number of methods for extracting text from a corpus. First, you can get a list of all words or a list of tagged tokens. A tagged token is simply a tuple of (word, tag). Next, you can get a list of every sentence and also every tagged sentence where the sentence is itself a list of words or tagged tokens. Finally, you can get a list of paragraphs, where each paragraph is a list of sentences and each sentence is a list of words or tagged tokens. The following is an inheritance diagram listing all the major methods:



There's more...

All the functions we just demonstrated depend on tokenizers to split the text. The TaggedCorpusReader class tries to have good defaults, but you can customize them by passing in your own tokenizers at the time of initialization.

Customizing the word tokenizer

The default word tokenizer is an instance of nltk.tokenize.WhitespaceTokenizer. If you want to use a different tokenizer, you can pass that in as word_tokenizer, as shown in the following code:

```
>>> from nltk.tokenize import SpaceTokenizer
>>> reader = TaggedCorpusReader('.', r'.*\.pos',
word_tokenizer=SpaceTokenizer())
>>> reader.words()
['The', 'expense', 'and', 'time', 'involved', 'are', ...]
```

Customizing the sentence tokenizer

The default sentence tokenizer is an instance of nltk.tokenize.RegexpTokenize with '\n' to identify the gaps. It assumes that each sentence is on a line all by itself, and individual sentences do not have line breaks. To customize this, you can pass in your own tokenizer as sent_tokenizer, as shown in the following code:

```
>>> from nltk.tokenize import LineTokenizer
>>> reader = TaggedCorpusReader('.', r'.*\.pos',
sent_tokenizer=LineTokenizer())
>>> reader.sents()
[['The', 'expense', 'and', 'time', 'involved', 'are',
'astronomical', '.']]
```

Customizing the paragraph block reader

Paragraphs are assumed to be split by blank lines. This is done with the para_block_reader function, which is nltk.corpus.reader.util.read_blankline_block. There are a number of other block reader functions in nltk.corpus.reader.util, whose purpose is to read blocks of text from a stream. Their usage will be covered in more detail later in the *Creating a custom corpus view* recipe, where we'll create a custom corpus reader.

Customizing the tag separator

If you don't want to use '/' as the word/tag separator, you can pass an alternative string to TaggedCorpusReader for sep. The default is sep='/', but if you want to split words and tags with '|', such as 'word|tag', then you should pass in sep='|'.

Converting tags to a universal tagset

NLTK 3.0 provides a method for converting known tagsets to a universal tagset. A **tagset** is just a list of part-of-speech tags used by one or more corpora. The **universal tagset** is a simplified and condensed tagset composed of only 12 part-of-speech tags, as shown in the following table:

Universal tag	Description
VERB	All verbs
NOUN	Common and proper nouns
PRON	Pronouns
ADJ	Adjectives
ADV	Adverbs
ADP	Prepositions and postpositions
CONJ	Conjunctions
DET	Determiners
NUM	Cardinal numbers
PRT	Participles
X	Other
	Punctuation

Mappings from a known tagset to the universal tagset can be found at nltk_data/taggers/ universal_tagset. For example, treebank tag mappings are in nltk_data/taggers/ universal_tagset/en-ptb.map. To map corpus tags to the universal tagset, the corpus reader must be initialized with a known tagset name. Then you pass in tagset='universal' to a method like tagged_words(), as shown in the following code:

```
>>> reader = TaggedCorpusReader('.', r'.*\.pos', tagset='en-brown')
>>> reader.tagged_words(tagset='universal')
[('The', 'DET'), ('expense', 'NOUN'), ('and', 'CONJ'), ...]
```

Most NLTK tagged corpora are initialized with a known tagset, making conversion easy. The following is an example with the treebank corpus:

```
>>> from nltk.corpus import treebank
>>> treebank.tagged_words()
[('Pierre', 'NNP'), ('Vinken', 'NNP'), (',', ','), ...]
>>> treebank.tagged_words(tagset='universal')
[('Pierre', 'NOUN'), ('Vinken', 'NOUN'), (',', '.'), ...]
```

If you try to map using an unknown mapping or tagset, every word will be tagged with UNK:

```
>>> treebank.tagged_words(tagset='brown')
[('Pierre', 'UNK'), ('Vinken', 'UNK'), (',', 'UNK'), ...]
```

See also

<u>Chapter 4</u>, *Part-of-speech Tagging*, will cover part-of-speech tags and tagging in much more detail. And for more on tokenizers, see the first three recipes of <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*.

In the next recipe, we'll create a **chunked phrase** corpus, where each phrase is also part-of-speech tagged.
Creating a chunked phrase corpus

A **chunk** is a short phrase within a sentence. If you remember sentence diagrams from grade school, they were a tree-like representation of phrases within a sentence. This is exactly what chunks are: subtrees within a sentence tree, and they will be covered in much more detail in <u>Chapter 5</u>, *Extracting Chunks*. The following is a sample sentence tree with three **Noun Phrase** (**NP**) chunks shown as subtrees:

NP have VBP trimmed VBN about IN NP * NP 5	
Factor IID and Factor NN State 100 and 100	V80

This recipe will cover how to create a corpus with sentences that contain chunks.

Getting ready

The following is an excerpt from the tagged treebank corpus. It has part-of-speech tags, as in the previous recipe, but it also has square brackets for denoting chunks. The text within the brackets has been highlighted to make the chunks more apparent. The following sentence is the same sentence as in the previous tree diagram, but in text form:

```
[Earlier/JJR staff-reduction/NN moves/NNS] have/VBP trimmed/VBN about/IN [300/CD jobs/NNS] ,/, [the/DT spokesman/NN] said/VBD ./.
```

In this format, every chunk is a noun phrase. Words that are not within brackets are part of the sentence tree, but are not part of any noun phrase subtree.

How to do it...

Put the previous excerpt into a file called treebank.chunk, and then do the following:

```
>>> from nltk.corpus.reader import ChunkedCorpusReader
>>> reader = ChunkedCorpusReader('.', r'.*\.chunk')
>>> reader.chunked_words()
[Tree('NP', [('Earlier', 'JJR'), ('staff-reduction', 'NN'),
('moves', 'NNS')]), ('have', 'VBP'), ...]
>>> reader.chunked_sents()
[Tree('S', [Tree('NP', [('Earlier', 'JJR'), ('staff-reduction',
'NN'), ('moves', 'NNS')]), ('have', 'VBP'), ('trimmed', 'VBN'),
('about', 'IN'), Tree('NP', [('300', 'CD'), ('jobs', 'NNS')]), (',',
','), Tree('NP', [('the', 'DT'), ('spokesman', 'NN')]), ('said',
'VBD'), ('.', '.')])]
>>> reader.chunked_paras()
```

```
[[Tree('S', [Tree('NP', [('Earlier', 'JJR'), ('staff-reduction',
'NN'), ('moves', 'NNS')]), ('have', 'VBP'), ('trimmed', 'VBN'),
('about', 'IN'), Tree('NP', [('300', 'CD'), ('jobs', 'NNS')]), (',',
','), Tree('NP', [('the', 'DT'), ('spokesman', 'NN')]), ('said',
'VBD'), ('.', '.')])]]
```

The ChunkedCorpusReader class provides the same methods as the TaggedCorpusReader for getting tagged tokens, along with three new methods for getting chunks. Each chunk is represented as an instance of nltk.tree.Tree. Sentence level trees look like Tree('S', [...]) while noun phrase trees look like Tree('NP', [...]). In chunked_sents(), you get a list of sentence trees, with each noun phrase as a subtree of the sentence. In chunked_words(), you get a list of noun phrase trees alongside tagged tokens of words that were not in a chunk. The following is an inheritance diagram listing the major methods:



Note

You can draw a tree by calling the draw() method. Using the corpus reader defined earlier, you could do reader.chunked_sents()[0].draw() to get the same sentence tree diagram shown at the beginning of this recipe.

How it works...

The ChunkedCorpusReader class is similar to the TaggedCorpusReader class from the previous recipe. It has the same default sent_tokenizer and para_block_reader functions, but instead of a word_tokenizer function, it uses a str2chunktree() function. The default is nltk.chunk.util.tagstr2tree(), which parses a sentence string containing bracketed chunks into a sentence tree, with each chunk as a noun phrase subtree. Words are split by whitespace, and the default word/tag separator is '/'. If you want to customize chunk parsing, then you can pass in your own function for str2chunktree().

There's more...

An alternative format for denoting chunks is called IOB tags. IOB tags are similar to part-of-speech tags, but provide a way to denote the inside, outside, and beginning of a chunk. They also have the benefit of allowing multiple different chunk phrase types, not just noun phrases. The following is an excerpt from the conll2000 corpus. Each word is on its own line with a part-of-speech tag followed by an IOB tag:

```
Mr. NNP B-NP
Meador NNP I-NP
had VBD B-VP
been VBN I-VP
executive JJ B-NP
vice NN I-NP
president NN I-NP
of IN B-PP
Balcor NNP B-NP
. . O
```

B-NP denotes the beginning of a noun phrase, while I-NP denotes that the word is inside of the current noun phrase. B-VP and I-VP denote the beginning and inside of a verb phrase. O ends the sentence.

To read a corpus using the IOB format, you must use the ConllChunkCorpusReader class. Each sentence is separated by a blank line, but there is no separation for paragraphs. This means that the para_* methods are not available. If you put the previous IOB example text into a file named conll.iob, you can create and use a ConllChunkCorpusReader class with the following code. The third argument to ConllChunkCorpusReader should be a tuple or list specifying the types of chunks in the file, which in this case is ('NP', 'VP', 'PP'):

```
>>> from nltk.corpus.reader import ConllChunkCorpusReader
>>> conllreader = ConllChunkCorpusReader('.', r'.*\.iob', ('NP',
```

```
'VP', 'PP'))
>>> conllreader.chunked words()
[Tree('NP', [('Mr.', 'NNP'), ('Meador', 'NNP')]), Tree('VP',
[('had', 'VBD'), ('been', 'VBN')]), ...]
>>> conllreader.chunked sents()
[Tree('S', [Tree('NP', [('Mr.', 'NNP'), ('Meador', 'NNP')]),
Tree('VP', [('had', 'VBD'), ('been', 'VBN')]), Tree('NP',
[('executive', 'JJ'), ('vice', 'NN'), ('president', 'NN')]),
Tree('PP', [('of', 'IN')]), Tree('NP', [('Balcor', 'NNP')]), ('.',
'.')])]
>>> conllreader.iob words()
[('Mr.', 'NNP', 'B-NP'), ('Meador', 'NNP', 'I-NP'), ...]
>>> conllreader.iob sents()
[[('Mr.', 'NNP', 'B-NP'), ('Meador', 'NNP', 'I-NP'), ('had', 'VBD',
'B-VP'), ('been', 'VBN', 'I-VP'), ('executive', 'JJ', 'B-NP'),
('vice', 'NN', 'I-NP'), ('president', 'NN', 'I-NP'), ('of', 'IN',
'B-PP'), ('Balcor', 'NNP', 'B-NP'), ('.', '.', 'O')]]
```

The previous code also shows the iob_words() and iob_sents() methods, which return lists of three tuples of (word, pos, iob). The inheritance diagram for ConllChunkCorpusReader looks like the following diagram, with most of the methods implemented by its superclass, ConllCorpusReader:



Tree leaves

When it comes to chunk trees, the leaves of a tree are the tagged tokens. So if you want to get a list of all the tagged tokens in a tree, call the leaves () method using the following code:

```
>>> reader.chunked_words()[0].leaves()
[('Earlier', 'JJR'), ('staff-reduction', 'NN'), ('moves', 'NNS')]
>>> reader.chunked_sents()[0].leaves()
[('Earlier', 'JJR'), ('staff-reduction', 'NN'), ('moves', 'NNS'),
('have', 'VBP'), ('trimmed', 'VBN'), ('about', 'IN'), ('300', 'CD'),
('jobs', 'NNS'), (',', ','), ('the', 'DT'), ('spokesman', 'NN'),
('said', 'VBD'), ('.', '.')]
>>> reader.chunked_paras()[0][0].leaves()
[('Earlier', 'JJR'), ('staff-reduction', 'NN'), ('moves', 'NNS'),
('have', 'VBP'), ('trimmed', 'VBN'), ('about', 'IN'), ('300', 'CD'),
```

('jobs', 'NNS'), (',', ','), ('the', 'DT'), ('spokesman', 'NN'), ('said', 'VBD'), ('.', '.')]

Treebank chunk corpus

The nltk.corpus.treebank_chunk corpus uses ChunkedCorpusReader to provide part-ofspeech tagged words and noun phrase chunks of *Wall Street Journal* headlines. NLTK comes with a 5 percent sample from the Penn Treebank Project. You can find out more at <u>http://www.cis.upenn.edu/~treebank/home.html</u>.

CoNLL2000 corpus

CoNLL stands for the **Conference on Computational Natural Language Learning**. For the year 2000 conference, a shared task was undertaken to produce a corpus of chunks based on the *Wall Street Journal* corpus. In addition to **Noun Phrases (NP)**, it also contains **Verb Phrases (VP)** and **Prepositional Phrases (PP)**. This chunked corpus is available as nltk.corpus.conll2000, which is an instance of ConllChunkCorpusReader. You can read more at http://www.cnts.ua.ac.be/conll2000/chunking/.

See also

<u>Chapter 5</u>, *Extracting Chunks*, will cover chunk extraction in detail. Also see the previous recipe for details on getting tagged tokens from a corpus reader.

Creating a categorized text corpus

If you have a large corpus of text, you might want to categorize it into separate sections. This can be helpful for organization, or for text classification, which is covered in <u>Chapter 7</u>, *Text Classification*. The brown corpus, for example, has a number of different categories, as shown in the following code:

```
>>> from nltk.corpus import brown
>>> brown.categories()
['adventure', 'belles_lettres', 'editorial', 'fiction',
'government', 'hobbies', 'humor', 'learned', 'lore', 'mystery',
'news', 'religion', 'reviews', 'romance', 'science fiction']
```

In this recipe, we'll learn how to create our own categorized text corpus.

Getting ready

The easiest way to categorize a corpus is to have one file for each category. The following are two excerpts from the movie reviews corpus:

• movie_pos.txt:

the thin red line is flawed but it provokes .

• movie_neg.txt:

a big-budget and glossy production can not make up for a lack of spontaneity that permeates their tv show .

With these two files, we'll have two categories: pos and neg.

How to do it...

We'll use the CategorizedPlaintextCorpusReader class, which inherits from both PlaintextCorpusReader and CategorizedCorpusReader. These two superclasses require three arguments: the root directory, the fileids arguments, and a category specification:

```
>>> from nltk.corpus.reader import CategorizedPlaintextCorpusReader
>>> reader = CategorizedPlaintextCorpusReader('.', r'movie_.*\.txt',
cat_pattern=r'movie_(\w+)\.txt')
>>> reader.categories()
['neg', 'pos']
>>> reader.fileids(categories=['neg'])
['movie_neg.txt']
>>> reader.fileids(categories=['pos'])
['movie pos.txt']
```

How it works...

The first two arguments to CategorizedPlaintextCorpusReader are the root directory and fileids, which are passed on to the PlaintextCorpusReader class to read in the files. The cat_pattern keyword argument is a regular expression for extracting the category names from the fileids arguments. In our case, the category is the part of the fileid argument after movie_ and before .txt. The category must be surrounded by grouping parenthesis.

The cat_pattern keyword is passed to CategorizedCorpusReader, which overrides the common corpus reader functions such as fileids(), words(), sents(), and paras() to accept a categories keyword argument. This way, you could get all the pos sentences by calling reader.sents(categories=['pos']). The CategorizedCorpusReader class also provides the categories() function, which returns a list of all the known categories in the corpus.

The CategorizedPlaintextCorpusReader class is an example of using multiple inheritance to join methods from multiple superclasses, as shown in the following diagram:



There's more...

Instead of cat_pattern, you could pass in a cat_map, which is a dictionary mapping a fileid argument to a list of category labels, as shown in the following code:

```
>>> reader = CategorizedPlaintextCorpusReader('.', r'movie_.*\.txt',
cat_map={'movie_pos.txt': ['pos'], 'movie_neg.txt': ['neg']})
>>> reader.categories()
['neg', 'pos']
```

Category file

A third way of specifying categories is to use the cat_file keyword argument to specify a filename containing a mapping of fileid to category. For example, the brown corpus has a file called cats.txt that looks like the following:

ca44 news cb01 editorial

The reuters corpus has files in multiple categories, and its cats.txt looks like the following:

test/14840 rubber coffee lumber palm-oil veg-oil
test/14841 wheat grain

Categorized tagged corpus reader

The brown corpus reader is actually an instance of CategorizedTaggedCorpusReader, which inherits from CategorizedCorpusReader and TaggedCorpusReader. Just like in CategorizedPlaintextCorpusReader, it overrides all the methods of TaggedCorpusReader to allow a categories argument, so you can call brown.tagged_sents(categories=['news']) to get all the tagged sentences from the news category. You can use the CategorizedTaggedCorpusReader class just like CategorizedPlaintextCorpusReader for your own categorized and tagged text corpora.

Categorized corpora

The movie_reviews corpus reader is an instance of CategorizedPlaintextCorpusReader, as is the reuters corpus reader. But where the movie_reviews corpus only has two categories (neg and pos), reuters has 90 categories. These corpora are often used for training and evaluating classifiers, which will be covered in <u>Chapter 7</u>, *Text Classification*.

See also

In the next chapter, we'll create a subclass of CategorizedCorpusReader and ChunkedCorpusReader for reading a categorized chunk corpus. Also, see <u>Chapter 7</u>, *Text Classification* in which we use categorized text for classification.

Creating a categorized chunk corpus reader

NLTK provides a CategorizedPlaintextCorpusReader and CategorizedTaggedCorpusReader class, but there's no categorized corpus reader for chunked corpora. So in this recipe, we're going to make one.

Getting ready

Refer to the earlier recipe, *Creating a chunked phrase corpus*, for an explanation of ChunkedCorpusReader, and refer to the previous recipe for details on CategorizedPlaintextCorpusReader and CategorizedTaggedCorpusReader, both of which inherit from CategorizedCorpusReader.

How to do it...

We'll create a class called CategorizedChunkedCorpusReader that inherits from both CategorizedCorpusReader and ChunkedCorpusReader. It is heavily based on the CategorizedTaggedCorpusReader class, and also provides three additional methods for getting categorized chunks. The following code is found in catchunked.py:

```
from nltk.corpus.reader import CategorizedCorpusReader,
ChunkedCorpusReader
class CategorizedChunkedCorpusReader(CategorizedCorpusReader,
ChunkedCorpusReader):
    def __init__(self, *args, **kwargs):
        CategorizedCorpusReader.__init__(self, kwargs)
        ChunkedCorpusReader.__init__(self, *args, **kwargs)
        ChunkedCorpusReader.__init__(self, *args, **kwargs)
        def __resolve(self, fileids, categories):
        if fileids is not None and categories is not None:
            raise ValueError('Specify fileids or categories, not both')
        if categories is not None:
            return self.fileids(categories)
        else:
            return fileids
```

All of the following methods call the corresponding function in ChunkedCorpusReader with the value returned from _resolve(). We'll start with the plain text methods:

```
def raw(self, fileids=None, categories=None):
    return ChunkedCorpusReader.raw(self, self._resolve(fileids,
categories))
    def words(self, fileids=None, categories=None):
    return ChunkedCorpusReader.words(self, self. resolve(fileids,
```

```
categories))

def sents(self, fileids=None, categories=None):
   return ChunkedCorpusReader.sents(self, self._resolve(fileids,
categories))

def paras(self, fileids=None, categories=None):
```

```
return ChunkedCorpusReader.paras(self, self._resolve(fileids,
categories))
```

Next is the code for the tagged text methods:

```
def tagged_words(self, fileids=None, categories=None):
    return ChunkedCorpusReader.tagged_words(self,
self._resolve(fileids, categories))

def tagged_sents(self, fileids=None, categories=None):
    return ChunkedCorpusReader.tagged_sents(self,
self._resolve(fileids, categories))

def tagged_paras(self, fileids=None, categories=None):
    return ChunkedCorpusReader.tagged_paras(self,
self. resolve(fileids, categories))
```

And finally, we have code for the chunked methods, which is what we've really been after:

```
def chunked_words(self, fileids=None, categories=None):
    return ChunkedCorpusReader.chunked_words(self,
self._resolve(fileids, categories))

def chunked_sents(self, fileids=None, categories=None):
    return ChunkedCorpusReader.chunked_sents(self,
self._resolve(fileids, categories))

def chunked_paras(self, fileids=None, categories=None):
    return ChunkedCorpusReader.chunked_paras(self,
self._resolve(fileids, categories))
```

All these methods together give us a complete CategorizedChunkedCorpusReader class.

How it works...

The CategorizedChunkedCorpusReader class overrides all the ChunkedCorpusReader methods to take a categories argument for locating fileids. These fileids are found with the internal _resolve() function. This _resolve() function makes use of CategorizedCorpusReader.fileids() to return fileids for a given list of categories. If no categories are given, _resolve() just returns the given fileids, which could be None, in which

case all the files are read. The initialization of both CategorizedCorpusReader and ChunkedCorpusReader is what makes all this possible. If you look at the code for CategorizedTaggedCorpusReader, you'll see that it's very similar.

The inheritance diagram looks like this:



The following is example code for using the treebank corpus. All we're doing is making categories out of the fileids arguments, but the point is that you could use the same techniques to create your own categorized chunk corpus:

```
>>> import nltk.data
>>> from catchunked import CategorizedChunkedCorpusReader
>>> path = nltk.data.find('corpora/treebank/tagged')
>>> reader = CategorizedChunkedCorpusReader(path, r'wsj_.*\.pos',
cat_pattern=r'wsj_(.*)\.pos')
>>> len(reader.categories()) == len(reader.fileids())
```

```
True
>>> len(reader.chunked_sents(categories=['0001']))
16
```

We use nltk.data.find() to search the data directories to get a FileSystemPathPointer class to the treebank corpus. All the treebank tagged files start with wsj_, followed by a number, and end with .pos. The previous code turns that file number into a category.

There's more...

As covered in the *Creating a chunked phrase corpus* recipe, there's an alternative format and reader for a chunk corpus using IOB tags. To have a categorized corpus of IOB chunks, we have to make a new corpus reader.

Categorized CoNLL chunk corpus reader

The following is the code for the subclass of CategorizedCorpusReader and ConllChunkReader called CategorizedConllChunkCorpusReader. It overrides all methods of ConllCorpusReader that take a fileids argument, so the methods can also take a categories argument. The ConllChunkCorpusReader is just a small subclass of ConllCorpusReader that handles initialization; most of the work is done in ConllCorpusReader. This code can also be found in catchunked.py.

```
from nltk.corpus.reader import CategorizedCorpusReader,
ConllCorpusReader, ConllChunkCorpusReader
```

```
class CategorizedConllChunkCorpusReader(CategorizedCorpusReader,
ConllChunkCorpusReader):
    def __init__(self, *args, **kwargs):
        CategorizedCorpusReader.__init__(self, kwargs)
        ConllChunkCorpusReader.__init__(self, *args, **kwargs)
    def __resolve(self, fileids, categories):
        if fileids is not None and categories is not None:
        raise ValueError('Specify fileids or categories, not both')
        if categories is not None:
        return self.fileids(categories)
        else:
            return fileids
```

All the following methods call the corresponding method of ConllCorpusReader with the value returned from _resolve(). We'll start with the plain text methods:

```
def raw(self, fileids=None, categories=None):
    return ConllCorpusReader.raw(self, self._resolve(fileids,
categories))
```

```
def words(self, fileids=None, categories=None):
    return ConllCorpusReader.words(self, self._resolve(fileids,
categories))
```

```
def sents(self, fileids=None, categories=None):
    return ConllCorpusReader.sents(self, self._resolve(fileids,
categories))
```

The ConllCorpusReader class does not recognize paragraphs, so there are no *_paras() methods. Next will be the code for the tagged and chunked methods, as follows:

```
def tagged_words(self, fileids=None, categories=None):
    return ConllCorpusReader.tagged_words(self,
self._resolve(fileids, categories))
    def tagged_sents(self, fileids=None, categories=None):
    return ConllCorpusReader.tagged_sents(self,
self._resolve(fileids, categories))
    def chunked_words(self, fileids=None, categories=None,
chunk_types=None):
    return ConllCorpusReader.chunked_words(self,
self._resolve(fileids, categories), chunk_types)
    def chunked_sents(self, fileids=None, categories=None,
chunk_types=None):
    return ConllCorpusReader.chunked_words(self,
self._resolve(fileids, categories), chunk_types)
    def chunked_sents(self, fileids=None, categories=None,
chunk_types=None):
    return ConllCorpusReader.chunked_sents(self,
```

self._resolve(fileids, categories), chunk_types)

categories))

For completeness, we must override the following methods of the ConllCorpusReader class:

```
def parsed_sents(self, fileids=None, categories=None,
pos_in_tree=None):
    return ConllCorpusReader.parsed_sents(
        self, self._resolve(fileids, categories), pos_in_tree)
    def srl_spans(self, fileids=None, categories=None):
        return ConllCorpusReader.srl_spans(self, self._resolve(fileids,
categories))
    def srl_instances(self, fileids=None, categories=None,
pos_in_tree=None, flatten=True):
        return ConllCorpusReader.srl_instances(self,
self._resolve(fileids, categories), pos_in_tree, flatten)
    def iob_words(self, fileids=None, categories=None):
        return ConllCorpusReader.iob words(self, self. resolve(fileids, self.)));
```

```
def iob_sents(self, fileids=None, categories=None):
    return ConllCorpusReader.iob_sents(self, self._resolve(fileids,
categories))
```

The inheritance diagram for this class is as follows:



Here is example code using the conll2000 corpus:

```
>>> import nltk.data
>>> from catchunked import CategorizedConllChunkCorpusReader
>>> path = nltk.data.find('corpora/conll2000')
>>> reader = CategorizedConllChunkCorpusReader(path, r'.*\.txt',
```

```
('NP','VP','PP'), cat_pattern=r'(.*)\.txt')
>>> reader.categories()
['test', 'train']
>>> reader.fileids()
['test.txt', 'train.txt']
>>> len(reader.chunked_sents(categories=['test']))
2012
```

Like with treebank, we're using the fileids for categories. The ConllChunkCorpusReader class requires a third argument to specify the chunk types. These chunk types are used to parse the IOB tags. As you learned in the *Creating a chunked phrase corpus* recipe, the conll2000 corpus recognizes the following three chunk types:

- NP for noun phrases
- VP for verb phrases
- PP for prepositional phrases

See also

In the *Creating a chunked phrase corpus* recipe of this chapter, we covered both the ChunkedCorpusReader and ConllChunkCorpusReader classes. And in the previous recipe, we covered CategorizedPlaintextCorpusReader and CategorizedTaggedCorpusReader, which share the same superclass used by CategorizedChunkedCorpusReader and CategorizedConllChunkReader, that is, CategorizedCorpusReader.

Lazy corpus loading

Loading a corpus reader can be an expensive operation due to the number of files, file sizes, and various initialization tasks. And while you'll often want to specify a corpus reader in a common module, you don't always need to access it right away. To speed up module import time when a corpus reader is defined, NLTK provides a LazyCorpusLoader class that can transform itself into your actual corpus reader as soon as you need it. This way, you can define a corpus reader in a common module without it slowing down module loading.

How to do it...

The LazyCorpusLoader class requires two arguments: the name of the corpus and the corpus reader class, plus any other arguments needed to initialize the corpus reader class.

The name argument specifies the root directory name of the corpus, which must be within a corpora subdirectory of one of the paths in nltk.data.path. See the *Setting up a custom corpus* recipe of this chapter for more details on nltk.data.path.

For example, if you have a custom corpora named cookbook in your local nltk_data directory, its path would be ~/nltk_data/corpora/cookbook. You'd then pass 'cookbook' to LazyCorpusLoader as the name, and LazyCorpusLoader will look in ~/nltk_data/ corpora for a directory named 'cookbook'.

The second argument to LazyCorpusLoader is reader_cls, which should be the name of a subclass of CorpusReader, such as WordListCorpusReader. You will also need to pass in any other arguments required by the reader_cls argument for initialization. This will be demonstrated as follows, using the same wordlist file we created in the earlier recipe, *Creating a wordlist corpus*. The third argument to LazyCorpusLoader is the list of filenames and fileids that will be passed to WordListCorpusReader at initialization:

```
>>> from nltk.corpus.util import LazyCorpusLoader
>>> from nltk.corpus.reader import WordListCorpusReader
>>> reader = LazyCorpusLoader('cookbook', WordListCorpusReader,
['wordlist'])
>>> isinstance(reader, LazyCorpusLoader)
True
>>> reader.fileids()
['wordlist']
>>> isinstance(reader, LazyCorpusLoader)
False
>>> isinstance(reader, WordListCorpusReader)
True
```

How it works...

The LazyCorpusLoader class stores all the arguments given, but otherwise does nothing until you try to access an attribute or method. This way, initialization is very fast, eliminating the overhead of loading the corpus reader immediately. As soon as you do access an attribute or method, it does the following:

- 1. Calls nltk.data.find('corpora/%s' % name) to find the corpus data root directory.
- 2. Instantiates the corpus reader class with the root directory and any other arguments.
- 3. Transforms itself into the corpus reader class.

So in the previous example code, before we call reader.fileids(), reader is an instance of LazyCorpusLoader, but after the call, reader becomes an instance of WordListCorpusReader.

There's more...

All of the corpora included with NLTK and defined in nltk.corpus are initially a LazyCorpusLoader class. The following is some code from nltk.corpus defining the treebank corpora:

```
treebank = LazyCorpusLoader('treebank/combined',
BracketParseCorpusReader, r'wsj_.*\.mrg',tagset='wsj',
encoding='ascii')
treebank_chunk = LazyCorpusLoader('treebank/tagged',
ChunkedCorpusReader,
r'wsj_.*\.pos',sent_tokenizer=RegexpTokenizer(r'(?<=/\.)\s*(?![^\[]*\
])', gaps=True),
    para_block_reader=tagged_treebank_para_block_reader,
encoding='ascii')
treebank_raw = LazyCorpusLoader('treebank/raw',
PlaintextCorpusReader, r'wsj_.*', encoding='ISO-8859-2')
```

As you can see in the previous code, any number of additional arguments can be passed through by LazyCorpusLoader to its reader cls argument.

Creating a custom corpus view

A **corpus view** is a class wrapper around a corpus file that reads in blocks of tokens as needed. Its purpose is to provide a view into a file without reading the whole file at once (since corpus files can often be quite large). If the corpus readers included by NLTK already meet all your needs, then you do not have to know anything about corpus views. But, if you have a custom file format that needs special handling, this recipe will show you how to create and use a custom corpus view. The main corpus view class is StreamBackedCorpusView, which opens a single file as a stream, and maintains an internal cache of blocks it has read.

Blocks of tokens are read in with a block reader function. A block can be any piece of text, such as a paragraph or a line, and tokens are parts of a block, such as individual words. In the *Creating a part-of-speech tagged word corpus* recipe, we discussed the default para_block_reader function of the TaggedCorpusReader class, which reads lines from a file until it finds a blank line, then returns those lines as a single paragraph token. The actual block reader function is

nltk.corpus.reader.util.read_blankline_block.The TaggedCorpusReader class passes this block reader function into a TaggedCorpusView class whenever it needs to read blocks from a file. The TaggedCorpusView class is a subclass of StreamBackedCorpusView that knows to split paragraphs of word/tag into (word, tag) tuples.

How to do it ...

We'll start with the simple case of a plain text file with a heading that should be ignored by the corpus reader. Let's make a file called heading_text.txt that looks like this:

```
A simple heading
Here is the actual text for the corpus.
Paragraphs are split by blanklines.
This is the 3rd paragraph.
```

Normally, we'd use the PlaintextCorpusReader class, but by default it will treat A simple heading as the first paragraph. To ignore this heading, we need to subclass the PlaintextCorpusReader class so we can override its CorpusView class variable with our own StreamBackedCorpusView subclass. The following is the code found in corpus.py:

```
from nltk.corpus.reader import PlaintextCorpusReader
from nltk.corpus.reader.util import StreamBackedCorpusView
class IgnoreHeadingCorpusView(StreamBackedCorpusView):
    def __init__(self, *args, **kwargs):
        StreamBackedCorpusView.__init__(self, *args, **kwargs)
        # open self._stream
        self._open()
```

```
# skip the heading block
self.read_block(self._stream)
# reset the start position to the current position in the stream
self._filepos = [self._stream.tell()]
```

```
class IgnoreHeadingCorpusReader(PlaintextCorpusReader):
    CorpusView = IgnoreHeadingCorpusView
```

To demonstrate that this works as expected, here is code showing that the default PlaintextCorpusReader class finds four paragraphs, while our IgnoreHeadingCorpusReader class only has three paragraphs:

```
>>> from nltk.corpus.reader import PlaintextCorpusReader
>>> plain = PlaintextCorpusReader('.', ['heading_text.txt'])
>>> len(plain.paras())
4
>>> from corpus import IgnoreHeadingCorpusReader
>>> reader = IgnoreHeadingCorpusReader('.', ['heading_text.txt'])
>>> len(reader.paras())
3
```

How it works...

The PlaintextCorpusReader class by design has a CorpusView class variable that can be overridden by subclasses. So we do just that, and make our IgnoreHeadingCorpusView class the CorpusView class variable.

Note

Most corpus readers do not have a CorpusView class variable because they require very specific corpus views.

The IgnoreHeadingCorpusView class is a subclass of StreamBackedCorpusView that does the following on initialization:

- Opens the file using self._open(). This function is defined by StreamBackedCorpusView, and sets the internal instance variable self._stream to the opened file.
- 2. Reads one block with read_blankline_block(), which then reads the heading as a paragraph, and moves the stream's file position forward to the next block.
- 3. Resets the start file position to the current position of self._stream. The self. filepos variable is an internal index of where each block is in the file.

The following is a diagram illustrating the relationships between the classes:



There's more...

Corpus views can get a lot fancier and more complicated, but the core concept is the same: read blocks from a stream to return a list of tokens. There are a number of block readers provided in nltk.corpus.reader.util, but you can always create your own. If you do want to define your own block reader function, then you have two choices on how to implement it:

- 1. Define it as a separate function and pass it into StreamBackedCorpusView as block_reader. This is a good option if your block reader is fairly simple, reusable, and doesn't require any outside variables or configuration.
- 2. Subclass StreamBackedCorpusView and override the read_block() method. This is what many custom corpus views do because the block reading is highly specialized and requires additional functions and configuration, usually provided by the corpus reader when the corpus view is initialized.

Block reader functions

The following is a survey of most of the included block readers in nltk.corpus.reader.util. Unless otherwise mentioned, each block reader function takes a single argument: the stream argument to read from:

- read_whitespace_block(): This will read 20 lines from the stream, splitting each line into tokens by whitespace.
- read_wordpunct_block(): This reads 20 lines from the stream, splitting each line using nltk.tokenize.wordpunct_tokenize().
- read_line_block(): This reads 20 lines from the stream and returns them as a list, with each line as a token.

- read_blankline_block(): This will read lines from the stream until it finds a blank line. It will then return a single token of all lines found combined into a single string.
- read_regexp_block(): This takes two additional arguments, which must be regular expressions that can be passed to re.match(): start_re and end_re. The start_re variable matches the starting line of a block, and end_re matches the ending line of the block. The end_re variable defaults to None, in which case the block will end as soon as a new start_re match is found. The return value is a single token of all lines in the block joined into a single string.

Pickle corpus view

If you want to have a corpus of pickled objects, you can use the PickleCorpusView, a subclass of StreamBackedCorpusView, found in nltk.corpus.reader.util. A file consists of blocks of pickled objects, and can be created with the PickleCorpusView.write() class method, which takes a sequence of objects and an output file, then pickles each object using pickle.dump() and writes it to the file. It overrides the read_block() method to return a list of unpickled objects from the stream, using pickle.load().

Concatenated corpus view

Also found in nltk.corpus.reader.util is the ConcatenatedCorpusView class. This class is useful if you have multiple files that you want a corpus reader to treat as a single file. A ConcatenatedCorpusView class is created by giving it a list of corpus_views, which are then iterated over as if they were a single view.

See also

The concept of block readers was introduced in the *Creating a part-of-speech tagged word corpus* recipe.

Creating a MongoDB-backed corpus reader

All the corpus readers we've dealt with so far have been file-based. That is in part due to the design of the CorpusReader base class, and also the assumption that most corpus data will be in text files. However, sometimes you'll have a bunch of data stored in a database that you want to access and use just like a text file corpus. In this recipe, we'll cover the case where you have documents in MongoDB, and you want to use a particular field of each document as your block of text.

Getting ready

MongoDB is a document-oriented database that has become a popular alternative to relational databases such as MySQL. The installation and setup of MongoDB is outside the scope of this book, but you can find instructions at <u>http://docs.mongodb.org/manual/</u>.

You'll also need to install PyMongo, a Python driver for MongoDB. You should be able to do this with either easy_install or pip, by typing sudo easy_install pymongo or sudo pip install pymongo.

The following code assumes that your database is on localhost port 27017, which is the MongoDB default configuration, and that you'll be using the test database with a collection named corpus that contains documents with a text field. Explanations for these arguments are available in the PyMongo documentation at <u>http://api.mongodb.org/python/current/</u>.

How to do it...

Since the CorpusReader class assumes you have a file-based corpus, we can't directly subclass it. Instead, we're going to emulate both the StreamBackedCorpusView and PlaintextCorpusReader classes. The StreamBackedCorpusView class is a subclass of nltk.util.AbstractLazySequence, so we'll subclass AbstractLazySequence to create a MongoDB view, and then create a new class that will use the view to provide functionality similar to the PlaintextCorpusReader class. The following is the code, which is found in mongoreader.py:

```
import pymongo
from nltk.data import LazyLoader
from nltk.tokenize import TreebankWordTokenizer
from nltk.util import AbstractLazySequence, LazyMap,
LazyConcatenation
class MongoDBLazySequence(AbstractLazySequence):
    def __init__(self, host='localhost', port=27017, db='test',
    collection='corpus', field='text'):
        self.conn = pymongo.MongoClient(host, port)
        self.collection = self.conn[db][collection]
        self.field = field
    def __len (self):
```

```
return self.collection.count()
  def iterate from(self, start):
    f = lambda d: d.get(self.field, '')
    return iter(LazyMap(f, self.collection.find(fields=[self.field],
skip=start)))
class MongoDBCorpusReader(object):
  def init (self, word tokenizer=TreebankWordTokenizer(),
    sent tokenizer=LazyLoader('tokenizers/punkt/PY3/
english.pickle'),**kwargs):
    self. seq = MongoDBLazySequence(**kwarqs)
    self. word tokenize = word tokenizer.tokenize
    self. sent tokenize = sent tokenizer.tokenize
  def text(self):
    return self. seq
  def words(self):
    return LazyConcatenation(LazyMap(self. word tokenize,
self.text()))
  def sents(self):
    return LazyConcatenation(LazyMap(self. sent tokenize,
self.text()))
```

How it works...

The AbstractLazySequence class is an abstract class that provides read-only, on-demand iteration. Subclasses must implement the __len__() and iterate_from(start) methods, while it provides the rest of the list and iterator emulation methods. By creating the MongoDBLazySequence subclass as our view, we can iterate over documents in the MongoDB collection on demand, without keeping all the documents in memory. The LazyMap class is a lazy version of Python's built-in map() function, and is used in iterate_from() to transform the document into the specific field that we're interested in. It's also a subclass of AbstractLazySequence.

The MongoDBCorpusReader class creates an internal instance of MongoDBLazySequence for iteration, then defines the word and sentence tokenization methods. The text() method simply returns the instance of MongoDBLazySequence, which results in a lazily evaluated list of each text field. The words() method uses LazyMap and LazyConcatenation to return a lazily evaluated list of all words, while the sents() method does the same for sentences. The sent_tokenizer is loaded on demand with LazyLoader, which is a wrapper around nltk.data.load(), analogous to LazyCorpusLoader. The LazyConcatentation class is a subclass of AbstractLazySequence too, and produces a flat list from a given list of lists (each list may also be lazy). In our case, we're concatenating the results of LazyMap to ensure we don't return nested lists.

There's more...

All of the parameters are configurable. For example, if you had a db named website, with a collection named comments, whose documents had a field called comment, you could create a MongoDBCorpusReader class as follows:

```
>>> reader = MongoDBCorpusReader(db='website',
collection='comments', field='comment')
```

You can also pass in custom instances for word_tokenizer and sent_tokenizer, as long as the objects implement the nltk.tokenize.TokenizerI interface by providing a tokenize(text) method.

See also

Corpus views were covered in the previous recipe, and tokenization was covered in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*.

Corpus editing with file locking

Corpus readers and views are all read-only, but there will be times when you want to add to or edit the corpus files. However, modifying a corpus file while other processes are using it, such as through a corpus reader, can lead to dangerous undefined behavior. This is where file locking comes in handy.

Getting ready

You must install the lockfile library using sudo <code>easy_install lockfile</code> or sudo <code>pip install lockfile</code>. This library provides cross-platform file locking, and so will work on Windows, Unix/Linux, Mac OS X, and more. You can find detailed documentation on lockfile at http://packages.python.org/lockfile/.

How to do it...

Here are two file editing functions: append_line() and remove_line(). Both try to acquire an exclusive lock on the file before updating it. An exclusive lock means that these functions will wait until no other process is reading from or writing to the file. Once the lock is acquired, any other process that tries to access the file will have to wait until the lock is released. This way, modifying the file will be safe and not cause any undefined behavior in other processes. These functions can be found in corpus.py, as follows:

```
import lockfile, tempfile, shutil
def append line(fname, line):
                                 with lockfile.FileLock(fname):
  fp = open(fname, 'a+')
  fp.write(line)
  fp.write('\n')
  fp.close()
def remove line(fname, line):
  with lockfile.FileLock(fname):
    tmp = tempfile.TemporaryFile()
    fp = open(fname, 'rw+')
    # write all lines from orig file, except if matches given line
    for 1 in fp:
      if l.strip() != line:
        tmp.write(l)
    # reset file pointers so entire files are copied
    fp.seek(0)
    tmp.seek(0)
    # copy tmp into fp, then truncate to remove trailing line(s)
    shutil.copyfileobj(tmp, fp)
    fp.truncate()
```

fp.close()
tmp.close()

The lock acquiring and releasing happens transparently when you do with lockfile.FileLock(fname).

Note

Instead of using with lockfile.FileLock(fname), you can also get a lock by calling lock =
lockfile.FileLock(fname), then call lock.acquire() to acquire the lock, and
lock.release() to release the lock.

How it works...

You can use these functions as follows:

```
>>> from corpus import append_line, remove_line
>>> append_line('test.txt', 'foo')
>>> remove line('test.txt', 'foo')
```

In append_line(), a lock is acquired, the file is opened in *append mode*, the text is written along with an end-of-line character, and then the file is closed, releasing the lock.

Tip

A lock acquired by lockfile only protects the file from other processes that also use lockfile. In other words, just because your Python process has a lock with lockfile doesn't mean a non-Python process can't modify the file. For this reason, it's best to only use lockfile with files that will not be edited by an non-Python processes, or Python processes that do not use lockfile.

The remove_line() function is a bit more complicated. Because we're removing a line, and not a specific section of the file, we need to iterate over the file to find each instance of the line to remove. The easiest way to do this while writing the changes back to the file, is to use a temporary file to hold the changes, then copy that file back into the original file using shutil.copyfileobj().

Note

The remove_line() function does not work on Mac OS X, but does work on Linux. For remove_line() to work, it must be able to open a file in both read and write modes, and Mac OS X does not allow this.

These functions are best suited for a wordlist corpus, or some other corpus type with presumably unique lines, that may be edited by multiple people at about the same time, such as through a web interface. Using these functions with a more document-oriented corpus such as brown, treebank, or conll2000, is probably a bad idea.

Chapter 4. Part-of-speech Tagging

In this chapter, we will cover the following recipes:

- Default tagging
- Training a unigram part-of-speech tagger
- Combining taggers with backoff tagging
- Training and combining ngram taggers
- Creating a model of likely word tags
- Tagging with regular expressions
- Affix tagging
- Training a Brill tagger
- Training the TnT tagger
- Using WordNet for tagging
- Tagging proper names
- Classifier-based tagging
- Training a tagger with NLTK-Trainer

Introduction

Part-of-speech tagging is the process of converting a sentence, in the form of a list of words, into a list of tuples, where each tuple is of the form (**word, tag**). The **tag** is a part-of-speech tag, and signifies whether the word is a noun, adjective, verb, and so on.

Part-of-speech tagging is a necessary step before chunking, which is covered in <u>Chapter 5</u>, *Extracting Chunks*. Without the part-of-speech tags, a chunker cannot know how to extract phrases from a sentence. But with part-of-speech tags, you can tell a chunker how to identify phrases based on tag patterns.

You can also use part-of-speech tags for grammar analysis and word sense disambiguation. For example, the word *duck* could refer to a bird, or it could be a verb indicating a downward motion. Computers cannot know the difference without additional information, such as part-of-speech tags. For more on word sense disambiguation, refer to the URL <u>https://en.wikipedia.org/wiki/Word_sense_disambiguation</u>.

Most of the taggers we'll cover are trainable. They use a list of tagged sentences as their training data, such as what you get from the tagged_sents() method of a TaggedCorpusReader class (see the *Creating a part-of-speech tagged word corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*, for more details). With these training sentences, the tagger generates an internal model that will tell it how to tag a word. Other taggers use external data sources or match word patterns to choose a tag for a word.

All taggers in NLTK are in the nltk.tag package and inherit from the TaggerI base class. TaggerI requires all subclasses to implement a tag() method, which takes a list of words as input and returns a list of tagged words as output. TaggerI also provides an evaluate() method for evaluating the accuracy of the tagger (covered at the end of the *Default tagging* recipe). Many taggers can also be combined into a backoff chain, so that if one tagger cannot tag a word, the next tagger is used, and so on.

Default tagging

Default tagging provides a baseline for part-of-speech tagging. It simply assigns the same part-of-speech tag to every token. We do this using the DefaultTagger class. This tagger is useful as a last-resort tagger, and provides a baseline to measure accuracy improvements.

Getting ready

We're going to use the treebank corpus for most of this chapter because it's a common standard and is quick to load and test. But everything we do should apply equally well to brown, conll2000, and any other part-of-speech tagged corpus.

How to do it...

The DefaultTagger class takes a single argument, the tag you want to apply. We'll give it NN, which is the tag for a singular noun. DefaultTagger is most useful when you choose the most common part-of-speech tag. Since nouns tend to be the most common types of words, a noun tag is recommended.

```
>>> from nltk.tag import DefaultTagger
>>> tagger = DefaultTagger('NN')
>>> tagger.tag(['Hello', 'World'])
[('Hello', 'NN'), ('World', 'NN')]
```

Every tagger has a tag() method that takes a list of tokens, where each token is a single word. This list of tokens is usually a list of words produced by a word tokenizer (see <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, for more on tokenization). As you can see, tag() returns a list of tagged tokens, where a tagged token is a tuple of (word, tag).

How it works...

DefaultTagger is a subclass of SequentialBackoffTagger. Every subclass of SequentialBackoffTagger must implement the choose_tag() method, which takes three arguments:

- The list of tokens
- The index of the current token whose tag we want to choose
- The history, which is a list of the previous tags

SequentialBackoffTagger implements the tag() method, which calls the choose_tag() method of the subclass for each index in the tokens list while accumulating a history of the previously tagged tokens. This history is the reason for the *Sequential* in SequentialBackoffTagger. We'll get to the backoff portion of the name in the *Combining taggers with backoff tagging* recipe. Here's a diagram showing the inheritance tree:



The choose_tag() method of DefaultTagger is very simple: it returns the tag we gave it at the time of initialization. It does not care about the current token or the history.

There's more...

There are a lot of different tags you could give to the DefaultTagger class. You can find a complete list of possible tags for the treebank corpus at http://www.ling.upenn.edu/courses/Fall_2003/ling001/ penn_treebank_pos.html. These tags are also documented in https://www.ling.upenn.edu/courses/Fall_2003/ling001/ penn_treebank_pos.html. These tags are also documented in https://www.ling.upenn.edu/courses/Fall_2003/ling001/ penn_treebank_pos.html. These tags are also documented in https://www.ling.upenn.edu/courses/Fall_2003/ling001/ penn_treebank_pos.html.

Evaluating accuracy

To know how accurate a tagger is, you can use the evaluate() method, which takes a list of tagged tokens as a gold standard to evaluate the tagger. Using our default tagger created earlier, we can evaluate it against a subset of the treebank corpus tagged sentences.

```
>>> from nltk.corpus import treebank
>>> test sents = treebank.tagged sents()[3000:]
```

```
>>> tagger.evaluate(test_sents)
0.14331966328512843
```

So, by just choosing NN for every tag, we can achieve 14 % accuracy testing on one-fourth of the treebank corpus. Of course, accuracy will be different if you choose a different default tag. We'll be reusing these same test sents for evaluating more taggers in the upcoming recipes.

Tagging sentences

TaggerI also implements a tag_sents() method that can be used to tag a list of sentences, instead of a single sentence. Here's an example of tagging two simple sentences:

```
>>> tagger.tag_sents([['Hello', 'world', '.'], ['How', 'are', 'you',
'?']])
[[('Hello', 'NN'), ('world', 'NN'), ('.', 'NN')], [('How', 'NN'),
('are', 'NN'), ('you', 'NN'), ('?', 'NN')]]
```

The result is a list of two tagged sentences, and of course, every tag is NN because we're using the DefaultTagger class. The tag_sents() method can be quiet useful if you have many sentences you wish to tag all at once.

Untagging a tagged sentence

Tagged sentences can be untagged using nltk.tag.untag(). Calling this function with a tagged sentence will return a list of words without the tags.

```
>>> from nltk.tag import untag
>>> untag([('Hello', 'NN'), ('World', 'NN')])
['Hello', 'World']
```

See also

For more on tokenization, see <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*. And to learn more about tagged sentences, see the *Creating a part-of-speech tagged word corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*. For a complete list of part-of-speech tags found in the treebank corpus, see <u>Appendix A</u>, *Penn Treebank Part-of-speech Tags*.

Training a unigram part-of-speech tagger

A **unigram** generally refers to a single token. Therefore, a unigram tagger only uses a single word as its context for determining the part-of-speech tag.

UnigramTagger inherits from NgramTagger, which is a subclass of ContextTagger, which inherits from SequentialBackoffTagger. In other words, UnigramTagger is a context-based tagger whose context is a single word, or unigram.

How to do it...

UnigramTagger can be trained by giving it a list of tagged sentences at initialization.

```
>>> from nltk.tag import UnigramTagger
>>> from nltk.corpus import treebank
>>> train_sents = treebank.tagged_sents()[:3000]
>>> tagger = UnigramTagger(train_sents)
>>> treebank.sents()[0]
['Pierre', 'Vinken', ',', '61', 'years', 'old', ',', 'will', 'join',
'the', 'board', 'as', 'a', 'nonexecutive', 'director', 'Nov.', '29',
'.']
>>> tagger.tag(treebank.sents()[0])
[('Pierre', 'NNP'), ('Vinken', 'NNP'), (',', ','), ('61', 'CD'),
('years', 'NNS'), ('old', 'JJ'), (',', ','), ('will', 'MD'),
('join', 'VB'), ('the', 'DT'), ('board', 'NN'), ('as', 'IN'), ('a',
'DT'), ('nonexecutive', 'JJ'), ('director', 'NN'), ('Nov.', 'NNP'),
('29', 'CD'), ('.', '.')]
```

We use the first 3000 tagged sentences of the treebank corpus as the training set to initialize the UnigramTagger class. Then, we see the first sentence as a list of words, and can see how it is transformed by the tag() function into a list of tagged tokens.

How it works...

UnigramTagger builds a context model from the list of tagged sentences. Because UnigramTagger inherits from ContextTagger, instead of providing a choose_tag() method, it must implement a context() method, which takes the same three arguments as choose_tag(). The result of context() is, in this case, the word token. The context token is used to create the model, and also to look up the best tag once the model is created. Here's an inheritance diagram showing each class, starting at SequentialBackoffTagger:



Let's see how accurate the UnigramTagger class is on the test sentences (see the previous recipe for how test sents is created).

```
>>> tagger.evaluate(test_sents)
0.8588819339520829
```

It has almost 86 % accuracy for a tagger that only uses single word lookup to determine the part-of-speech tag. All accuracy gains from here on will be much smaller.

Note

Actual accuracy values may change each time you run the code. This is because the default iteration order in Python 3 is random. To get consistent accuracy values, run Python with the PYTHONHASHSEED environment variable set to 0 or any positive integer. For example:

\$ PYTHONHASHSEED=0 python chapter4.py

All accuracy values in this book were calculated with PYTHONHASHSEED=0.

There's more...

The model building is actually implemented in ContextTagger. Given the list of tagged sentences, it calculates the frequency that a tag has occurred for each context. The tag with the highest frequency for a context is stored in the model.

Overriding the context model

All taggers that inherit from ContextTagger can take a pre-built model instead of training their own. This model is simply a Python dict mapping a context key to a tag. The context keys will depend on what the ContextTagger subclass returns from its context() method. For UnigramTagger, context keys are individual words. But for other NgramTagger subclasses, the context keys will be tuples.

Here's an example where we pass a very simple model to the UnigramTagger class instead of a training set.

```
>>> tagger = UnigramTagger(model={'Pierre': 'NN'})
>>> tagger.tag(treebank.sents()[0])
[('Pierre', 'NN'), ('Vinken', None), (',', None), ('61', None),
('years', None), ('old', None), (',', None), ('will', None),
('join', None), ('old', None), ('board', None), ('as', None), ('a',
None), ('nonexecutive', None), ('director', None), ('Nov.', None),
('29', None), ('.', None)]
```

Since the model only contained the context key Pierre, only the first word got a tag. Every other word got None as the tag since the context word was not in the model. So, unless you know exactly what you are doing, let the tagger train its own model instead of passing in your own.

One good case for passing a self-created model to the UnigramTagger class is for when you have a dictionary of words and tags, and you know that every word should always map to its tag. Then, you can put this UnigramTagger as your first backoff tagger (covered in the next recipe) to look up tags for unambiguous words.

Minimum frequency cutoff

The ContextTagger class uses frequency of occurrence to decide which tag is most likely for a given context. By default, it will do this even if the context word and tag occurs only once. If you'd like to set a minimum frequency threshold, then you can pass a cutoff value to the UnigramTagger class.

```
>>> tagger = UnigramTagger(train_sents, cutoff=3)
>>> tagger.evaluate(test_sents)
0.7757392618173969
```

In this case, using cutoff=3 has decreased accuracy, but there may be times when a cutoff is a good idea.

See also

In the next recipe, we'll cover **backoff tagging** to combine taggers, and in the *Creating a model of likely word tags* recipe, we'll learn how to statistically determine tags for very common words.

Combining taggers with backoff tagging

Backoff tagging is one of the core features of SequentialBackoffTagger. It allows you to chain taggers together so that if one tagger doesn't know how to tag a word, it can pass the word on to the next backoff tagger. If that one can't do it, it can pass the word on to the next backoff tagger, and so on until there are no backoff taggers left to check.

How to do it...

Every subclass of SequentialBackoffTagger can take a backoff keyword argument whose value is another instance of a SequentialBackoffTagger. So, we'll use the DefaultTagger class from the *Default tagging* recipe in this chapter as the backoff to the UnigramTagger class covered in the previous recipe, *Training a unigram part-of-speech tagger*. Refer to both the recipes for details on train_sents and test_sents.

```
>>> tagger1 = DefaultTagger('NN')
>>> tagger2 = UnigramTagger(train_sents, backoff=tagger1)
>>> tagger2.evaluate(test_sents)
0.8758471832505935
```

By using a default tag of NN whenever the UnigramTagger is unable to tag a word, we've increased the accuracy by almost 2%!

How it works...

When a SequentialBackoffTagger class is initialized, it creates an internal list of backoff taggers with itself as the first element. If a backoff tagger is given, then the backoff tagger's internal list of taggers is appended. Here's some code to illustrate this:

```
>>> tagger1._taggers == [tagger1]
True
>>> tagger2._taggers == [tagger2, tagger1]
True
```

The _taggers list is the internal list of backoff taggers that the SequentialBackoffTagger class uses when the tag() method is called. It goes through its list of taggers, calling choose_tag() on each one. As soon as a tag is found, it stops and returns that tag. This means that if the primary tagger can tag the word, then that's the tag that will be returned. But if it returns None, then the next tagger is tried, and so on until a tag is found, or else None is returned. Of course, None will never be returned if your final backoff tagger is a DefaultTagger.

There's more...

While most of the taggers included in NLTK are subclasses of SequentialBackoffTagger, not all of them are. There's a few taggers that we'll cover in the later recipes that cannot be used as part of a backoff tagging chain, such as the BrillTagger class. However, these taggers generally take another
tagger to use as a baseline, and a SequentialBackoffTagger class is often a good choice for that baseline.

Saving and loading a trained tagger with pickle

Since training a tagger can take a while, and you generally only need to do the training once, pickling a trained tagger is a useful way to save it for later usage. If your trained tagger is called tagger, then here's how to dump and load it with pickle:

```
>>> import pickle
>>> f = open('tagger.pickle', 'wb')
>>> pickle.dump(tagger, f)
>>> f.close()
>>> f = open('tagger.pickle', 'rb')
>>> tagger = pickle.load(f)
```

If your tagger pickle file is located in an NLTK data directory, you could also use nltk.data.load('tagger.pickle') to load the tagger.

See also

In the next recipe, we'll combine more taggers with backoff tagging. Also, see the previous two recipes for details on the DefaultTagger and UnigramTagger classes.

Training and combining ngram taggers

In addition to UnigramTagger, there are two more NgramTagger subclasses: BigramTagger and TrigramTagger. The BigramTagger subclass uses the previous tag as part of its context, while the TrigramTagger subclass uses the previous two tags. An **ngram** is a subsequence of *n* items, so the BigramTagger subclass looks at two items (the previous tagged word and the current word), and the TrigramTagger subclass looks at three items.

These two taggers are good at handling words whose part-of-speech tag is context-dependent. Many words have a different part of speech depending on how they are used. For example, we've been talking about taggers that tag words. In this case, *tag* is used as a verb. But the result of tagging is a part-of-speech tag, so *tag* can also be a noun. The idea with the NgramTagger subclasses is that by looking at the previous words and part-of-speech tags, we can better guess the part-of-speech tag for the current word. Internally, each tagger maintains a context dictionary (implemented in the ContextTagger parent class) that is used to guess that tag based on the context. In the case of NgramTagger subclasses, the context is some number of previous tagged words.

Getting ready

Refer to the first two recipes of this chapter for details on constructing train_sents and test_sents.

How to do it...

By themselves, BigramTagger and TrigramTagger perform quite poorly. This is partly because they cannot learn context from the first word(s) in a sentence. Since a UnigramTagger class doesn't care about the previous context, it is able to have higher baseline accuracy by simply guessing the most common tag for each word.

```
>>> from nltk.tag import BigramTagger, TrigramTagger
>>> bitagger = BigramTagger(train_sents)
>>> bitagger.evaluate(test_sents)
0.11310166199007123
>>> tritagger = TrigramTagger(train_sents)
>>> tritagger.evaluate(test_sents)
0.0688107058061731
```

Where BigramTagger and TrigramTagger can make a contribution is when we combine them with backoff tagging. This time, instead of creating each tagger individually, we'll create a function that will take train_sents, a list of SequentialBackoffTagger classes, and an optional final backoff tagger, then train each tagger with the previous tagger as a backoff. Here's the code from tag_util.py:

```
def backoff_tagger(train_sents, tagger_classes, backoff=None):
    for cls in tagger_classes:
        backoff = cls(train_sents, backoff=backoff)
```

return backoff

And to use it, we can do the following:

```
>>> from tag_util import backoff_tagger
>>> backoff = DefaultTagger('NN')
>>> tagger = backoff_tagger(train_sents, [UnigramTagger,
BigramTagger, TrigramTagger], backoff=backoff)
>>> tagger.evaluate(test_sents)
0.8806820634578028
```

So, we've gained almost 1% accuracy by including the BigramTagger and TrigramTagger subclasses in the backoff chain. For corpora other than treebank, the accuracy gain may be more or less significant, depending on the nature of the text.

How it works...

The backoff_tagger function creates an instance of each tagger class in the list, giving it train_sents and the previous tagger as a backoff. The order of the list of tagger classes is quite important: the first class in the list (UnigramTagger) will be trained first and given the initial backoff tagger (the DefaultTagger). This tagger will then become the backoff tagger for the next tagger class in the list. The final tagger returned will be an instance of the last tagger class in the list (TrigramTagger). Here's some code to clarify this chain:

```
>>> tagger._taggers[-1] == backoff
True
>>> isinstance(tagger._taggers[0], TrigramTagger)
True
>>> isinstance(tagger._taggers[1], BigramTagger)
True
```

So, we get a TrigramTagger, whose first backoff is a BigramTagger. Then, the next backoff will be a UnigramTagger, whose backoff is the DefaultTagger.

There's more...

The backoff_tagger function doesn't just work with NgramTagger classes, it can also be used for constructing a chain containing any subclasses of SequentialBackoffTagger.

BigramTagger and TrigramTagger, because they are subclasses of NgramTagger and ContextTagger, can also take a model and cutoff argument, just like the UnigramTagger. But unlike for UnigramTagger, the context keys of the model must be two tuples, where the first element is a section of the history and the second element is the current token. For the BigramTagger, an appropriate context key looks like ((prevtag,), word), and for TrigramTagger, it looks like ((prevtag1, prevtag2), word).

Quadgram tagger

The NgramTagger class can be used by itself to create a tagger that uses more than three ngrams for its context key.

```
>>> from nltk.tag import NgramTagger
>>> quadtagger = NgramTagger(4, train_sents)
>>> quadtagger.evaluate(test_sents)
0.058234405352903085
```

It's even worse than the TrigramTagger! Here's an alternative implementation of a QuadgramTagger class that we can include in a list to backoff_tagger. This code can be found in taggers.py.

```
from nltk.tag import NgramTagger
class QuadgramTagger(NgramTagger):
    def __init__(self, *args, **kwargs):
        NgramTagger.__init__(self, 4, *args, **kwargs)
```

This is essentially how BigramTagger and TrigramTagger are implemented: simple subclasses of NgramTagger that pass in the number of ngrams to look at in the history argument of the context() method.

Now, let's see how it does as part of a backoff chain.

```
>>> from taggers import QuadgramTagger
>>> quadtagger = backoff_tagger(train_sents, [UnigramTagger,
BigramTagger, TrigramTagger, QuadgramTagger], backoff=backoff)
>>> quadtagger.evaluate(test_sents)
0.8806388948845241
```

It's actually slightly worse than before, when we stopped with the TrigramTagger. So, the lesson is that too much context can have a negative effect on accuracy.

See also

The previous two recipes cover the UnigramTagger and backoff tagging.

Creating a model of likely word tags

As previously mentioned in the *Training a unigram part-of-speech tagger* recipe, using a custom model with a UnigramTagger class should only be done if you know exactly what you're doing. In this recipe, we're going to create a model for the most common words, most of which always have the same tag no matter what.

How to do it...

To find the most common words, we can use nltk.probability.FreqDist to count word frequencies in the treebank corpus. Then, we can create a ConditionalFreqDist class for tagged words, where we count the frequency of every tag for every word. Using these counts, we can construct a model of the 200 most frequent words as keys, with the most frequent tag for each word as a value. Here's the model creation function defined in tag_util.py.

```
from nltk.probability import FreqDist, ConditionalFreqDist
def word_tag_model(words, tagged_words, limit=200):
    fd = FreqDist(words)
    cfd = ConditionalFreqDist(tagged_words)
    most_freq = (word for word, count in fd.most_common(limit))
    return dict((word, cfd[word].max()) for word in most freq)
```

And to use it with a UnigramTagger class, we can do the following:

```
>>> from tag_util import word_tag_model
>>> from nltk.corpus import treebank
>>> model = word_tag_model(treebank.words(), treebank.tagged_words())
>>> tagger = UnigramTagger(model=model)
>>> tagger.evaluate(test_sents)
0.559680552557738
```

An accuracy of almost 56% is ok, but nowhere near as good as the trained UnigramTagger. Let's try adding it to our backoff chain.

```
>>> default_tagger = DefaultTagger('NN')
>>> likely_tagger = UnigramTagger(model=model,
backoff=default_tagger)
>>> tagger = backoff_tagger(train_sents, [UnigramTagger,
BigramTagger, TrigramTagger], backoff=likely_tagger)
>>> tagger.evaluate(test_sents)
0.8806820634578028
```

The final accuracy is exactly the same as without the <code>likely_tagger</code>. This is because the frequency calculations we did to create the model are almost exactly the same as what happens when we train a <code>UnigramTagger class</code>.

How it works...

The word_tag_model() function takes a list of all words, a list of all tagged words, and the maximum number of words we want to use for our model. We give the list of words to a FreqDist class, which counts the frequency of each word. Then, we get the top 200 words from the FreqDist class by calling fd.most_common(), which obviously returns a list of the most common words and counts. The FreqDist class is actually a subclass of collections.Counter, which provides the most_common() method.

Next, we give the list of tagged words to ConditionalFreqDist, which creates a FreqDist class of tags for each word, with the word as the condition. Finally, we return a dict of the top 200 words mapped to their most likely tag.

Note

In the previous edition of this book, we used the keys() method of the FreqDist class because in NLTK2, the keys were returned in sorted order, from the most frequent to the least. But in NLTK3, FreqDist inherits from collections.Counter, and the keys() method does not use any predictable ordering.

There's more...

It may seem useless to include this tagger as it does not change the accuracy. But the point of this recipe is to demonstrate how to construct a useful model for a UnigramTagger class. Custom model construction is a way to create a manual override of trained taggers that are otherwise black boxes. And by putting the likely tagger at the front of the chain, we can actually improve accuracy a little bit:

```
>>> tagger = backoff_tagger(train_sents, [UnigramTagger,
BigramTagger, TrigramTagger], backoff=default_tagger)
>>> likely_tagger = UnigramTagger(model=model, backoff=tagger)
>>> likely_tagger.evaluate(test_sents)
0.8824088063889488
```

Putting custom model taggers at the front of the backoff chain gives you complete control over how specific words are tagged, while letting the trained taggers handle everything else.

See also

The *Training a unigram part-of-speech tagger* recipe has details on the UnigramTagger class and a simple custom model example. See the earlier *recipes Combining taggers with backoff tagging* and *Training and combining ngram taggers* for details on backoff tagging.

Tagging with regular expressions

You can use regular expression matching to tag words. For example, you can match numbers with \d to assign the tag **CD** (which refers to a Cardinal number). Or you could match on known word patterns, such as the suffix "ing". There's a lot of flexibility here, but be careful of over-specifying since language is naturally inexact, and there are always exceptions to the rule.

Getting ready

For this recipe to make sense, you should be familiar with the regular expression syntax and Python's remodule.

How to do it...

The RegexpTagger class expects a list of two tuples, where the first element in the tuple is a regular expression and the second element is the tag. The patterns shown in the following code can be found in tag_util.py:

```
patterns = [
    (r'^\d+$', 'CD'),
    (r'.*ing$', 'VBG'), # gerunds, i.e. wondering
    (r'.*ment$', 'NN'), # i.e. wonderment
    (r'.*ful$', 'JJ') # i.e. wonderful
]
```

Once you've constructed this list of patterns, you can pass it into RegexpTagger.

```
>>> from tag_util import patterns
>>> from nltk.tag import RegexpTagger
>>> tagger = RegexpTagger(patterns)
>>> tagger.evaluate(test_sents)
0.037470321605870924
```

So, it's not too great with just a few patterns, but since RegexpTagger is a subclass of SequentialBackoffTagger, it can be a useful part of a backoff chain. For example, it could be positioned just before a DefaultTagger class, to tag words that the ngram tagger(s) missed.

How it works...

The RegexpTagger class saves the patterns given at initialization, then on each call to choose_tag(), it iterates over the patterns and returns the tag for the first expression that matches the current word using re.match(). This means that if you have two expressions that could match, the tag of the first one will always be returned, and the second expression won't even be tried.

There's more...

The RegexpTagger class can replace the DefaultTagger class if you give it a pattern such as (r'.*', 'NN'). This pattern should, of course, be last in the list of patterns, otherwise no other patterns will match.

See also

In the next recipe, we'll cover the AffixTagger class, which learns how to tag based on prefixes and suffixes of words. See the *Default tagging* recipe for details on the DefaultTagger class.

Affix tagging

The AffixTagger class is another ContextTagger subclass, but this time the context is either the prefix or the suffix of a word. This means the AffixTagger class is able to learn tags based on fixed-length substrings of the beginning or ending of a word.

How to do it...

The default arguments for an AffixTagger class specify three-character suffixes, and that words must be at least five characters long. If a word is less than five characters, then None is returned as the tag.

```
>>> from nltk.tag import AffixTagger
>>> tagger = AffixTagger(train_sents)
>>> tagger.evaluate(test_sents)
0.27558817181092166
```

So, it does ok by itself with the default arguments. Let's try it by specifying three-character prefixes.

```
>>> prefix_tagger = AffixTagger(train_sents, affix_length=3)
>>> prefix_tagger.evaluate(test_sents)
0.23587308439456076
```

To learn on two-character suffixes, the code will look like this:

```
>>> suffix_tagger = AffixTagger(train_sents, affix_length=-2)
>>> suffix_tagger.evaluate(test_sents)
0.31940427368875457
```

How it works...

A positive value for affix_length means that the AffixTagger class will learn word prefixes, essentially word[:affix_length]. If affix_length is negative, then suffixes are learned using word[affix length:].

There's more...

You can combine multiple affix taggers in a backoff chain if you want to learn on multiple character length affixes. Here's an example of four AffixTagger classes learning on 2 and 3 character prefixes and suffixes:

```
>>> pre3_tagger = AffixTagger(train_sents, affix_length=3)
>>> pre3_tagger.evaluate(test_sents)
0.23587308439456076
>>> pre2_tagger = AffixTagger(train_sents, affix_length=2,
backoff=pre3_tagger)
>>> pre2_tagger.evaluate(test_sents)
```

```
0.29786315562270665
>>> suf2_tagger = AffixTagger(train_sents, affix_length=-2,
backoff=pre2_tagger)
>>> suf2_tagger.evaluate(test_sents)
0.32467083962875026
>>> suf3_tagger = AffixTagger(train_sents, affix_length=-3,
backoff=suf2_tagger)
>>> suf3_tagger.evaluate(test_sents)
0.3590761925318368
```

As you can see, the accuracy goes up each time.

Note

The ordering in the previous block of code is not the best, nor is it the worst. I'll leave it to you to explore the possibilities and discover the best backoff chain of values for AffixTagger and affix_length.

Working with min_stem_length

The AffixTagger class also takes a min_stem_length keyword argument, with a default value of 2. If the word length is less than min_stem_length plus the absolute value of affix_length, then None is returned by the context() method. Increasing min_stem_length forces the AffixTagger class to only learn on longer words, while decreasing min_stem_length will allow it to learn on shorter words. Of course, for shorter words, the affix_length argument could be equal to or greater than the word length, and AffixTagger would essentially be acting like a UnigramTagger class.

See also

You can manually specify prefixes and suffixes using regular expressions, as shown in the previous recipe. The *Training a unigram part-of-speech tagger* and *Training and combining ngram taggers* recipes have details on NgramTagger subclasses, which are also subclasses of ContextTagger.

Training a Brill tagger

The BrillTagger class is a transformation-based tagger. It is the first tagger that is not a subclass of SequentialBackoffTagger. Instead, the BrillTagger class uses a series of rules to correct the results of an initial tagger. These rules are scored based on how many errors they correct minus the number of new errors they produce.

How to do it...

```
Here's a function from tag util.py that trains a BrillTagger class using
BrillTaggerTrainer. It requires an initial tagger and train sents.
from nltk.tag import brill, brill trainer
def train brill tagger(initial tagger, train sents, **kwargs):
  templates = [
    brill.Template(brill.Pos([-1])),
    brill.Template(brill.Pos([1])),
    brill.Template(brill.Pos([-2])),
    brill.Template(brill.Pos([2])),
    brill.Template(brill.Pos([-2, -1])),
    brill.Template(brill.Pos([1, 2])),
    brill.Template(brill.Pos([-3, -2, -1])),
    brill.Template(brill.Pos([1, 2, 3])),
    brill.Template(brill.Pos([-1]), brill.Pos([1])),
    brill.Template(brill.Word([-1])),
    brill.Template(brill.Word([1])),
    brill.Template(brill.Word([-2])),
    brill.Template(brill.Word([2])),
    brill.Template(brill.Word([-2, -1])),
    brill.Template(brill.Word([1, 2])),
    brill.Template(brill.Word([-3, -2, -1])),
    brill.Template(brill.Word([1, 2, 3])),
    brill.Template(brill.Word([-1]), brill.Word([1])),
  1
  trainer = brill trainer.BrillTaggerTrainer(initial tagger,
templates, deterministic=True)
  return trainer.train(train sents, **kwargs)
```

To use it, we can create our initial_tagger from a backoff chain of NgramTagger classes, then pass that into the train_brill_tagger() function to get a BrillTagger back.

```
>>> default_tagger = DefaultTagger('NN')
>>> initial_tagger = backoff_tagger(train_sents, [UnigramTagger,
BigramTagger, TrigramTagger], backoff=default_tagger)
```

```
>>> initial_tagger.evaluate(test_sents)
0.8806820634578028
>>> from tag_util import train_brill_tagger
>>> brill_tagger = train_brill_tagger(initial_tagger, train_sents)
>>> brill_tagger.evaluate(test_sents)
0.8827541549751781
```

So, the BrillTagger class has slightly increased accuracy over the initial_tagger.

How it works...

The BrillTaggerTrainer class takes an initial_tagger argument and a list of templates. These templates must implement the BrillTemplateI interface, which is found in the nltk.tbl.template module. The brill.Template class is such an implementation, and is actually imported from nltk.tbl.template. The brill.Pos and brill.Word classes are subclasses of nltk.tbl.template.Feature, and they describe what kind of features to use in the template, in this case, one or more part-of-speech tags or words.

The templates specify how to learn transformation rules. For example, brill.Template(brill.Pos([-1])) means that a rule can be generated using the previous part-of-speech tag. The brill.Template(brill.Pos([1])) statement means that you can look at the next part-of-speech tag to generate a rule. And brill.Template(brill.Word([-2, -1])) means you can look at the combination of the previous two words to learn a transformation rule.

The thinking behind a transformation-based tagger is this: given the correct training sentences, the output of the initial tagger, and the templates specifying features, try to generate transformation rules that correct the initial tagger's output to be more in-line with the training sentences. The job of BrillTaggerTrainer is to produce these rules, and to do so in a way that increases accuracy. A transformation rule that fixes one problem may cause an error in another condition; thus, every rule must be measured by how many errors it corrects versus how many new errors it introduces.

The workflow looks something like this:



There's more...

You can control the number of rules generated using the max_rules keyword argument to the BrillTaggerTrainer.train() method. The default value is 200. You can also control the quality of rules used with the min_score keyword argument. The default value is 2, though 3 can be a good choice as well. The score is a measure of how well a rule corrects errors compared to how many new errors it introduces.

Note

Increasing max_rules or min_score will greatly increase training time, without necessarily increasing accuracy. Change these values with care.

Tracing

```
You can watch the BrillTaggerTrainer class do its work by passing trace=True into the constructor, for example, trainer = brill.BrillTaggerTrainer(initial_tagger, templates, deterministic=True, trace=True). This will give you the following output:
```

```
TBL train (fast) (seqs: 3000; tokens: 77511; tpls: 18; min score: 2;
min acc: None)
Finding initial useful rules...
Found 9869 useful rules.
Selecting rules...
```

This means it found 77511 rules with a score of at least min_score, and then it selects the best rules, keeping no more than max_rules.

The default is trace=False, which means the trainer will work silently without printing its status.

See also

The *Training and combining ngram taggers* recipe details the construction of the initial_tagger argument used earlier, and the *Default tagging* recipe explains the default_tagger argument.

Training the TnT tagger

TnT stands for **Trigrams'n'Tags**. It is a statistical tagger based on second order Markov models. The details of this are out of the scope of this book, but you can read more about the original implementation at <u>http://www.coli.uni-saarland.de/~thorsten/tnt/</u>.

How to do it...

The TnT tagger has a slightly different API than the previous taggers we've encountered. You must explicitly call the train() method after you've created it. Here's a basic example.

```
>>> from nltk.tag import tnt
>>> tnt_tagger = tnt.TnT()
>>> tnt_tagger.train(train_sents)
>>> tnt_tagger.evaluate(test_sents)
0.8756313403842003
```

It's quite a good tagger all by itself, only slightly less accurate than the BrillTagger class from the previous recipe. But if you do not call train() before evaluate(), you'll get an accuracy of 0%.

How it works...

The TnT tagger maintains a number of internal FreqDist and ConditionalFreqDist instances based on the training data. These frequency distributions count unigrams, bigrams, and trigrams. Then, during tagging, the frequencies are used to calculate the probabilities of possible tags for each word. So, instead of constructing a backoff chain of NgramTagger subclasses, the TnT tagger uses all the ngram models together to choose the best tag. It also tries to guess the tags for the whole sentence at once by choosing the most likely model for the entire sentence, based on the probabilities of each possible tag.

Note

Training is fairly quick, but tagging is significantly slower than the other taggers we've covered. This is due to all the floating point math that must be done to calculate the tag probabilities of each word.

There's more...

The TnT tagger accepts a few optional keyword arguments. You can pass in a tagger for unknown words as unk. If this tagger is already trained, then you must also pass in Trained=True. Otherwise, it will call unk.train(data) with the same data you pass into the train() method. Since none of the previous taggers have a public train() method, I recommend always passing Trained=True if you also pass an unk tagger. Here's an example using a DefaultTagger class, which does not require any training.

```
>>> from nltk.tag import DefaultTagger
>>> unk = DefaultTagger('NN')
>>> tnt_tagger = tnt.TnT(unk=unk, Trained=True)
```

>>> tnt_tagger.train(train_sents)
>>> tnt_tagger.evaluate(test_sents)
0.892467083962875

So, we got an almost 2% increase in accuracy! You must use a tagger that can tag a single word without having seen that word before. This is because the unknown tagger's tag() method is only called with a single word sentence. Other good candidates for an unknown tagger are RegexpTagger and AffixTagger. Passing in a UnigramTagger class that's been trained on the same data is pretty much useless, as it will have seen the exact same words and, therefore, have the same unknown word blind spots.

Controlling the beam search

Another parameter you can modify for TnT is N, which controls the number of possible solutions the tagger maintains while trying to guess the tags for a sentence. N defaults to 1000. Increasing it will greatly increase the amount of memory used during tagging, without necessarily increasing the accuracy. Decreasing N will decrease memory usage, but could also decrease accuracy. Here's what happens when the value is changed to N=100.

```
>>> tnt_tagger = tnt.TnT(N=100)
>>> tnt_tagger.train(train_sents)
>>> tnt_tagger.evaluate(test_sents)
0.8756313403842003
```

So, the accuracy is exactly the same, but we use significantly less memory to achieve it. However, don't assume that accuracy will not change if you decrease N; experiment with your own data to be sure.

Significance of capitalization

You can pass C=True to the TnT constructor if you want capitalization of words to be significant. The default is C=False, which means all words are lowercase. The documentation on C says that treating capitalization as significant probably will not increase accuracy. In my own testing, there was a very slight (< 0.01%) increase in accuracy with C=True, probably because case-sensitivity can help identify proper nouns.

See also

We have covered the DefaultTagger class in the *Default tagging* recipe, backoff tagging in the *Combining taggers with backoff tagging* recipe, NgramTagger subclasses in the *Training a unigram part-of-speech tagger* and *Training and combining ngram taggers* recipes, RegexpTagger in the *Tagging with regular expressions recipe*, and the AffixTagger class in the *Affix tagging recipe*.

Using WordNet for tagging

If you remember from the *Looking up Synsets for a word in WordNet* recipe in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, WordNet Synsets specify a part-of-speech tag. It's a very restricted set of possible tags, and many words have multiple Synsets with different part-of-speech tags, but this information can be useful for tagging unknown words. WordNet is essentially a giant dictionary, and it's likely to contain many words that are not in your training data.

Getting ready

First, we need to decide how to map WordNet part-of-speech tags to the Penn Treebank part-of-speech tags we've been using. The following is a table mapping one to the other. See the *Looking up Synsets for a word in WordNet* recipe in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, for more details. The s, which was not shown before, is just another kind of adjective, at least for tagging purposes.

WordNet tag	Treebank tag
n	NN
a	JJ
s	Jì
r	RB
v	VB

How to do it...

Now we can create a class that will look up words in WordNet, and then choose the most common tag from the Synsets it finds. The WordNetTagger class defined in the following code can be found in taggers.py:

```
from nltk.tag import SequentialBackoffTagger
from nltk.corpus import wordnet
from nltk.probability import FreqDist
class WordNetTagger(SequentialBackoffTagger):
    '''
    >>> wt = WordNetTagger()
    >>> wt.tag(['food', 'is', 'great'])
```

```
[('food', 'NN'), ('is', 'VB'), ('great', 'JJ')]
. . .
def init (self, *args, **kwargs):
  SequentialBackoffTagger. init (self, *args, **kwargs)
  self.wordnet tag map = {
    'n': 'NN',
    's': 'JJ',
    'a': 'JJ',
    'r': 'RB',
    'v': 'VB'
  }
def choose tag(self, tokens, index, history):
  word = tokens[index]
  fd = FreqDist()
  for synset in wordnet.synsets(word):
    fd[synset.pos()] += 1
  return self.wordnet tag map.get(fd.max())
```

Tip

Another way the FreqDist API has changed between NLTK2 and NLTK3 is that the inc() method has been removed. Instead, you must use fd[key] += 1. Since FreqDist inherits from collections.Counter, it's ok if fd[key] doesn't exist the first time you increment.

How it works...

The WordNetTagger class simply counts the number of each part-of-speech tag found in the Synsets for a word. The most common tag is then mapped to a treebank tag using internal mapping. Here's some sample usage code:

```
>>> from taggers import WordNetTagger
>>> wn_tagger = WordNetTagger()
>>> wn_tagger.evaluate(train_sents)
0.17914876598160262
```

So, it's not too accurate, but that's to be expected. We only have enough information to produce four different kinds of tags, while there are 36 possible tags in treebank. There are many words that can have different part-of-speech tags depending on their context. But if we put the WordNetTagger class at the end of an NgramTagger backoff chain, then we can improve accuracy over the DefaultTagger class.

>>> from tag_util import backoff_tagger
>>> from nltk.tag import UnigramTagger, BigramTagger, TrigramTagger

```
>>> tagger = backoff_tagger(train_sents, [UnigramTagger,
BigramTagger, TrigramTagger], backoff=wn_tagger)
>>> tagger.evaluate(test_sents)
0.8848262464925534
```

See also

The Looking up Synsets for a word in WordNet recipe in <u>Chapter 1</u>, Tokenizing Text and WordNet Basics, details how to use the wordnet corpus and what kinds of part-of-speech tags it knows about. And in the Combining taggers with backoff tagging and Training and combining ngram taggers recipes, we went over backoff tagging with ngram taggers.

Tagging proper names

Using the included names corpus, we can create a simple tagger for tagging names as proper nouns.

How to do it...

The NamesTagger class is a subclass of SequentialBackoffTagger as it's probably only useful near the end of a backoff chain. At initialization, we create a set of all names in the names corpus, lower-casing each name to make lookup easier. Then, we implement the choose_tag() method, which simply checks whether the current word is in the names_set list. If it is, we return the NNP tag (which is the tag for proper nouns). If it isn't, we return None, so the next tagger in the chain can tag the word. The following code can be found in taggers.py:

```
from nltk.tag import SequentialBackoffTagger
from nltk.corpus import names
class NamesTagger(SequentialBackoffTagger):
    def __init__(self, *args, **kwargs):
        SequentialBackoffTagger.__init__(self, *args, **kwargs)
        self.name_set = set([n.lower() for n in names.words()])
    def choose_tag(self, tokens, index, history):
        word = tokens[index]
        if word.lower() in self.name_set:
            return 'NNP'
        else:
            return None
```

How it works...

The NamesTagger class should be pretty self-explanatory. The usage is also simple.

```
>>> from taggers import NamesTagger
>>> nt = NamesTagger()
>>> nt.tag(['Jacob'])
[('Jacob', 'NNP')]
```

It's probably best to use the NamesTagger class right before a DefaultTagger class, so it's at the end of a backoff chain. But it could probably go anywhere in the chain since it's unlikely to mis-tag a word.

See also

The *Combining taggers with backoff tagging* recipe goes over the details of using the SequentialBackoffTagger subclasses.

Classifier-based tagging

The ClassifierBasedPOSTagger class uses classification to do part-of-speech tagging. Features are extracted from words, and then passed to an internal classifier. The classifier classifies the features and returns a label, in this case, a part-of-speech tag. Classification will be covered in detail in <u>Chapter</u> <u>7</u>, *Text Classification*.

The ClassifierBasedPOSTagger class is a subclass of ClassifierBasedTagger that implements a feature detector that combines many of the techniques of the previous taggers into a single feature set. The feature detector finds multiple length suffixes, does some regular expression matching, and looks at the unigram, bigram, and trigram history to produce a fairly complete set of features for each word. The feature sets it produces are used to train the internal classifier, and are used for classifying words into part-of-speech tags.

How to do it...

The basic usage of the ClassifierBasedPOSTagger class is much like any other SequentialBackoffTaggger. You pass in training sentences, it trains an internal classifier, and you get a very accurate tagger.

```
>>> from nltk.tag.sequential import ClassifierBasedPOSTagger
>>> tagger = ClassifierBasedPOSTagger(train=train_sents)
>>> tagger.evaluate(test_sents)
0.9309734513274336
```

Note

Notice a slight modification to initialization: train_sents must be passed in as the train keyword argument.

How it works...

The ClassifierBasedPOSTagger class inherits from ClassifierBasedTagger and only implements a feature_detector() method. All the training and tagging is done in ClassifierBasedTagger. It defaults to training a NaiveBayesClassifier class with the given training data. Once this classifier is trained, it is used to classify word features produced by the feature_detector() method.

Note

The ClassifierBasedTagger class is often the most accurate tagger, but it's also one of the slowest taggers. If speed is an issue, you should stick with a BrillTagger class based on a backoff chain of NgramTagger subclasses and other simple taggers.

The ClassifierBasedTagger class also inherits from FeatursetTaggerI (which is just an empty class), creating an inheritance tree that looks like this:



There's more...

You can use a different classifier instead of NaiveBayesClassifier by passing in your own classifier_builder function. For example, to use a MaxentClassifier, you'd do the following:

```
>>> from nltk.classify import MaxentClassifier
>>> me_tagger = ClassifierBasedPOSTagger(train=train_sents,
classifier_builder=MaxentClassifier.train)
>>> me_tagger.evaluate(test_sents)
0.9258363911072739
```

Note

The MaxentClassifier class takes even longer to train than NaiveBayesClassifier. If you have SciPy and NumPy installed, training will be faster than normal, but still slower than NaiveBayesClassifier.

Detecting features with a custom feature detector

If you want to do your own feature detection, there are two ways to do it:

1. Subclass ClassifierBasedTagger and implement a feature_detector() method.

2. Pass a function as the feature_detector keyword argument into ClassifierBasedTagger at initialization.

Either way, you need a feature detection method that can take the same arguments as choose_tag(): tokens, index, history. But instead of returning a tag, you return a dict of key-value features, where the key is the feature name and the value is the feature value. A very simple example would be a unigram feature detector (found in tag util.py).

```
def unigram_feature_detector(tokens, index, history):
    return {'word': tokens[index]}
```

Then, using the second method, you'd pass this into ClassifierBasedTagger as feature_detector.

```
>>> from nltk.tag.sequential import ClassifierBasedTagger
>>> from tag_util import unigram_feature_detector
>>> tagger = ClassifierBasedTagger(train=train_sents,
feature_detector=unigram_feature_detector)
>>> tagger.evaluate(test_sents)
0.8733865745737104
```

Setting a cutoff probability

Because a classifier will always return the best result it can, passing in a backoff tagger is useless unless you also pass in a cutoff_prob argument to specify the probability threshold for classification. Then, if the probability of the chosen tag is less than cutoff_prob, the backoff tagger will be used. Here's an example using the DefaultTagger class as the backoff, and setting cutoff_prob to 0.3:

```
>>> default = DefaultTagger('NN')
>>> tagger = ClassifierBasedPOSTagger(train=train_sents,
backoff=default, cutoff_prob=0.3)
>>> tagger.evaluate(test_sents)
0.9311029570472696
```

So, we get a slight increase in accuracy if the ClassifierBasedPOSTagger class uses the DefaultTagger class whenever its tag probability is less than 30%.

Using a pre-trained classifier

If you want to use a classifier that's already been trained, then you can pass that into ClassifierBasedTagger or ClassifierBasedPOSTagger as the classifier. In this case, the classifier_builder argument is ignored and no training takes place. However, you must ensure that the classifier has been trained on and can classify feature sets produced by whatever feature detector() method you use.

See also

Chapter 7, Text Classification, will cover classification in depth.

Training a tagger with NLTK-Trainer

As you can tell from all the previous recipes in this chapter, there are many different ways to train taggers, and it's impossible to know which methods and parameters will work best without doing training experiments. But training experiments can be tedious, since they often involve many small code changes (and lots of cut and paste) before you converge on an optimal tagger. In an effort to simplify the process, and make my own work easier, I created a project called NLTK-Trainer.

NLTK-Trainer is a collection of scripts that give you the ability to run training experiments without writing a single line of code. The project is available on GitHub at https://github.com/japerk/nltk-trainer and has documentation at https://github.com/japerk/nltk-trainer and has documentation at http://nltk-trainer.readthedocs.org/. This recipe will introduce the tagging related scripts, and will show you how to combine many of the previous recipes into a single training command. For download and installation instructions, please go to http://nltk-trainer.readthedocs.org/.

How to do it...

The simplest way to run train_tagger.py is with the name of an NLTK corpus. If we use the treebank corpus, the command and output should look something like this:

```
$ python train_tagger.py treebank
loading treebank
3914 tagged sents, training on 3914
training AffixTagger with affix -3 and backoff <DefaultTagger:
tag=-None->
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <AffixTagger: size=2536>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=4933>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=2325>
evaluating TrigramTagger
accuracy: 0.992372
dumping TrigramTagger to /Users/jacob/nltk_data/taggers/
treebank_aubt.pickle
```

That's all it takes to train a tagger on treebank and have it dumped to a pickle file at ~/nltk_data/taggers/treebank_aubt.pickle. "Wow, and it's over 99% accurate!" I hear you saying. But look closely at the second line of output: 3914 tagged sents, training on 3914. This means that the tagger was trained on the entire treebank corpus, and then tested against those same training sentences. This is a very misleading way to evaluate any trained model. In the previous recipes, we used the first 3000 sentences for training and the remaining 914 sentences for testing, or about a 75% split. Here's how to do that with train_tagger.py, and also skip dumping a pickle file:

```
$ python train_tagger.py treebank --fraction 0.75 --no-pickle
loading treebank
```

```
3914 tagged sents, training on 2936
training AffixTagger with affix -3 and backoff <DefaultTagger:
tag=-None->
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <AffixTagger: size=2287>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=4176>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1836>
evaluating TrigramTagger
accuracy: 0.906082
```

How it works...

The train tagger.py script roughly performers the following steps:

- 1. Construct training and testing sentences from corpus arguments.
- 2. Build tagger training function from tagger arguments.
- 3. Train a tagger on the training sentences using the training function.
- 4. Evaluate and/or save the tagger.

The first argument to the script is corpus. This could be the name of an NLTK corpus that can be found in the nltk.corpus module, such as treebank or brown. It could also be the path to a custom corpus directory. If it's a path to a custom corpus, then you'll also need to use the --reader argument to specify the corpus reader class, such as

nltk.corpus.reader.tagged.TaggedCorpusReader.

The default training algorithm is aubt, which is shorthand for a sequential backoff tagger composed of AffixTagger + UnigramTagger + BigramTagger + TrigramTagger. It's probably easiest to understand by replicating many of the previous recipes using train_tagger.py. Let's start with a default tagger.

```
$ python train_tagger.py treebank --no-pickle --default NN
--sequential ''
loading treebank
3914 tagged sents, training on 3914
evaluating DefaultTagger
accuracy: 0.130776
```

Using --default NN lets us assign a default tag of NN, while --sequential '' disables the default aubt sequential backoff algorithm. The --fraction argument is omitted in this case because there's not actually any training happening.

Now let's try a unigram tagger:

```
$ python train_tagger.py treebank --no-pickle --fraction 0.75
--sequential u
```

loading treebank
3914 tagged sents, training on 2936
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <DefaultTagger: tag=-None->
evaluating UnigramTagger
accuracy: 0.855603

Specifying --sequential u tells train_tagger.py to train with a unigram tagger. As we did earlier, we can boost the accuracy a bit by using a default tagger:

```
$ python train_tagger.py treebank --no-pickle --default NN
--fraction 0.75 --sequential u
loading treebank
3914 tagged sents, training on 2936
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <DefaultTagger: tag=NN>
evaluating UnigramTagger
accuracy: 0.873462
```

Now, let's try adding a bigram tagger and trigram tagger:

```
$ python train_tagger.py treebank --no-pickle --default NN
--fraction 0.75 --sequential ubt
loading treebank
3914 tagged sents, training on 2936
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <DefaultTagger: tag=NN>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=8709>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1836>
evaluating TrigramTagger
accuracy: 0.879012
```

Note

The PYTHONHASHSEED environment variable has been omitted for clarity. This means that when you run train_tagger.py, your output and accuracy may vary. To get consistent accuracy values, run train_tagger.py like this:

\$ PYTHONHASHSEED=0 python train_tagger.py treebank ...

The default training algorithm is -sequential aubt, and the default affix is -3. But you can modify this with one or more -a arguments. So, if we want to use an affix of -2 as well as an affix of -3, you can do the following:

```
$ python train tagger.py treebank --no-pickle --default NN
--fraction 0.75 -a -3 -a -2
loading treebank
3914 tagged sents, training on 2936
training AffixTagger with affix -3 and backoff <DefaultTagger:
tag=NN>
training AffixTagger with affix -2 and backoff <AffixTagger:
size=2143>
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <AffixTagger: size=248>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=5204>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1838>
evaluating TrigramTagger
accuracy: 0.908696
```

The order of multiple -a arguments matters, and if you switch the order, the results and accuracy will change, because the backoff order changes:

```
$ python train tagger.py treebank --no-pickle --default NN
--fraction 0.75 -a -2 -a -3
loading treebank
3914 tagged sents, training on 2936
training AffixTagger with affix -2 and backoff <DefaultTagger:
tag=NN>
training AffixTagger with affix -3 and backoff <AffixTagger:</pre>
size=606>
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <AffixTagger: size=1313>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=4169>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1829>
evaluating TrigramTagger
accuracy: 0.914367
```

You can also train a Brill tagger using the --brill argument. The template bounds the default to (1, 1) but can be customized with the --template bounds argument.

```
$ python train_tagger.py treebank --no-pickle --default NN
--fraction 0.75 --brill
loading treebank
3914 tagged sents, training on 2936
training AffixTagger with affix -3 and backoff <DefaultTagger:
tag=NN>
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
```

```
backoff <AffixTagger: size=2143>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=4179>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1824>
Training Brill tagger on 2936 sentences...
Finding initial useful rules...
Found 1304 useful rules.
Selecting rules...
evaluating BrillTagger
accuracy: 0.909138
```

Finally, you can train a classifier-based tagger with the --classifier argument, which specifies the name of a classifier. Be sure to also pass in --sequential '' because, as we learned previously, training a sequential backoff tagger in addition to a classifier-based tagger is useless. The --default argument is also useless, because the classifier will always guess something.

```
$ python train_tagger.py treebank --no-pickle --fraction 0.75
--sequential '' --classifier NaiveBayes
loading treebank
3914 tagged sents, training on 2936
training ['NaiveBayes'] ClassifierBasedPOSTagger
Constructing training corpus for classifier.
Training classifier (75814 instances)
training NaiveBayes classifier
evaluating ClassifierBasedPOSTagger
accuracy: 0.928646
```

There are a few other classifier algorithms available besides NaiveBayes, and even more if you have NumPy and SciPy installed.

Note

While classifier-based taggers tend to be more accurate, they are also slower to train, and much slower at tagging. If speed is important to you, I recommend sticking with sequential taggers.

There's more...

The train_tagger.py script supports many other arguments not shown here, all of which you can see by running the script with --help. A few additional arguments are presented next, followed by an introduction to two other tagging-related scripts available in NLTK-Trainer.

Saving a pickled tagger

Without the --no-pickle argument, train_tagger.py will save a pickled tagger at ~/nltk_data/taggers/NAME.pickle, where NAME is a combination of the corpus name and

training algorithm. You can specify a custom filename for your tagger using the --filename argument like this:

\$ python train_tagger.py treebank --filename path/to/tagger.pickle

Training on a custom corpus

If you have a custom corpus that you want to use for training a tagger, you can do that by passing in the path to the corpus and the classname of a corpus reader in the --reader argument. The corpus path can either be absolute or relative to a nltk_data directory. The corpus reader class must provide a tagged_sents() method. Here's an example using a relative path to the treebank tagged corpus:

```
$ python train_tagger.py corpora/treebank/tagged --reader
nltk.corpus.reader.ChunkedCorpusReader --no-pickle --fraction 0.75
loading corpora/treebank/tagged
51002 tagged sents, training on 38252
training AffixTagger with affix -3 and backoff <DefaultTagger:
tag=-None->
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <AffixTagger: size=2092>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=4121>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1627>
evaluating TrigramTagger
accuracy: 0.883175
```

Training with universal tags

You can train a tagger with the universal tagset using the --tagset argument as follows:

```
$ python train_tagger.py treebank --no-pickle --fraction 0.75
--tagset universal
loading treebank
using universal tagset
3914 tagged sents, training on 2936
training AffixTagger with affix -3 and backoff <DefaultTagger:
tag=-None->
training <class 'nltk.tag.sequential.UnigramTagger'> tagger with
backoff <AffixTagger: size=2287>
training <class 'nltk.tag.sequential.BigramTagger'> tagger with
backoff <UnigramTagger: size=2889>
training <class 'nltk.tag.sequential.TrigramTagger'> tagger with
backoff <BigramTagger: size=1014>
evaluating TrigramTagger
accuracy: 0.934800
```

Because the universal tagset has fewer tags, these taggers tend to be more accurate; this will only work on a corpus that has universal tagset mappings. The universal tagset was covered in the *Creating a part-of-speech tagged word corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*.

Analyzing a tagger against a tagged corpus

Every previous example in this chapter has been about training and evaluating a tagger on a single corpus. But how do you know how well that tagger will perform on a different corpus? The analyze_tagger_coverage.py script gives you a simple way to test the performance of a tagger against another tagged corpus. Here's how to test NLTK's built-in tagger against the treebank corpus:

\$ python analyze_tagger_coverage.py treebank --metrics

The output has been omitted for brevity, but I encourage you to run it yourself to see the results. It's especially useful for evaluating a tagger's performance on a corpus that it was not trained on, such as conll2000 or brown.

If you only provide a corpus argument, this script will use NLTK's built-in tagger. To evaluate your own tagger, you can use the --tagger argument, which takes a path to a pickled tagger. The path can be absolute or relative to a nltk_data directory. For example:

\$ python analyze_tagger_coverage.py treebank --metrics --tagger path/ to/tagger.pickle

You can also use a custom corpus just like we did earlier with train_tagger.py, but if your corpus is not tagged, then you must omit the --metrics argument. In that case, you will only get tag counts, with no notion of accuracy, because there are no tags to compare to.

Analyzing a tagged corpus

Finally, there is a script called analyze_tagged_corpus.py, which, as the name implies, will read in a tagged corpus and print out stats about the number of words and tags. You can run it as follows:

\$ python analyze_tagged_corpus.py treebank

The results are available in <u>Appendix A</u>, *Penn Treebank Part-of-speech Tags*. As with the other commands, you can pass in a custom corpus path and reader to analyze your own tagged corpus.

See also

The previous recipes in this chapter cover the details of the classes and methods that power the functionality of train_tagger.py. The *Training a chunker with NLTK-Trainer* recipe at the end of <u>Chapter 5</u>, *Extracting Chunks*, will introduce NLTK-Trainer's chunking-related scripts, and classification-related scripts will be covered in the *Training a classifier with NLTK-Trainer* recipe at the end of <u>Chapter 7</u>, *Text Classification*.

Chapter 5. Extracting Chunks

In this chapter, we will cover the following recipes:

- Chunking and chinking with regular expressions
- · Merging and splitting chunks with regular expressions
- · Expanding and removing chunks with regular expressions
- · Partial parsing with regular expressions
- Training a tagger-based chunker
- Classification-based chunking
- Extracting named entities
- Extracting proper noun chunks
- Extracting location chunks
- Training a named entity chunker
- Training a chunker with NLTK-Trainer

Introduction

Chunk extraction, or **partial parsing**, is the process of extracting short phrases from a part-of-speech tagged sentence. This is different from full parsing in that we're interested in standalone **chunks**, or **phrases**, instead of full parse trees (for more on parse trees, see <u>https://en.wikipedia.org/wiki/</u> <u>Parse_tree</u>). The idea is that meaningful phrases can be extracted from a sentence by looking for particular patterns of part-of-speech tags.

As in <u>Chapter 4</u>, *Part-of-speech Tagging*, we'll be using the **Penn Treebank** corpus for basic training and testing chunk extraction. We'll also be using the **CoNLL2000** corpus as it has a simpler and more flexible format that supports multiple chunk types (for more details on the conll2000 corpus and IOB tags, see the *Creating a chunked phrase corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*).

Chunking and chinking with regular expressions

Using modified regular expressions, we can define **chunk patterns**. These are patterns of part-of-speech tags that define what kinds of words make up a chunk. We can also define patterns for what kinds of words should not be in a chunk. These unchunked words are known as **chinks**.

A ChunkRule class specifies what to *include* in a chunk, while a ChinkRule class specifies what to *exclude* from a chunk. In other words, chunking creates chunks, while chinking breaks up those chunks.

Getting ready

We first need to know how to define chunk patterns. These are modified regular expressions designed to match sequences of part-of-speech tags. An individual tag is specified by surrounding angle brackets, such as $\langle NN \rangle$ to match a noun tag. Multiple tags can then be combined, as in $\langle DT \rangle \langle NN \rangle$ to match a determiner followed by a noun. Regular expression syntax can be used within the angle brackets to match individual tag patterns, so you can do $\langle NN . * \rangle$ to match all nouns including NN and NNS. You can also use regular expression syntax outside of the angle brackets to match patterns of tags. $\langle DT \rangle ? \langle NN . * \rangle +$ will match an optional determiner followed by one or more nouns. The chunk patterns are internally converted to regular expressions using the tag pattern2re pattern() function.

```
>>> from nltk.chunk.regexp import tag_pattern2re_pattern
>>> tag_pattern2re_pattern('<DT>?<NN.*>+')
'(<(DT)>)?(<(NN[^\\{\\}<>]*)>)+'
```

You don't have to use this function to do chunking, but it might be useful or interesting to see how your chunk patterns convert to regular expressions. This function is used by the RegexpParser class (explained in the next section) to convert chunk patterns into regular expressions to match chunking rules.

How to do it...

The pattern for specifying a chunk is to use surrounding curly braces, such as $\{<DT><NN>\}$. To specify a chink, you flip the braces, such as $\{<VB>\}$. These rules can be combined into a **grammar** for a particular phrase type. Here's a grammar for noun phrases that combines both a chunk and a chink pattern, along with the result of parsing the sentence the book has many chapters:

```
>>> from nltk.chunk import RegexpParser
>>> chunker = RegexpParser(r'''
... NP:
... {<DT><NN.*><.*>*<NN.*>}
... }<VB.*>{
... ''')
>>> chunker.parse([('the', 'DT'), ('book', 'NN'), ('has', 'VBZ'),
('many', 'JJ'), ('chapters', 'NNS')])
Tree('S', [Tree('NP', [('the', 'DT'), ('book', 'NN')]), ('has',
'VBZ'), Tree('NP', [('many', 'JJ'), ('chapters', 'NNS')])])
```

The grammar tells the RegexpParser class that there are two rules for parsing NP chunks. The first chunk pattern says that a chunk starts with a determiner followed by any kind of noun. Then, any number of other words are allowed until a final noun is found. The second pattern says that verbs should be chinked, thus separating any large chunks that contain a verb. The result is a tree with two noun-phrase chunks: the book and many chapters.

Note

Tagged sentences are always parsed into a Tree (found in the nltk.tree module). The top label of the Tree is S, which stands for sentence. Any chunks found will be subtrees whose labels will refer to the chunk type. In this case, the chunk type is NP for noun-phrase chunks. Trees can be drawn calling the draw() method using t.draw().

How it works...

Here's what happens, step-by-step:

1. The sentence is converted into a flat Tree:



- 2. The Tree is used to create a ChunkString.
- 3. The RegexpParser parses the grammar to create a NP RegexpChunkParser with the given rules.
- 4. A ChunkRule is created and applied to the ChunkString, which matches the entire sentence into a chunk:



5. A ChinkRule is created and applied to the same ChunkString, which splits the big chunk into two smaller chunks with a verb between them:



6. The ChunkString is converted back to a Tree, now with two NP chunk subtrees:



You can do this yourself using the classes in nltk.chunk.regexp. The ChunkRule and ChinkRule classes are both subclasses of RegexpChunkRule, and require two arguments: the pattern and a description of the rule. ChunkString is an object that starts with a flat tree, which is then modified by each rule when it is passed into the rule's apply() method. A ChunkString is converted back to a Tree with the to_chunkstruct() method. Here's some code to demonstrate this:

```
>>> from nltk.chunk.regexp import ChunkString, ChunkRule, ChinkRule
>>> from nltk.tree import Tree
>>> t = Tree('S', [('the', 'DT'), ('book', 'NN'), ('has', 'VBZ'),
'many', 'JJ'), ('chapters', 'NNS')])
>>> cs = ChunkString(t)
>>> cs
<ChunkString: '<DT><NN><VBZ><JJ><NNS>'>
>>> ur = ChunkRule('<DT><NN.*><.*>*<NN.*>', 'chunk determiners and
nouns')
>>> ur.apply(cs)
>>> cs
<ChunkString: '{<DT><NN><VBZ><JJ><NNS>}'>
>>> ir = ChinkRule('<VB.*>', 'chink verbs')
>>> ir.apply(cs)
>>> cs
<ChunkString: '{<DT><NN>}<VBZ>{<JJ><NNS>}'>
```

```
>>> cs.to_chunkstruct()
Tree('S', [Tree('CHUNK', [('the', 'DT'), ('book', 'NN')]), ('has',
'VBZ'), Tree('CHUNK', [('many', 'JJ'), ('chapters', 'NNS')])])
```

The tree diagrams shown earlier can be drawn at each step by calling cs.to_chunkstruct().draw().

There's more...

You'll notice that the subtrees from the ChunkString class are tagged as CHUNK and not NP. That's because the rules mentioned earlier are phrase agnostic; they create chunks without needing to know what kind of chunks they are.

Internally, the RegexpParser class creates a RegexpChunkParser for each chunk phrase type. So, if you're only chunking NP phrases, there will only be one RegexpChunkParser. The RegexpChunkParser class gets all the rules for the specific chunk type, and handles applying the rules in order and converting the CHUNK trees to the specific chunk type, such as NP.

Here's some code to illustrate the usage of RegexpChunkParser. We pass both the rules mentioned earlier into the RegexpChunkParser class, and then parse the same sentence tree we created before. The resulting tree is just like what we got from applying both rules in order, except that CHUNK has been replaced with NP in both the subtrees. This is because RegexpChunkParser defaults to chunk label='NP'.

```
>>> from nltk.chunk import RegexpChunkParser
>>> chunker = RegexpChunkParser([ur, ir])
>>> chunker.parse(t)
Tree('S', [Tree('NP', [('the', 'DT'), ('book', 'NN')]), ('has',
'VBZ'), Tree('NP', [('many', 'JJ'), ('chapters', 'NNS')])])
```

Parsing different chunk types

If you wanted to parse a different chunk type, then you could pass that in as chunk_label to RegexpChunkParser. Here's the same code that we saw in the previous section, but instead of NP subtrees, we'll call them CP for custom phrase:

```
>>> from nltk.chunk import RegexpChunkParser
>>> chunker = RegexpChunkParser([ur, ir], chunk_label='CP')
>>> chunker.parse(t)
Tree('S', [Tree('CP', [('the', 'DT'), ('book', 'NN')]), ('has',
'VBZ'), Tree('CP', [('many', 'JJ'), ('chapters', 'NNS')])])
```

The RegexpParser class does this internally when you specify multiple phrase types. This will be covered in the *Partial parsing with regular expressions* recipe.

Parsing alternative patterns

The same parsing results can be obtained using two chunk patterns in the grammar and discarding the chink pattern:

```
>>> chunker = RegexpParser(r'''
... NP:
... {<DT><NN.*>}
... {<JJ><NN.*>}
... ''')
>>> chunker.parse(t)
Tree('S', [Tree('NP', [('the', 'DT'), ('book', 'NN')]), ('has',
'VBZ'), Tree('NP', [('many', 'JJ'), ('chapters', 'NNS')])])
```

In fact, you could reduce the two chunk patterns into a single pattern.

```
>>> chunker = RegexpParser(r'''
... NP:
... {(<DT>|<JJ>)<NN.*>}
... ''')
>>> chunker.parse(t)
Tree('S', [Tree('NP', [('the', 'DT'), ('book', 'NN')]), ('has',
'VBZ'), Tree('NP', [('many', 'JJ'), ('chapters', 'NNS')])])
```

How you create and combine patterns is really up to you. Pattern creation is a process of trial and error, and entirely depends on what your data looks like and which patterns are easiest to express.

Chunk rule with context

You can also create chunk rules with a surrounding tag context. For example, if your pattern is <DT>{<NN>}, that will be parsed into a ChunkRuleWithContext class. So, context in this case is referring to the parts of the rule that are not chinks or chunks, such as <DT>. For example, in the phrase the dog, the would be context to the noun dog. Any time there's a tag on either side of the curly braces, you'll get a ChunkRuleWithContext class instead of a ChunkRule class. This can allow you to be more specific about when to parse particular kinds of chunks.

Here's an example of using ChunkRuleWithContext directly. It takes four arguments: the left context, the pattern to chunk, the right context, and a description:

```
>>> from nltk.chunk.regexp import ChunkRuleWithContext
>>> ctx = ChunkRuleWithContext('<DT>', '<NN.*>', '<.*>', 'chunk
nouns only after determiners')
>>> cs = ChunkString(t)
>>> cs
<ChunkString: '<DT><NN><VBZ><JJ><NNS>'>
>>> ctx.apply(cs)
>>> cs
```
```
<ChunkString: '<DT>{<NN>}<VBZ><JJ><NNS>'>
>>> cs.to_chunkstruct()
Tree('S', [('the', 'DT'), Tree('CHUNK', [('book', 'NN')]), ('has',
'VBZ'), ('many', 'JJ'), ('chapters', 'NNS')])
```

This example only chunks nouns that follow a determiner, therefore ignoring the noun that follows an adjective. Here's how it would look using the RegexpParser class:

```
>>> chunker = RegexpParser(r'''
... NP:
... <DT>{<NN.*>}
... ''')
>>> chunker.parse(t)
Tree('S', [('the', 'DT'), Tree('NP', [('book', 'NN')]), ('has',
'VBZ'), ('many', 'JJ'), ('chapters', 'NNS')])
```

See also

In the next recipe, we'll cover merging and splitting chunks.

Merging and splitting chunks with regular expressions

In this recipe, we'll cover two more rules for chunking. A MergeRule class can merge two chunks together based on the end of the first chunk and the beginning of the second chunk. A SplitRule class will split a chunk into two chunks based on the specified split pattern.

How to do it ...

A SplitRule class is specified with two opposing curly braces surrounded by a pattern on either side. To split a chunk after a noun, you would do $\langle NN. * \rangle \} \{\langle . * \rangle$. A MergeRule class is specified by flipping the curly braces, and will join chunks where the end of the first chunk matches the left pattern and the beginning of the next chunk matches the right pattern. To merge two chunks where the first ends with a noun and the second begins with a noun, you'd use $\langle NN. * \rangle \{ \} \langle NN. * \rangle$.

Note

Note that the order of rules is very important, and reordering can affect the results. The RegexpParser class applies the rules one at a time from top to bottom, so each rule will be applied to the ChunkString resulting from the previous rule.

An example of splitting and merging, starting with the sentence tree, is shown next:



The whole sentence is chunked, as shown in the following diagram:



The chunk is split into multiple chunks after every noun, as shown in the following tree:



Each chunk with a determiner is split into separate chunks, creating four chunks where there were three:



Chunks ending with a noun are merged with the next chunk if it begins with a noun, reducing the four chunks back down to three, as shown in the following diagram:



Using the RegexpParser class, the code looks like this:

```
>>> chunker = RegexpParser(r'''
... NP:
... {<DT><.*>*<NN.*>}
... <NN.*>}{<.*>
... <NN.*>}{<DT>
... <NN.*>{}<DT>
... <NN.*>{}<NN.*>
... ''')
>>> sent = [('the', 'DT'), ('sushi', 'NN'), ('roll', 'NN'), ('was',
'VBD'), ('filled', 'VBN'), ('with', 'IN'), ('the', 'DT'), ('fish',
'NN')]
```

```
>>> chunker.parse(sent)
Tree('S', [Tree('NP', [('the', 'DT'), ('sushi', 'NN'), ('roll',
'NN')]), Tree('NP', [('was', 'VBD'), ('filled', 'VBN'), ('with',
'IN')]), Tree('NP', [('the', 'DT'), ('fish', 'NN')])])
```

And the final tree of NP chunks is shown in the following diagram:



How it works...

The MergeRule and SplitRule classes take two arguments: the left pattern and the right pattern. The RegexpParser class takes care of splitting the original patterns on the curly braces to get the left and right sides, but you can also create these manually. Here's a step-by-step walkthrough of how the original sentence is modified by applying each rule:

```
>>> from nltk.chunk.regexp import MergeRule, SplitRule
>>> cs = ChunkString(Tree('S', sent))
>>> cs
<ChunkString: '<DT><NN><VBD><VBN><IN><DT><NN>'>
>>> ur = ChunkRule('<DT><.*>*<NN.*>', 'chunk determiner to noun')
>>> ur.apply(cs)
>>> cs
<ChunkString: '{<DT><NN><VBD><VBN><IN><DT><NN>}'>
>>> sr1 = SplitRule('<NN.*>', '<.*>', 'split after noun')
>>> srl.apply(cs)
>>> cs
<ChunkString: '{<DT><NN>}{<NN>}{<VBD><VBN><IN><DT><NN>}'>
>>> sr2 = SplitRule('<.*>', '<DT>', 'split before determiner')
>>> sr2.apply(cs)
>>> cs
<ChunkString: '{<DT><NN>}{<VBD><VBN><IN>}{<DT><NN>}'>
>>> mr = MergeRule('<NN.*>', '<NN.*>', 'merge nouns')
>>> mr.apply(cs)
>>> cs
<ChunkString: '{<DT><NN>} {<VBD><VBN><IN>} {<DT><NN>} '>
>>> cs.to chunkstruct()
Tree('S', [Tree('CHUNK', [('the', 'DT'), ('sushi', 'NN'), ('roll',
```

```
'NN')]), Tree('CHUNK', [('was', 'VBD'), ('filled', 'VBN'), ('with',
'IN')]), Tree('CHUNK', [('the', 'DT'), ('fish', 'NN')])])
```

There's more...

The parsing of the rules and splitting of left and right patterns is done in the static parse() method of the RegexpChunkRule superclass. This is called by the RegexpParser class to get the list of rules to pass into the RegexpChunkParser class. Here are some examples of parsing the patterns we used earlier:

```
>>> from nltk.chunk.regexp import RegexpChunkRule
>>> RegexpChunkRule.fromstring('{<DT><.*>*<NN.*>}')
<ChunkRule: '<DT><.*>*<NN.*>'>
>>> RegexpChunkRule.fromstring('<.*>}{<DT>')
<SplitRule: '<.*>', '<DT>'>
>>> RegexpChunkRule.fromstring('<NN.*>{}<NN.*>')
<MergeRule: '<NN.*>', '<NN.*>'>
```

Specifying rule descriptions

Descriptions for each rule can be specified with a comment string after the rule (a comment string must start with #). If no comment string is found, the rule's description will be empty. Here's an example:

```
>>> RegexpChunkRule.fromstring('{<DT><.*>*<NN.*>} # chunk
everything').descr()
'chunk everything'
>>> RegexpChunkRule.fromstring('{<DT><.*>*<NN.*>}').descr()
''
```

Comment string descriptions can also be used within grammar strings that are passed to RegexpParser.

See also

The previous recipe goes over how to use ChunkRule, and how rules are passed into RegexpChunkParser.

Expanding and removing chunks with regular expressions

There are three RegexpChunkRule subclasses that are not supported by RegexpChunkRule.fromstring() or RegexpParser, and therefore must be created manually if you want to use them. These rules are as follows:

- ExpandLeftRule: Add unchunked (chink) words to the left of a chunk
- ExpandRightRule: Add unchunked (chink) words to the right of a chunk
- UnChunkRule: Unchunk any matching chunk

How to do it...

ExpandLeftRule and ExpandRightRule both take two patterns along with a description as arguments. For ExpandLeftRule, the first pattern is the chink we want to add to the beginning of the chunk, while the right pattern will match the beginning of the chunk we want to expand. With ExpandRightRule, the left pattern should match the end of the chunk we want to expand, and the right pattern matches the chink we want to add to the end of the chunk. The idea is similar to the MergeRule class, but in this case, we're merging chink words instead of other chunks.

UnChunkRule is the opposite of ChunkRule. Any chunk that exactly matches the UnChunkRule pattern will be unchunked and become a chink. Here's some code demonstrating the usage with the RegexpChunkParser class:

```
>>> from nltk.chunk.regexp import ChunkRule, ExpandLeftRule,
ExpandRightRule, UnChunkRule
>>> from nltk.chunk import RegexpChunkParser
>>> ur = ChunkRule('<NN>', 'single noun')
>>> el = ExpandLeftRule('<DT>', '<NN>', 'get left determiner')
>>> er = ExpandRightRule('<NN>', '<NNS>', 'get right plural noun')
>>> un = UnChunkRule('<DT><NN.*>*', 'unchunk everything')
>>> chunker = RegexpChunkParser([ur, el, er, un])
>>> sent = [('the', 'DT'), ('sushi', 'NN'), ('rolls', 'NNS')]
>>> chunker.parse(sent)
Tree('S', [('the', 'DT'), ('sushi', 'NN'), ('rolls', 'NNS')])
```

You'll notice that the end result is a flat sentence, which is exactly what we started with. That's because the final UnChunkRule undid the chunk created by the previous rules. Read on to see what happened step by step.

How it works...

The rules mentioned earlier were applied in the following order, starting with the sentence tree as follows:



1. Make single nouns into a chunk:



2. Expand left determiners into chunks that begin with a noun:



3. Expand right plural nouns into chunks that end with a noun, chunking the whole sentence as follows:



4. Unchunk every chunk that is a *determiner* + *noun* + *plural noun*, resulting in the original sentence tree:



Here's the code showing each step:

```
>>> from nltk.chunk.regexp import ChunkString
>>> from nltk.tree import Tree
>>> cs = ChunkString(Tree('S', sent))
>>> cs
<ChunkString: '<DT><NN><NNS>'>
>>> ur.apply(cs)
>>> cs
<ChunkString: '<DT>{<NN>}<NNS>'>
>>> el.apply(cs)
>>> cs
<ChunkString: '{<DT><NN>}<NNS>'>
>>> er.apply(cs)
>>> cs
<ChunkString: '{<DT><NN><NNS>}'>
>>> un.apply(cs)
>>> cs
<ChunkString: '<DT><NN><NNS>'>
```

There's more...

In practice, you can probably get away with only using the previous four rules: ChunkRule, ChinkRule, MergeRule, and SplitRule. But if you do need very fine-grained control over chunk parsing and removing chunks, now you know how to do it with the expansion and unchunk rules.

See also

The previous two recipes covered the more common chunk rules that are supported by RegexpChunkRule.fromstring() and RegexpParser.

Partial parsing with regular expressions

So far, we've only been parsing noun phrases. But RegexpParser supports grammars with multiple phrase types, such as verb phrases and prepositional phrases. We can put the rules we've learned to use and define a grammar that can be evaluated against the conll2000 corpus, which has NP, VP, and PP phrases.

How to do it...

Now, we will define a grammar to parse three phrase types. For noun phrases, we have a ChunkRule class that looks for an optional determiner followed by one or more nouns. We then have a MergeRule class for adding an adjective to the front of a noun chunk. For prepositional phrases, we simply chunk any IN word, such as in or on. For verb phrases, we chunk an optional modal word (such as should) followed by a verb.

Note

Each grammar rule is followed by a # comment. This comment is passed into each rule as the description. Comments are optional, but they can be helpful notes for understanding what the rule does, and will be included in trace output.

```
>>> chunker = RegexpParser(r'''
... NP:
... {<DT>?<NN.*>+} # chunk optional determiner with nouns
... <JJ>{}<NN.*> # merge adjective with noun chunk
... PP:
... {<IN>} # chunk preposition
... VP:
... {<MD>?<VB.*>} # chunk optional modal with verb
... ''')
>>> from nltk.corpus import conll2000
>>> score = chunker.evaluate(conll2000.chunked_sents())
>>> score.accuracy()
0.6148573545757688
```

When we call evaluate() on the chunker argument, we give it a list of chunked sentences and get back a ChunkScore object, which can give us the accuracy of the chunker along with a number of other metrics.

How it works...

The RegexpParser class parses the grammar string into sets of rules, one set of rules for each phrase type. These rules are used to create a RegexpChunkParser class. The rules are parsed using RegexpChunkRule.fromstring(), which returns one of the five subclasses: ChunkRule, ChinkRule, MergeRule, SplitRule, or ChunkRuleWithContext.

Now that the grammar has been translated into sets of rules, these rules are used to parse a tagged sentence into a Tree structure. The RegexpParser class inherits from ChunkParserI, which provides a parse() method to parse the tagged words. Whenever a part of the tagged tokens matches a chunk rule, a subtree is constructed so that the tagged tokens become the leaves of a Tree whose label is the chunk tag. The ChunkParserI interface also provides the evaluate() method, which compares the given chunked sentences to the output of the parse() method to construct and return a ChunkScore object.

There's more...

You can also evaluate this chunker argument on the treebank_chunk corpus:

```
>>> from nltk.corpus import treebank_chunk
>>> treebank_score = chunker.evaluate(treebank_chunk.chunked_sents())
>>> treebank_score.accuracy()
0.49033970276008493
```

The treebank_chunk corpus is a special version of the treebank corpus that provides a chunked_sents() method. The regular treebank corpus cannot provide that method due to its file format.

The ChunkScore metrics

The ChunkScore metrics provide a few other metrics besides accuracy. Of the chunks the chunker argument was able to guess, **precision** tells you how many were correct and **recall** tells you how well the chunker did at finding correct chunks compared to how many total chunks there were. For more about precision and recall, see <u>https://en.wikipedia.org/wiki/Precision and recall</u>.

```
>>> score.precision()
0.60201948127375
>>> score.recall()
0.606072502505847
```

You can also get lists of chunks that were missed by the chunker, chunks that were incorrectly found, correct chunks, and the total guessed chunks. These can be useful to figure out how to improve your chunk grammar:

```
>>> len(score.missed())
47161
>>> len(score.incorrect())
47967
>>> len(score.correct())
119720
>>> len(score.guessed())
120526
```

As you can see by the number of incorrect chunks, and by comparing guessed() and correct(), our chunker guessed that there were more chunks than actually existed. And it also missed a good number of correct chunks.

Looping and tracing chunk rules

If you want to apply the chunk rules in your grammar more than once, you can pass loop=2 into RegexpParser at initialization. The default is loop=1, which will apply each rule once. Since a chunk can change after every rule application, it may sometimes make sense to re-apply the same rules multiple times.

To watch an internal trace of the chunking process, pass trace=1 into RegexpParser. To get even more output, pass in trace=2. This will give you a printout of what the chunker is doing as it is doing it. Rule comments/descriptions will be included in the trace output, giving you a good idea of which rule is applied when.

See also

If coming up with regular expression chunk patterns seems like too much work, then read the next recipes, where we'll cover how to train a chunker based on a corpus of chunked sentences.

Training a tagger-based chunker

Training a chunker can be a great alternative to manually specifying regular expression chunk patterns. Instead of a pain-staking process of trial and error to get the exact right patterns, we can use existing corpus data to train chunkers much like we did for part-of-speech tagging in the previous chapter.

How to do it...

As with the part-of-speech tagging, we'll use the treebank corpus data for training. But this time, we'll use the treebank_chunk corpus, which is specifically formatted to produce chunked sentences in the form of trees. These chunked_sents() methods will be used by a TagChunker class to train a tagger-based chunker. The TagChunker class uses a helper function, conll_tag_chunks(), to extract a list of (pos, iob) tuples from a list of Trees. These (pos, iob) tuples are then used to train a tagger in the same way (word, pos) tuples were used in <u>Chapter 4</u>, *Part-of-speech Tagging*, to train part-of-speech taggers. But instead of learning part-of-speech tags for words, we're learning IOB tags for part-of-speech tags. Here's the code from chunkers.py:

```
from nltk.chunk import ChunkParserI
from nltk.chunk.util import tree2conlltags, conlltags2tree
from nltk.tag import UnigramTagger, BigramTagger
from tag util import backoff tagger
def conll tag chunks (chunk sents):
  tagged sents = [tree2conlltags(tree) for tree in chunk sents]
  return [[(t, c) for (w, t, c) in sent] for sent in tagged sents]
class TagChunker(ChunkParserI):
  def __init__(self, train chunks, tagger classes=[UnigramTagger,
BigramTagger]):
    train sents = conll tag chunks(train chunks)
    self.tagger = backoff tagger(train sents, tagger classes)
  def parse(self, tagged sent):
    if not tagged sent: return None
    (words, tags) = zip(*tagged sent)
    chunks = self.tagger.tag(tags)
    wtc = zip(words, chunks)
    return conlltags2tree([(w,t,c) for (w,(t,c)) in wtc])
```

Once we have our trained TagChunker, we can then evaluate the ChunkScore class the same way we did for the RegexpParser class in the previous recipes:

```
>>> from chunkers import TagChunker
>>> from nltk.corpus import treebank_chunk
>>> train_chunks = treebank_chunk.chunked_sents()[:3000]
```

```
>>> test_chunks = treebank_chunk.chunked_sents()[3000:]
>>> chunker = TagChunker(train_chunks)
>>> score = chunker.evaluate(test_chunks)
>>> score.accuracy()
0.9732039335251428
>>> score.precision()
0.9166534370535006
>>> score.recall()
0.9465573770491803
```

Pretty darn accurate! Training a chunker is clearly a great alternative to manually specified grammars and regular expressions.

How it works...

Recall from the *Creating a chunked phrase corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*, that the conll2000 corpus defines chunks using IOB tags, which specify the type of chunk and where it begins and ends. We can train a part-of-speech tagger on these IOB tag patterns and then use that to power a ChunkerI subclass. But first, we need to transform a Tree that you'd get from the chunked_sents() method of a corpus into a format usable by a part-of-speech tagger. This is what conll_tag_chunks() does. It uses tree2conlltags() to convert a sentence Tree into a list of three tuples of the form (word, pos, iob), where pos is the part-of-speech tag and iob is an IOB tag, such as B-NP to mark the beginning of a noun-phrase, or I-NP to mark that the word is inside the noun-phrase. The reverse of this method is conlltags2tree(). Here's some code to demonstrate these nltk.chunk functions:

```
>>> from nltk.chunk.util import tree2conlltags, conlltags2tree
>>> from nltk.tree import Tree
>>> t = Tree('S', [Tree('NP', [('the', 'DT'), ('book', 'NN')])])
>>> tree2conlltags(t)
[('the', 'DT', 'B-NP'), ('book', 'NN', 'I-NP')]
>>> conlltags2tree([('the', 'DT', 'B-NP'), ('book', 'NN', 'I-NP')])
Tree('S', [Tree('NP', [('the', 'DT'), ('book', 'NN')])])
```

The next step is to convert these 3-tuples into 2-tuples that the tagger can recognize. Because the RegexpParser class uses part-of-speech tags for chunk patterns, we'll do that here too and use part-of-speech tags as if they were words to tag. By simply dropping the word from the 3-tuples (word, pos, iob), the conll_tag_chunks() function returns a list of 2-tuples of the form (pos, iob). When we consider the previous example Tree in a list, the results are in a format we can feed to a tagger:

```
>>> conll_tag_chunks([t])
[[('DT', 'B-NP'), ('NN', 'I-NP')]]
```

The final step is a subclass of ChunkParserI called TagChunker. It trains on a list of chunk trees using an internal tagger. This internal tagger is composed of a UnigramTagger and a

BigramTagger class in a backoff chain, using the backoff_tagger() method created in the *Training and combining ngram taggers* recipe in <u>Chapter 4</u>, *Part-of-speech Tagging*.

Finally, ChunkerI subclasses must implement a parse() method that expects a part-of-speech tagged sentence. We unzip that sentence into a list of words and part-of-speech tags. The tags are then tagged by the tagger to get IOB tags, which are then recombined with the words and part-of-speech tags to create 3-tuples we can pass to conlltags2tree() to return a final Tree.

There's more...

Since we've been talking about the conll IOB tags, let's see how the TagChunker class does on the conll2000 corpus:

```
>>> from nltk.corpus import conll2000
>>> conll_train = conll2000.chunked_sents('train.txt')
>>> conll_test = conll2000.chunked_sents('test.txt')
>>> chunker = TagChunker(conll_train)
>>> score = chunker.evaluate(conll_test)
>>> score.accuracy()
0.8950545623403762
>>> score.precision()
0.8114841974355675
>>> score.recall()
0.8644191676944863
```

Not quite as good as on treebank_chunk, but conll2000 is a much larger corpus, so it's not too surprising.

Using different taggers

If you want to use different tagger classes with the TagChunker class, you can pass them in as tagger classes. For example, here's the TagChunker class using just a UnigramTagger class:

```
>>> from nltk.tag import UnigramTagger
>>> uni_chunker = TagChunker(train_chunks,
tagger_classes=[UnigramTagger])
>>> score = uni_chunker.evaluate(test_chunks)
>>> score.accuracy()
0.9674925924335466
```

The tagger_classes argument will be passed directly into the backoff_tagger() function, which means they must be subclasses of SequentialBackoffTagger. In testing, the default of tagger_classes=[UnigramTagger, BigramTagger] generally produces the best results, but it can vary depending on the corpus.

See also

The *Training and combing ngram taggers* recipe in <u>Chapter 4</u>, *Part-of-speech Tagging*, covers backoff tagging with a UnigramTagger and BigramTagger class. The ChunkScore metrics returned by the evaluate() method of a chunker are explained in the previous recipe.

Classification-based chunking

Unlike most part-of-speech taggers, the ClassifierBasedTagger class learns from features. That means we can create a ClassifierChunker class that can learn from both the words and part-of-speech tags, instead of only the part-of-speech tags as the TagChunker class does.

How to do it...

For the ClassifierChunker class, we don't want to discard the words from the training sentences as we did in the previous recipe. Instead, to remain compatible with the 2-tuple (word, pos) format required for training a ClassiferBasedTagger class, we convert the (word, pos, iob) 3-tuples from tree2conlltags() into ((word, pos), iob) 2-tuples using the chunk_trees2train_chunks() function. This code can be found in chunkers.py:

```
from nltk.chunk import ChunkParserI
from nltk.chunk.util import tree2conlltags, conlltags2tree
from nltk.tag import ClassifierBasedTagger
def chunk trees2train chunks(chunk sents):
```

```
tag_sents = [tree2conlltags(sent) for sent in chunk_sents]
return [[((w,t),c) for (w,t,c) in sent] for sent in tag_sents]
```

Next, we need a feature detector function to pass into ClassifierBasedTagger. Our default feature detector function, prev_next_pos_iob(), knows that the list of tokens is really a list of (word, pos) tuples, and can use that to return a feature set suitable for a classifier. In fact, any feature detector function used with the ClassifierChunker class (defined next) should recognize that tokens are a list of (word, pos) tuples, and have the same function signature as prev_next_pos_iob(). To give the classifier as much information as we can, this feature set contains the current, previous, and next word and part-of-speech tag, along with the previous IOB tag:

```
def prev_next_pos_iob(tokens, index, history):
  word, pos = tokens[index]

  if index == 0:
    prevword, prevpos, previob = ('<START>',)*3
  else:
    prevword, prevpos = tokens[index-1]
    previob = history[index-1]

  if index == len(tokens) - 1:
    nextword, nextpos = ('<END>',)*2
  else:
    nextword, nextpos = tokens[index+1]

  feats = {
```

```
'word': word,
'pos': pos,
'nextword': nextword,
'nextpos': nextpos,
'prevword': prevword,
'prevpos': prevword,
'previob': previob
}
return feats
```

Now, we can define the ClassifierChunker class, which uses an internal

ClassifierBasedTagger with features extracted using prev_next_pos_iob() and training sentences from chunk_trees2train_chunks(). As a subclass of ChunkerParserI, it implements the parse() method, which converts the ((w, t), c) tuples produced by the internal tagger into Trees using conlltags2tree():

```
class ClassifierChunker(ChunkParserI):
    def __init__(self, train_sents,
    feature_detector=prev_next_pos_iob, **kwargs):
        if not feature_detector:
            feature_detector = self.feature_detector
        train_chunks = chunk_trees2train_chunks(train_sents)
        self.tagger = ClassifierBasedTagger(train=train_chunks,
        feature_detector=feature_detector, **kwargs)
    def parse(self, tagged_sent):
        if not tagged_sent: return None
        chunks = self.tagger.tag(tagged_sent)
        return conlltags2tree([(w,t,c) for ((w,t),c) in chunks])
```

Using the same train_chunks and test_chunks from the treebank_chunk corpus in the previous recipe, we can evaluate this code from chunkers.py:

```
>>> from chunkers import ClassifierChunker
>>> chunker = ClassifierChunker(train_chunks)
>>> score = chunker.evaluate(test_chunks)
>>> score.accuracy()
0.9721733155838022
>>> score.precision()
0.9258838793383068
>>> score.recall()
0.9359016393442623
```

Compared to the TagChunker class, all the scores have gone up a bit. Let's see how it does on conll2000:

```
>>> chunker = ClassifierChunker(conll_train)
>>> score = chunker.evaluate(conll_test)
>>> score.accuracy()
0.9264622074002153
>>> score.precision()
0.8737924310910219
>>> score.recall()
0.9007354620620346
```

This is much improved over the TagChunker class.

How it works...

Like the TagChunker class in the previous recipe, we are training a part-of-speech tagger for IOB tagging. But in this case, we want to include the word as a feature to power a classifier. By creating nested 2-tuples of the form ((word, pos), iob), we can pass the word through the tagger into our feature detector function. The chunk_trees2train_chunks() method produces these nested 2-tuples, and prev_next_pos_iob() is aware of them and uses each element as a feature. The following features are extracted:

- The current word and part-of-speech tag
- The previous word, part-of-speech tag, and IOB tag
- The next word and part-of-speech tag

The arguments to prev_next_pos_iob() look the same as the feature_detector() method of the ClassifierBasedTagger class: tokens, index, and history. But this time, tokens will be a list of (word, pos) two tuples, and history will be a list of IOB tags. The special feature values <START> and <END> are used if there are no previous or next tokens.

The ClassifierChunker class uses an internal ClassifierBasedTagger and prev_next_pos_iob() as its default feature_detector. The results from the tagger, which are in the same nested 2-tuple form, are then reformated into 3-tuples to return a final Tree using conlltags2tree().

There's more...

You can use your own feature detector function by passing it into the ClassifierChunker class as feature_detector. The tokens argument will contain a list of (word, tag) tuples, and history will be a list of the previous IOB tags found.

Using a different classifier builder

The ClassifierBasedTagger class defaults to using NaiveBayesClassifier.train as its classifier_builder. But you can use any classifier you want by overriding the classifier_builder keyword argument. Here's an example using MaxentClassifier.train:

```
>>> from nltk.classify import MaxentClassifier
>>> builder = lambda toks: MaxentClassifier.train(toks, trace=0,
max_iter=10, min_lldelta=0.01)
>>> me_chunker = ClassifierChunker(train_chunks,
classifier_builder=builder)
>>> score = me_chunker.evaluate(test_chunks)
>>> score.accuracy()
0.9743204362949285
>>> score.precision()
0.9334423548650859
>>> score.recall()
0.9357377049180328
```

Instead of using MaxentClassifier.train directly, I wrapped it in a lambda argument so that its output is quite similar to (trace=0) and it finishes in a reasonable amount of time. As you can see, the scores are slightly different compared to using the NaiveBayesClassifier class.

Note

The MaxentClassifier score values mentioned earlier were computed with the environment variable PYTHONHASHSEED=0. If you use a different value, or do not set this environment variable, your score values may differ.

See also

The previous recipe, *Training a tagger-based chunker*, introduced the idea of using a part-of-speech tagger for training a chunker. The *Classifier-based tagging* recipe in <u>Chapter 4</u>, *Part-of-speech Tagging*, describes ClassifierBasedPOSTagger, which is a subclass of ClassifierBasedTagger. And in <u>Chapter 7</u>, *Text Classification*, we'll cover classification in detail.

Extracting named entities

Named entity recognition is a specific kind of chunk extraction that uses entity tags instead of, or in addition to, chunk tags. Common entity tags include PERSON, ORGANIZATION, and LOCATION. Part-of-speech tagged sentences are parsed into chunk trees as with normal chunking, but the labels of the trees can be entity tags instead of chunk phrase tags.

How to do it...

NLTK comes with a pre-trained named entity chunker. This chunker has been trained on data from the ACE program, **National Institute of Standards and Technology** (**NIST**) sponsored program for **Automatic Content Extraction**, which you can read more about at http://www.itl.nist.gov/iad/894.01/tests/ace/. Unfortunately, this data is not included in the NLTK corpora, but the trained chunker is. This chunker can be used through the ne_chunk() method in the nltk.chunk module. The ne_chunk() method will chunk a single sentence into a Tree. The following is an example using ne_chunk() on the first tagged sentence of the treebank_chunk corpus:

```
>>> from nltk.chunk import ne_chunk
>>> ne_chunk(treebank_chunk.tagged_sents()[0])
Tree('S', [Tree('PERSON', [('Pierre', 'NNP')]), Tree('ORGANIZATION',
[('Vinken', 'NNP')]), (',', ','), ('61', 'CD'), ('years', 'NNS'),
('old', 'JJ'), (',', ','), ('will', 'MD'), ('join', 'VB'), ('the',
'DT'), ('board', 'NN'), ('as', 'IN'), ('a', 'DT'), ('nonexecutive',
'JJ'), ('director', 'NN'), ('Nov.', 'NNP'), ('29', 'CD'), ('.',
'.')])
```

You can see that two entity tags are found: PERSON and ORGANIZATION. Each of these subtrees contains a list of the words that are recognized as a PERSON or ORGANIZATION. To extract these named entities, we can write a simple helper method that will get the leaves of all the subtrees we are interested in:

```
def sub_leaves(tree, label):
    return [t.leaves() for t in tree.subtrees(lambda s: label() ==
label)]
```

Then, we can call this method to get all the PERSON or ORGANIZATION leaves from a tree:

```
>>> tree = ne_chunk(treebank_chunk.tagged_sents()[0])
>>> from chunkers import sub_leaves
>>> sub_leaves(tree, 'PERSON')
[[('Pierre', 'NNP')]]
>>> sub_leaves(tree, 'ORGANIZATION')
[[('Vinken', 'NNP')]]
```

You will notice that the chunker has mistakenly separated Vinken into its own ORGANIZATION Tree instead of including it with the PERSON Tree containing Pierre. Such is the case with statistical natural language processing—you can't always expect perfection.

How it works...

The pre-trained named entity chunker is much like any other chunker, and in fact uses a MaxentClassifier powered ClassifierBasedTagger to determine IOB tags. But instead of B-NP and I-NP IOB tags, it uses B-PERSON, I-PERSON, B-ORGANIZATION, I-ORGANIZATION, and more. It also uses the O tag to mark words that are not part of a named entity (and thus are *outside* the named entity subtrees).

There's more...

To process multiple sentences at a time, you can use <code>chunk_ne_sents()</code>. Here's an example where we process the first 10 sentences from treebank_chunk.tagged_sents() and get ORGANIZATION sub_leaves():

```
>>> from nltk.chunk import chunk_ne_sents
>>> trees = chunk_ne_sents(treebank_chunk.tagged_sents()[:10])
>>> [sub_leaves(t, 'ORGANIZATION') for t in trees]
[[[('Vinken', 'NNP')]], [[('Elsevier', 'NNP')]], [[('Consolidated',
'NNP'), ('Gold', 'NNP'), ('Fields', 'NNP')]], [], [], [[('Inc.',
'NNP')], [('Micronite', 'NN')]], [[('New', 'NNP'), ('England',
'NNP'), ('Journal', 'NNP')]], [[('Lorillard', 'NNP')]], [], []]
```

You can see that there are a couple of multiword ORGANIZATION chunks, such as New England Journal. There were also a few sentences that had no ORGANIZATION chunks, as indicated by the empty lists [].

Binary named entity extraction

If you don't care about the particular kind of named entity to extract, you can pass binary=True into ne_chunk() or chunk_ne_sents(). Now, all named entities will be tagged with NE:

```
>>> ne_chunk(treebank_chunk.tagged_sents()[0], binary=True)
Tree('S', [Tree('NE', [('Pierre', 'NNP'), ('Vinken', 'NNP')]), (',',
','), ('61', 'CD'), ('years', 'NNS'), ('old', 'JJ'), (',', ','),
('will', 'MD'), ('join', 'VB'), ('the', 'DT'), ('board', 'NN'),
('as', 'IN'), ('a', 'DT'), ('nonexecutive', 'JJ'), ('director',
'NN'), ('Nov.', 'NNP'), ('29', 'CD'), ('.', '.')])
```

So, binary in this case means that an arbitrary chunk either is or is not a named entity. If we get the sub_leaves(), we can see that Pierre Vinken is correctly combined into a single named entity:

```
>>> subleaves(ne_chunk(treebank_chunk.tagged_sents()[0],
binary=True), 'NE')
[[('Pierre', 'NNP'), ('Vinken', 'NNP')]]
```

See also

In the next recipe, we'll create our own simple named entity chunker.

Extracting proper noun chunks

A simple way to do named entity extraction is to chunk all proper nouns (tagged with NNP). We can tag these chunks as NAME, since the definition of a proper noun is the name of a person, place, or thing.

How to do it...

Using the RegexpParser class, we can create a very simple grammar that combines all proper nouns into a NAME chunk. Then, we can test this on the first tagged sentence of treebank_chunk to compare the results with the previous recipe:

```
>>> chunker = RegexpParser(r'''
... NAME:
... {<NNP>+}
... ''')
>>> sub_leaves(chunker.parse(treebank_chunk.tagged_sents()[0]),
'NAME')
[[('Pierre', 'NNP'), ('Vinken', 'NNP')], [('Nov.', 'NNP')]]
```

Although we get Nov. as a NAME chunk, this isn't a wrong result, as Nov. is the name of a month.

How it works...

The NAME chunker is a simple usage of the RegexpParser class, covered in the *Chunking and chinking with regular expressions*, *Merging and splitting chunks with regular expressions*, and *Partial parsing with regular expressions* recipes. All sequences of NNP tagged words are combined into NAME chunks.

There's more...

If we wanted to be sure to only chunk the names of people, then we can build a PersonChunker class that uses the names corpus for chunking. This class can be found in chunkers.py:

```
from nltk.chunk import ChunkParserI
from nltk.chunk.util import conlltags2tree
from nltk.corpus import names
class PersonChunker(ChunkParserI):
   def __init__(self):
      self.name_set = set(names.words())

   def parse(self, tagged_sent):
      iobs = []
      in_person = False
      for word, tag in tagged sent:
```

```
if word in self.name_set and in_person:
    iobs.append((word, tag, 'I-PERSON'))
    elif word in self.name_set:
        iobs.append((word, tag, 'B-PERSON'))
        in_person = True
    else:
        iobs.append((word, tag, 'O'))
        in_person = False
    return conlltags2tree(iobs)
```

The PersonChunker class iterates over the tagged sentence, checking whether each word is in its names_set (constructed from the names corpus). If the current word is in the names_set, then it uses either the B-PERSON or I-PERSON IOB tags, depending on whether the previous word was also in the names_set. Any word that's not in the names_set argument gets the O IOB tag. When complete, the list of IOB tags is converted to a Tree using conlltags2tree(). Using it on the same tagged sentence as before, we get the following result:

```
>>> from chunkers import PersonChunker
>>> chunker = PersonChunker()
>>> sub_leaves(chunker.parse(treebank_chunk.tagged_sents()[0]),
'PERSON')
[[('Pierre', 'NNP')]]
```

We no longer get Nov., but we've also lost Vinken, as it is not found in the names corpus. This recipe highlights some of the difficulties of chunk extraction and natural language processing in general:

- If you use general patterns, you'll get general results
- If you're looking for specific results, you must use specific data
- If your specific data is incomplete, your results will be incomplete too

See also

The previous recipe defines the sub_leaves() function used to show the found chunks. In the next recipe, we'll cover how to find LOCATION chunks based on the gazetteers corpus.

Extracting location chunks

To identify LOCATION chunks, we can make a different kind of ChunkParserI subclass that uses the gazetteers corpus to identify location words. The gazetteers corpus is a WordListCorpusReader class that contains the following location words:

- Country names
- U.S. states and abbreviations
- Major U.S. cities
- Canadian provinces
- Mexican states

How to do it...

The LocationChunker class, found in chunkers.py, iterates over a tagged sentence looking for words that are found in the gazetteers corpus. When it finds one or more location words, it creates a LOCATION chunk using IOB tags. The helper method iob_locations() is where the IOB LOCATION tags are produced, and the parse() method converts these IOB tags into a Tree:

```
from nltk.chunk import ChunkParserI
from nltk.chunk.util import conlltags2tree
from nltk.corpus import gazetteers
class LocationChunker(ChunkParserI):
  def init (self):
    self.locations = set(gazetteers.words())
    self.lookahead = 0
    for loc in self.locations:
      nwords = loc.count(' ')
      if nwords > self.lookahead:
        self.lookahead = nwords
  def iob locations(self, tagged sent):
    i = 0
    l = len(tagged sent)
    inside = False
    while i < l:
      word, tag = tagged sent[i]
      j = i + 1
      k = j + self.lookahead
      nextwords, nexttags = [], []
      loc = False
      while j < k:
```

```
if ' '.join([word] + nextwords) in self.locations:
        if inside:
          yield word, tag, 'I-LOCATION'
        else:
          yield word, tag, 'B-LOCATION'
        for nword, ntag in zip(nextwords, nexttags):
          yield nword, ntag, 'I-LOCATION'
        loc, inside = True, True
        i = j
        break
      if j < l:
        nextword, nexttag = tagged sent[j]
        nextwords.append(nextword)
        nexttags.append(nexttag)
        j += 1
      else:
        break
    if not loc:
      inside = False
      i += 1
      yield word, tag, '0'
def parse(self, tagged sent):
  iobs = self.iob locations(tagged sent)
  return conlltags2tree(iobs)
```

We can use the LocationChunker class to parse the following sentence into two locations—San Francisco CA is cold compared to San Jose CA:

```
>>> from chunkers import LocationChunker
>>> t = loc.parse([('San', 'NNP'), ('Francisco', 'NNP'), ('CA',
'NNP'), ('is', 'BE'), ('cold', 'JJ'), ('compared', 'VBD'), ('to',
'TO'), ('San', 'NNP'), ('Jose', 'NNP'), ('CA', 'NNP')])
>>> sub_leaves(t, 'LOCATION')
[[('San', 'NNP'), ('Francisco', 'NNP'), ('CA', 'NNP')], [('San',
'NNP'), ('Jose', 'NNP'), ('CA', 'NNP')]]
```

And the result is that we get two LOCATION chunks, just as expected.

How it works...

The LocationChunker class starts by constructing a set of all locations in the gazetteers corpus. Then, it finds the maximum number of words in a single location string so it knows how many words it must look ahead when parsing a tagged sentence.

The parse() method calls a helper method, iob_locations(), which generates 3-tuples of the form (word, pos, iob), where iob is either 0 if the word is not a location, or B-LOCATION or I-LOCATION for LOCATION chunks. The iob_locations() method finds location chunks by looking at the current word and the next words to check if the combined word is in the locations set. Multiple location words that are next to each other are then put into the same LOCATION chunk, such as in the previous example with San Francisco and CA.

Like in the previous recipe, it's simpler and more convenient to construct a list of (word, pos, iob) tuples to pass into conlltags2tree() to return a Tree. The alternative is to construct a Tree manually, but that requires keeping track of children, subtrees, and where you currently are in the Tree.

There's more...

One of the nice aspects of this LocationChunker class is that it doesn't care about the part-of-speech tags. As long as the location words are found in the location's set, any part-of-speech tag will do.

See also

In the next recipe, we'll cover how to train a named entity chunker using the ieer corpus.

Training a named entity chunker

You can train your own named entity chunker using the *ieer* corpus, which stands for **Information Extraction: Entity Recognition**. It takes a bit of extra work, though, because the *ieer* corpus has chunk trees but no part-of-speech tags for words.

How to do it...

Using the ieertree2conlltags() and ieer_chunked_sents() functions in chunkers.py, we can create named entity chunk trees from the ieer corpus to train the ClassifierChunker class created in the *Classification-based chunking* recipe:

```
import nltk.tag
from nltk.chunk.util import conlltags2tree
from nltk.corpus import ieer
def ieertree2conlltags(tree, tag=nltk.tag.pos tag):
  words, ents = zip(*tree.pos())
  iobs = []
  prev = None
  for ent in ents:
    if ent == tree.label():
      iobs.append('0')
      prev = None
    elif prev == ent:
      iobs.append('I-%s' % ent)
    else:
      iobs.append('B-%s' % ent)
      prev = ent
  words, tags = zip(*tag(words))
  return zip(words, tags, iobs)
def ieer chunked sents(tag=nltk.tag.pos tag):
  for doc in ieer.parsed docs():
    tagged = ieertree2conlltags(doc.text, tag)
    yield conlltags2tree(tagged)
```

We'll use 80 out of 94 sentences for training, and the rest for testing. Then, we can see how it does on the first sentence of the treebank_chunk corpus:

```
>>> from chunkers import ieer_chunked_sents, ClassifierChunker
>>> from nltk.corpus import treebank_chunk
>>> ieer_chunks = list(ieer_chunked_sents())
>>> len(ieer_chunks)
```

```
94
>>> chunker = ClassifierChunker(ieer_chunks[:80])
>>> chunker.parse(treebank_chunk.tagged_sents()[0])
Tree('S', [Tree('LOCATION', [('Pierre', 'NNP'), ('Vinken', 'NNP')]),
(',', ','), Tree('DURATION', [('61', 'CD'), ('years', 'NNS')]),
Tree('MEASURE', [('old', 'JJ')]), (',', ','), ('will', 'MD'),
('join', 'VB'), ('the', 'DT'), ('board', 'NN'), ('as', 'IN'), ('a',
'DT'), ('nonexecutive', 'JJ'), ('director', 'NN'), Tree('DATE',
[('Nov.', 'NNP'), ('29', 'CD')]), ('.', '.')])
```

So, it found a correct DURATION and DATE, but tagged Pierre Vinken as a LOCATION. Let's see how it scores against the rest of the ieer chunk trees:

```
>>> score = chunker.evaluate(ieer_chunks[80:])
>>> score.accuracy()
0.8829018388070625
>>> score.precision()
0.4088717454194793
>>> score.recall()
0.5053635280095352
```

Accuracy is pretty good, but precision and recall are very low. That means lots of false negatives and false positives.

How it works...

The truth is, we're not working with ideal training data. The ieer trees generated by ieer_chunked_sents() are not entirely accurate. First, there are no explicit sentence breaks, so each document is a single tree. Second, the words are not explicitly tagged, so we have to guess using nltk.tag.pos_tag().

The ieer corpus provides a parsed_docs() method that returns a list of documents with a text attribute. This text attribute is a document Tree that is converted to a list of 3-tuples of the form (word, pos, iob). To get these final 3-tuples, we must first flatten the Tree using tree.pos(), which returns a list of 2-tuples of the form (word, entity), where entity is either the entity tag or the top tag of the tree. Any words whose entity is the top tag are outside the named entity chunks and get the IOB tag 0. All words that have unique entity tags are either the beginning of or inside a named entity chunk. Once we have all the IOB tags, then we can get the part-of-speech tags of all the words and join the words, part-of-speech tags, and IOB tags into 3-tuples using zip().

There's more...

Despite the non-ideal training data, the ieer corpus provides a good place to start for training a named entity chunker. The data comes from *New York Times* and *AP Newswire* reports. Each doc from ieer.parsed_docs() also contains a headline attribute that is a Tree:

```
>>> from nltk.corpus import ieer
>>> ieer.parsed_docs()[0].headline
Tree('DOCUMENT', ['Kenyans', 'protest', 'tax', 'hikes'])
```

See also

The *Extracting named entities* recipe covers the pre-trained named entity chunker that comes included with NLTK.

Training a chunker with NLTK-Trainer

At the end of the previous chapter, <u>Chapter 4</u>, *Part-of-speech Tagging*, we introduced NLTK-Trainer and the train_tagger.py script. In this recipe, we will cover the script for training chunkers: train chunker.py.

Note

You can find NLTK-Trainer at <u>https://github.com/japerk/nltk-trainer</u> and the online documentation at <u>http://nltk-trainer.readthedocs.org/</u>.

How to do it...

As with train_tagger.py, the only required argument to train_chunker.py is the name of a corpus. In this case, we need a corpus that provides a chunked_sents() method, such as treebank_chunk. Here's an example of running train_chunker.py on treebank_chunk:

```
$ python train chunker.py treebank chunk
loading treebank chunk
4009 chunks, training on 4009
training ub TagChunker
evaluating TagChunker
ChunkParse score:
                   97.0%
   IOB Accuracy:
   Precision:
                   90.8%
   Recall:
                   93.9%
   F-Measure:
                    92.3%
dumping TagChunker to /Users/jacob/nltk data/chunkers/
treebank chunk ub.pickle
```

Just like with train_tagger.py, we can use the --no-pickle argument to skip saving a pickled chunker, and the --fraction argument to limit the training set and evaluate the chunker against a test set:

```
$ python train_chunker.py treebank_chunk --no-pickle --fraction 0.75
loading treebank_chunk
4009 chunks, training on 3007
training ub TagChunker
evaluating TagChunker
ChunkParse score:
    IOB Accuracy: 97.3%
    Precision: 91.6%
    Recall: 94.6%
    F-Measure: 93.1%
```

The score output you see is what you get when you print a ChunkScore object. This ChunkScore is the result of calling the chunker's evaluate() method, and has been explained in more detail earlier in this chapter in the *Partial parsing with regular expressions* recipe. Surprisingly, the chunker's scores actually increase slightly when using a smaller training set. This may indicate that the chunker training algorithm is susceptible to over-fitting, meaning that too many training examples can cause the chunker to over-value incorrect or noisy data.

Note

The PYTHONHASHSEED environment variable has been omitted for clarity. This means that when you run train_chunker.py, your score values may vary. To get consistent score values, run train_chunker.py like this:

\$ PYTHONHASHSEED=0 python train_chunker.py treebank_chunk ...

How it works...

The default training algorithm for train_chunker.py is to use a tagger-based chunker composed of a BigramTagger and UnigramTagger class. This is what is meant by the output line training ub TagChunker. The details for how to train a tag chunker have been covered earlier in this chapter in the *Training a tagger-based chunker* recipe. You can modify this algorithm using the -- sequential argument. Here's how to train a UnigramTagger based chunker:

```
$ python train_chunker.py treebank_chunk --no-pickle --fraction 0.75
--sequential u
loading treebank_chunk
4009 chunks, training on 3007
training u TagChunker
evaluating TagChunker
ChunkParse score:
    IOB Accuracy: 96.7%
    Precision: 89.7%
    Recall: 93.1%
    F-Measure: 91.3%
```

And here's how to twith additional BigramTagger and TrigramTagger classes:

```
$ python train_chunker.py treebank_chunk --no-pickle --fraction 0.75
--sequential ubt
loading treebank_chunk
4009 chunks, training on 3007
training ubt TagChunker
evaluating TagChunker
ChunkParse score:
    IOB Accuracy: 97.2%
    Precision: 91.6%
```

Recall: 94.4% F-Measure: 93.0%

You can also train a classifier-based chunker, which was covered in the previous recipe, *Classification-based chunking*.

```
$ python train_chunker.py treebank_chunk --no-pickle --fraction 0.75
--sequential '' --classifier NaiveBayes
loading treebank_chunk
4009 chunks, training on 3007
training ClassifierChunker with ['NaiveBayes'] classifier
Constructing training corpus for classifier.
Training classifier (71088 instances)
training NaiveBayes classifier
evaluating ClassifierChunker
ChunkParse score:
    IOB Accuracy: 97.2%
    Precision: 92.6%
    Recall: 93.6%
```

There's more...

The train_chunker.py script supports many other arguments not shown here, all of which you can see by running the script with --help. A few additional arguments are presented next, followed by an introduction to two other chunking-related scripts available in nltk-trainer.

Saving a pickled chunker

F-Measure: 93.1%

Without the --no-pickle argument, train_chunker.py will save a pickled chunker at ~/nltk_data/chunkers/NAME.pickle, where NAME is a combination of the corpus name and training algorithm. You can specify a custom filename for your chunker using the --filename argument like this:

\$ python train_chunker.py treebank_chunker --filename path/to/ tagger.pickle

Training a named entity chunker

We can use train_chunker.py to replicate the chunker we trained on the ieer corpus in the *Training a named entity chunker* recipe. This is possible because the special handling required for training on ieer is built-in to NLTK-Trainer.

```
$ python train_chunker.py ieer --no-pickle --fraction 0.85
--sequential '' --classifier NaiveBayes
loading ieer
converting ieer parsed docs to chunked sentences
94 chunks, training on 80
```

training ClassifierChunker with ['NaiveBayes'] classifier Constructing training corpus for classifier. Training classifier (47000 instances) training NaiveBayes classifier evaluating ClassifierChunker ChunkParse score: IOB Accuracy: 88.3% Precision: 40.9% Recall: 50.5% F-Measure: 45.2%

Training on a custom corpus

If you have a custom corpus that you want to use for training a chunker, you can do that by passing in the path to the corpus and the classname of a corpus reader in the --reader argument. The corpus path can either be absolute or relative to a nltk_data directory. The corpus reader class must provide a chunked_sents() method. Here's an example using a relative path to the treebank chunked corpus:

```
$ python train_chunker.py corpora/treebank/tagged --reader
nltk.corpus.reader.ChunkedCorpusReader --no-pickle --fraction 0.75
loading corpora/treebank/tagged
51002 chunks, training on 38252
training ub TagChunker
evaluating TagChunker
ChunkParse score:
    IOB Accuracy: 98.4%
    Precision: 97.7%
    Recall: 98.9%
    F-Measure: 98.3%
```

Training on parse trees

The train_chunker.py script supports two arguments that allow it to train on full parse trees from a corpus reader's parsed_sents() method instead of using chunked sentences. A parse tree differs from a chunk tree in that it can be much deeper, with subphrases and even subphrases of those subphrases. But the chunking algorithms we've covered so far cannot learn from deep parse trees, so we need to flatten them somehow. The first argument is --flatten-deep-tree, which trains chunks from the leaf labels of a parse tree.

```
$ python train_chunker.py treebank --no-pickle --fraction 0.75
--flatten-deep-tree
loading treebank
flattening deep trees from treebank
3914 chunks, training on 2936
training ub TagChunker
evaluating TagChunker
ChunkParse score:
```

IOB Accuracy:	72. 4 %
Precision:	51.6%
Recall:	52.2%
F-Measure:	51.9%

We use the treebank corpus instead of treebank_chunk, because it has full parse trees accessible with the parsed_sents() method. The other parse tree argument is --shallow-tree, which trains chunks from the top-level labels of a parse tree.

```
$ python train_chunker.py treebank --no-pickle --fraction 0.75
--shallow-tree
loading treebank
creating shallow trees from treebank
3914 chunks, training on 2936
training ub TagChunker
evaluating TagChunker
ChunkParse score:
    IOB Accuracy: 73.1%
    Precision: 60.0%
    Recall: 56.2%
    F-Measure: 58.0%
```

These options are more useful for corpora that don't provide chunked sentences, such as cess_cat and cess_esp.

Analyzing a chunker against a chunked corpus

So how do you know how well a chunker will perform on a different corpus that you didn't train it on? The analyze_chunker_coverage.py script gives you a simple way to test the performance of a chunker against another chunked corpus. Here's how to test NLTK's built-in chunker against the treebank_chunk corpus:

```
$ python analyze_chunker_coverage.py treebank_chunk --score
loading tagger taggers/maxent_treebank_pos_tagger/english.pickle
loading chunker chunkers/maxent_ne_chunker/
english_ace_multiclass.pickle
evaluating chunker score
ChunkParse score:
    IOB Accuracy: 45.4%
    Precision: 0.0%
    Recall: 0.0%
    F-Measure: 0.0%
```

analyzing chunker coverage of treebank_chunk with NEChunkParser

IOB	Found
	========
FACILITY	56
GPE	1874
GSP	38
LOCATION	34
ORGANIZATION	1572
PERSON	2108

As you can see, NLTK's default chunker does not do well against the treebank_chunk corpus. This is because the default chunker is looking for named entities, not NP phrases. This is shown by the coverage analysis of IOB tags that were found. These results do not necessarily mean that the default chunker is bad, just that it was not trained for finding noun phrases, and thus cannot be accurately evaluated against the treebank_chunk corpus.

While the analyze_chunker_coverage.py script defaults to using NLTK's built-in tagger and chunker, you can evaluate on your own tagger and/or chunker using the --tagger and/or -- chunker arguments, both of which accept a path to a pickled tagger or chunker. Consider the following code:

\$ python train_chunker.py treebank_chunker --tagger path/to/ tagger.pickle --chunker path/to/chunker.pickle

You can also use a custom corpus just like we did earlier with train_chunker.py; however, if your corpus is not chunked, then you must omit the --score argument, because you have nothing to compare the results to. In that case, you will only get IOB tag counts with no scores, because there are no chunks to compare to.

Analyzing a chunked corpus

Finally, there is a script called analyze_chunked_corpus.py, which as the name implies, will read in a chunked corpus and print out stats about the number of words and tags. You can run it like this:

\$ python analyze_chunked_corpus.py treebank_chunk

The results are very similar to analyze_tagged_corpus.py, with additional columns for each IOB tag. Each IOB tag column shows the counts for each part-of-speech tag that was present in chunks for that IOB tag. For example, NN words (nouns) may occur 300 times in total, and for 280 of those times, the NN words occurred with a NP IOB tag, meaning that most nouns occur within noun phrases.

As with the other commands, you can pass in a custom corpus path and reader to analyze your own chunked corpus.
See also

- The *Training a tagger-based chunker*, the *Classification-based chunking*, and the *Training a named entity chunker* recipes cover many of the ideas that went into the train_chunker.py script
- In <u>Chapter 4</u>, *Part-of-speech Tagging*, we showed how to use NLTK-Trainer for training a tagger in the *Training a tagger with NLTK-Trainer* recipe

Chapter 6. Transforming Chunks and Trees

In this chapter, we will cover the following recipes:

- Filtering insignificant words from a sentence
- Correcting verb forms
- Swapping verb phrases
- Swapping noun cardinals
- Swapping infinitive phrases
- Singularizing plural nouns
- Chaining chunk transformations
- Converting a chunk tree to text
- Flattening a deep tree
- Creating a shallow tree
- Converting tree labels

Introduction

Now that you know how to get chunks/phrases from a sentence, what do you do with them? This chapter will show you how to do various transforms on both chunks and trees. The **chunk transforms** are for grammatical correction and rearranging phrases without loss of meaning. The **tree transforms** give you ways to modify and flatten deep parse trees. The functions detailed in these recipes modify data, as opposed to learning from it. This means it's not safe to apply them indiscriminately. A thorough knowledge of the data you want to transform, along with a few experiments, should help you decide which functions to apply and when.

Whenever the term **chunk** is used in this chapter, it could refer to an actual chunk extracted by a chunker, or it could simply refer to a short phrase or sentence in the form of a list of tagged words. What's important in this chapter is what you can do with a chunk, not where it came from.

Filtering insignificant words from a sentence

Many of the most commonly used words are insignificant when it comes to discerning the meaning of a phrase. For example, in the phrase *the movie was terrible*, the most **significant** words are *movie* and *terrible*, while *the* and *was* are almost useless. You could get the same meaning if you took them out, that is, *movie terrible* or *terrible movie*. Either way, the sentiment is the same. In this recipe, we'll learn how to remove the insignificant words and keep the significant ones by looking at their part-of-speech tags.

Getting ready

First, we need to decide which part-of-speech tags are significant and which are not. Looking through the treebank corpus for stopwords yields the following table of insignificant words and tags:

Word	Tag
a	DT
all	PDT
an	DT
and	CC
or	CC
that	WDT
the	DT

Other than CC, all the tags end with DT. This means we can filter out insignificant words by looking at the tag's suffix. Refer to <u>Appendix A</u>, *Penn Treebank Part-of-speech Tags*, for details on tag meanings.

How to do it...

In transforms.py is a function called filter_insignificant(). It takes a single chunk, which should be a list of tagged words, and returns a new chunk without any insignificant tagged words. It defaults to filtering out any tags that end with DT or CC:

```
def filter_insignificant(chunk, tag_suffixes=['DT', 'CC']):
  good = []
  for word, tag in chunk:
    ok = True
    for suffix in tag_suffixes:
        if tag.endswith(suffix):
            ok = False
            break
    if ok:
        good.append((word, tag))
    return good
```

And now we can use it on the part-of-speech tagged version of *the terrible movie*:

```
>>> from transforms import filter_insignificant
>>> filter_insignificant([('the', 'DT'), ('terrible', 'JJ'),
 ('movie', 'NN')])
[('terrible', 'JJ'), ('movie', 'NN')]
```

As you can see, the word the is eliminated from the chunk.

How it works...

The filter_insignificant() function iterates over the tagged words in the chunk. For each tag, it checks whether that tag ends with any of the tag_suffixes. If it does, then the tagged word is skipped. But if the tag is ok, then the tagged word is appended to a new good chunk that is returned.

There's more...

The way filter_insignificant() is defined, you can pass in your own tag suffixes if DT and CC are not enough, or are incorrect for your case. For example, you might decide that possessive words and pronouns such as *you*, *your*, *their*, and *theirs* are no good, but DT and CC words are ok. The tag suffixes would then be PRP and PRP\$:

```
>>> filter_insignificant([('your', 'PRP$'), ('book', 'NN'), ('is',
'VBZ'), ('great', 'JJ')], tag_suffixes=['PRP', 'PRP$'])
[('book', 'NN'), ('is', 'VBZ'), ('great', 'JJ')]
```

Filtering insignificant words can be a good complement to stopword filtering for purposes such as search engine indexing and querying and text classification.

See also

This recipe is analogous to the *Filtering stopwords in a tokenized sentence* recipe in <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*.

Correcting verb forms

It's fairly common to find incorrect verb forms in real-world language. For example, the correct form of *is our children learning*? is *are our children learning*? The verb *is* should only be used with singular nouns, while *are* is for plural nouns, such as *children*. We can correct these mistakes by creating verb correction mappings that are used depending on whether there's a plural or singular noun in the chunk.

Getting ready

We first need to define the verb correction mappings in transforms.py. We'll create two mappings, one for plural to singular and another for singular to plural:

```
plural_verb_forms = {
  ('is', 'VBZ'): ('are', 'VBP'),
  ('was', 'VBD'): ('were', 'VBD')
}
singular_verb_forms = {
  ('are', 'VBP'): ('is', 'VBZ'),
  ('were', 'VBD'): ('was', 'VBD')
}
```

Each mapping has a tagged verb that maps to another tagged verb. These initial mappings cover the basics of mapping is to are, was to were, and vice versa.

How to do it...

In transforms.py is a function called correct_verbs(). Pass it a chunk with incorrect verb forms and you'll get a corrected chunk back. It uses a helper function, first_chunk_index(), to search the chunk for the position of the first tagged word where pred returns True. The pred argument should be a callable function that takes a (word, tag) tuple and returns True or False. Here's first_chunk_index():

```
def first_chunk_index(chunk, pred, start=0, step=1):
    l = len(chunk)
    end = l if step > 0 else -1
    for i in range(start, end, step):
        if pred(chunk[i]):
            return i
    return None
```

For first_chunk_index() to be useful, we need to use a predicate function. In the case of correct_verbs(), the predicate function we need should return True if the tag in the (word, tag) argument starts with a given tag prefix, and False otherwise.

```
def tag_startswith(prefix):
    def f(wt):
        return wt[1].startswith(prefix)
        return f
```

The tag_startswith() function takes a tag prefix, such as NN, and returns a predicate function that will take a (word, tag) tuple and return True if the tag starts with the given prefix. A function that returns another function is called a **higher order function**. This is not as complicated as it might sound—just as you can use a function to generate and return new variables and values, some programming languages (such as Python) let you generate functions inside of other functions. In this case, we want a function that takes a single argument: (word, tag). But we also want this function to have access to a prefix variable. Since we cannot add arguments to the function definition, we instead generate a higher order function that has access to the prefix variable, while preserving the single (word, tag) argument.

```
Now that we have defined first_chunk_index() and tag_startswith(), we can actually implement correct_verbs(). This may seem like overkill for a single function, but we will be using first_chunk_index() and tag_startswith() in subsequent recipes.
```

```
def correct verbs(chunk):
  vbidx = first chunk index(chunk, tag startswith('VB'))
  # if no verb found, do nothing
  if vbidx is None:
    return chunk
  verb, vbtag = chunk[vbidx]
  nnpred = tag startswith('NN')
  # find nearest noun to the right of verb
  nnidx = first chunk index(chunk, nnpred, start=vbidx+1)
  # if no noun found to right, look to the left
  if nnidx is None:
    nnidx = first chunk index(chunk, nnpred, start=vbidx-1, step=-1)
  # if no noun found, do nothing
  if nnidx is None:
    return chunk
  noun, nntag = chunk[nnidx]
  # get correct verb form and insert into chunk
  if nntag.endswith('S'):
    chunk[vbidx] = plural verb forms.get((verb, vbtag), (verb,
vbtaq))
  else:
    chunk[vbidx] = singular verb forms.get((verb, vbtag), (verb,
vbtaq))
  return chunk
```

When we call the preceding function on a part-of-speech tagged is our children learning chunk, we get back the correct form, are our children learning.

```
>>> from transforms import correct_verbs
>>> correct_verbs([('is', 'VBZ'), ('our', 'PRP$'), ('children',
'NNS'), ('learning', 'VBG')])
[('are', 'VBP'), ('our', 'PRP$'), ('children', 'NNS'), ('learning',
'VBG')]
```

We can also try this with a *singular noun* and an incorrect *plural verb*:

```
>>> correct_verbs([('our', 'PRP$'), ('child', 'NN'), ('were',
'VBD'), ('learning', 'VBG')])
[('our', 'PRP$'), ('child', 'NN'), ('was', 'VBD'), ('learning',
'VBG')]
```

In this case, were becomes was because child is a singular noun.

How it works...

The correct_verbs () function starts by looking for a verb in the chunk. If no verb is found, the chunk is returned with no changes. Once a verb is found, we keep the verb, its tag, and its index in the chunk. Then, we look on either side of the verb to find the nearest noun, starting on the right and looking to the left only if no noun is found on the right. If no noun is found at all, the chunk is returned as is. But if a noun is found, then we look up the correct verb form depending on whether or not the noun is plural.

Recall from <u>Chapter 4</u>, *Part-of-speech Tagging*, that plural nouns are tagged with NNS, while singular nouns are tagged with NN. That means we can check the plurality of a noun by looking to see whether its tag ends with S. Once we get the corrected verb form, it is inserted into the chunk to replace the original verb form.

See also

The next four recipes all make use of first_chunk_index() to perform chunk transformations.

Swapping verb phrases

Swapping the words around a verb can eliminate the passive voice from particular phrases. For example, the book was great can be transformed into the great book. This kind of normalization can also help with frequency analysis, by counting two apparently different phrases as the same phrase.

How to do it...

In transforms.py is a function called swap_verb_phrase(). It swaps the right-hand side of the chunk with the left-hand side, using the verb as the **pivot point**. It uses the first_chunk_index() function defined in the previous recipe to find the verb to pivot around.

```
def swap_verb_phrase(chunk):
    def vbpred(wt):
        word, tag = wt
        return tag != 'VBG' and tag.startswith('VB') and len(tag) > 2
    vbidx = first_chunk_index(chunk, vbpred)
    if vbidx is None:
        return chunk
    return chunk[vbidx+1:] + chunk[:vbidx]
```

Now we can see how it works on the part-of-speech tagged phrase the book was great:

```
>>> swap_verb_phrase([('the', 'DT'), ('book', 'NN'), ('was', 'VBD'),
  ('great', 'JJ')])
 [('great', 'JJ'), ('the', 'DT'), ('book', 'NN')]
```

And the result is great the book. This phrase clearly isn't grammatically correct, so read on to learn how to fix it.

How it works...

Using first_chunk_index() from the previous recipe with the vbpred() function defined inline, we start by finding the first matching verb that is not a gerund (a word that ends in *ing*) tagged with VBG. Once we've found the verb, we return the chunk with the right side before the left, and remove the verb.

The reason we don't want to pivot around a gerund is that gerunds are commonly used to describe nouns, and pivoting around one would remove that description. Here's an example where you can see how not pivoting around a gerund is a good thing:

```
>>> swap_verb_phrase([('this', 'DT'), ('gripping', 'VBG'), ('book',
'NN'), ('is', 'VBZ'), ('fantastic', 'JJ')])
```

```
[('fantastic', 'JJ'), ('this', 'DT'), ('gripping', 'VBG'), ('book', 'NN')]
```

If we had pivoted around the gerund, the result would be book is fantastic this, and we'd lose the gerund gripping.

There's more...

Filtering insignificant words makes the final result more readable. By filtering either before or after swap_verb_phrase(), we get fantastic gripping book instead of fantastic this gripping book:

```
>>> from transforms import swap_verb_phrase, filter_insignificant
>>> swap_verb_phrase(filter_insignificant([('this', 'DT'),
  ('gripping', 'VBG'), ('book', 'NN'), ('is', 'VBZ'), ('fantastic',
  'JJ')]))
[('fantastic', 'JJ'), ('gripping', 'VBG'), ('book', 'NN')]
>>> filter_insignificant(swap_verb_phrase([('this', 'DT'),
  ('gripping', 'VBG'), ('book', 'NN'), ('is', 'VBZ'), ('fantastic',
  'JJ')]))
[('fantastic', 'JJ'), ('gripping', 'VBG'), ('book', 'NN')]
```

Either way, we get a shorter grammatical chunk with no loss of meaning.

See also

The previous recipe, *Correcting verb forms*, defines first_chunk_index(), which is used to find the verb in the chunk.

Swapping noun cardinals

In a chunk, a *cardinal* word, tagged as CD, refers to a number, such as *10*. These cardinals often occur before or after a noun. For normalization purposes, it can be useful to always put the cardinal before the noun.

How to do it ...

The swap_noun_cardinal() function is defined in transforms.py. It swaps any cardinal that occurs immediately after a noun with the noun so that the cardinal occurs immediately before the noun. It uses a helper function, tag_equals(), which is similar to tag_startswith(), but in this case, the function it returns does an equality comparison with the given tag:

```
def tag_equals(tag):
    def f(wt):
        return wt[1] == tag
    return f
Now we can define swap_noun_cardinal():
def swap_noun_cardinal(chunk):
    cdidx = first_chunk_index(chunk, tag_equals('CD'))
    # cdidx must be > 0 and there must be a noun immediately before it
    if not cdidx or not chunk[cdidx-1][1].startswith('NN'):
        return chunk
    noun, nntag = chunk[cdidx-1]
    chunk[cdidx-1] = chunk[cdidx]
    chunk[cdidx] = noun, nntag
    return chunk
```

Let's try it on a date, such as Dec 10, and another common phrase, the top 10.

```
>>> swap_noun_cardinal([('Dec.', 'NNP'), ('10', 'CD')])
[('10', 'CD'), ('Dec.', 'NNP')]
>>> swap_noun_cardinal([('the', 'DT'), ('top', 'NN'), ('10', 'CD')])
[('the', 'DT'), ('10', 'CD'), ('top', 'NN')]
```

The result is that the numbers are now in front of the noun, creating 10 Dec and the 10 top.

How it works...

We start by looking for a CD tag in the chunk. If no CD is found, or if the CD is at the beginning of the chunk, then the chunk is returned as is. There must also be a noun immediately before the CD. If we do find a CD with a noun preceding it, then we swap the noun and cardinal.

See also

The *Correcting verb forms* recipe defines the first_chunk_index() function used to find tagged words in a chunk.

Swapping infinitive phrases

An infinitive phrase has the form A of B, such as book of recipes. These can often be transformed into a new form while retaining the same meaning, such as recipes book.

How to do it...

An infinitive phrase can be found by looking for a word tagged with IN. The swap_infinitive_phrase() function, defined in transforms.py, will return a chunk that swaps the portion of the phrase after the IN word with the portion before the IN word:

```
def swap_infinitive_phrase(chunk):
    def inpred(wt):
        word, tag = wt
        return tag == 'IN' and word != 'like'
    inidx = first_chunk_index(chunk, inpred)
    if inidx is None:
        return chunk
    nnidx = first_chunk_index(chunk, tag_startswith('NN'),
    start=inidx, step=-1) or 0
    return chunk[:nnidx] + chunk[inidx+1:] + chunk[nnidx:inidx]
```

The function can now be used to transform book of recipes into recipes book:

```
>>> from transforms import swap_infinitive_phrase
>>> swap_infinitive_phrase([('book', 'NN'), ('of', 'IN'),
 ('recipes', 'NNS')])
[('recipes', 'NNS'), ('book', 'NN')]
```

How it works...

This function is similar to the swap_verb_phrase() function described in the Swapping verb
phrases recipe. The inpred function is passed to first_chunk_index() to look for a word
whose tag is IN. Next, we find the first noun that occurs before the IN word, so we can insert the
portion of the chunk after the IN word between the noun and the beginning of the chunk. A more
complicated example should demonstrate this:

```
>>> swap_infinitive_phrase([('delicious', 'JJ'), ('book', 'NN'),
  ('of', 'IN'), ('recipes', 'NNS')])
 [('delicious', 'JJ'), ('recipes', 'NNS'), ('book', 'NN')]
```

We don't want the result to be recipes delicious book. Instead, we want to insert recipes before the noun book but after the adjective delicious, hence the need to find the nnidx occurring before the inidx.

There's more...

You'll notice that the inpred function checks to make sure the word is not like. That's because like phrases must be treated differently, as transforming them the same way will result in an ungrammatical phrase. For example, tastes like chicken should not be transformed into chicken tastes.

```
>>> swap_infinitive_phrase([('tastes', 'VBZ'), ('like', 'IN'),
  ('chicken', 'NN')])
 [('tastes', 'VBZ'), ('like', 'IN'), ('chicken', 'NN')]
```

See also

In the next recipe, we'll learn how to transform recipes book into the more normal form recipe book.

Singularizing plural nouns

As we saw in the previous recipe, the transformation process can result in phrases such as recipes book. This is a NNS followed by a NN, when a more proper version of the phrase would be recipe book, which is a NN followed by another NN. We can do another transform to correct these improper plural nouns.

How to do it...

The transforms.py script defines a function called singularize_plural_noun() which will depluralize a plural noun (tagged with NNS) that is followed by another noun:

```
def singularize_plural_noun(chunk):
    nnsidx = first_chunk_index(chunk, tag_equals('NNS'))
    if nnsidx is not None and nnsidx+1 < len(chunk) and
    chunk[nnsidx+1][1][:2] == 'NN':
        noun, nnstag = chunk[nnsidx]
        chunk[nnsidx] = (noun.rstrip('s'), nnstag.rstrip('S'))
    return chunk</pre>
```

And using it on recipes book, we get the more correct form, recipe book.

```
>>> singularize_plural_noun([('recipes', 'NNS'), ('book', 'NN')])
[('recipe', 'NN'), ('book', 'NN')]
```

How it works...

We start by looking for a plural noun with the tag NNS. If found, and if the next word is a noun (determined by making sure the tag starts with NN), then we depluralize the plural noun by removing s from the right side of both the tag and the word. The tag is assumed to be capitalized, so an uppercase s is removed from the right-hand side of the tag, while a lowercase s is removed from the right-hand side of the tag.

See also

The previous recipe shows how a transformation can result in a plural noun followed by a singular noun, though this could also occur naturally in real-world text.

Chaining chunk transformations

The transform functions defined in the previous recipes can be chained together to normalize chunks. The resulting chunks are often shorter with no loss of meaning.

How to do it...

In transforms.py is the function transform_chunk(). It takes a single chunk and an optional list of transform functions. It calls each transform function on the chunk, one at a time, and returns the final chunk:

```
def transform_chunk(chunk, chain=[filter_insignificant,
swap_verb_phrase, swap_infinitive_phrase, singularize_plural_noun],
trace=0):
    for f in chain:
        chunk = f(chunk)
        if trace:
            print f.__name__, ':', chunk
        return chunk
```

Using it on the phrase the book of recipes is delicious, we get delicious recipe book:

```
>>> from transforms import transform_chunk
>>> transform_chunk([('the', 'DT'), ('book', 'NN'), ('of', 'IN'),
 ('recipes', 'NNS'), ('is', 'VBZ'), ('delicious', 'JJ')])
[('delicious', 'JJ'), ('recipe', 'NN'), ('book', 'NN')]
```

How it works...

The transform chunk () function defaults to chaining the following functions in the given order:

- filter_insignificant()
- swap_verb_phrase()
- swap_infinitive_phrase()
- singularize_plural_noun()

Each function transforms the chunk that results from the previous function, starting with the original chunk.

Note

The order in which you apply transform functions can be significant. Experiment with your own data to determine which transforms are best, and in which order they should be applied.

There's more...

You can pass trace=1 into transform_chunk() to get an output at each step:

```
>>> from transforms import transform_chunk
>>> transform_chunk([('the', 'DT'), ('book', 'NN'), ('of', 'IN'),
('recipes', 'NNS'), ('is', 'VBZ'), ('delicious', 'JJ')], trace=1)
filter_insignificant : [('book', 'NN'), ('of', 'IN'), ('recipes',
'NNS'), ('is', 'VBZ'), ('delicious', 'JJ')]
swap_verb_phrase : [('delicious', 'JJ'), ('book', 'NN'), ('of',
'IN'), ('recipes', 'NNS')]
swap_infinitive_phrase : [('delicious', 'JJ'), ('recipes', 'NNS'),
('book', 'NN')]
singularize_plural_noun : [('delicious', 'JJ'), ('recipe', 'NN'),
('book', 'NN')]
[('delicious', 'JJ'), ('recipe', 'NN'), ('book', 'NN')]
```

This shows you the result of each transform function, which is then passed in to the next transform until a final chunk is returned.

See also

The transform functions used were defined in the previous recipes of this chapter.

Converting a chunk tree to text

At some point, you may want to convert a Tree or subtree back to a sentence or chunk string. This is mostly straightforward, except when it comes to properly outputting punctuation.

How to do it...

We'll use the first tree of the treebank_chunk corpus as our example. The obvious first step is to join all the words in the tree with a space:

```
>>> from nltk.corpus import treebank_chunk
>>> tree = treebank_chunk.chunked_sents()[0]
>>> ' '.join([w for w, t in tree.leaves()])
'Pierre Vinken , 61 years old , will join the board as a
nonexecutive director Nov. 29 .'
```

But as you can see, the punctuation isn't quite right. The commas and period are treated as individual words, and so get the surrounding spaces as well. But we can fix this using regular expression substitution. This is implemented in the chunk_tree_to_sent() function found in transforms.py:

```
import re
punct_re = re.compile(r'\s([,\.;\?])')

def chunk_tree_to_sent(tree, concat=' '):
   s = concat.join([w for w, t in tree.leaves()])
   return re.sub(punct re, r'\g<1>', s)
```

Using chunk_tree_to_sent() results in a cleaner sentence, with no space before each punctuation mark:

>>> from transforms import chunk_tree_to_sent
>>> chunk_tree_to_sent(tree)
'Pierre Vinken, 61 years old, will join the board as a nonexecutive
director Nov. 29.'

How it works...

To correct the extra spaces in front of the punctuation, we create a regular expression, punct_re, that will match a space followed by any of the known punctuation characters. We have to escape both '.' and '?' with a '\' since they are special characters. The punctuation is surrounded by parentheses so we can use the matched group for substitution.

Once we have our regular expression, we define chunk_tree_to_sent(), whose first step is to join the words by a concatenation character that defaults to a space. Then, we can call re.sub() to

replace all the punctuation matches with just the punctuation group. This eliminates the space in front of the punctuation characters, resulting in a more correct string.

There's more...

We can simplify this function a little using nltk.tag.untag() to get words from the tree's leaves, instead of using our own list comprehension:

```
import nltk.tag, re
punct_re = re.compile(r'\s([,\.;\?])')

def chunk_tree_to_sent(tree, concat=' '):
   s = concat.join(nltk.tag.untag(tree.leaves()))
   return re.sub(punct_re, r'\g<1>', s)
```

See also

The nltk.tag.untag() function is covered at the end of the *Default tagging* recipe in <u>Chapter 4</u>, *Part-of-speech Tagging*.

Flattening a deep tree

Some of the included corpora contain parsed sentences, which are often deep trees of nested phrases. Unfortunately, these trees are too deep to use for training a chunker, since IOB tag parsing is not designed for nested chunks. To make these trees usable for chunker training, we must flatten them.

Getting ready

We're going to use the first parsed sentence of the treebank corpus as our example. Here's a diagram showing how deeply nested this tree is:



You may notice that the part-of-speech tags are part of the tree structure instead of being included with the word. This will be handled later using the Tree.pos() method, which was designed specifically for combining words with preterminal Tree labels such as part-of-speech tags.

How to do it...

In transforms.py is a function named flatten_deeptree(). It takes a single Tree and will return a new Tree that keeps only the lowest-level trees. It uses a helper function, flatten childtrees(), to do most of the work:

```
from nltk.tree import Tree

def flatten_childtrees(trees):
    children = []

for t in trees:
    if t.height() < 3:
        children.extend(t.pos())
    elif t.height() == 3:
        children.append(Tree(t.label(), t.pos()))
    else:
        children.extend(flatten childtrees([c for c in t]))</pre>
```

```
return children
def flatten_deeptree(tree):
  return Tree(tree.label(), flatten childtrees([c for c in tree]))
```

We can use it on the first parsed sentence of the treebank corpus to get a flatter tree:

```
>>> from nltk.corpus import treebank
>>> from transforms import flatten_deeptree
>>> flatten_deeptree(treebank.parsed_sents()[0])
Tree('S', [Tree('NP', [('Pierre', 'NNP'), ('Vinken', 'NNP')]), (',',
','), Tree('NP', [('61', 'CD'), ('years', 'NNS')]), ('old', 'JJ'),
(',', ','), ('will', 'MD'), ('join', 'VB'), Tree('NP', [('the',
'DT'), ('board', 'NN')]), ('as', 'IN'), Tree('NP', [('a', 'DT'),
('nonexecutive', 'JJ'), ('director', 'NN')]), Tree('NP-TMP',
[('Nov.', 'NNP'), ('29', 'CD')]), ('.', '.')])
```

The result is a much flatter Tree that only includes NP phrases. Words that are not part of an NP phrase are separated. This flatter tree is shown in the following diagram:



This Tree is quite similar to the first chunk Tree from the treebank_chunk corpus. The main difference is that the rightmost NP Tree is separated into two subtrees above, one of them named NP-TMP.

The first tree from treebank_chunk is shown in the following diagram for comparison. The main difference is the right side of the tree, which has only one NP subtree instead of two subtrees:



How it works...

The solution is composed of two functions: flatten_deeptree() returns a new Tree from the given tree by calling flatten_childtrees() on each of the given tree's children.

The flatten_childtrees() function is a recursive function that drills down into the Tree until it finds child trees whose height() is equal to or less than 3. A Tree whose height() is less than 3 looks like this:

>>> from nltk.tree import Tree
>>> Tree('NNP', ['Pierre']).height()2



These short trees are converted into lists of tuples using the pos() function.

```
>>> Tree('NNP', ['Pierre']).pos()
[('Pierre', 'NNP')]
```

Trees whose height() is equal to 3 are the lowest level trees that we're interested in keeping. These trees look like this:



```
>>> Tree('NP', [Tree('NNP', ['Pierre']), Tree('NNP',
['Vinken'])]).height()
3
```

And when we call pos() on that tree, we get:

```
>>> Tree('NP', [Tree('NNP', ['Pierre']), Tree('NNP',
['Vinken'])]).pos()
[('Pierre', 'NNP'), ('Vinken', 'NNP')]
```

The recursive nature of flatten childtrees () eliminates all trees whose height is greater than 3.

There's more...

Flattening a deep Tree allows us to call nltk.chunk.util.tree2conlltags() on the flattened Tree, a necessary step to train a chunker. If you try to call this function before flattening the Tree, you get a ValueError exception:

```
>>> from nltk.chunk.util import tree2conlltags
>>> tree2conlltags(treebank.parsed_sents()[0])
Traceback (most recent call last):
   File "<stdin>", line 1, in <module>
   File "/usr/local/lib/python2.6/dist-packages/nltk/chunk/util.py",
line 417, in tree2conlltags
      raise ValueError, "Tree is too deeply nested to be printed in
CoNLL format"
ValueError: Tree is too deeply nested to be printed in CoNLL format
```

But after flattening, there's no problem:

```
>>> tree2conlltags(flatten_deeptree(treebank.parsed_sents()[0]))
[('Pierre', 'NNP', 'B-NP'), ('Vinken', 'NNP', 'I-NP'), (',', ',',
'O'), ('61', 'CD', 'B-NP'), ('years', 'NNS', 'I-NP'), ('old', 'JJ',
'O'), (',', ',', 'O'), ('will', 'MD', 'O'), ('join', 'VB', 'O'),
('the', 'DT', 'B-NP'), ('board', 'NN', 'I-NP'), ('as', 'IN', 'O'),
('a', 'DT', 'B-NP'), ('nonexecutive', 'JJ', 'I-NP'), ('director',
'NN', 'I-NP'), ('Nov.', 'NNP', 'B-NP-TMP'), ('29', 'CD',
'I-NP-TMP'), ('.', '.', 'O')]
```

Being able to flatten trees opens up the possibility of training a chunker on corpora consisting of deep parse trees.

The cess_esp and cess_cat treebank

The cess_esp and cess_cat corpora are Spanish and Catalan corpora that have parsed sentences but no chunked sentences. In other words, they have deep trees that must be flattened in order to train a chunker. In fact, the trees are so deep that a diagram would be overwhelming, but the flattening can be demonstrated by showing the height() of the tree before and after flattening:

```
>>> from nltk.corpus import cess_esp
>>> cess_esp.parsed_sents()[0].height()
22
>>> flatten_deeptree(cess_esp.parsed_sents()[0]).height()
3
```

See also

The *Training a tagger-based chunker* recipe in <u>Chapter 5</u>, *Extracting Chunks*, covers training a chunker using IOB tags.

Creating a shallow tree

In the previous recipe, we flattened a deep Tree by only keeping the lowest level subtrees. In this recipe, we'll keep only the highest level subtrees instead.

How to do it...

We'll be using the first parsed sentence from the treebank corpus as our example. Recall from the previous recipe that the sentence Tree looks like this:



The shallow_tree() function defined in transforms.py eliminates all the nested subtrees, keeping only the top subtree labels:

```
from nltk.tree import Tree

def shallow_tree(tree):
    children = []

for t in tree:
    if t.height() < 3:
        children.extend(t.pos())
    else:
        children.append(Tree(t.label(), t.pos()))

return Tree(tree.label(), children)</pre>
```

Using it on the first parsed sentence in treebank results in a Tree with only two subtrees:

```
>>> from transforms import shallow_tree
>>> shallow_tree(treebank.parsed_sents()[0])
Tree('S', [Tree('NP-SBJ', [('Pierre', 'NNP'), ('Vinken', 'NNP'),
(',', ','), ('61', 'CD'), ('years', 'NNS'), ('old', 'JJ'), (',',
',')]), Tree('VP', [('will', 'MD'), ('join', 'VB'), ('the', 'DT'),
```

```
('board', 'NN'), ('as', 'IN'), ('a', 'DT'), ('nonexecutive', 'JJ'), ('director', 'NN'), ('Nov.', 'NNP'), ('29', 'CD')]), ('.', '.')])
```

We can visually and programmatically see the difference in the following diagram:



```
>>> treebank.parsed_sents()[0].height()
7
>>> shallow_tree(treebank.parsed_sents()[0]).height()
3
```

As in the previous recipe, the height of the new tree is 3 so it can be used for training a chunker.

How it works...

The shallow_tree() function iterates over each of the top-level subtrees in order to create new child trees. If the height() of a subtree is less than 3, then that subtree is replaced by a list of its part-of-speech tagged children. All other subtrees are replaced by a new Tree whose children are the part-of-speech tagged leaves. This eliminates all nested subtrees while retaining the top-level subtrees.

This function is an alternative to flatten_deeptree() from the previous recipe, for when you want to keep the higher-level tree labels and ignore the lower-level labels.

See also

The previous recipe covers how to flatten a Tree and keep the lowest-level subtrees, as opposed to keeping the highest-level subtrees.

Converting tree labels

As you've seen in previous recipes, parse trees often have a variety of Tree label types that are not present in chunk trees. If you want to use parse trees to train a chunker, then you'll probably want to reduce this variety by converting some of these tree labels to more common label types.

Getting ready

First, we have to decide which Tree labels need to be converted. Let's take a look at that first Tree again:



Immediately, you can see that there are two alternative NP subtrees: NP-SBJ and NP-TMP. Let's convert both of those to NP. The mapping will be as follows:

Original Label	New Label
NP-SBJ	NP
NP-TMP	NP

How to do it...

In transforms.py is the function convert_tree_labels(). It takes two arguments: the Tree to convert and a label conversion mapping. It returns a new Tree with all matching labels replaced based on the values in the mapping:

```
from nltk.tree import Tree
def convert_tree_labels(tree, mapping):
    children = []
```

```
for t in tree:
    if isinstance(t, Tree):
        children.append(convert_tree_labels(t, mapping))
    else:
        children.append(t)
label = mapping.get(tree.label(), tree.label())
return Tree(label, children)
```

Using the mapping table we saw earlier, we can pass it in as a dict to convert_tree_labels() and convert the first parsed sentence from treebank:

```
>>> from transforms import convert_tree_labels
>>> mapping = {'NP-SBJ': 'NP', 'NP-TMP': 'NP'}
>>> convert_tree_labels(treebank.parsed_sents()[0], mapping)
Tree('S', [Tree('NP', [Tree('NP', [Tree('NNP', ['Pierre']),
Tree('NNP', ['Vinken'])]), Tree(',', [',']), Tree('ADJP',
[Tree('NP', [Tree('CD', ['61']), Tree('NNS', ['years'])]),
Tree('JJ', ['old'])]), Tree(',', [','])]), Tree('VP', [Tree('MD',
['will']), Tree('VP', [Tree('VB', ['join']), Tree('VP', [Tree('MD',
['will']), Tree('NN', ['board'])]), Tree('PP-CLR', [Tree('IN',
['as']), Tree('NP', [Tree('DT', ['a']), Tree('JJ',
['nonexecutive']), Tree('NN', ['director'])]]), Tree('NP',
[Tree('NNP', ['Nov.']), Tree('CD', ['29'])])])]), Tree('.', ['.'])])
```

As you can see in the following diagram, the NP-* subtrees have been replaced with NP subtrees:



How it works...

The convert_tree_labels() function recursively converts every child subtree using the mapping. The Tree is then rebuilt with the converted labels and children until the entire Tree has been converted.

The result is a brand new Tree instance with new subtrees whose labels have been converted.

See also

The previous two recipes cover different methods of flattening a parse Tree, both of which can produce subtrees that may require mapping before using them to train a chunker. Chunker training is covered in the *Training a tagger-based chunker* recipe in <u>Chapter 5</u>, *Extracting Chunks*.

Chapter 7. Text Classification

In this chapter, we will cover the following recipes:

- Bag of words feature extraction
- Training a Naive Bayes classifier
- Training a decision tree classifier
- Training a maximum entropy classifier
- Training scikit-learn classifiers
- · Measuring precision and recall of a classifier
- Calculating high information words
- Combining classifiers with voting
- Classifying with multiple binary classifiers
- Training a classifier with NLTK-Trainer

Introduction

Text classification is a way to categorize documents or pieces of text. By examining the word usage in a piece of text, classifiers can decide what class label to assign to it. A **binary classifier** decides between two labels, such as positive or negative. The text can either be one label or another, but not both, whereas a **multi-label classifier** can assign one or more labels to a piece of text.

Classification works by learning from **labeled feature sets**, or training data, to later classify an **unlabeled feature set**. A labeled feature set is simply a tuple that looks like (feat, label), while an unlabeled feature set is a feat by itself. A **feature set** is basically a key-value mapping of feature names to feature values. In the case of text classification, the feature names are usually words, and the values are all True. As the documents may have unknown words, and the number of possible words may be very large, words that don't occur in the text are omitted, instead of including them in a feature set with the value False.

An **instance** is another term for a feature set. It represents a single occurrence of a combination of features. I will use instance and feature set interchangeably. A **labeled feature set** is an instance with a known class label that we can use for training or evaluation. To summarize, (feat, label) is a labeled feature set, or labeled instance. feat is a feature set, normally represented as a key-value dictionary. When feat does not have an associated label, it is also called an **unlabeled feature set**, or instance.

Bag of words feature extraction

Text feature extraction is the process of transforming what is essentially a list of words into a feature set that is usable by a classifier. The NLTK classifiers expect dict style feature sets, so we must therefore transform our text into a dict. The **bag of words** model is the simplest method; it constructs a word presence feature set from all the words of an instance. This method doesn't care about the order of the words, or how many times a word occurs, all that matters is whether the word is present in a list of words.

How to do it...

The idea is to convert a list of words into a dict, where each word becomes a key with the value True. The bag of words () function in featx.py looks like this:

```
def bag_of_words(words):
    return dict([(word, True) for word in words])
```

We can use it with a list of words; in this case, the tokenized sentence the quick brown fox:

```
>>> from featx import bag_of_words
>>> bag_of_words(['the', 'quick', 'brown', 'fox'])
{'quick': True, 'brown': True, 'the': True, 'fox': True}
```

The resulting dict is known as a **bag of words** because the words are not in order, and it doesn't matter where in the list of words they occurred, or how many times they occurred. All that matters is that the word is found at least once.

Tip

You can use different values than True, but it is important to keep in mind that the NLTK classifiers learn from the unique combination of (key, value). That means that ('fox', 1) is treated as a different feature than ('fox', 2).

How it works...

The bag_of_words () function is a very simple list comprehension that constructs a dict from the given words, where every word gets the value True.

Since we have to assign a value to each word in order to create a dict, True is a logical choice for the value to indicate word presence. If we knew the universe of all possible words, we could assign the value False to all the words that are not in the given list of words. But most of the time, we don't know all the possible words beforehand. Plus, the dict that would result from assigning False to every possible word would be very large (assuming all words in the English language are possible). So instead, to keep feature extraction simple and use less memory, we stick to assigning the value True to all words that occur at least once. We don't assign the value False to any word since we don't know what the set of possible words are; we only know about the words we are given.

There's more...

In the default bag of words model, all words are treated equally. But that's not always a good idea. As we already know, some words are so common that they are practically meaningless. If you have a set of words that you want to exclude, you can use the bag_of_words_not_in_set() function in featx.py:

```
def bag_of_words_not_in_set(words, badwords):
    return bag of words(set(words) - set(badwords))
```

This function can be used, among other things, to filter stopwords. Here's an example where we filter the word the from the quick brown fox:

```
>>> from featx import bag_of_words_not_in_set
>>> bag_of_words_not_in_set(['the', 'quick', 'brown', 'fox'],
['the'])
{'quick': True, 'brown': True, 'fox': True}
```

As expected, the resulting dict has quick, brown, and fox, but not the.

Filtering stopwords

Stopwords are words that are often useless in NLP, in that they don't convey much meaning, such as the word the. Here's an example of using the bag_of_words_not_in_set() function to filter all English stopwords:

```
from nltk.corpus import stopwords

def bag_of_non_stopwords(words, stopfile='english'):
    badwords = stopwords.words(stopfile)
    return bag of words not in set(words, badwords)
```

You can pass a different language filename as the stopfile keyword argument if you are using a language other than English. Using this function produces the same result as the previous example:

```
>>> from featx import bag_of_non_stopwords
>>> bag_of_non_stopwords(['the', 'quick', 'brown', 'fox'])
{'quick': True, 'brown': True, 'fox': True}
```

Here, the is a stopword, so it is not present in the returned dict.

Including significant bigrams

In addition to single words, it often helps to include significant bigrams. As significant bigrams are less common than most individual words, including them in the bag of words model can help the classifier make better decisions. We can use the BigramCollocationFinder class covered in the *Discovering word collocations* recipe of <u>Chapter 1</u>, *Tokenizing Text and WordNet Basics*, to find

significant bigrams. The bag_of_bigrams_words() function found in featx.py will return a dict of all words along with the 200 most significant bigrams:

```
from nltk.collocations import BigramCollocationFinder
from nltk.metrics import BigramAssocMeasures
def bag_of_bigrams_words(words, score_fn=BigramAssocMeasures.chi_sq,
n=200):
    bigram_finder = BigramCollocationFinder.from_words(words)
    bigrams = bigram_finder.nbest(score_fn, n)
    return bag of words(words + bigrams)
```

The bigrams will be present in the returned dict as (word1, word2) and will have the value as True. Using the same example words as we did earlier, we get all words plus every bigram:

```
>>> from featx import bag_of_bigrams_words
>>> bag_of_bigrams_words(['the', 'quick', 'brown', 'fox'])
{'brown': True, ('brown', 'fox'): True, ('the', 'quick'):
True, 'fox': True, ('quick', 'brown'): True, 'quick': True, 'the':
True}
```

You can change the maximum number of bigrams found by altering the keyword argument *n*.

See also

The Discovering word collocations recipe of <u>Chapter 1</u>, Tokenizing Text and WordNet Basics, covers the BigramCollocationFinder class in more detail. In the next recipe, we will train a NaiveBayesClassifier class using feature sets created with the bag of words model.

Training a Naive Bayes classifier

Now that we can extract features from text, we can train a classifier. The easiest classifier to get started with is the NaiveBayesClassifier class. It uses the **Bayes theorem** to predict the probability that a given feature set belongs to a particular label. The formula is:

P(label | features) = P(label) * P(features | label) / P(features)

The following list describes the various parameters from the previous formula:

- P(label): This is the prior probability of the label occurring, which is the likelihood that a random feature set will have the label. This is based on the number of training instances with the label compared to the total number of training instances. For example, if 60/100 training instances have the label, the prior probability of the label is 60%.
- P(features | label): This is the prior probability of a given feature set being classified as that label. This is based on which features have occurred with each label in the training data.
- P(features): This is the prior probability of a given feature set occurring. This is the likelihood of a random feature set being the same as the given feature set, and is based on the observed feature sets in the training data. For example, if the given feature set occurs twice in 100 training instances, the prior probability is 2%.
- P(label | features): This tells us the probability that the given features should have that label. If this value is high, then we can be reasonably confident that the label is correct for the given features.

Getting ready

We are going to be using the movie_reviews corpus for our initial classification examples. This corpus contains two categories of text: pos and neg. These categories are exclusive, which makes a classifier trained on them a **binary classifier**. Binary classifiers have only two classification labels, and will always choose one or the other.

Each file in the movie_reviews corpus is composed of either positive or negative movie reviews. We will be using each file as a single instance for both training and testing the classifier. Because of the nature of the text and its categories, the classification we will be doing is a form of sentiment analysis. If the classifier returns pos, then the text expresses a positive sentiment, whereas if we get neg, then the text expresses a negative sentiment.

How to do it...

For training, we need to first create a list of labeled feature sets. This list should be of the form [(featureset, label)], where the featureset variable is a dict and label is the known class label for the featureset. The label_feats_from_corpus() function in featx.py takes a corpus, such as movie_reviews, and a feature_detector function, which defaults to bag_of_words. It then constructs and returns a mapping of the form {label: [featureset]}. We can use this mapping to create a list of labeled training instances and testing instances. The reason to do it this way is to get a fair sample from each label. It is important to get a fair sample, because parts of

the corpus may be (unintentionally) biased towards one label or the other. Getting a fair sample should eliminate this possible bias:

```
import collections

def label_feats_from_corpus(corp, feature_detector=bag_of_words):
    label_feats = collections.defaultdict(list)
    for label in corp.categories():
        for fileid in corp.fileids(categories=[label]):
            feats = feature_detector(corp.words(fileids=[fileid]))
            label_feats[label].append(feats)
        return label feats
```

Once we can get a mapping of label | feature sets, we want to construct a list of labeled training instances and testing instances. The split_label_feats() function in featx.py takes a mapping returned from label_feats_from_corpus() and splits each list of feature sets into labeled training and testing instances:

```
def split_label_feats(lfeats, split=0.75):
    train_feats = []
    test_feats = []
    for label, feats in lfeats.items():
        cutoff = int(len(feats) * split)
        train_feats.extend([(feat, label) for feat in feats[:cutoff]])
        test_feats.extend([(feat, label) for feat in feats[cutoff:]])
        return train feats, test feats
```

Using these functions with the movie_reviews corpus gives us the lists of labeled feature sets we need to train and test a classifier:

```
>>> from nltk.corpus import movie_reviews
>>> from featx import label_feats_from_corpus, split_label_feats
>>> movie_reviews.categories()
['neg', 'pos']
>>> lfeats = label_feats_from_corpus(movie_reviews)
>>> lfeats.keys()
dict_keys(['neg', 'pos'])
>>> train_feats, test_feats = split_label_feats(lfeats, split=0.75)
>>> len(train_feats)
1500
>>> len(test_feats)
500
```

So there are 1000 pos files, 1000 neg files, and we end up with 1500 labeled training instances and 500 labeled testing instances, each composed of equal parts of pos and neg. If we were using a different dataset, where the classes were not balanced, our training and testing data would have the same imbalance.

Now we can train a NaiveBayesClassifier class using its train() class method:

```
>>> from nltk.classify import NaiveBayesClassifier
>>> nb_classifier = NaiveBayesClassifier.train(train_feats)
>>> nb_classifier.labels()
['neg', 'pos']
```

Let's test the classifier on a couple of made up reviews. The classify() method takes a single argument, which should be a feature set. We can use the same bag_of_words() feature detector on a list of words to get our feature set:

```
>>> from featx import bag_of_words
>>> negfeat = bag_of_words(['the', 'plot', 'was', 'ludicrous'])
>>> nb_classifier.classify(negfeat)
'neg'
>>> posfeat = bag_of_words(['kate', 'winslet', 'is', 'accessible'])
>>> nb_classifier.classify(posfeat)
'pos'
```

How it works...

The label_feats_from_corpus() function assumes that the corpus is categorized, and that a single file represents a single instance for feature extraction. It iterates over each category label, and extracts features from each file in that category using the feature_detector() function, which defaults to bag_of_words(). It returns a dict whose keys are the category labels, and the values are lists of instances for that category.

If we had label_feats_from_corpus() return a list of labeled feature sets instead of a dict, it would be much harder to get balanced training data. The list would be ordered by label, and if you took a slice of it, you would almost certainly be getting far more of one label than another. By returning a dict, you can take slices from the feature sets of each label, in the same proportion that exists in the data.

Now we need to split the labeled feature sets into training and testing instances using split_label_feats(). This function allows us to take a fair sample of labeled feature sets from each label, using the split keyword argument to determine the size of the sample. The split argument defaults to 0.75, which means the first 75% of the labeled feature sets for each label will be used for training, and the remaining 25% will be used for testing.

Once we have gotten our training and testing feats split up, we train a classifier using the NaiveBayesClassifier.train() method. This class method builds two probability distributions for calculating prior probabilities. These are passed into the NaiveBayesClassifier constructor. The label_probdist constructor contains the prior probability for each label, or P(label). The feature_probdist constructor contains P(feature name = feature value | label). In our case, it will store P(word=True | label). Both are calculated based on the frequency of occurrence of each label and each feature name and value in the training data.
The NaiveBayesClassifier class inherits from ClassifierI, which requires subclasses to provide a labels () method, and at least one of the classify () or prob_classify () methods. The following diagram shows other methods, which will be covered shortly:



There's more...

We can test the accuracy of the classifier using nltk.classify.util.accuracy() and the test_feats variable created previously:

```
>>> from nltk.classify.util import accuracy
>>> accuracy(nb_classifier, test_feats)
0.728
```

This tells us that the classifier correctly guessed the label of nearly 73% of the test feature sets.

Tip

The code in this chapter is run with the PYTHONHASHSEED=0 environment variable so that accuracy calculations are consistent. If you run the code with a different value for PYTHONHASHSEED, or without setting this environment variable, your accuracy values may differ.

Classification probability

While the classify() method returns only a single label, you can use the prob_classify() method to get the classification probability of each label. This can be useful if you want to use probability thresholds for classification:

```
>>> probs = nb_classifier.prob_classify(test_feats[0][0])
>>> probs.samples()
dict_keys(['neg', 'pos'])
>>> probs.max()
'pos'
>>> probs.prob('pos')
0.9999999646430913
>>> probs.prob('neg')
3.535688969240647e-08
```

In this case, the classifier says that the first test instance is nearly 100% likely to be pos. Other instances may have more mixed probabilities. For example, if the classifier says an instance is 60% pos and 40% neg, that means the classifier is 60% sure the instance is pos, but there is a 40% chance that it is neg. It can be useful to know this for situations where you only want to use strongly classified instances, with a threshold of 80% or greater.

Most informative features

The NaiveBayesClassifier class has two methods that are quite useful for learning about your data. Both methods take a keyword argument n to control how many results to show. The most_informative_features() method returns a list of the form [(feature name, feature value)] ordered by most informative to least informative. In our case, the feature value will always be True:

```
>>> nb_classifier.most_informative_features(n=5)
[('magnificent', True), ('outstanding', True), ('insulting', True),
('vulnerable', True), ('ludicrous', True)]
```

The show_most_informative_features() method will print out the results from most_informative_features() and will also include the probability of a feature pair belonging to each label:

```
>>> nb_classifier.show_most_informative_features(n=5)
Most Informative Features
```

```
magnificent = Truepos : neg = 15.0 : 1.0outstanding = Truepos : neg = 13.6 : 1.0insulting = Trueneg : pos = 13.0 : 1.0vulnerable = Truepos : neg = 12.3 : 1.0ludicrous = Trueneg : pos = 11.8 : 1.0
```

The informativeness, or information gain, of each feature pair is based on the prior probability of the feature pair occurring for each label. More informative features are those that occur primarily in one label and not on the other. The less informative features are those that occur frequently with both labels. Another way to state this is that the entropy of the classifier decreases more when using a more informative feature. See https://en.wikipedia.org/wiki/Information_gain_in_decision_trees for more on information gain and entropy (while it specifically mentions decision trees, the same concepts are applicable to all classifiers).

Training estimator

During training, the NaiveBayesClassifier class constructs probability distributions for each feature using an estimator parameter, which defaults to nltk.probability.ELEProbDist. The estimator is used to calculate the probability of a label parameter given a specific feature. In ELEProbDist, **ELE** stands for **Expected Likelihood Estimate**, and the formula for calculating the label probabilities for a given feature is (c+0.5)/(N+B/2). Here, *c* is the count of times a single feature occurs, *N*

is the total number of feature outcomes observed, and *B* is the number of bins or unique features in the feature set. In cases where the feature values are all True, N == B. In other cases, where the number of times a feature occurs is recorded, then $N \ge B$.

You can use any estimator parameter you want, and there are quite a few to choose from. The only constraints are that it must inherit from nltk.probability.ProbDistI and its constructor must take a bins keyword argument. Here's an example using the LaplaceProdDist class, which uses the formula (c+1)/(N+B):

```
>>> from nltk.probability import LaplaceProbDist
>>> nb_classifier = NaiveBayesClassifier.train(train_feats,
estimator=LaplaceProbDist)
>>> accuracy(nb_classifier, test_feats)
0.716
```

As you can see, accuracy is slightly lower, so choose your estimator parameter carefully.

You cannot use nltk.probability.MLEProbDist as the estimator, or any ProbDistI subclass that does not take the bins keyword argument. Training will fail with TypeError: __init__() got an unexpected keyword argument 'bins'.

Manual training

You don't have to use the train() class method to construct a NaiveBayesClassifier. You can instead create the label_probdist and feature_probdist variables manually. The label_probdist variable should be an instance of ProbDistI, and should contain the prior probabilities for each label. The feature_probdist variable should be a dict whose keys are tuples of the form (label, feature name) and whose values are instances of ProbDistI that have the probabilities for each feature value. In our case, each ProbDistI should have only one value, True=1. Here's a very simple example using a manually constructed DictionaryProbDist class:

```
>>> from nltk.probability import DictionaryProbDist
>>> label_probdist = DictionaryProbDist({'pos': 0.5, 'neg': 0.5})
>>> true_probdist = DictionaryProbDist({True: 1})
>>> feature_probdist = {('pos', 'yes'): true_probdist, ('neg',
'no'): true_probdist}
>>> classifier = NaiveBayesClassifier(label_probdist,
feature_probdist)
>>> classifier.classify({'yes': True})
'pos'
>>> classifier.classify({'no': True})
'neg'
```

See also

In the next recipes, we will train two more classifiers, DecisionTreeClassifier and MaxentClassifier. In the *Measuring precision and recall of a classifier* recipe in this chapter, we will use precision and recall instead of accuracy to evaluate the classifiers. And then in the *Calculating high information words* recipe, we will see how using only the most informative features can improve classifier performance.

The movie_reviews corpus is an instance of CategorizedPlaintextCorpusReader, which is covered in the *Creating a categorized text corpus* recipe in <u>Chapter 3</u>, *Creating Custom Corpora*.

Training a decision tree classifier

The DecisionTreeClassifier class works by creating a tree structure, where each node corresponds to a feature name and the branches correspond to the feature values. Tracing down the branches, you get to the leaves of the tree, which are the classification labels.

How to do it...

Using the same train_feats and test_feats variables we created from the movie_reviews corpus in the previous recipe, we can call the DecisionTreeClassifier.train() class method to get a trained classifier. We pass binary=True because all of our features are binary: either the word is present or it's not. For other classification use cases where you have multivalued features, you will want to stick to the default binary=False.

Tip

In this context, binary refers to *feature values*, and is not to be confused with a *binary classifier*. Our word features are binary because the value is either True or the word is not present. If our features could take more than two values, we would have to use binary=False. A **binary classifier**, on the other hand, is a classifier that only chooses between two labels. In our case, we are training a binary DecisionTreeClassifier on binary features. But it's also possible to have a binary classifier with non-binary features, or a non-binary classifier with binary features.

The following is the code for training and evaluating the accuracy of a DecisionTreeClassifier class:

```
>>> from nltk.classify import DecisionTreeClassifier
>>> dt_classifier = DecisionTreeClassifier.train(train_feats,
binary=True, entropy_cutoff=0.8, depth_cutoff=5, support_cutoff=30)
>>> accuracy(dt_classifier, test_feats)
0.688
```

The DecisionTreeClassifier class can take much longer to train than the NaiveBayesClassifier class. For that reason, I have overridden the default parameters so it trains faster. These parameters will be explained later.

How it works...

The DecisionTreeClassifier class, like the NaiveBayesClassifier class, is also an instance of ClassifierI, as shown in the following diagram:



During training, the DecisionTreeClassifier class creates a tree where the child nodes are also instances of DecisionTreeClassifier. The leaf nodes contain only a single label, while the intermediate child nodes contain decision mappings for each feature. These decisions map each feature value to another DecisionTreeClassifier, which itself may contain decisions for another feature, or it may be a final leaf node with a classification label. The train() class method builds this tree from the ground up, starting with the leaf nodes. It then refines itself to minimize the number of decisions needed to get to a label by putting the most informative features at the top.

To classify, the DecisionTreeClassifier class looks at the given feature set and traces down the tree, using known feature names and values to make decisions. Because we are creating a binary tree, each DecisionTreeClassifier instance also has a default decision tree, which it uses when a known feature is not present in the feature set being classified. This is a common occurrence in text-based feature sets, and indicates that a known word was not in the text being classified. This also contributes information towards a classification decision.

There's more...

The parameters passed into DecisionTreeClassifier.train() can be tweaked to improve accuracy or decrease training time. Generally, if you want to improve accuracy, you must accept a longer training time and if you want to decrease the training time, the accuracy will most likely decrease as well. But be careful not to optimize for accuracy too much. A really high accuracy may indicate overfitting, which means the classifier will be excellent at classifying the training data, but not so good on data it has never seen. See https://en.wikipedia.org/wiki/Over_fitting for more on this concept.

Controlling uncertainty with entropy_cutoff

Entropy is the uncertainty of the outcome. As entropy approaches 1.0, uncertainty increases. Conversely, as entropy approaches 0.0, uncertainty decreases. In other words, when you have similar probabilities, the entropy will be high as each probability has a similar likelihood (or uncertainty of occurrence). But the more the probabilities differ, the lower the entropy will be.

The entropy_cutoff value is used during the tree refinement process. The tree refinement process is how the decision tree decides to create new branches. If the entropy of the probability distribution of label choices in the tree is greater than the entropy_cutoff value, then the tree is refined further by creating more branches. But if the entropy is lower than the entropy_cutoff value, then tree refinement is halted.

Entropy is calculated by giving nltk.probability.entropy() a MLEProbDist value created from a FreqDist of label counts. Here's an example showing the entropy of various FreqDist values. The value of 'pos' is kept at 30, while the value of 'neg' is manipulated to show that when 'neg' is close to 'pos', entropy increases, but when it is closer to 1, entropy decreases:

```
>>> from nltk.probability import FreqDist, MLEProbDist, entropy
>>> fd = FreqDist({'pos': 30, 'neg': 10})
>>> entropy(MLEProbDist(fd))
0.8112781244591328
>>> fd['neg'] = 25
>>> entropy(MLEProbDist(fd))
0.9940302114769565
>>> fd['neg'] = 30
>>> entropy(MLEProbDist(fd))
1.0
>>> fd['neg'] = 1
>>> entropy(MLEProbDist(fd))
0.20559250818508304
```

What this all means is that if the label occurrence is very skewed one way or the other, the tree doesn't need to be refined because entropy/uncertainty is low. But when the entropy is greater than entropy_cutoff, then the tree must be refined with further decisions to reduce the uncertainty. Higher values of entropy_cutoff will decrease both accuracy and training time.

Controlling tree depth with depth_cutoff

The depth_cutoff value is also used during refinement to control the depth of the tree. The final decision tree will never be deeper than the depth_cutoff value. The default value is 100, which means that classification may require up to 100 decisions before reaching a leaf node. Decreasing the depth_cutoff value will decrease the training time and most likely decrease the accuracy as well.

Controlling decisions with support_cutoff

The support_cutoff value controls how many labeled feature sets are required to refine the tree. As the DecisionTreeClassifier class refines itself, labeled feature sets are eliminated once they no longer provide value to the training process. When the number of labeled feature sets is less than or equal to support cutoff, refinement stops, at least for that section of the tree.

Another way to look at it is that support_cutoff specifies the minimum number of instances that are required to make a decision about a feature. If support_cutoff is 20, and you have less than 20 labeled feature sets with a given feature, then you don't have enough instances to make a good decision, and refinement around that feature must come to a stop.

See also

The previous recipe covered the creation of training and test feature sets from the movie_reviews corpus. In the next recipe, we will cover training a MaxentClassifier class, and in the *Measuring precision and recall of a classifier* recipe in this chapter, we will use precision and recall to evaluate all the classifiers.

Training a maximum entropy classifier

The third classifier we will cover is the MaxentClassifier class, also known as a **conditional exponential classifier** or **logistic regression classifier**. The **maximum entropy classifier** converts labeled feature sets to vectors using encoding. This encoded vector is then used to calculate weights for each feature that can then be combined to determine the most likely label for a feature set. For more details on the math behind this, see <u>https://en.wikipedia.org/wiki/Maximum_entropy_classifier</u>.

Getting ready

The MaxentClassifier class requires the NumPy package. This is because the feature encodings use NumPy arrays. You can find installation details at the following link:

http://www.scipy.org/Installing_SciPy

Tip

The MaxentClassifier class algorithms can be quite memory hungry, so you may want to quit all your other programs while training a MaxentClassifier class, just to be safe.

How to do it ...

We will use the same train_feats and test_feats variables from the movie_reviews corpus that we constructed before, and call the MaxentClassifier.train() class method. Like the DecisionTreeClassifier class, MaxentClassifier.train() has its own specific parameters that I have tweaked to speed up training. These parameters will be explained in more detail later:

```
>>> from nltk.classify import MaxentClassifier
>>> me_classifier = MaxentClassifier.train(train_feats, trace=0,
max_iter=1, min_lldelta=0.5)
>>> accuracy(me_classifier, test_feats)
0.5
```

The reason this classifier has such a low accuracy is because I set the parameters such that it is unable to learn a more accurate model. This is due to the time required to train a suitable model using the default iis algorithm. A better algorithm is gis, which can be trained like this:

```
>>> me_classifier = MaxentClassifier.train(train_feats,
algorithm='gis', trace=0, max_iter=10, min_lldelta=0.5)
>>> accuracy(me_classifier, test_feats)
0.722
```

The gis algorithm is a bit faster and generally more accurate than the default is algorithm, and can be allowed to run for up to 10 iterations in a reasonable amount of time. Both is and gis will be explained in more detail in the next section.

Tip

If training is taking a long time, you can usually cut it off manually by hitting Ctrl + C. This should stop the current iteration and still return a classifier based on whatever state the model is in.

How it works...

Like the previous classifiers, MaxentClassifier inherits from ClassifierI, as shown in the following diagram:



Depending on the algorithm, MaxentClassifier.train() calls one of the training functions in the nltk.classify.maxent module. The default algorithm is iis, and the function used is train_maxent_classifier_with_iis(). The other algorithm that's included is gis, which uses the train_maxent_classifier_with_gis() function. **GIS** stands for **General Iterative Scaling**, while **IIS** stands for **Improved Iterative Scaling**. The only difference between these two algorithms that really matters is that gis is much faster than iis.

If megam is installed and you specify the megam algorithm, then

train_maxent_classifier_with_megam() is used (megam is covered in more detail in the
next section).

Note

Previous versions of NLTK provided additional algorithms if SciPy was installed. These algorithms have been removed, but many other algorithms can be used in conjunction with scikit-learn, which we will cover in the next recipe, *Training scikit-learn classifiers*.

The basic idea behind the maximum entropy model is to build some probability distributions that fit the observed data and then choose whichever probability distribution has the highest entropy. The gis and iis algorithms do so by iteratively improving the weights used to classify features. This is where the max_iter and min_lldelta parameters come into play.

The max_iter variable specifies the maximum number of iterations to go through and update the weights. More iterations will generally improve accuracy, but only up to a point. Eventually, the changes from one iteration to the next will hit a plateau and further iterations are useless.

The min_lldelta variable specifies the minimum change in the log likelihood required to continue iteratively improving the weights. Before beginning training iterations, an instance of nltk.classify.util.CutoffChecker is created. When its check() method is called, it uses functions such as nltk.classify.util.log_likelihood() to decide whether the cutoff limits have been reached. The log likelihood is the log (using math.log()) of the average label probability of the training data (which is the log of the average likelihood of a label). As the log likelihood increases, the model improves. But it too will reach a plateau where further increases are so small that there is no point in continuing. Specifying the min_lldelta variable allows you to control how much each iteration must increase the log likelihood before stopping the iterations.

There's more...

Like the NaiveBayesClassifier class, you can see the most informative features by calling the show most informative features() method:

```
>>> me_classifier.show_most_informative_features(n=4)
-0.740 worst==True and label is 'pos'
0.740 worst==True and label is 'neg'
0.715 bad==True and label is 'neg'
-0.715 bad==True and label is 'pos'
```

The numbers shown are the weights for each feature. This tells us that the word worst is negatively weighted towards the pos label, and positively weighted towards the neg label. In other words, if the word worst is found in the feature set, then there's a strong possibility that the text should be classified neg.

Megam algorithm

If you have installed the megam package, then you can use the megam algorithm. It's faster than the included algorithms and much more accurate, but it can also be difficult to install. Installation instructions and information can be found at the following link:

http://www.umiacs.umd.edu/~hal/megam/

The nltk.classify.megam.config_megam() function can be used to specify where the megam executable is found. Or, if megam can be found in the standard executable paths, NLTK will configure it automatically:

```
>>> me_classifier = MaxentClassifier.train(train_feats,
algorithm='megam', trace=0, max_iter=10)
[Found megam: /usr/local/bin/megam]
>>> accuracy(me_classifier, test_feats)
0.8679999999999999999
```

See also

The *Bag of words feature extraction* and the *Training a Naive Bayes classifier* recipes in this chapter show how to construct the training and testing features from the movie_reviews corpus. The next recipe shows how to train even more accurate classifiers with scikit-learn. After that, we will cover how and why to evaluate a classifier using precision and recall instead of accuracy, in the *Measuring precision and recall of a classifier* recipe.

Training scikit-learn classifiers

Scikit-learn is one of the best machine learning libraries available in any programming language. It contains all sorts of machine learning algorithms for many different purposes, but they all follow the same fit/predict design pattern:

- Fit the model to the data
- Use the model to make predictions

We won't be accessing the scikit-learn models directly in this recipe. Instead, we'll be using NLTK's SklearnClassifier class, which is a wrapper class around a scikit-learn model to make it conform to NLTK's ClassifierI interface. This means that the SklearnClassifier class can be trained and used much like the classifiers we've used in the previous recipes in this chapter.

Note

I may use the terms scikit-learn and sklearn interchangeably in this recipe.

Getting ready

To use the SklearnClassifier class, you must have scikit-learn installed. Instructions are available online at <u>http://scikit-learn.org/stable/install.html</u>. If you have all the dependencies installed, such as NumPy and SciPy, you should be able to install scikit-learn with pip:

\$ pip install scikit-learn

To test if everything is installed correctly, try to import the SklearnClassifier class:

>>> from nltk.classify import scikitlearn

If the import fails, then you are still missing scikit-learn and its dependencies.

How to do it...

Training an SklearnClassifier class has a slightly different series of steps than classifiers covered in the previous recipes of this chapter:

- 1. Create training features (covered in the previous recipes).
- 2. Choose and import an sklearn algorithm.
- 3. Construct an SklearnClassifier class with the chosen algorithm.
- 4. Train the SklearnClassifier class with your training features.

The main difference with NLTK classifiers is that steps 3 and 4 are usually combined. Let's put this into practice using the MultinomialNB classifier from sklearn. Refer to the earlier recipe, *Training a Naive Bayes classifier*, for details on constructing train_feats and test_feats:

```
>>> from nltk.classify.scikitlearn import SklearnClassifier
>>> from sklearn.naive_bayes import MultinomialNB
>>> sk_classifier = SklearnClassifier(MultinomialNB())
>>> sk_classifier.train(train_feats)
<SklearnClassifier(MultinomialNB(alpha=1.0, class_prior=None,
fit prior=True))>
```

Now that we have a trained classifier, we can evaluate the accuracy:

```
>>> accuracy(sk_classifier, test_feats)
0.83
```

How it works...

The SklearnClassifier class is a small wrapper class whose main job is to convert NLTK feature dictionaries into sklearn compatible feature vectors. Here's the complete class code, minus all comments, docstrings, and most imports:

```
from sklearn.feature extraction import DictVectorizer
from sklearn.preprocessing import LabelEncoder
class SklearnClassifier(ClassifierI):
    def init (self, estimator, dtype=float, sparse=True):
        self. clf = estimator
        self. encoder = LabelEncoder()
        self. vectorizer = DictVectorizer(dtype=dtype, sparse=sparse)
    def batch classify(self, featuresets):
        X = self. vectorizer.transform(featuresets)
        classes = self. encoder.classes
        return [classes[i] for i in self. clf.predict(X)]
    def batch prob classify(self, featuresets):
        X = self. vectorizer.transform(featuresets)
        y_proba_list = self._clf.predict_proba(X)
        return [self. make probdist(y proba) for y proba in
y_proba list]
    def labels(self):
        return list(self._encoder.classes_)
    def train(self, labeled featuresets):
        X, y = list(compat.izip(*labeled featuresets))
        X = self. vectorizer.fit transform(X)
        y = self. encoder.fit transform(y)
        self. clf.fit(X, y)
        return self
```

```
def _make_probdist(self, y_proba):
    classes = self._encoder.classes_
    return DictionaryProbDist(dict((classes[i], p) for i, p in
enumerate(y_proba)))
```

The class is initialized with an estimator, which is the algorithm we pass in, such as MultinomialNB. It then creates a LabelEncoder and DictVectorizer object. The LabelEncoder object transforms label strings to numbers. For example, the pos class may be encoded as 1, and the neg class may be encoded as 0. The DictVectorizer object is for transforming the NLTK feature dictionaries into sklearn compatible feature vectors.

In the train() method, the labeled feature sets are first encoded and transformed using the LabelEncoder and DictVectorizer objects. Then, the model we gave as an estimator, such as MultinomialNB, is fit to the data. Because the sk_classifier class is created before it is trained, you might forget to train it before you try to do any classification. Luckily, this will produce an exception with the message 'DictVectorizer' object has no attribute 'vocabulary_'. Since Python dictionaries are unordered (unlike vectors), the DictVectorizer object must maintain a vocabulary in order to know where in the vector a feature value belongs. This ensures that new feature dictionaries are vectorized in a manner consistent with the training features.

To classify a feature set, it is transformed to a vector and then passed to the trained model's predict() method. This is done in the <code>batch_classify()</code> method.

There's more...

The scikit-learn model contains many different algorithms for classification, and this recipe covers only a few. But not all the classification algorithms are compatible with the SklearnClassifier class, because it uses sparse vectors. Sparse vectors are more efficient because they only store the data they need, using a kind of data compression. However, some algorithms, such as sklearn's DecisionTreeClassifier, require dense vectors, which store every entry in the vector, even if it has no value. If you try a different algorithm with the SklearnClassifier class and get an exception, this is probably why.

Comparing Naive Bayes algorithms

As you saw earlier, the MultinomialNB algorithm got an accuracy of 83%. This is much higher than the 72.8% accuracy we got from NLTK's NaiveBayesClassifier class. The big difference between these two algorithms is that MultinomialNB can work with discrete feature values, such as word frequencies, whereas NaiveBayesClassifier class assumes a small set of feature values, such as strings or Booleans. There is another sklearn Naive Bayes algorithm, BernoulliNB, which can also work with discrete values by binarizing those values, so that the final values are 1 or 0. Our features are actually already binarized, because the feature values are True or False:

>>> from sklearn.naive_bayes import BernoulliNB
>>> sk classifier = SklearnClassifier(BernoulliNB())

```
>>> sk_classifier.train(train_feats)
<SklearnClassifier(BernoulliNB(alpha=1.0, binarize=0.0,
class_prior=None, fit_prior=True))>
>>> accuracy(sk_classifier, test_feats)
0.812
```

Clearly, the sklearn algorithm performs better than NLTK's Naive Bayes implementation. The sklearn classifiers also have a much smaller memory footprint, and will produce much smaller pickle files on disk. Their classification speed is often slightly slower than the NaiveBayesClassifier class, but I think the accuracy and memory gains are quite worth it.

Training with logistic regression

Earlier in this chapter, we covered the maximum entropy classifier. This algorithm is also known as **logistic regression**, and scikit-learn provides a corresponding implementation.

Again, we see that the sklearn algorithm has better performance than NLTK's MaxentClassifier, which only had 72.2% accuracy. The logistic regression algorithm also has a much faster training time than the IIS or GIS algorithms, even when those algorithms have a limited number of iterations. This can be explained by sklearn's focus on optimized numeric processing using NumPy.

Training with LinearSVC

A third family of algorithms that NLTK does not support directly is **Support Vector Machines**, or **SVM**. These algorithms have been shown to be effective at learning on high-dimensional data, such as text classification, where every word feature counts as a dimension. You can learn more about support vector machines at <u>https://en.wikipedia.org/wiki/Support_vector_machine</u>. Here are some examples of using the sklearn implementations:

```
>>> from sklearn.svm import SVC
>>> sk_classifier = SklearnClassifier(svm.SVC())
>>> sk_classifier.train(train_feats)
<SklearnClassifier(SVC(C=1.0, cache_size=200, class_weight=None,
coef0=0.0, degree=3, gamma=0.0,
    kernel='rbf', max_iter=-1, probability=False, random_state=None,
    shrinking=True, tol=0.001, verbose=False))>
>>> accuracy(sk_classifier, test_feats)
0.69
```

```
>>> from sklearn.svm import LinearSVC
>>> sk classifier = SklearnClassifier(LinearSVC())
>>> sk classifier.train(train feats)
<SklearnClassifier(LinearSVC(C=1.0, class weight=None, dual=True,
fit intercept=True,
         intercept scaling=1, loss='l2', multi class='ovr',
penalty='12',
         random state=None, tol=0.0001, verbose=0))>
>>> accuracy(sk classifier, test feats)
0.864
>>> from sklearn.svm import NuSVC
>>> sk classifier = SklearnClassifier(svm.NuSVC())
>>> sk classifier.train(train feats)
/Users/jacob/py3env/lib/python3.3/site-packages/scipy/sparse/
compressed.py:119: UserWarning: indptr array has non-integer dtype
(float64)
  % self.indptr.dtype.name)
<SklearnClassifier(NuSVC(cache size=200, coef0=0.0, degree=3,
gamma=0.0, kernel='rbf',
  max iter=-1, nu=0.5, probability=False, random state=None,
   shrinking=True, tol=0.001, verbose=False))>
>>> accuracy(sk classifier, test feats)
0.882
```

You can see that in this case, NuSVC is the most accurate SVM classifier, just above LinearSVC, while SVC is much less accurate than either. These accuracy differences are a result of the different algorithm implementations and the default parameters. You can learn more about these specific implementations at the following link:

http://scikit-learn.org/stable/modules/svm.html

See also

If you are interested in exploring more aspects of machine learning with Python, the scikit-learn documentation is a great place to start:

http://scikit-learn.org/stable/documentation.html

Earlier in this chapter, we covered the *Training a Naive Bayes classifier* and *Training a maximum entropy classifier* recipes. We will use the LinearSVC and NuSVC classifiers again in the following recipes.

Measuring precision and recall of a classifier

In addition to accuracy, there are a number of other metrics used to evaluate classifiers. Two of the most common are **precision** and **recall**. To understand these two metrics, we must first understand **false positives** and **false negatives**. False positives happen when a classifier classifier a feature set with a label it shouldn't have gotten. False negatives happen when a classifier doesn't assign a label to a feature set that should have it. In a binary classifier, these errors happen at the same time.

Here's an example: the classifier classifies a movie review as pos when it should have been neg. This counts as a false positive for the pos label, and a false negative for the neg label. If the classifier had correctly guessed neg, then it would count as a **true positive** for the neg label, and a **true negative** for the pos label.

How does this apply to precision and recall? Precision is the *lack of false positives*, and recall is the *lack of false negatives*. As you will see, these two metrics are often in competition: the more precise a classifier is, the lower the recall, and vice versa.

How to do it...

Let's calculate the precision and recall of the NaiveBayesClassifier class we trained in the *Training a Naive Bayes classifier* recipe. The precision_recall() function in classification.py looks like this:

```
import collections
from nltk import metrics
def precision recall(classifier, testfeats):
  refsets = collections.defaultdict(set)
  testsets = collections.defaultdict(set)
  for i, (feats, label) in enumerate(testfeats):
    refsets[label].add(i)
    observed = classifier.classify(feats)
    testsets[observed].add(i)
  precisions = \{\}
  recalls = \{\}
  for label in classifier.labels():
    precisions[label] = metrics.precision(refsets[label],
testsets[label])
    recalls[label] = metrics.recall(refsets[label], testsets[label])
  return precisions, recalls
```

This function takes two arguments:

- The trained classifier
- Labeled test features, also known as a gold standard

These are the same arguments you pass to accuracy(). The precision_recall() function returns two dictionaries; the first holds the precision for each label, and the second holds the recall for each label. Here's an example usage with nb_classifier and test_feats we created in the *Training a Naive Bayes classifier* recipe earlier:

```
>>> from classification import precision_recall
>>> nb_precisions, nb_recalls = precision_recall(nb_classifier,
test_feats)
>>> nb_precisions['pos']
0.6413612565445026
>>> nb_precisions['neg']
0.9576271186440678
>>> nb_recalls['pos']
0.98
>>> nb_recalls['pos']
0.452
```

This tells us that while the NaiveBayesClassifier class can correctly identify most of the pos feature sets (high recall), it also classifies many of the neg feature sets as pos (low precision). This behavior contributes to high precision but low recall for the neg label—as the neg label isn't given often (low recall), when it is, it's very likely to be correct (high precision). The conclusion could be that there are certain common words that are biased towards the pos label, but occur frequently enough in the neg feature sets to cause mis-classifications. To correct this behavior, we will use only the most informative words in the next recipe, *Calculating high information words*.

How it works...

To calculate precision and recall, we must build two sets for each label. The first set is known as the **reference set**, and contains all the correct values. The second set is called the **test set**, and contains the values guessed by the classifier. These two sets are compared to calculate the precision or recall for each label.

Precision is defined as the size of the intersection of both sets divided by the size of the test set. In other words, the percentage of the test set that was guessed correctly. In Python, the code is float (len(reference.intersection(test))) / len(test).

Recall is the size of the intersection of both sets divided by the size of the reference set, or the percentage of the reference set that was guessed correctly. The Python code is float (len(reference.intersection(test))) / len(reference).

The precision_recall() function in classification.py iterates over the labeled test features and classifies each one. We store the numeric index of the feature set (starting with 0) in the reference set for the known training label, and also store the index in the test set for the guessed label. If

the classifier guesses pos but the training label is neg, then the index is stored in the reference set for neg and the test set for pos.

Note

We use the numeric index because the feature sets aren't hashable, and we need a unique value for each feature set.

The nltk.metrics package contains functions for calculating both precision and recall, so all we really have to do is build the sets and then call the appropriate function.

There's more...

Let's try it with the MaxentClassifier class of GIS, which we trained in the *Training a maximum entropy classifier* recipe:

```
>>> me_precisions, me_recalls = precision_recall(me_classifier,
test_feats)
>>> me_precisions['pos']
0.6456692913385826
>>> me_precisions['neg']
0.9663865546218487
>>> me_recalls['pos']
0.984
>>> me_recalls['neg']
0.46
```

This classifier is just as biased as the NaiveBayesClassifier class. Chances are it would be less biased if allowed to train for more iterations and/or approach a smaller log likelihood change. Now, let's try the SklearnClassifier class of NuSVC from the previous recipe, *Training scikit-learn classifiers*:

```
>>> sk_precisions, sk_recalls = precision_recall(sk_classifier,
test_feats)
>>> sk_precisions['pos']
0.9063829787234042
>>> sk_precisions['neg']
0.8603773584905661
>>> sk_recalls['pos']
0.852
>>> sk_recalls['neg']
0.912
```

In this case, the label bias is much less significant, and the reason is that the SklearnClassifier class of NuSVC weighs its features according to its own internal model. This is also true for logistic regression and many of the other scikit-learn algorithms. Words that are more significant are

those that occur primarily in a single label, and will get higher weights in the model. Words that are common to both labels will get lower weights, as they are less significant.

F-measure

The **F-measure** is defined as the weighted harmonic mean of precision and recall. If p is the precision, and r is the recall, the formula is:

1/(alpha/p + (1-alpha)/r)

Here, *alpha* is a weighing constant that defaults to 0.5. You can use

nltk.metrics.f_measure() to get the F-measure. It takes the same arguments as for the precision() and recall() functions: a reference set and a test set. It's often used instead of accuracy to measure a classifier, because if either precision or recall are very low, it will be reflected in the F-measure, but not necessarily in the accuracy. However, I find precision and recall to be much more useful metrics by themselves, as the F-measure can obscure the kinds of imbalances we saw with the NaiveBayesClassifier class.

See also

In the *Training a Naive Bayes classifier* recipe, we collected training and testing feature sets and trained the NaiveBayesClassifier class. The MaxentClassifier class was trained in the *Training a maximum entropy classifier* recipe, and the SklearnClassifier class was trained in the *Training scikit-learn classifiers* recipe. In the next recipe, we will explore eliminating the less significant words, and use only the high information words to create our feature sets.

Calculating high information words

A high information word is a word that is strongly biased towards a single classification label. These are the kinds of words we saw when we called the show_most_informative_features() method on both the NaiveBayesClassifier class and the MaxentClassifier class. Somewhat surprisingly, the top words are different for both classifiers. This discrepancy is due to how each classifier calculates the significance of each feature, and it's actually beneficial to have these different methods as they can be combined to improve accuracy, as we will see in the next recipe, *Combining classifiers with voting*.

The **low information** words are words that are common to all labels. It may be counter-intuitive, but eliminating these words from the training data can actually improve accuracy, precision, and recall. The reason this works is that using only high information words reduces the noise and confusion of a classifier's internal model. If all the words/features are highly biased one way or the other, it's much easier for the classifier to make a correct guess.

How to do it...

First, we need to calculate the high information words in the movie_review corpus. We can do this using the high_information_words () function in featx.py:

```
from nltk.metrics import BigramAssocMeasures
from nltk.probability import FreqDist, ConditionalFreqDist
def high information words (labelled words,
score fn=BigramAssocMeasures.chi sq, min score=5):
  word fd = FreqDist()
  label word fd = ConditionalFreqDist()
  for label, words in labelled words:
    for word in words:
      word fd[word] += 1
      label word fd[label][word] += 1
  n xx = label word fd.N()
  high info words = set()
  for label in label word fd.conditions():
    n xi = label word fd[label].N()
    word scores = collections.defaultdict(int)
    for word, n ii in label word fd[label].items():
      n ix = word fd[word]
      score = score fn(n ii, (n ix, n xi), n xx)
      word scores[word] = score
```

```
bestwords = [word for word, score in word_scores.items() if
score >= min_score]
    high_info_words |= set(bestwords)
return high info words
```

It takes one argument from a list of two tuples of the form [(label, words)] where label is the classification label, and words is a list of words that occur under that label. It returns a set of the high information words.

Once we have the high information words, we use the feature detector function bag_of_words_in_set(), also found in featx.py, which will let us filter out all low information words.

```
def bag_of_words_in_set(words, goodwords):
    return bag_of_words(set(words) & set(goodwords))
```

With this new feature detector, we can call label_feats_from_corpus() and get a new train_feats and test_feats function using split_label_feats(). These two functions were covered in the *Training a Naive Bayes classifier* recipe earlier in this chapter.

```
>>> from featx import high_information_words, bag_of_words_in_set
>>> labels = movie_reviews.categories()
>>> labeled_words = [(l, movie_reviews.words(categories=[l])) for l
in labels]
>>> high_info_words = set(high_information_words(labeled_words))
>>> feat_det = lambda words: bag_of_words_in_set(words,
high_info_words)
>>> lfeats = label_feats_from_corpus(movie_reviews,
feature_detector=feat_det)
>>> train feats, test feats = split label feats(lfeats)
```

Now that we have new training and testing feature sets, let's train and evaluate a NaiveBayesClassifier class:

```
>>> nb_classifier = NaiveBayesClassifier.train(train_feats)
>>> accuracy(nb_classifier, test_feats)
0.91
>>> nb_precisions, nb_recalls = precision_recall(nb_classifier,
test_feats)
>>> nb_precisions['pos']
0.8988326848249028
>>> nb_precisions['neg']
0.9218106995884774
>>> nb_recalls['pos']
0.924
>>> nb_recalls['neg']
0.896
```

While the neg precision and pos recall have both decreased somewhat, neg recall and pos precision have increased drastically. Accuracy is now a little higher than the MaxentClassifier class.

How it works...

The high_information_words () function starts by counting the frequency of every word, as well as the conditional frequency for each word within each label. This is why we need the words to be labeled, so we know how often each word occurs for each label.

Once we have the FreqDist and ConditionalFreqDist variables, we can score each word on a per-label basis.

The default score_fn is nltk.metrics.BigramAssocMeasures.chi_sq(), which calculates the chi-square score for each word using the following parameters:

- n ii: This is the frequency of the word for the label
- n ix: This is the total frequency of the word across all labels
- n_xi: This is the total frequency of all words that occurred for the label
- n_xx: This is the total frequency for all words in all labels

The formula is n_xx * nltk.metrics.BigramAssocMeasures.phi_sq.The phi_sq() function is the squared Pearson correlation coefficient, which you can read more about at https://en.wikipedia.org/wiki/Pearson product-moment correlation coefficient.

The simplest way to think about these numbers is that the closer n_{ii} is to n_{ix} , the higher the score. Or, the more often a word occurs in a label, relative to its overall occurrence, the higher the score.

Once we have the scores for each word in each label, we can filter out all words whose score is below the min_score threshold. We keep the words that meet or exceed the threshold and return all high scoring words in each label.

Tip

It is recommended to experiment with different values of min_score to see what happens. In some cases, less words may improve the metrics even more, while in other cases more words is better.

There's more...

There are a number of other scoring functions available in the <code>BigramAssocMeasures</code> class, such as <code>phi_sq()</code> for phi-square, <code>pmi()</code> for pointwise mutual information, and <code>jaccard()</code> for using the Jaccard index. They all take the same arguments, and so can be used interchangeably with <code>chi_sq()</code>. These functions are all documented in http://www.nltk.org/_modules/nltk/metrics/association.html with links to the source code of the formulas.

The MaxentClassifier class with high information words

Let's evaluate the MaxentClassifier class using the high information words feature sets:

```
>>> me_classifier = MaxentClassifier.train(train_feats,
algorithm='gis', trace=0, max_iter=10, min_lldelta=0.5)
>>> accuracy(me_classifier, test_feats)
0.912
>>> me_precisions, me_recalls = precision_recall(me_classifier,
test_feats)
>>> me_precisions['pos']
0.8992248062015504
>>> me_precisions['neg']
0.9256198347107438
>>> me_recalls['pos']
0.928
>>> me_recalls['pos']
0.896
```

This also led to significant improvements for MaxentClassifier. But as we'll see, not all algorithms will benefit from high information word filtering, and in some cases, accuracy will decrease.

The DecisionTreeClassifier class with high information words

Now, let's evaluate the DecisionTreeClassifier class:

```
>>> dt_classifier = DecisionTreeClassifier.train(train_feats,
binary=True, depth_cutoff=20, support_cutoff=20, entropy_cutoff=0.01)
>>> accuracy(dt_classifier, test_feats)
0.686000000000005
>>> dt_precisions, dt_recalls = precision_recall(dt_classifier,
test_feats)
>>> dt_precisions['pos']
0.6741573033707865
>>> dt_precisions['neg']
0.69957081545064381
>>> dt_recalls['pos']
0.71999999999999997
>>> dt_recalls['neg']
0.6520000000000002
```

The accuracy is about the same, even with a larger depth_cutoff, and smaller support_cutoff and entropy_cutoff. These results lead me to believe that the DecisionTreeClassifier class was already putting the high information features at the top of the tree, and it will only improve if we increase the depth significantly. But that could make training time prohibitively long and risk overfitting the tree.

The SklearnClassifier class with high information words

Let's evaluate the LinearSVC SklearnClassifier with the same train feats function:

```
>>> sk_classifier = SklearnClassifier(LinearSVC()).train(train_feats)
>>> accuracy(sk_classifier, test_feats)
0.86
>>> sk_precisions, sk_recalls = precision_recall(sk_classifier,
test_feats)
>>> sk_precisions['pos']
0.871900826446281
>>> sk_precisions['neg']
0.8488372093023255
>>> sk_recalls['pos']
0.844
>>> sk_recalls['pos']
0.876
```

Its accuracy before was 86.4%, so we actually got a very slight decrease. In general, support vector machine and logistic regression-based algorithms will benefit less, or perhaps even be harmed, by prefiltering the training features. This is because these algorithms are able to learn feature weights that correspond to the significance of each feature, whereas Naive Bayes algorithms do not.

See also

We started this chapter with the Bag of words feature extraction recipe. The

NaiveBayesClassifier class was originally trained in the *Training a Naive Bayes classifier* recipe, and the MaxentClassifier class was trained in the *Training a maximum entropy classifier* recipe. Details on precision and recall can be found in the *Measuring precision and recall of a classifier* recipe. We will be using only high information words in the next two recipes, where we combine classifiers.

Combining classifiers with voting

One way to improve classification performance is to combine classifiers. The simplest way to combine multiple classifiers is to use voting, and choose whichever label gets the most votes. For this style of voting, it's best to have an odd number of classifiers so that there are no ties. This means combining at least three classifiers together. The individual classifiers should also use different algorithms; the idea is that multiple algorithms are better than one, and the combination of many can compensate for individual bias. However, combining a poorly performing classifier with better performing classifiers is generally not a good idea, because the poor performance of one classifier can bring the total accuracy down.

Getting ready

As we need to have at least three trained classifiers to combine, we are going to use a NaiveBayesClassifier class, a DecisionTreeClassifier class, and a MaxentClassifier class, all trained on the highest information words of the movie_reviews corpus. These were all trained in the previous recipe, so we will combine these three classifiers with voting.

How to do it...

In the classification.py module, there is a MaxVoteClassifier class:

```
import itertools
from nltk.classify import ClassifierI
from nltk.probability import FreqDist

class MaxVoteClassifier(ClassifierI):
    def __init__(self, *classifiers):
        self._classifiers = classifiers
        self._labels = sorted(set(itertools.chain(*[c.labels() for c in
        classifiers])))

    def labels(self):
        return self._labels

    def classify(self, feats):
        counts = FreqDist()

    for classifier in self._classifiers:
        counts[classifier.classify(feats)] += 1
        return counts.max()
```

To create it, you pass in a list of classifiers that you want to combine. Once created, it works just like any other classifier. Though it may take about three times longer to classify, it should generally be at least as accurate as any individual classifier.

```
>>> from classification import MaxVoteClassifier
>>> mv classifier = MaxVoteClassifier(nb classifier, dt classifier,
me classifier, sk classifier)
>>> mv classifier.labels()
['neg', 'pos']
>>> accuracy(mv classifier, test feats)
0.894
>>> mv precisions, mv recalls = precision recall(mv classifier,
test feats)
>>> mv precisions['pos']
0.9156118143459916
>>> mv precisions['neg']
0.8745247148288974
>>> mv recalls['pos']
0.868
>>> mv recalls['neg']
0.92
```

These metrics are about on-par with the best sklearn classifiers, as well as the MaxentClassifier and NaiveBayesClassifier classes with high information features. Some numbers are slightly better, some worse. It's likely that a significant improvement to the DecisionTreeClassifier class could produce better numbers.

How it works...

The MaxVoteClassifier class extends the nltk.classify.ClassifierI interface, which requires the implementation of at least two methods:

- The labels () method must return a list of possible labels. This will be the union of the labels () method of each classifier passed in at initialization.
- The classify() method takes a single feature set and returns a label. The MaxVoteClassifier class iterates over its classifiers and calls classify() on each of them, recording their label as a vote in a FreqDist variable. The label with the most votes is returned using FreqDist.max().

The following is the inheritance diagram:



While it doesn't check for this, the MaxVoteClassifier class assumes that all the classifiers passed in at initialization use the same labels. Breaking this assumption may lead to odd behavior.

See also

In the previous recipe, we trained a NaiveBayesClassifier class, a MaxentClassifier class, and a DecisionTreeClassifier class using only the highest information words. In the next recipe, we will use the reuters corpus and combine many binary classifiers in order to create a multi-label classifier.

Classifying with multiple binary classifiers

So far we have focused on **binary classifiers**, which classify with one of two possible labels. The same techniques for training a binary classifier can also be used to create a multi-class classifier, which is a classifier that can classify with one of the many possible labels. But there are also cases where you need to be able to classify with multiple labels. A classifier that can return more than one label is a **multi-label classifier**.

A common technique for creating a multi-label classifier is to combine many binary classifiers, one for each label. You train each binary classifier so that it either returns a known label or returns something else to signal that the label does not apply. Then, you can run all the binary classifiers on your feature set to collect all the applicable labels.

Getting ready

The reuters corpus contains multi-labeled text that we can use for training and evaluation:

```
>>> from nltk.corpus import reuters
>>> len(reuters.categories())
90
```

We will train one binary classifier per label, which means we will end up with 90 binary classifiers.

How to do it...

First, we should calculate the high information words in the reuters corpus. This is done with the reuters_high_info_words() function in featx.py:

```
from nltk.corpus import reuters

def reuters_high_info_words(score_fn=BigramAssocMeasures.chi_sq):
    labeled_words = []

for label in reuters.categories():
    labeled_words.append((label, reuters.words(categories=[label])))
    return high information words(labeled words, score fn=score fn)
```

Then, we need to get training and test feature sets based on those high information words. This is done with the reuters_train_test_feats() function, also found in featx.py. It defaults to using bag_of_words() as its feature_detector, but we will be overriding this using bag of words in set() to use only the high information words:

```
def reuters_train_test_feats(feature_detector=bag_of_words):
    train_feats = []
    test_feats = []
```

```
for fileid in reuters.fileids():
    if fileid.startswith('training'):
        featlist = train_feats
    else: # fileid.startswith('test')
        featlist = test_feats
    feats = feature_detector(reuters.words(fileid))
    labels = reuters.categories(fileid)
    featlist.append((feats, labels))
return train feats, test feats
```

We can use these two functions to get a list of multi-labeled training and testing feature sets.

```
>>> from featx import reuters_high_info_words,
reuters_train_test_feats
>>> rwords = reuters_high_info_words()
>>> featdet = lambda words: bag_of_words_in_set(words, rwords)
>>> multi_train_feats, multi_test_feats =
reuters_train_test_feats(featdet)
```

The multi_train_feats and multi_test_feats functions are multi-labeled feature sets. That means they have a list of labels instead of a single label, and they look like [(featureset, [label])], as each feature set can have one or more labels. With this training data, we can train multiple binary classifiers. The train_binary_classifiers() function in classification.py takes a training function, a list of multi-label feature sets, and a set of possible labels to return a dict of label : binary classifier:

```
def train_binary_classifiers(trainf, labelled_feats, labelset):
    pos_feats = collections.defaultdict(list)
    neg_feats = collections.defaultdict(list)
    classifiers = {}
    for feat, labels in labelled_feats:
        for label in labels:
            pos_feats[label].append(feat)
        for label in labelset - set(labels):
            neg_feats[label].append(feat)
    for label in labelset:
        postrain = [(feat, label) for feat in pos_feats[label]]
        negtrain = [(feat, '!%s' % label) for feat in neg_feats[label]]
        classifiers[label] = trainf(postrain + negtrain)
    return classifiers
```

To use this function, we need to provide a training function that takes a single argument, which is the training data. This will be a simple lambda wrapper around a sklearn logistic regression SklearnClassifier class.

```
>>> from classification import train_binary_classifiers
>>> trainf = lambda train_feats:
SklearnClassifier(LogisticRegression()).train(train_feats)
>>> labelset = set(reuters.categories())
>>> classifiers = train_binary_classifiers(trainf,
multi_train_feats, labelset)
>>> len(classifiers)
90
```

Also in classification.py, we can define a MultiBinaryClassifier class, which takes a list of labeled classifiers of the form [(label, classifier)], where the classifier is assumed to be a binary classifier that either returns the label or something else if the label doesn't apply.

```
from nltk.classify import MultiClassifierI

class MultiBinaryClassifier (MultiClassifierI):
    def __init__(self, *label_classifiers):
        self.label_classifiers = dict(label_classifiers)
        self.labels = sorted(self.label_classifiers.keys())

    def labels(self):
        return self.labels

    def classify(self, feats):
        lbls = set()

    for label, classifier in self.label_classifiers.items():
        if classifier.classify(feats) == label:
        lbls.add(label)

    return lbls
```

Now we can construct this class using the binary classifiers we just created:

```
>>> from classification import MultiBinaryClassifier
>>> multi classifier = MultiBinaryClassifier(*classifiers.items())
```

To evaluate this classifier, we can use precision and recall, but not accuracy. That's because the accuracy function assumes single values, and doesn't take into account partial matches. For example, if the multi_classifier returns three labels for a feature set, and two of them are correct but the third is not, then the accuracy() function would mark that as incorrect. So, instead of using accuracy, we

will use **masi distance**, which measures the partial overlap between two sets using the formula from this paper:

http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.113.3752

If the masi distance is close to 0, the better the match. But if the masi distance is close to 1, there is little or no overlap. A lower average masi distance, therefore, means more accurate partial matches. The multi_metrics() function in classification.py calculates the precision and recall of each label, along with the average masi distance.

```
import collections
from nltk import metrics
def multi metrics (multi classifier, test feats):
  mds = []
  refsets = collections.defaultdict(set)
  testsets = collections.defaultdict(set)
  for i, (feat, labels) in enumerate(test feats):
    for label in labels:
      refsets[label].add(i)
    guessed = multi classifier.classify(feat)
    for label in guessed:
      testsets[label].add(i)
    mds.append(metrics.masi distance(set(labels), guessed))
  avg md = sum(mds) / float(len(mds))
  precisions = \{\}
  recalls = {}
  for label in multi classifier.labels():
    precisions[label] = metrics.precision(refsets[label],
testsets[label])
    recalls[label] = metrics.recall(refsets[label], testsets[label])
  return precisions, recalls, avg md
```

Using this with the multi classifier function we just created gives us the following results:

```
>>> from classification import multi_metrics
>>> multi_precisions, multi_recalls, avg_md =
multi_metrics(multi_classifier, multi_test_feats)
>>> avg_md
0.23310715863026216
```

So our average masi distance isn't too bad. Lower is better, which means our multi-label classifier is only partially accurate. Let's take a look at a few precisions and recalls:

In general, the labels that have more feature sets will have higher precision and recall, and those with less feature sets will have lower performance. Many of the categories have 0 values, because when there are not a lot of feature sets for a classifier to learn from, you can't expect it to perform well.

How it works...

The reuters_high_info_words() function is fairly simple; it constructs a list of [(label, words)] for each category of the reuters corpus, then passes it into the high_information_words() function to return a list of the most informative words in the reuters corpus.

With the resulting set of words, we create a feature detector function using the bag_of_words_in_set() function. This is then passed into the reuters_train_test_feats() function, which returns two lists, the first containing [(feats, labels)] for all the training files, and the second list has the same for all the test files.

Next, we train a binary classifier for each label using the train_binary_classifiers() function. This function constructs two lists for each label, one containing positive training feature sets and the other containing negative training feature sets. The **positive feature sets** are those feature sets that classify for the label. The **negative feature sets** for a label comes from the positive feature sets for all other labels. For example, a feature set that is positive for zinc and sunseed is a negative example for all the other 88 labels. Once we have positive and negative feature sets for each label, we can train a binary classifier for each label using the given training function.

With the resulting dictionary of binary classifiers, we create an instance of the MultiBinaryClassifier class. This class extends the nltk.classify.MultiClassifierI interface, which requires at least two functions:

• The labels () function must return a list of possible labels.

• The classify() function takes a single feature set and returns a set of labels. To create this set, we iterate over the binary classifiers, and any time a call to the classify() function returns its label, we add it to the set. If it returns something else, we continue.

The following is the inheritance diagram:



Finally, we evaluate the multi-label classifier using the multi_metrics() function. It is similar to the precision_recall() function from the *Measuring precision and recall of a classifier* recipe, but in this case, we know that the classifier is an instance of the MultiClassifierI interface and it can therefore return multiple labels. It also keeps track of the masi distance for each set of classification labels using the nltk.metrics.masi_distance() function. The multi_metrics() function returns three values:

- A dictionary of precisions for each label
- A dictionary of recalls for each label
- The average masi distance for each feature set

There's more...

The nature of the reuters corpus introduces the **class-imbalance problem**. This problem occurs when some labels have very few feature sets, and other labels have many. The binary classifiers that have few positive instances to train on, end up with far more negative instances, and are therefore strongly biased towards the negative label. There's nothing inherently wrong about this, as the bias reflects the data, but the negative instances can overwhelm the classifier to the point where it's nearly impossible to get a positive result. There are a number of advanced techniques for overcoming this problem, but they are out of the scope of this book. The paper available at http://www.ijetae.com/files/Volume2Issue4/IJETAE_0412_07.pdf provides a good starting reference of techniques to overcome this problem.

See also

The SklearnClassifier class is covered in the *Training scikit-learn classifiers* recipe in this chapter. The *Measuring precision and recall of a classifier* recipe shows how to evaluate a classifier, while the *Calculating high information words* recipe describes how to use only the best features.
Training a classifier with NLTK-Trainer

In this recipe, we'll cover the train_classifier.py script from NLTK-Trainer, which lets you train NLTK classifiers from the command line. NLTK-Trainer was previously introduced at the end of <u>Chapter 4</u>, *Part-of-speech Tagging*, and again at the end of <u>Chapter 5</u>, *Extracting Chunks*.

Note

You can find NLTK-Trainer at <u>https://github.com/japerk/nltk-trainer</u> and the online documentation at <u>http://nltk-trainer.readthedocs.org/</u>.

How to do it...

Like train_tagger.py and train_chunker.py, the only required argument for train_classifier.py is the name of a corpus. The corpus must have a categories () method, because text classification is all about learning to classify categories. Here's an example of running train classifier.py on the movie reviews corpus:

```
$ python train_classifier.py movie_reviews
loading movie_reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
2000 training feats, 2000 testing feats
training NaiveBayes classifier
accuracy: 0.967000
neg precision: 1.000000
neg recall: 0.934000
neg f-measure: 0.965874
pos precision: 0.938086
pos recall: 1.000000
pos f-measure: 0.968054
dumping NaiveBayesClassifier to ~/nltk_data/classifiers/
movie_reviews_NaiveBayes.pickle
```

We can use the --no-pickle argument to skip saving the classifier and the --fraction argument to limit the training set and evaluate the classifier against a test set. This example replicates what we did earlier in the *Training a Naive Bayes classifier recipe*.

```
$ python train_classifier.py movie_reviews --no-pickle --fraction
0.75
loading movie_reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
1500 training feats, 500 testing feats
training NaiveBayes classifier
accuracy: 0.726000
```

```
neg precision: 0.952000
neg recall: 0.476000
neg f-measure: 0.634667
pos precision: 0.650667
pos recall: 0.976000
pos f-measure: 0.780800
```

You can see that not only do we get accuracy, we also get the precision and recall of each class, like we covered earlier in the recipe, *Measuring precision and recall of a classifier*.

Note

The PYTHONHASHSEED environment variable has been omitted for clarity. This means that when you run train_classifier.py, your accuracy, precision, and recall values may vary. To get consistent values, run train classifier.py like this:

\$ PYTHONHASHSEED=0 python train_classifier.py movie_reviews

How it works...

The train classifier.py script goes through a series of steps to train a classifier:

- 1. Loads the categorized corpus.
- 2. Extracts features.
- 3. Trains the classifier.

Depending on the arguments used, there may be further steps, such as evaluating the classifier and/or saving the classifier.

The default feature extraction is a bag of words, which we covered in the first recipe of this chapter, *Bag of words feature extraction*. And the default classifier is the NaiveBayesClassifier class, which we covered earlier in the *Training a Naive Bayes classifier* recipe. You can choose a different classifier using the --classifier argument. Here's an example with DecisionTreeClassifier, replicating the same arguments we used in the *Training a decision tree classifier* recipe:

```
$ python train_classifier.py movie_reviews --no-pickle --fraction
0.75 --classifier DecisionTree --trace 0 --entropy_cutoff 0.8
--depth_cutoff 5 --support_cutoff 30 --binary
accuracy: 0.672000
neg precision: 0.683761
neg recall: 0.640000
neg f-measure: 0.661157
pos precision: 0.661654
pos recall: 0.704000
pos f-measure: 0.682171
```

There's more...

The train_classifier.py script supports many other arguments not shown here, all of which you can see by running the script with --help. Some additional arguments are presented next along with examples for other classification algorithms, followed by an introduction to another classification-related script available in nltk-trainer.

Saving a pickled classifier

Without the --no-pickle argument, train_classifier.py will save a pickled classifier at ~/nltk_data/classifiers/NAME.pickle, where NAME is a combination of the corpus name and training algorithm. You can specify a custom filename for your classifier using the --filename argument like this:

\$ python train_classifier.py movie_reviews --filename path/to/ classifier.pickle

Using different training instances

By default, train_classifier.py uses individual files as training instances. That means a single categorized file will be used as one instance. But you can instead use paragraphs or sentences as training instances. Here's an example using sentences from the movie reviews corpus:

```
$ python train_classifier.py movie_reviews --no-pickle --fraction
0.75 --instances sents
loading movie_reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
50820 training feats, 16938 testing feats
training NaiveBayes classifier
accuracy: 0.638623
neg precision: 0.694942
neg recall: 0.470786
neg f-measure: 0.561313
pos precision: 0.610546
pos recall: 0.800580
pos f-measure: 0.692767
```

To use paragraphs instead of files or sentences, you can do --instances paras.

The most informative features

In the earlier recipe, *Training a Naive Bayes classifier*, we covered how to see the most informative features. This can also be done as an argument in train_classifier.py:

```
$ python train_classifier.py movie_reviews --no-pickle --fraction
0.75 --show-most-informative 5
```

```
loading movie reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
1500 training feats, 500 testing feats
training NaiveBayes classifier
accuracy: 0.726000
neg precision: 0.952000
neg recall: 0.476000
neg f-measure: 0.634667
pos precision: 0.650667
pos recall: 0.976000
pos f-measure: 0.780800
5 most informative features
Most Informative Features
             finest = True
                                        pos : neg
                                                     =
                                                           13.4 : 1.0
         astounding = True
                                        pos : neg
                                                     =
                                                           11.0 : 1.0
                                        pos : neg
                                                           11.0 : 1.0
             avoids = True
                                                     =
             inject = True
                                        neg : pos
                                                          10.3 : 1.0
                                                     =
          strongest = True
                                        pos : neg
                                                           10.3 : 1.0
                                                     =
```

The Maxent and LogisticRegression classifiers

In the *Training a maximum entropy classifier* recipe, we covered the MaxentClassifier class with the GIS algorithm. Here's how to use train classifier.py to do this:

```
$ python train_classifier.py movie_reviews --no-pickle --fraction
0.75 --classifier GIS --max_iter 10 --min_lldelta 0.5
loading movie_reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
1500 training feats, 500 testing feats
training GIS classifier
    => Training (10 iterations)
accuracy: 0.712000
neg precision: 0.964912
neg recall: 0.440000
neg f-measure: 0.604396
pos precision: 0.637306
pos recall: 0.984000
pos f-measure: 0.773585
```

If you have scikit-learn installed, then you can use many different sklearn algorithms for classification. In the *Training scikit-learn classifiers* recipe, we covered the LogisticRegression classifier, so here's how to do it with train_classifier.py:

\$ python train classifier.py movie reviews --no-pickle --fraction 0.75 -- classifier sklearn.LogisticRegression loading movie reviews 2 labels: ['neg', 'pos'] using bag of words feature extraction 1500 training feats, 500 testing feats training sklearn.LogisticRegression with { 'penalty': '12', 'C': 1.0} using dtype bool training sklearn.LogisticRegression classifier accuracy: 0.856000 neg precision: 0.847656 neg recall: 0.868000 neg f-measure: 0.857708 pos precision: 0.864754 pos recall: 0.844000 pos f-measure: 0.854251

SVMs

SVM classifiers were introduced in the *Training scikit-learn classifiers* recipe, and can also be used with train classifier.py. Here's the parameters for LinearSVC:

```
$ python train classifier.py movie reviews --no-pickle --fraction
0.75 -- classifier sklearn.LinearSVC
loading movie reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
1500 training feats, 500 testing feats
training sklearn.LinearSVC with {'penalty': '12', 'loss': '12', 'C':
1.0}
using dtype bool
training sklearn.LinearSVC classifier
accuracy: 0.860000
neg precision: 0.851562
neg recall: 0.872000
neg f-measure: 0.861660
pos precision: 0.868852
pos recall: 0.848000
pos f-measure: 0.858300
```

And here's the parameters for NuSVC:

```
$ python train_classifier.py movie_reviews --no-pickle --fraction
0.75 --classifier sklearn.NuSVC
loading movie_reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
```

1500 training feats, 500 testing feats training sklearn.NuSVC with {'kernel': 'rbf', 'nu': 0.5} using dtype bool training sklearn.NuSVC classifier accuracy: 0.850000 neg precision: 0.827715 neg recall: 0.884000 neg f-measure: 0.854932 pos precision: 0.875536 pos recall: 0.816000 pos f-measure: 0.844720

Combining classifiers

In the *Combining classifiers with voting* recipe, we covered how to combine multiple classifiers into a single classifier using a max vote method. The train_classifier.py script can also combine classifiers, but it uses a slightly different algorithm. Instead of counting votes, it sums probabilities together to produce a final probability distribution, which is then used to classify each instance. Here's an example with three sklearn classifiers:

```
$ python train_classifier.py movie reviews --no-pickle --fraction
0.75 -- classifier sklearn.LogisticRegression sklearn.MultinomialNB
sklearn.NuSVC
loading movie reviews
2 labels: ['neg', 'pos']
using bag of words feature extraction
1500 training feats, 500 testing feats
training sklearn.LogisticRegression with { 'penalty': '12', 'C': 1.0}
using dtype bool
training sklearn.MultinomialNB with {'alpha': 1.0}
using dtype bool
training sklearn.NuSVC with {'kernel': 'rbf', 'nu': 0.5}
using dtype bool
training sklearn.LogisticRegression classifier
training sklearn.MultinomialNB classifier
training sklearn.NuSVC classifier
accuracy: 0.856000
neg precision: 0.839695
neg recall: 0.880000
neg f-measure: 0.859375
pos precision: 0.873950
pos recall: 0.832000
pos f-measure: 0.852459
```

High information words and bigrams

In the *Calculating high information words* recipe, we calculated the information gain of words, and then used only words with high information gain as features. The train_classifier.py script can do this too:

```
$ python train classifier.py movie reviews --no-pickle --fraction
0.75 --classifier NaiveBayes --min score 5 --ngrams 1 2
loading movie reviews
2 labels: ['neg', 'pos']
calculating word scores
using bag of words from known set feature extraction
9989 words meet min score and/or max feats
1500 training feats, 500 testing feats
training NaiveBayes classifier
accuracy: 0.860000
neg precision: 0.901786
neg recall: 0.808000
neg f-measure: 0.852321
pos precision: 0.826087
pos recall: 0.912000
pos f-measure: 0.866920
```

Cross-fold validation

Cross-fold validation is a method for evaluating a classification algorithm. The typical way to do it is using 10 folds, leaving one fold out for testing. What this means is that the training corpus is first split into 10 parts (or folds). Then, it is trained on nine of the folds and tested against the remaining fold. This is repeated nine more times, choosing a different fold to leave out for testing each time. By using a different set of training and testing examples each time, you can avoid any bias that might be present in the training set. Here's how to do this with train classifier.py:

```
neg f_measure mean: 0.870630
neg f_measure variance: 0.000290
pos f_measure mean: 0.868246
pos f_measure variance: 0.000610
```

Most of the output has been omitted for clarity. What really matters is the final evaluation, which is the mean and variance of the results across all folds.

Analyzing a classifier

Also included in NLTK-Trainer is a script called analyze_classifier_coverage.py. As the name implies, you can use it to see how a classifier categorizes a given corpus. It expects the name of a corpus and a path to a pickled classifier to run on the corpus. If the corpus is categorized, you can also use the --metrics argument to get the accuracy, precision, and recall. The script supports many of the same corpus-related arguments as train_classifier.py, and also has an optional --speed argument, so you can see how fast the classifier is. Here's an example of analyzing a pickled NaiveBayesClassifier class against the movie reviews corpus:

```
$ python analyze_classifier_coverage.py movie_reviews --classifier
classifiers/movie_reviews_NaiveBayes.pickle --metrics --speed
loading time: 0secs
accuracy: 0.967
neg precision: 1.000000
neg recall: 0.934000
neg f-measure: 0.965874
pos precision: 0.938086
pos recall: 1.000000
pos f-measure: 0.968054
neg 934
pos 1066
average time per classify: 3secs / 2000 feats = 1.905661 ms/feat
```

See also

NLTK-Trainer was introduced at the end of <u>Chapter 4</u>, *Part-of-speech Tagging*, in the *Training a tagger* with NLTK-Trainer recipe. It was also covered at the end of <u>Chapter 5</u>, *Extracting Chunks*, in the *Training a chunker with NLTK-Trainer* recipe. All the previous recipes in the chapter explain various aspects of how the train_classifier.py script works.

Chapter 8. Distributed Processing and Handling Large Datasets

In this chapter, we will cover the following recipes:

- Distributed tagging with execnet
- Distributed chunking with execnet
- Parallel list processing with execnet
- Storing a frequency distribution in Redis
- Storing a conditional frequency distribution in Redis
- Storing an ordered dictionary in Redis
- · Distributed word scoring with Redis and execnet

Introduction

NLTK is great for in-memory, single-processor natural language processing. However, there are times when you have a lot of data to process and want to take advantage of multiple CPUs, multicore CPUs, and even multiple computers. Or, you might want to store frequencies and probabilities in a persistent, shared database so multiple processes can access it simultaneously. For the first case, we'll be using **execnet** to do parallel and distributed processing with NLTK. For the second case, you'll learn how to use the Redis data structure server/database to store frequency distributions and more.

Distributed tagging with execnet

Execnet is a distributed execution library for Python. It allows you to create gateways and channels for remote code execution. A **gateway** is a connection from the calling process to a remote environment. The remote environment can be a local subprocess or an SSH connection to a remote node. A **channel** is created from a gateway and handles communication between the channel creator and the remote code. In this way, execute is a kind of **Message Passing Interface** (**MPI**), where the gateway creates the connection and the channel is used to send messages back and forth.

Since many NLTK processes take 100% CPU during computation, execute is an ideal way to distribute that computation for maximum resource usage. You can create one gateway per CPU core, and it doesn't matter whether the cores are in your local computer or spread across remote machines. In many situations, you only need to have the trained objects and data on a single machine and can send the objects and data to the remote nodes as needed.

Getting ready

You'll need to install execnet for this to work. It should be as simple as sudo pip install execnet or sudo easy_install execnet. The current version of execnet, as of this writing, is 1.2. The execnet home page, which has API documentation and examples, is at http://codespeak.net/execnet/.

How to do it...

We start by importing the required modules, as well as an additional module, remote_tag.py, that will be explained in the *How it works*... section. We also need to import pickle so we can serialize (transmit) the tagger. Execnet does not natively know how to deal with complex objects such as a part-of-speech tagger, so we must dump the tagger to a string using pickle.dumps(). We'll use the default tagger that's used by the nltk.tag.pos_tag() function, but you could use any pre-trained part-of-speech tagger as long as it implements the TaggerI interface.

Once we have a serialized tagger, we start execnet by making a gateway with execnet.makegateway(). The default gateway creates a Python subprocess, and we can call the remote_exec() function of the remote_tag module to create a channel. With an open channel, we send over the serialized tagger, followed by the first tokenized sentence of the treebank corpus.

Note

You don't have to do any special serialization of simple types such as lists and tuples, since execnet already knows how to handle serializing the built-in types.

Now, if we call channel.receive(), we get back a tagged sentence that is equivalent to the first tagged sentence in the treebank corpus, so we know the tagging worked. We end by exiting the gateway, which closes the channel and kills the subprocess.

```
>>> import execnet, remote_tag, nltk.tag, nltk.data
>>> from nltk.corpus import treebank
>>> import pickle
>>> pickled_tagger =
pickle.dumps(nltk.data.load(nltk.tag._POS_TAGGER))
>>> gw = execnet.makegateway()
>>> channel = gw.remote_exec(remote_tag)
>>> channel.send(pickled_tagger)
>>> channel.send(treebank.sents()[0])
>>> tagged_sentence = channel.receive()
>>> tagged_sentence == treebank.tagged_sents()[0]
True
>>> gw.exit()
```

Visually, the communication process looks like this:



How it works...

The gateway's remote_exec() method takes a single argument that can be one of the following three types:

- A string of code to execute remotely
- The name of a **pure function** that will be serialized and executed remotely
- The name of a **pure module** whose source will be executed remotely

We use option three with the remote tag.py module, which is defined as follows:

```
import pickle

if __name__ == '__channelexec__':
  tagger = pickle.loads(channel.receive())

for sentence in channel:
    channel.send(tagger.tag(sentence))
```

A **pure module** is a module that is self-contained: it can only access Python modules that are available where it executes, and does not have access to any variables or states that exist wherever the gateway is initially created. Similarly, a **pure function** is a self-contained function, with no external dependencies. To detect that the module is being executed by <code>execnet</code>, you can look at the <code>__name__</code> variable. If it's equal to '__channelexec__', then it is being used to create a remote channel. This is similar to doing if <code>__name__</code> == '__main__' to check if a module is being executed on the command line.

The first thing we do is call channel.receive() to get the serialized tagger, which we load using pickle.loads(). You may notice that channel is not imported anywhere—that's because it is included in the global namespace of the module. Any module that executes remotely has access to the channel variable in order to communicate with the channel creator.

Once we have the tagger, we iteratively tag() each tokenized sentence that we receive from the channel. This allows us to tag as many sentences as the sender wants to send, as iteration will not stop until the channel is closed. What we've essentially created is a compute node for part-of-speech tagging that dedicates 100% of its resources to tagging whatever sentences it receives. As long as the channel remains open, the node is available for processing.

There's more...

This is a simple example that opens a single gateway and channel. But execnet can do a lot more, such as opening multiple channels to increase parallel processing, as well as opening gateways to remote hosts over SSH to do distributed processing.

Creating multiple channels

We can create multiple channels, one per gateway, to make the processing more parallel. Each gateway creates a new subprocess (or remote interpreter if using an SSH gateway), and we use one channel per gateway for communication. Once we've created two channels, we can combine them using the MultiChannel class, which allows us to iterate over the channels and make a receive queue to receive messages from each channel.

After creating each channel and sending the tagger, we cycle through the channels to send an even number of sentences to each channel for tagging. Then, we collect all the responses from the queue. A call to queue.get() will return a 2-tuple of (channel, message) in case you need to know which channel the message came from.

Note

If you don't want to wait forever, you can also pass a timeout keyword argument with the maximum number of seconds you want to wait, as in queue.get(timeout=4). This can be a good way to handle network errors.

Once all the tagged sentences have been collected, we can exit the gateways. Here's the code:

```
>>> import itertools
>>> gw1 = execnet.makegateway()
>>> gw2 = execnet.makegateway()
>>> ch1 = gw1.remote exec(remote tag)
>>> chl.send(pickled tagger)
>>> ch2 = gw2.remote exec(remote tag)
>>> ch2.send(pickled tagger)
>>> mch = execnet.MultiChannel([ch1, ch2])
>>> queue = mch.make receive queue()
>>> channels = itertools.cycle(mch)
>>> for sentence in treebank.sents()[:4]:
         channel = next(channels)
. . .
         channel.send(sentence)
. . .
>>> tagged sentences = []
>>> for i in range(4):
         channel, tagged sentence = queue.get()
. . .
         tagged sentences.append(tagged sentence)
. . .
>>> len(tagged sentences)
4
>>> gwl.exit()
>>> gw2.exit()
```

In the example code, we're only sending four sentences, but in real-life, you'd want to send thousands. A single computer can tag four sentences very quickly, but when thousands, or hundreds of thousands of sentences need to be tagged, sending sentences to multiple computers can be much faster than waiting for a single computer to do it all.

Local versus remote gateways

The default gateway spec is popen, which creates a Python subprocess on the local machine. This means execnet.makegateway() is equivalent to execnet.makegateway('popen'). If you have password-less SSH access to a remote machine, then you can create a remote gateway using execnet.makegateway('ssh=remotehost'), where remotehost should be the hostname of the machine. An SSH gateway spawns a new Python interpreter for executing the code remotely. As long as the code you're using for remote execution is **pure**, you only need a Python interpreter on the remote machine.

Channels work exactly the same no matter what kind of gateway is used; the only difference will be communication time. This means you can mix and match local subprocesses with remote interpreters to

distribute your computations across many machines in a network. There are many more details on gateways in the API documentation at <u>http://codespeak.net/execnet/basics.html</u>.

See also

Part-of-speech tagging and taggers are covered in detail in <u>Chapter 4</u>, *Part-of-speech Tagging*. In the next recipe, we'll use execut to do distributed chunk extraction.

Distributed chunking with execnet

In this recipe, we'll do chunking and tagging over an execut gateway. This will be very similar to the tagging in the previous recipe, but we'll be sending two objects instead of one, and we will be receiving a Tree instead of a list, which requires pickling and unpickling for serialization.

Getting ready

As in the previous recipe, you must have execnet installed.

How to do it...

The setup code is very similar to the last recipe, and we'll use the same pickled tagger as well. First, we'll pickle the default chunker used by nltk.chunk.ne_chunk(), though any chunker would do. Next, we make a gateway for the remote_chunk module, get a channel, and send the pickled tagger and chunker over. Then, we receive a pickled Tree, which we can unpickle and inspect to see the result. Finally, we exit the gateway:

```
>>> import execnet, remote chunk
>>> import nltk.data, nltk.tag, nltk.chunk
>>> import pickle
>>> from nltk.corpus import treebank chunk
>>> tagger = pickle.dumps(nltk.data.load(nltk.tag. POS TAGGER))
>>> chunker =
pickle.dumps(nltk.data.load(nltk.chunk. MULTICLASS NE CHUNKER))
>>> gw = execnet.makegateway()
>>> channel = gw.remote exec(remote chunk)
>>> channel.send(tagger)
>>> channel.send(chunker)
>>> channel.send(treebank chunk.sents()[0])
>>> chunk tree = pickle.loads(channel.receive())
>>> chunk tree
Tree('S', [Tree('PERSON', [('Pierre', 'NNP')]), Tree('ORGANIZATION',
[('Vinken', 'NNP')]), (',', ','), ('61', 'CD'), ('years', 'NNS'),
('old', 'JJ'), (',', ','), ('will', 'MD'), ('join', 'VB'), ('the',
'DT'), ('board', 'NN'), ('as', 'IN'), ('a', 'DT'), ('nonexecutive',
'JJ'), ('director', 'NN'), ('Nov.', 'NNP'), ('29', 'CD'), ('.',
'.')])
>>> gw.exit()
```

The communication this time is slightly different, as shown in the following diagram:



How it works...

The remote_chunk.py module is just a little bit more complicated than the remote_tag.py module from the previous recipe. In addition to receiving a pickled tagger, it also expects to receive a pickled chunker that implements the ChunkerI interface. Once it has both a tagger and a chunker, it expects to receive any number of tokenized sentences, which it tags and parses into a Tree. This Tree is then pickled and sent back over the channel:

import pickle

```
if __name__ == '__channelexec__':
  tagger = pickle.loads(channel.receive())
  chunker = pickle.loads(channel.receive())
  for sentence in channel:
    chunk_tree = chunker.parse(tagger.tag(sent))
    channel.send(pickle.dumps(chunk_tree))
```

Note

The Tree must be pickled because it is not a simple built-in type.

There's more...

Note that the remote_chunk module is pure. Its only external dependency is the pickle module, which is part of the Python standard library. It doesn't need to import any NLTK modules in order to use the tagger or chunker, because all the necessary data is pickled and sent over the channel. As long as you structure your remote code like this, with no external dependencies, you only need NLTK to be installed on a single machine—the one that starts the gateway and sends the objects over the channel.

Python subprocesses

If you look at your task/system monitor (or top on *nix) while running the execnet code, you may notice a few extra Python processes. Every gateway spawns a new, self-contained, shared-nothing Python interpreter process, which is killed when you call the exit() method. Unlike with threads, there is no shared memory to worry about, and no global interpreter lock to slow things down. All you have are separate communicating processes. This is true whether the processes are local or remote. Instead of locking and synchronization, all you have to worry about is the order in which the messages are sent and received.

See also

The previous recipe explains execnet gateways and channels in detail. In the next recipe, we'll use execnet to process a list in parallel.

Parallel list processing with execnet

This recipe presents a pattern for using execnet to process a list in parallel. It's a function pattern for mapping each element in the list to a new value, using execnet to do the mapping in parallel.

How to do it...

First, we need to decide exactly what we want to do. In this example, we'll just double integers, but we could do any pure computation. Following is the remote_double.py module, which will be executed by executed. It receives a 2-tuple of (i, arg), assumes arg is a number, and sends back (i, arg*2). The need for i will be explained in the next section.

```
if __name__ == '__channelexec__':
    for (i, arg) in channel:
        channel.send((i, arg * 2))
```

To use this module to double every element in a list, we import the plists module (explained in the *How it works...* section) and call plists.map() with the remote_double module, and a list of integers to double.

```
>>> import plists, remote_double
>>> plists.map(remote_double, range(10))
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]
```

Communication between channels is very simple, as shown in the following diagram:



How it works...

The map() function is defined in plists.py. It takes a pure module, a list of arguments, and an optional list of 2-tuples consisting of (spec, count). The default specs are [('popen', 2)],

which means we'll open two local gateways and channels. Once these channels are opened, we put them into an *itertools* cycle, which creates an infinite iterator that cycles back to the beginning once it hits the end.

Now we can send each argument in args to a channel for processing, and since the channels are cycled, each channel gets an almost even distribution of arguments. This is where i comes in—we don't know in what order we'll get the results back, so i, as the index of each arg in the list, is passed to the channel and back so we can combine the results in the original order. We then wait for the results with a MultiChannel receive queue and insert them into a prefilled list that's the same length as the original args. Once we have all the expected results, we can exit the gateways and return the results:

```
import itertools, execnet
def map(mod, args, specs=[('popen', 2)]):
 qateways = []
 channels = []
  for spec, count in specs:
    for i in range(count):
      gw = execnet.makegateway(spec)
      gateways.append(gw)
      channels.append(gw.remote exec(mod))
 cyc = itertools.cycle(channels)
  for i, arg in enumerate(args):
   channel = next(cyc)
   channel.send((i, arg))
 mch = execnet.MultiChannel(channels)
 queue = mch.make receive queue()
  l = len(args)
 results = [None] * 1 # creates a list of length 1, where every
element is None
  for i in range(l):
   channel, (i, result) = queue.get()
   results[i] = result
  for gw in gateways: [1] gw.exit()
 return results
```

There's more...

You can increase the parallelization by modifying the specs, as follows:

>>> plists.map(remote_double, range(10), [('popen', 4)])
[0, 2, 4, 6, 8, 10, 12, 14, 16, 18]

However, more parallelization does not necessarily mean faster processing. It depends on the available resources, and the more gateways and channels you have open, the more overhead is required. Ideally, there should be one gateway and channel per CPU core to get maximum resource utilization.

You can use plists.map() with any pure module as long as it receives and sends back 2-tuples where i is the first element. This pattern is most useful when you have a bunch of numbers to crunch and want to process them as quickly as possible.

See also

The previous two recipes cover execnet features in greater detail.

Storing a frequency distribution in Redis

The nltk.probability.FreqDist class is used in many classes throughout NLTK for storing and managing frequency distributions. It's quite useful, but it's all in-memory, and doesn't provide a way to persist the data. A single FreqDist is also not accessible to multiple processes. We can change all that by building a FreqDist on top of Redis.

Redis is a **data structure server** that is one of the more popular *NoSQL* databases. Among other things, it provides a network-accessible database for storing dictionaries (also known as **hash maps**). Building a FreqDist interface to a Redis hash map will allow us to create a persistent FreqDist that is accessible to multiple local and remote processes at the same time.

Note

Most Redis operations are **atomic**, so it's even possible to have multiple processes write to the FreqDist concurrently.

Getting ready

For this and the subsequent recipes, we need to install both Redis and redis-py. The Redis website is at <u>http://redis.io/</u> and includes many documentation resources. To use hash maps, you should install the latest version, which at the time of this writing is 2.8.9.

The Redis Python driver, redis-py, can be installed using pip install redis or easy_install redis. The latest version at this time is 2.9.1. The redis-py home page is at http://github.com/andymccurdy/redis-py/.

Once both are installed and a redis-server process is running, you're ready to go. Let's assume redis-server is running on localhost on port 6379 (the default host and port).

How to do it...

The FreqDist class extends the standard library collections. Counter class, which makes a FreqDist a small wrapper with a few extra methods, such as N(). The N() method returns the number of sample outcomes, which is the sum of all the values in the frequency distribution.

We can create an API-compatible class on top of Redis by extending a RedisHashMap (which will be explained in the next section) and then implementing the N() method. Since the FreqDist only stores integers, we also override a few other methods to ensure values are always integers. This RedisHashFreqDist (defined in redisprob.py) sums all the values in the hash map for the N() method:

```
from rediscollections import RedisHashMap
class RedisHashFreqDist(RedisHashMap):
    def N(self):
```

```
return int(sum(self.values()))

def __missing__(self, key):
   return 0

def __getitem__(self, key):
   return int(RedisHashMap.__getitem__(self, key) or 0)

def values(self):
   return [int(v) for v in RedisHashMap.values(self)]

def items(self):
   return [(k, int(v)) for (k, v) in RedisHashMap.items(self)]
```

We can use this class just like a FreqDist. To instantiate it, we must pass a Redis connection and the name of our hash map. The name should be a unique reference to this particular FreqDist so that it doesn't clash with any other keys in Redis.

```
>>> from redis import Redis
>>> from redisprob import RedisHashFreqDist
>>> r = Redis()
>>> rhfd = RedisHashFreqDist(r, 'test')
>>> len(rhfd)
0
>>> rhfd['foo'] += 1
>>> rhfd['foo'] 1
1
>>> rhfd.items()
>>> len(rhfd)
1
```

Note

The name of the hash map and the sample keys will be encoded to replace whitespace and & characters with _. This is because the Redis protocol uses these characters for communication. It's best if the name and keys don't include whitespace to begin with.

How it works...

Most of the work is done in the RedisHashMap class, found in rediscollections.py, which extends collections.MutableMapping and then overrides all methods that require Redisspecific commands. Here's an outline of each method that uses a specific Redis command:

- __len__(): This uses the hlen command to get the number of elements in the hash map
- _____ contains___(): This uses the hexists command to check if an element exists in the hash map
- ____getitem___(): This uses the hget command to get a value from the hash map

- setitem (): This uses the hset command to set a value in the hash map
- delitem (): This uses the hdel command to remove a value from the hash map
- keys (): This uses the hkeys command to get all the keys in the hash map
- values(): This uses the hvals command to get all the values in the hash map
- items(): This uses the hgetall command to get a dictionary containing all the keys and values in the hash map
- clear (): This uses the delete command to remove the entire hash map from Redis

Note

Extending collections.MutableMapping provides a number of other dict compatible methods based on the previous methods, such as update() and setdefault(), so we don't have to implement them ourselves.

The initialization used for RedisHashFreqDist is actually implemented here, and requires a Redis connection and a name for the hash map. The connection and name are both stored internally to use with all the subsequent commands. As mentioned earlier, whitespace is replaced by an underscore in the name and all keys for compatibility with the Redis network protocol.

```
import collections, re
white = re.compile('[\s\&]+')
def encode key(key):
 return white.sub(' ', key.strip())
class RedisHashMap(collections.MutableMapping):
 def init (self, r, name):
    self. r = r
   self. name = encode key(name)
 def iter (self):
   return self.items()
 def len (self):
    return self. r.hlen(self. name)
 def contains (self, key):
   return self. r.hexists(self. name, encode key(key))
 def getitem (self, key):
    return self. r.hget(self. name, encode key(key))
 def setitem (self, key, val):
   self._r.hset(self._name, encode_key(key), val)
 def __delitem__(self, key):
```

```
self._r.hdel(self._name, encode_key(key))

def keys(self):
   return self._r.hkeys(self._name)

def values(self):
   return self._r.hvals(self._name)

def items(self):
   return self._r.hgetall(self._name).items()

def get(self, key, default=0):
   return self[key] or default

def clear(self):
   self._r.delete(self._name)
```

There's more...

The RedisHashMap can be used by itself as a persistent key-value dictionary. However, while the hash map can support a large number of keys and arbitrary string values, its storage structure is more optimal for integer values and smaller numbers of keys. However, don't let that stop you from taking full advantage of Redis. It's very fast (for a network server) and does its best to efficiently encode whatever data you throw at it.

Note

While Redis is quite fast for a network database, it will be significantly slower than the in-memory FreqDist. There's no way around this, but while you sacrifice speed, you gain persistence and the ability to do concurrent processing.

See also

In the next recipe, we'll create a conditional frequency distribution based on the Redis frequency distribution created here.

Storing a conditional frequency distribution in Redis

The nltk.probability.ConditionalFreqDist class is a container for FreqDist instances, with one FreqDist per condition. It is used to count frequencies that are dependent on another condition, such as another word or a class label. We used this class in the *Calculating high information words* recipe in <u>Chapter 7</u>, *Text Classification*. Here, we'll create an API-compatible class on top of Redis using the RedisHashFreqDist from the previous recipe.

Getting ready

As in the previous recipe, you'll need to have Redis and redis-py installed with an instance of redis-server running.

How to do it...

We define a RedisConditionalHashFreqDist class in redisprob.py that extends nltk.probability.ConditionalFreqDist and overrides the __getitem__() method. We override __getitem__() so we can create an instance of RedisHashFreqDist instead of a FreqDist:

```
from nltk.probability import ConditionalFreqDist
from rediscollections import encode key
class RedisConditionalHashFreqDist(ConditionalFreqDist):
 def init (self, r, name, cond samples=None):
   self. r = r
    self. name = name
   ConditionalFreqDist. init (self, cond samples)
   for key in self. r.keys(encode key('%s:*' % name)):
      condition = key.split(':')[1]
      self[condition] # calls self. getitem (condition)
 def getitem (self, condition):
    if condition not in self. fdists:
     key = '%s:%s' % (self. name, condition)
     val = RedisHashFreqDist(self. r, key)
      super(RedisConditionalHashFreqDist,
self). setitem (condition, val)
    return super(RedisConditionalHashFreqDist,
self).__getitem__(condition)
 def clear(self):
```

```
for fdist in self.values():
    fdist.clear()
```

An instance of this class can be created by passing in a Redis connection and a **base name**. After that, it works just like a ConditionalFreqDist:

```
>>> from redis import Redis
>>> from redisprob import RedisConditionalHashFreqDist
>>> r = Redis()
>>> rchfd = RedisConditionalHashFreqDist(r, 'condhash')
>>> rchfd.N()
0
>>> rchfd.conditions()
[]
>>> rchfd['cond1']['foo'] += 1
>>> rchfd.N()
1
>>> rchfd['cond1']['foo']
1
>>> rchfd.conditions()
['cond1']
>>> rchfd.clear()
```

How it works...

The RedisConditionalHashFreqDist uses name prefixes to reference RedisHashFreqDist instances. The name passed into the RedisConditionalHashFreqDist is a base name that is combined with each condition to create a unique name for each RedisHashFreqDist. For example, if the base name of the RedisConditionalHashFreqDist is 'condhash', and the condition is 'cond1', then the final name for the RedisHashFreqDist is 'condhash:cond1'. This naming pattern is used at initialization to find all the existing hash maps using the keys command. By searching for all keys matching 'condhash:*', we can identify all the existing conditions and create an instance of RedisHashFreqDist for each.

Combining strings with colons is a common naming convention for Redis keys as a way to define namespaces. In our case, each RedisConditionalHashFreqDist instance defines a single namespace of hash maps.

There's more...

RedisConditionalHashFreqDist also defines a clear() method. This is a helper method that calls clear() on all the internal RedisHashFreqDist instances. The clear() method is not defined in ConditionalFreqDist.

See also

The previous recipe covers RedisHashFreqDist in detail. Also, see the *Calculating high information words* recipe in <u>Chapter 7</u>, *Text Classification*, for example usage of ConditionalFreqDist.

Storing an ordered dictionary in Redis

An ordered dictionary is like a normal dict, but the keys are ordered by an ordering function. In the case of Redis, it supports ordered dictionaries whose keys are strings and whose values are floating point scores. This structure can come in handy in cases where we need to calculate the information gain (covered in the *Calculating high information words* recipe in <u>Chapter 7</u>, *Text Classification*), and when you want to store all the words and scores for later use.

Getting ready

Again, you'll need Redis and redis-py installed with an instance of redis-server running, as explained in the earlier recipe, *Storing a frequency distribution in Redis*.

How to do it...

The RedisOrderedDict class in rediscollections.py extends collections.MutableMapping to get a number of dict compatible methods for free. Then, it implements all the key methods that require Redis ordered set (also known as **Zset**) commands:

```
class RedisOrderedDict(collections.MutableMapping):
 def init (self, r, name):
   self. r = r
   self. name = encode key(name)
 def iter (self):
   return iter(self.items())
 def len (self):
   return self. r.zcard(self. name)
 def getitem (self, key):
   return self. r.zscore(self. name, encode key(key))
 def setitem (self, key, score):
    self. r.zadd(self. name, encode key(key), score)
 def delitem (self, key):
    self. r.zrem(self. name, encode key(key))
 def keys(self, start=0, end=-1):
    # we use zrevrange to get keys sorted by high value instead of
by lowest
   return self. r.zrevrange(self. name, start, end)
 def values(self, start=0, end=-1):
    return [v for (k, v) in self.items(start=start, end=end)]
```

```
def items(self, start=0, end=-1):
   return self._r.zrevrange(self._name, start, end, withscores=True)
def get(self, key, default=0):
   return self[key] or default
def iteritems(self):
   return iter(self)
def clear(self):
   self. r.delete(self. name)
```

You can create an instance of RedisOrderedDict by passing in a Redis connection and a unique name:

```
>>> from redis import Redis
>>> from rediscollections import RedisOrderedDict
>>> r = Redis()
>>> rod = RedisOrderedDict(r, 'test')
>>> rod.get('bar')
>>> len(rod)
0
>>> rod['bar'] = 5.2
>>> rod['bar']
5.20000000000002
>>> len(rod)
1
>>> rod.items()
[(b'bar', 5.2)]
>>> rod.clear()
```

Note

By default, keys are returned as binary strings. If you want a plain string, you can convert the keys using key.decode(). You can always look up values with normal strings.

How it works...

Much of the code may look similar to the RedisHashMap, which is to be expected since they both extend collections.MutableMapping. The main difference here is that RedisOrderedSet orders keys by floating point values, and so it is not suited for arbitrary key-value storage like the RedisHashMap. Here's an outline explaining each key method and how they work with Redis:

- __len__(): This uses the zcard command to get the number of elements in the ordered set.
- _____getitem___(): This uses the zscore command to get the score of a key, and returns 0 if the key does not exist.

- _____setitem___(): This uses the zadd command to add a key to the ordered set with the given score, or updates the score if the key already exists.
- __delitem__(): This uses the zrem command to remove a key from the ordered set.
- keys(): This uses the zrevrange command to get all the keys in the ordered set, sorted by the highest score. It takes two optional keyword arguments, start and end, to more efficiently get a slice of the ordered keys.
- values(): This extracts all the scores from the items() method.
- items(): This uses the zrevrange command to get the scores of each key in order to return a list of 2-tuples ordered by the highest score. Like keys(), it takes start and end keyword arguments to efficiently get a slice.
- clear (): This uses the delete command to remove the entire ordered set from Redis.

Note

The default ordering of items in a Redis ordered set is low-to-high, so that the key with the lowest score comes first. This is the same as Python's default list ordering when you call <code>sort()</code> or <code>sorted()</code>, but this is not what we want when it comes to scoring. For storing scores, we expect items to be sorted from high-to-low, which is why keys() and items() use <code>zrevrange</code> instead of <code>zrange</code>.

All the Redis commands are documented at http://redis.io/commands.

There's more...

As mentioned previously, the keys () and items () methods take optional start and end keyword arguments to get a slice of the results. This makes RedisOrderedDict optimal for storing scores and getting the top N keys.

Note

The start and end keyword arguments are inclusive, so if you use start=0 and end=2, you will get up to three elements.

Here's a simple example where we assign three word scores and get the top two:

```
>>> from redis import Redis
>>> from rediscollections import RedisOrderedDict
>>> r = Redis()
>>> rod = RedisOrderedDict(r, 'scores')
>>> rod['best'] = 10
>>> rod['worst'] = 0.1
>>> rod['middle'] = 5
>>> rod.keys()
[b'best', b'middle', b'worst']
>>> rod.keys(start=0, end=1)
[b'best', b'middle']
>>> rod.clear()
```

See also

The *Calculating high information words* recipe in <u>Chapter 7</u>, *Text Classification*, describes how to calculate information gain, which is a good case for storing word scores in a RedisOrderedDict. The *Storing a frequency distribution in Redis* recipe introduces Redis and the RedisHashMap.

Distributed word scoring with Redis and execnet

We can use Redis and execnet together to do distributed word scoring. In the *Calculating high information words* recipe in <u>Chapter 7</u>, *Text Classification*, we calculated the information gain of each word in the movie_reviews corpus using a FreqDist and ConditionalFreqDist. Now that we have Redis, we can do the same thing using a RedisHashFreqDist and a RedisConditionalHashFreqDist, and then store the scores in a RedisOrderedDict. We can use execut to distribute the counting in order to get a better performance out of Redis.

Getting ready

Redis, redis-py, and execnet must be installed, and an instance of redis-server must be running on localhost.

How to do it ...

We start by getting a list of (label, words) tuples for each label in the movie_reviews corpus (which only has pos and neg labels). Then, we get the word_scores using score_words() from the dist_featx module. The word_scores function is an instance of RedisOrderedDict, and we can see that the total number of words is 39,764. Using the keys() method, we can then get the top 1,000 words and inspect the top five, just to see what they are. Once we've gotten all we want from word_scores, we can delete the keys in Redis, as we no longer need the data.

```
>>> from dist featx import score words
>>> from nltk.corpus import movie reviews
>>> labels = movie reviews.categories()
>>> labelled words = [(l, movie reviews.words(categories=[l])) for l
in labels]
>>> word scores = score words (labelled words)
>>> len(word scores)
39767
>>> topn words = word scores.keys(end=1000)
>>> topn words[0:5]
[b'bad', b',', b'and', b'?', b'movie']
>>> from redis import Redis
>>> r = Redis()
>>> [r.delete(key) for key in ['word fd', 'label word fd:neg',
'label word fd:pos', 'word scores']]
[1, 1, 1, 1]
```

The score_words() function from dist_featx can take a while to complete, so expect to wait a couple of minutes. The overhead of using execnet and Redis means it will take significantly longer than a nondistributed, in-memory version of the function.

How it works...

The dist featx.py module contains the score words () function, which does the following:

- Opens gateways and channels, sending initialization data to each channel
- Sends each (label, words) tuple over a channel for counting
- Sends a done message to each channel, waits for a done reply back, then closes the channels and gateways
- Calculates the score of each word based on the counts and stores in a RedisOrderedDict

In our case of counting words in the movie_reviews corpus, calling score_words() opens two gateways and channels, one for counting the pos words and the other for counting the neg words. The communication looks like the following diagram:



Once the counting is finished, we can score all the words and store the results. The code itself is as follows:

import itertools, execnet, remote_word_count from nltk.metrics import BigramAssocMeasures from redis import Redis from redisprob import RedisHashFreqDist, RedisConditionalHashFreqDist from rediscollections import RedisOrderedDict

def score_words(labelled_words, score_fn=BigramAssocMeasures.chi_sq,

```
host='localhost', specs=[('popen', 2)]):
  gateways = []
  channels = []
  for spec, count in specs:
    for i in range(count):
      gw = execnet.makegateway(spec)
      gateways.append(gw)
      channel = gw.remote exec(remote word count)
      channel.send((host, 'word fd', 'label word fd'))
      channels.append(channel)
  cyc = itertools.cycle(channels)
  for label, words in labelled words:
    channel = next(cyc)
    channel.send((label, list(words)))
  for channel in channels:
    channel.send('done')
    assert 'done' == channel.receive()
    channel.waitclose(5)
  for gateway in gateways:
    gateway.exit()
  r = \text{Redis(host)}
  fd = RedisHashFreqDist(r, 'word fd')
  cfd = RedisConditionalHashFreqDist(r, 'label word fd')
  word scores = RedisOrderedDict(r, 'word scores')
  n xx = cfd.N()
  for label in cfd.conditions():
    n xi = cfd[label].N()
    for word, n ii in cfd[label].iteritems():
      word = word.decode()
      n ix = fd[word]
      if n ii and n ix and n xi and n xx:
        score = score_fn(n_ii, (n_ix, n_xi), n_xx)
        word scores[word] = score
  return word scores
```

Note

Note that this scoring method will only be accurate for comparing two labels. If there are more than two labels, a different scoring method should be used, and its requirements will dictate how you store word scores.

```
The remote word count.py module looks like the following code:
```

```
from redis import Redis
from redisprob import RedisHashFreqDist, RedisConditionalHashFreqDist
if __name__ == '__channelexec__':
    host, fd_name, cfd_name = channel.receive()
    r = Redis(host)
    fd = RedisHashFreqDist(r, fd_name)
    cfd = RedisConditionalHashFreqDist(r, cfd_name)
    for data in channel:
        if data == 'done':
            channel.send('done')
            break
    label, words = data
    for word in words:
        fd[word] += 1
        cfd[label][word] += 1
```

You'll notice that this is not a pure module, as it requires being able to import both redis and redisprob. The reason is that instances of RedisHashFreqDist and RedisConditionalHashFreqDist cannot be pickled and sent over the channel. Instead, we send the hostname and key names over the channel so we can create the instances in the remote module. Once we have the instances, there are two kinds of data we can receive over the channel:

- A done message, which signals that there is no more data coming in over the channel. We reply back with another done message, then exit the loop to close the channel.
- A 2-tuple of (label, words), which we then iterate over to increment counts in both the RedisHashFreqDist and RedisConditionalHashFreqDist.

There's more...

In this particular case, it would be faster to compute the scores without using Redis or execnet. However, by using Redis, we can store the scores persistently for later examination and usage. Being able to inspect all the word counts and scores manually is a great way to learn about your data. We can also tweak feature extraction without having to re-compute the scores. For example, you could use featx.bag_of_words_in_set() (found in <u>Chapter 7</u>, *Text Classification*) with the top N words from the RedisOrderedDict, where N could be 1,000, 2,000, or whatever number you want. If our data size is much greater, the benefits of execnet will be much more apparent. Horizontal scalability using execnet or some other method to distribute computations across many nodes becomes more valuable as the size of the data you need to process increases. This method of word scoring is much slower than if we weren't using Redis, but the benefit is that the numbers are stored persistently.

See also

The *Calculating high information words* recipe in <u>Chapter 7</u>, *Text Classification*, introduces information gain scoring of words for feature extraction and classification. The first three recipes of this chapter show how to use <code>execnet</code>, while the next three recipes describe <code>RedisHashFreqDist</code>, <code>RedisConditionalHashFreqDist</code>, and <code>RedisOrderedDict</code>, respectively.
Chapter 9. Parsing Specific Data Types

In this chapter, we will cover the following recipes:

- Parsing dates and times with dateutil
- Timezone lookup and conversion
- Extracting URLs from HTML with lxml
- Cleaning and stripping HTML
- Converting HTML entities with BeautifulSoup
- Detecting and converting character encodings

Introduction

This chapter covers parsing specific kinds of data, focusing primarily on dates, times, and HTML. Luckily, there are a number of useful libraries to accomplish this, so we don't have to delve into tricky and overly complicated regular expressions. These libraries can be great complements to NLTK:

- dateutil provides datetime parsing and timezone conversion
- lxml and BeautifulSoup can parse, clean, and convert HTML
- charade and UnicodeDammit can detect and convert text character encoding

These libraries can be useful for preprocessing text before passing it to an NLTK object, or postprocessing text that has been processed and extracted using NLTK. Coming up is an example that ties many of these tools together.

Let's say you need to parse a blog article about a restaurant. You can use lxml or BeautifulSoup to extract the article text, outbound links, and the date and time when the article was written. The date and time can then be parsed to a Python datetime object with dateutil. Once you have the article text, you can use charade to ensure it's utf-8 before cleaning out the HTML and running it through NLTK-based part-of-speech tagging, chunk extraction, and/or text classification to create additional metadata about the article. Real-world text processing often requires more than just NLTK-based natural language processing, and the functionality covered in this chapter can help with those additional requirements.

Parsing dates and times with dateutil

If you need to parse dates and times in Python, there is no better library than dateutil. The parser module can parse datetime strings in many more formats than can be shown here, while the tz module provides everything you need for looking up timezones. When combined, these modules make it quite easy to parse strings into timezone-aware datetime objects.

Getting ready

You can install dateutil using pip or easy_install, that is, sudo pip install dateutil==2.0 or sudo easy_install dateutil==2.0. You need the 2.0 version for Python 3 compatibility. The complete documentation can be found at http://labix.org/python-dateutil

How to do it...

Let's dive into a few parsing examples:

```
>>> from dateutil import parser
>>> parser.parse('Thu Sep 25 10:36:28 2010')
datetime.datetime(2010, 9, 25, 10, 36, 28)
>>> parser.parse('Thursday, 25. September 2010 10:36AM')
datetime.datetime(2010, 9, 25, 10, 36)
>>> parser.parse('9/25/2010 10:36:28')
datetime.datetime(2010, 9, 25, 10, 36, 28)
>>> parser.parse('9/25/2010')
datetime.datetime(2010, 9, 25, 0, 0)
>>> parser.parse('2010-09-25T10:36:28Z')
datetime.datetime(2010, 9, 25, 10, 36, 28, tzinfo=tzutc())
```

As you can see, all it takes is importing the parser module and calling the parse() function with a datetime string. The parser will do its best to return a sensible datetime object, but if it cannot parse the string, it will raise a ValueError.

How it works...

The parser does not use regular expressions. Instead, it looks for recognizable tokens and does its best to guess what those tokens refer to. The order of these tokens matters; for example, some cultures use a date format that looks like *Month/Day/Year* (the default order), while others use a *Day/Month/Year* format. To deal with this, the parse() function takes an optional keyword argument, dayfirst, which defaults to False. If you set it to True, it can correctly parse dates in the latter format.

```
>>> parser.parse('25/9/2010', dayfirst=True)
datetime.datetime(2010, 9, 25, 0, 0)
```

Another ordering issue can occur with two-digit years. For example, '10-9-25' is ambiguous. Since dateutil defaults to the *Month-Day-Year* format, '10-9-25' is parsed to the year 2025. But if you pass yearfirst=True into parse(), it will be parsed to the year 2010:

```
>>> parser.parse('10-9-25')
datetime.datetime(2025, 10, 9, 0, 0)
>>> parser.parse('10-9-25', yearfirst=True)
datetime.datetime(2010, 9, 25, 0, 0)
```

There's more...

The dateutil parser can also do fuzzy parsing, which allows it to ignore extraneous characters in a datetime string. With the default value of False, parse() will raise a ValueError when it encounters unknown tokens. But if fuzzy=True, then a datetime object can usually be returned:

```
>>> try:
... parser.parse('9/25/2010 at about 10:36AM')
... except ValueError:
... 'cannot parse'
'cannot parse'
>>> parser.parse('9/25/2010 at about 10:36AM', fuzzy=True)
datetime.datetime(2010, 9, 25, 10, 36)
```

See also

In the next recipe, we'll use the tz module of dateutil to do timezone lookup and conversion.

Timezone lookup and conversion

Most datetime objects returned from the dateutil parser are naïve, meaning they don't have an explicit tzinfo, which specifies the timezone and UTC offset. In the previous recipe, only one of the examples had a tzinfo, and that's because it's in the standard ISO format for UTC datetime strings. UTC is the coordinated universal time, and is basically the same as GMT. **ISO** is the **International Standards Organization**, which among other things, specifies standard datetime formatting.

Python datetime objects can either be naïve or aware. If a datetime object has a tzinfo, then it is aware. Otherwise, the datetime is naïve. To make a naïve datetime object timezone aware, you must give it an explicit tzinfo. However, the Python datetime library only defines an abstract baseclass for tzinfo, and leaves it up to others to actually implement tzinfo creation. This is where the tz module of dateutil comes in—it provides everything you need to look up timezones from your OS timezone data.

Getting ready

dateutil should be installed using pip or easy_install. You should also make sure your operating system has timezone data. On Linux, this is usually found in /usr/share/zoneinfo, and the Ubuntu package is called tzdata. If you have a number of files and directories in /usr/share/zoneinfo, such as America/ and Europe/, then you should be ready to proceed. The upcoming examples show directory paths for Ubuntu Linux.

How to do it...

Let's start by getting a UTC tzinfo object. This can be done by calling tz.tzutc(), and you can check that the offset is 0 by calling the utcoffset() method with a UTC datetime object:

```
>>> from dateutil import tz
>>> tz.tzutc()
tzutc()
>>> import datetime
>>> tz.tzutc().utcoffset(datetime.datetime.utcnow())
datetime.timedelta(0)
```

To get tzinfo objects for other timezones, you can pass in a timezone file path to the gettz() function:

```
>>> tz.gettz('US/Pacific')
tzfile('/usr/share/zoneinfo/US/Pacific')
>>> tz.gettz('US/Pacific').utcoffset(datetime.datetime.utcnow())
datetime.timedelta(-1, 61200)
>>> tz.gettz('Europe/Paris')
tzfile('/usr/share/zoneinfo/Europe/Paris')
>>> tz.gettz('Europe/Paris').utcoffset(datetime.datetime.utcnow())
datetime.timedelta(0, 7200)
```

You can see that the UTC offsets are timedelta objects, where the first number is days and the second number is seconds.

Tip

If you're storing datetimes in a database, it's a good idea to store them all in UTC to eliminate any timezone ambiguity. Even if the database can recognize timezones, it's still good practice.

To convert a non-UTC datetime object to UTC, it must be made timezone aware. If you try to convert a naïve datetime to UTC, you'll get a ValueError exception. To make a naïve datetime timezone aware, you simply call the replace () method with the correct tzinfo. Once a datetime object has a tzinfo, then UTC conversion can be performed by calling the astimezone () method with tz.tzutc().

```
>>> pst = tz.gettz('US/Pacific')
Υ
>>> dt = datetime.datetime(2010, 9, 25, 10, 36)
>>> dt.tzinfo
>>> dt.astimezone(tz.tzutc())
Traceback (most recent call last):
  File "/usr/lib/python2.6/doctest.py", line 1248, in run
  compileflags, 1) in test.globs
  File "<doctest main [22]>", line 1, in <module>
  dt.astimezone(tz.tzutc())
ValueError: astimezone() cannot be applied to a naive datetime
>>> dt.replace(tzinfo=pst)
datetime.datetime(2010, 9, 25, 10, 36, tzinfo=tzfile('/usr/share/
zoneinfo/US/Pacific'))
>>> dt.replace(tzinfo=pst).astimezone(tz.tzutc())
datetime.datetime(2010, 9, 25, 17, 36, tzinfo=tzutc())
```

Note

The tzfile paths vary across operating systems, so your tzfile paths may differ from the examples. There is no cause for concern, unless you are getting different datetime values.

How it works...

The tzutc and tzfile objects are both subclasses of tzinfo. As such, they know the correct UTC offset for timezone conversion (which is 0 for tzutc). A tzfile object knows how to read your operating system's zoneinfo files to get the necessary offset data. The replace () method of a datetime object does what the name implies—it replaces attributes. Once a datetime has a tzinfo, the astimezone () method will be able to convert the time using the UTC offsets, and then replace the current tzinfo with the new tzinfo.

Note

Note that both replace () and astimezone () return new datetime objects. They do not modify the current object.

There's more...

You can pass a tzinfos keyword argument into the dateutil parser to detect the otherwise unrecognized timezones:

```
>>> parser.parse('Wednesday, Aug 4, 2010 at 6:30 p.m. (CDT)',
fuzzy=True)
datetime.datetime(2010, 8, 4, 18, 30)
>>> tzinfos = {'CDT': tz.gettz('US/Central')}
>>> parser.parse('Wednesday, Aug 4, 2010 at 6:30 p.m. (CDT)',
fuzzy=True, tzinfos=tzinfos)
datetime.datetime(2010, 8, 4, 18, 30, tzinfo=tzfile('/usr/share/
zoneinfo/US/Central'))
```

In the first instance, we get a naïve datetime since the timezone is not recognized. But when we pass in the tzinfos mapping, we get a timezone-aware datetime.

Local timezone

If you want to look up your local timezone, you can call tz.tzlocal(), which will use whatever your operating system thinks is the local timezone. In Ubuntu Linux, this is usually specified in the /etc/timezone file.

Custom offsets

You can create your own tzinfo object with a custom UTC offset using the tzoffset object. A custom offset of 1 hour could be created as follows:

```
>>> tz.tzoffset('custom', 3600)
tzoffset('custom', 3600)
```

You must provide a name as the first argument and the offset time in seconds as the second argument.

See also

The previous recipe, *Parsing dates and times with dateutil*, covers parsing datetime strings with dateutil.parser.

Extracting URLs from HTML with lxml

A common task when parsing HTML is extracting links. This is one of the core functions of every general web crawler. There are a number of Python libraries for parsing HTML, and lxml is one of the best. As you'll see, it comes with some great helper functions geared specifically towards link extraction.

Getting ready

lxml is a Python binding for the C libraries libxml2 and libxslt. This makes it a very fast XML and HTML parsing library, while still being Pythonic. But that also means you need to install the C libraries for it to work. Installation instructions are available at <u>http://lxml.de/installation.html</u>. But if you're running Ubuntu Linux, installation is as easy as sudo apt-get install python-lxml. You can also try doing pip install lxml. The latest version as of this writing is 3.3.5.

How to do it...

lxml comes with an html module designed specifically for parsing HTML. Using the
fromstring() function, we can parse an HTML string and get a list of all the links. The
iterlinks() method generates 4-tuples of the form (element, attr, link, pos):

- element: This is the parsed node of the anchor tag from which the link is extracted. If you're just interested in the link, you can ignore this.
- attr: This is the attribute the link came from, which is usually 'href'.
- link: This is the actual URL extracted from the anchor tag.
- pos: This is the numeric index of the anchor tag in the document. The first tag has a pos of 0, the second has a pos of 1, and so on.

Here's some code to demonstrate:

```
>>> from lxml import html
>>> doc = html.fromstring('Hello <a href="/world">world</a>')
>>> links = list(doc.iterlinks())
>>> len(links)
1
>>> (el, attr, link, pos) = links[0]
>>> attr
'href'
>>> link
'/world'
>>> pos
0
```

How it works...

lxml parses the HTML into an ElementTree. This is a tree structure of parent nodes and child nodes, where each node represents an HTML tag and contains all the corresponding attributes of that

tag. Once the tree is created, it can be iterated on to find elements, such as the **a** or **anchor** tag. The core tree handling code is in the lxml.etree module, while the lxml.html module contains only HTML-specific functions for creating and iterating a tree. For complete documentation, see the lxml tutorial at http://lxml.de/tutorial.html.

There's more...

You'll notice that the link mentioned earlier is **relative**, meaning it's not an absolute URL. We can make it **absolute** by calling the make_links_absolute() method with a base URL before extracting the links:

```
>>> doc.make_links_absolute('http://hello')
>>> abslinks = list(doc.iterlinks())
>>> (el, attr, link, pos) = abslinks[0]
>>> link
'http://hello/world'
```

Extracting links directly

If you don't want to do anything other than extract links, you can call the *iterlinks()* function with an HTML string:

```
>>> links = list(html.iterlinks('Hello <a href="/world">world</a>'))
>>> links[0][2]
'/world'
```

Parsing HTML from URLs or files

Instead of parsing an HTML string using the fromstring() function, you can call the parse() function with a URL or filename; for example, html.parse('http://my/url') or html.parse('/path/to/file'). The result will be the same as if you loaded the URL or file into a string yourself and then called fromstring().

Extracting links with XPaths

Instead of using the iterlinks () method, you can also get links using the xpath() method, which is a general way to extract whatever you want from HTML or XML parse trees:

>>> doc.xpath('//a/@href')[0]
'http://hello/world'

For more on XPath syntax, see <u>http://www.w3schools.com/XPath/xpath_syntax.asp</u>.

See also

In the next recipe, we'll cover cleaning and stripping HTML.

Cleaning and stripping HTML

Cleaning up text is one of the unfortunate but entirely necessary aspects of text processing. When it comes to parsing HTML, you probably don't want to deal with any embedded JavaScript or CSS, and are only interested in the tags and text.

Getting ready

You'll need to install lxml. See the previous recipe or <u>http://lxml.de/installation.html</u> for installation instructions.

How to do it...

We can use the clean_html() function in the lxml.html.clean module to remove unnecessary HTML tags and embedded JavaScript from an HTML string:

```
>>> import lxml.html.clean
>>> lxml.html.clean.clean_html('<html><head></head><body
onload=loadfunc()>my text</body></html>')
'<div><body>my text</body></div>'
```

The result is much cleaner and easier to deal with.

How it works...

The lxml.html.clean_html() function parses the HTML string into a tree and then iterates over and removes all nodes that should be removed. It also cleans nodes of unnecessary attributes (such as embedded JavaScript) using regular expression matching and substitution.

There's more...

The lxml.html.clean module defines a default Cleaner class that's used when you call clean_html(). You can customize the behavior of this class by creating your own instance and calling its clean_html() method. For more details on this class, see http://lxml.de/lxmlhtml.html#cleaning-up-html.

See also

The lxml.html module was introduced in the previous recipe for parsing HTML and extracting links. In the next recipe, we'll cover unescaping HTML entities.

Converting HTML entities with BeautifulSoup

HTML entities are strings such as "&" or "<". These are encodings of normal ASCII characters that have special uses in HTML. For example, "<" is the entity for "<", but you can't just have "<" within HTML tags because it is the beginning character for an HTML tag, hence the need to escape it and define the "<" entity. "&" is the entity code for "&", which as we've just seen is the beginning character for an entity code. If you need to process the text within an HTML document, then you'll want to convert these entities back to their normal characters so you can recognize them and handle them appropriately.

Getting ready

You'll need to install BeautifulSoup, which you should be able to do with sudo pip install beautifulsoup4 or sudo easy_install beautifulsoup4. You can read more about BeautifulSoup at http://www.crummy.com/software/BeautifulSoup/.

How to do it...

BeautifulSoup is an HTML parser library that can also be used for entity conversion. It's quite simple: create an instance of BeautifulSoup given a string containing HTML entities, then get the string attribute:

```
>>> from bs4 import BeautifulSoup
>>> BeautifulSoup('<').string
'<'
>>> BeautifulSoup('&amp;').string
'&'
```

However, the reverse is not true. If you try to do BeautifulSoup('<'), you will get a None result because that is not valid in HTML.

How it works...

To convert the HTML entities, BeautifulSoup looks for tokens that look like an entity and replaces them with their corresponding value in the htmlentitydefs.name2codepoint dictionary from the Python standard library. It can do this if the entity token is within an HTML tag, or when it's in a normal string.

There's more...

BeautifulSoup is an excellent HTML and XML parser in its own right, and can be a great alternative to lxml. It's particularly good at handling malformed HTML. You can read more about how to use it at <u>http://www.crummy.com/software/BeautifulSoup/bs4/doc/</u>.

Extracting URLs with BeautifulSoup

Here's an example of using BeautifulSoup to extract URLs, like we did in the *Extracting URLs from HTML with lxml* recipe. You first create the soup with an HTML string, call the findAll() method with 'a' to get all anchor tags, and pull out the 'href' attribute to get the URLs:

```
>>> from bs4 import BeautifulSoup
>>> soup = BeautifulSoup('Hello <a href="/world">world</a>')
>>> [a['href'] for a in soup.findAll('a')]
['/world']
```

See also

In the *Extracting URLs from HTML with lxml* recipe, we covered how to use lxml to extract URLs from an HTML string, and we also covered the *Cleaning and stripping HTML* recipe after that.

Detecting and converting character encodings

A common occurrence with text processing is finding text that has nonstandard character encoding. Ideally, all text would be ASCII or utf-8, but that's just not the reality. In cases when you have non-ASCII or non-utf-8 text and you don't know what the character encoding is, you'll need to detect it and convert the text to a standard encoding before doing further processing.

Getting ready

You'll need to install the charade module using sudo pip install charade or sudo easy_install charade. You can learn more about charade at https://pypi.python.org/pypi/charade.

How to do it...

Encoding detection and conversion functions are provided in encoding.py. These are simple wrapper functions around the charade module. To detect the encoding of a string, call encoding.detect(string).You'll get back a dict containing two attributes: confidence and encoding. The confidence attribute is a probability of how confident charade is that the value for encoding is correct.

```
# -*- coding: utf-8 -*-
import charade
def detect(s):
  try:
    if isinstance(s, str):
      return charade.detect(s.encode())
    else:
      return charade.detect(s)
  except UnicodeDecodeError:
    return charade.detect(s.encode('utf-8'))
def convert(s):
  if isinstance(s, str):
    s = s.encode()
  encoding = detect(s)['encoding']
  if encoding == 'utf-8':
    return s.decode()
  else:
    return s.decode(encoding)
```

And here's some example code using detect() to determine character encoding:

```
>>> import encoding
>>> encoding.detect('ascii')
{'confidence': 1.0, 'encoding': 'ascii'}
>>> encoding.detect('abcdé')
{'confidence': 0.505, 'encoding': 'utf-8'}
>>> encoding.detect(bytes('\222\222\223\225', 'latin-1'))
{'confidence': 0.5, 'encoding': 'windows-1252'}
```

To convert a string to a standard unicode encoding, call encoding.convert(). This will decode the string from its original encoding and then re-encode it as utf-8.

```
>>> encoding.convert('ascii')
'ascii'
>>> encoding.convert('abcdé')
'abcdé'
>>> encoding.convert((bytes('\222\223\225', 'latin-1'))
'\u2019\u2019\u201c\u2022'
```

How it works...

The detect() function is a wrapper around charade.detect() that can encode strings and handle UnicodeDecodeError exceptions. The charade.detect() method expects a bytes object, not a string, so in these cases, the string is encoded before trying to detect the encoding.

The convert() function first calls detect() to get the encoding and, then returns a decoded string.

There's more...

The comment at the top of the module, # -*- coding: utf-8 -*-, is a hint to the Python interpreter that tells which encoding to use for the strings in the code. This is helpful for when you have non-ASCII strings in your source code, and is documented in detail at <u>http://www.python.org/dev/peps/pep-0263/</u>.

Converting to ASCII

If you want pure ASCII text, with non-ASCII characters converted to ASCII equivalents or dropped if there is no equivalent character, then you can use the unicodedata.normalize() function:

```
>>> import unicodedata
>>> unicodedata.normalize('NFKD', 'abcd\xe9').encode('ascii',
'ignore')
b'abcde'
```

Specifying 'NFKD' as the first argument ensures that the non-ASCII characters are replaced with their equivalent ASCII versions, and the final call to encode () with 'ignore' as the second argument will remove any extraneous unicode characters. This returns a bytes object, which you can call decode () on to get a string.

UnicodeDammit conversion

The BeautifulSoup library contains a helper class called UnicodeDammit, which can do automatic conversion to unicode. Its usage is very simple:

```
>>> from bs4 import UnicodeDammit
>>> UnicodeDammit('abcd\xe9').unicode_markup
'abcdé'
```

Installing BeautifulSoup is covered in the previous recipe, *Converting HTML entities with BeautifulSoup*.

See also

Encoding detection and conversion is a recommended first step before doing HTML processing with lxml or BeautifulSoup, covered in the *Extracting URLs from HTML with lxml* and *Converting HTML entities with BeautifulSoup* recipes.

Appendix A. Penn Treebank Part-of-speech Tags

The following is a table of all the part-of-speech tags that occur in the treebank corpus distributed with NLTK. The tags and counts shown here were acquired using the following code:

```
>>> from nltk.probability import FreqDist
>>> from nltk.corpus import treebank
>>> fd = FreqDist()
>>> for word, tag in treebank.tagged_words():
... fd[tag] += 1
>>> fd.items()
```

The FreqDist fd contains all the counts shown here for every tag in the treebank corpus. You can inspect each tag count individually, by doing fd[tag], for example, fd['DT']. Punctuation tags are also shown, along with special tags such as -NONE-, which signifies that the part-of-speech tag is unknown. Descriptions of most of the tags can be found at the following link:

http://www.ling.upenn.edu/courses/Fall 2003/ling001/penn treebank pos.html

Part-of-speech tag	Frequency of occurrence
#	16
\$	724
• •	694
,	4886
-LRB-	120
-NONE-	6592
-RRB-	126
•	384
:	563

Part-of-speech tag	Frequency of occurrence
	712
сс	2265
CD	3546
DT	8165
EX	88
FW	4
IN	9857
JJ	5834
JJR	381
JJS	182
LS	13
MD	927
NN	13166
NNP	9410
NNPS	244
NNS	6047

Part-of-speech tag	Frequency of occurrence
PDT	27
POS	824
PRP	1716
PRP\$	766
RB	2822
RBR	136
RBS	35
RP	216
SYM	1
ТО	2179
UH	3
VB	2554
VBD	3043
VBG	1460
VBN	2134
VBP	1321

Part-of-speech tag	Frequency of occurrence
VBZ	2125
WDT	445
WP	241
WP\$	14
WRB	178

Part 3. Module 3

Mastering Natural Language Processing with Python

Maximize your NLP capabilities while creating amazing NLp projects in Python

Chapter 1. Working with Strings

Natural Language Processing (NLP) is concerned with the interaction between natural language and the computer. It is one of the major components of **Artificial Intelligence** (**AI**) and computational linguistics. It provides a seamless interaction between computers and human beings and gives computers the ability to understand human speech with the help of machine learning. The fundamental data type used to represent the contents of a file or a document in programming languages (for example, C, C++, JAVA, Python, and so on) is known as string. In this chapter, we will explore various operations that can be performed on strings that will be useful to accomplish various NLP tasks.

This chapter will include the following topics:

- Tokenization of text
- Normalization of text
- Substituting and correcting tokens
- Applying Zipf's law to text
- Applying similarity measures using the Edit Distance Algorithm
- Applying similarity measures using Jaccard's Coefficient
- Applying similarity measures using Smith Waterman

Tokenization

Tokenization may be defined as the process of splitting the text into smaller parts called tokens, and is considered a crucial step in NLP.

When NLTK is installed and Python IDLE is running, we can perform the tokenization of text or paragraphs into individual sentences. To perform tokenization, we can import the sentence tokenization function. The argument of this function will be text that needs to be tokenized. The sent_tokenize function uses an instance of NLTK known as PunktSentenceTokenizer. This instance of NLTK has already been trained to perform tokenization on different European languages on the basis of letters or punctuation that mark the beginning and end of sentences.

Tokenization of text into sentences

Now, let's see how a given text is tokenized into individual sentences:

```
>>> import nltk
>>> text=" Welcome readers. I hope you find it interesting. Please
do reply."
>>> from nltk.tokenize import sent_tokenize
>>> sent_tokenize(text)
[' Welcome readers.', 'I hope you find it interesting.', 'Please do
reply.']
```

So, a given text is split into individual sentences. Further, we can perform processing on the individual sentences.

To tokenize a large number of sentences, we can load PunktSentenceTokenizer and use the tokenize() function to perform tokenization. This can be seen in the following code:

>>> import nltk
>>> tokenizer=nltk.data.load('tokenizers/punkt/english.pickle')
>>> text=" Hello everyone. Hope all are fine and doing well. Hope
you find the book interesting"
>>> tokenizer.tokenize(text)
[' Hello everyone.', 'Hope all are fine and doing well.', 'Hope you
find the book interesting']

Tokenization of text in other languages

For performing tokenization in languages other than English, we can load the respective language pickle file found in tokenizers/punkt and then tokenize the text in another language, which is an argument of the tokenize() function. For the tokenization of French text, we will use the french.pickle file as follows:

```
>> import nltk
>>> french tokenizer=nltk.data.load('tokenizers/punkt/french.pickle')
>>> french tokenizer.tokenize('Deux agressions en quelques jours,
voilà ce qui a motivé hier matin le débrayage collège
franco-britanniquedeLevallois-Perret. Deux agressions en quelques
jours, voilà ce qui a motivé hier matin le débrayage Levallois.
L'équipe pédagogique de ce collège de 750 élèves avait déjà été
choquée par l'agression, janvier, d'un professeur d'histoire.
L'équipe pédagogique de ce collège de 750 élèves avait déjà été
choquée par l'agression, mercredi, d'un professeur d'histoire')
['Deux agressions en quelques jours, voilà ce qui a motivé hier
matin le débrayage collège franco-britanniquedeLevallois-Perret.',
'Deux agressions en quelques jours, voilà ce qui a motivé hier matin
le débrayage Levallois.', 'L'équipe pédagogique de ce collège de
750 élèves avait déjà été choquée par l'agression, janvier, d'un
professeur d'histoire.', 'L'équipe pédagogique de ce collège de 750
élèves avait déjà été choquée par l'agression, mercredi, d'un
professeur d'histoire']
```

Tokenization of sentences into words

Now, we'll perform processing on individual sentences. Individual sentences are tokenized into words. Word tokenization is performed using a word_tokenize() function. The word_tokenize function uses an instance of NLTK known as TreebankWordTokenizer to perform word tokenization.

The tokenization of English text using word tokenize is shown here:

```
>>> import nltk
>>> text=nltk.word_tokenize("PierreVinken , 59 years old , will join
as a nonexecutive director on Nov. 29 .»)
>>> print(text)
[' PierreVinken', ',', '59', ' years', ' old', ',', 'will', 'join',
'as', 'a', 'nonexecutive', 'director' , 'on', 'Nov.', '29', '.']
```

Tokenization of words can also be done by loading TreebankWordTokenizer and then calling the tokenize() function, whose argument is a sentence that needs to be tokenized into words. This instance of NLTK has already been trained to perform the tokenization of sentence into words on the basis of spaces and punctuation.

The following code will help us obtain user input, tokenize it, and evaluate its length:

```
>>> import nltk
>>> from nltk import word_tokenize
>>> r=input("Please write a text")
Please write a textToday is a pleasant day
>>> print("The length of text is",len(word_tokenize(r)),"words")
The length of text is 5 words
```

Tokenization using TreebankWordTokenizer

Let's have a look at the code that performs tokenization using TreebankWordTokenizer:

```
>>> import nltk
>>> from nltk.tokenize import TreebankWordTokenizer
>>> tokenizer = TreebankWordTokenizer()
>>> tokenizer.tokenize("Have a nice day. I hope you find the book
interesting")
['Have', 'a', 'nice', 'day.', 'I', 'hope', 'you', 'find', 'the',
'book', 'interesting']
```

TreebankWordTokenizer uses conventions according to Penn Treebank Corpus. It works by separating contractions. This is shown here:

```
>>> import nltk
>>> text=nltk.word_tokenize(" Don't hesitate to ask questions")
>>> print(text)
['Do', "n't", 'hesitate', 'to', 'ask', 'questions']
```

Another word tokenizer is PunktWordTokenizer. It works by splitting punctuation; each word is kept instead of creating an entirely new token. Another word tokenizer is WordPunctTokenizer. It provides splitting by making punctuation an entirely new token. This type of splitting is usually desirable:

```
>>> from nltk.tokenize import WordPunctTokenizer
>>> tokenizer=WordPunctTokenizer()
>>> tokenizer.tokenize(" Don't hesitate to ask questions")
['Don', "'", 't', 'hesitate', 'to', 'ask', 'questions']
```

The inheritance tree for tokenizers is given here:



Tokenization using regular expressions

The tokenization of words can be performed by constructing regular expressions in these two ways:

- By matching with words
- By matching spaces or gaps

We can import RegexpTokenizer from NLTK. We can create a Regular Expression that can match the tokens present in the text:

```
>>> import nltk
>>> from nltk.tokenize import RegexpTokenizer
>>> tokenizer=RegexpTokenizer([\w]+")
>>> tokenizer.tokenize("Don't hesitate to ask questions")
["Don't", 'hesitate', 'to', 'ask', 'questions']
```

Instead of instantiating class, an alternative way of tokenization would be to use this function:

```
>>> import nltk
>>> from nltk.tokenize import regexp_tokenize
>>> sent="Don't hesitate to ask questions"
```

```
>>> print(regexp_tokenize(sent, pattern='\w+|\$[\d\.]+|\S+'))
['Don', "'t", 'hesitate', 'to', 'ask', 'questions']
```

RegularexpTokenizer uses the re.findall() function to perform tokenization by matching tokens. It uses the re.split() function to perform tokenization by matching gaps or spaces.

Let's have a look at an example of how to tokenize using whitespaces:

```
>>> import nltk
>>> from nltk.tokenize import RegexpTokenizer
>>> tokenizer=RegexpTokenizer('\s+',gaps=True)
>>> tokenizer.tokenize("Don't hesitate to ask questions")
["Don't", 'hesitate', 'to', 'ask', 'questions']
```

To select the words starting with a capital letter, the following code is used:

```
>>> import nltk
>>> from nltk.tokenize import RegexpTokenizer
>>> sent=" She secured 90.56 % in class X . She is a meritorious
student"
>>> capt = RegexpTokenizer('[A-Z]\w+')
>>> capt.tokenize(sent)
['She', 'She']
```

The following code shows how a predefined Regular Expression is used by a subclass of RegexpTokenizer:

```
>>> import nltk
>>> sent=" She secured 90.56 % in class X . She is a meritorious
student"
>>> from nltk.tokenize import BlanklineTokenizer
>>> BlanklineTokenizer().tokenize(sent)
[' She secured 90.56 % in class X \n. She is a meritorious student\
n']
```

The tokenization of strings can be done using whitespace—tab, space, or newline:

```
>>> import nltk
>>> sent=" She secured 90.56 % in class X . She is a meritorious
student"
>>> from nltk.tokenize import WhitespaceTokenizer
>>> WhitespaceTokenizer().tokenize(sent)
['She', 'secured', '90.56', '%', 'in', 'class', 'X', '.', 'She',
'is', 'a', 'meritorious', 'student']
```

WordPunctTokenizer makes use of the regular expression $w+|[^w]+$ to perform the tokenization of text into alphabetic and non-alphabetic characters.

Tokenization using the split () method is depicted in the following code:

```
>>>import nltk
>>>sent= She secured 90.56 % in class X. She is a meritorious
student"
>>> sent.split()
['She', 'secured', '90.56', '%', 'in', 'class', 'X', '.', 'She',
'is', 'a', 'meritorious', 'student']
>>> sent.split('')
['', 'She', 'secured', '90.56', '%', 'in', 'class', 'X', '.', 'She',
'is', 'a', 'meritorious', 'student']
>>> sent=" She secured 90.56 % in class X \n. She is a meritorious
student\n"
>>> sent.split('\n')
[' She secured 90.56 % in class X ', '. She is a meritorious
student', '']
Similar to sent.split('\n'), LineTokenizer works by tokenizing text into lines:
>>> import nltk
>>> from nltk.tokenize import BlanklineTokenizer
>>> sent=" She secured 90.56 \% in class X \n. She is a meritorious
student\n"
>>> BlanklineTokenizer().tokenize(sent)
[' She secured 90.56 \% in class X \n. She is a meritorious student\
n'l
>>> from nltk.tokenize import LineTokenizer
>>> LineTokenizer(blanklines='keep').tokenize(sent)
[' She secured 90.56 % in class X ', '. She is a meritorious
student']
>>> LineTokenizer (blanklines='discard').tokenize (sent)
[' She secured 90.56 \% in class X ', '. She is a meritorious
student']
SpaceTokenizer works similar to sent.split(''):
>>> import nltk
>>> sent=" She secured 90.56 % in class X \n. She is a meritorious
student\n"
>>> from nltk.tokenize import SpaceTokenizer
>>> SpaceTokenizer().tokenize(sent)
['', 'She', 'secured', '90.56', '%', 'in', 'class', 'X', '\n.',
'She', 'is', 'a', 'meritorious', 'student\n']
```

nltk.tokenize.util module works by returning the sequence of tuples that are offsets of the tokens in a sentence:

```
>>> import nltk
>>> from nltk.tokenize import WhitespaceTokenizer
>>> sent=" She secured 90.56 % in class X \n. She is a meritorious
student\n"
>>> list(WhitespaceTokenizer().span_tokenize(sent))
[(1, 4), (5, 12), (13, 18), (19, 20), (21, 23), (24, 29), (30, 31),
(33, 34), (35, 38), (39, 41), (42, 43), (44, 55), (56, 63)]
```

Given a sequence of spans, the sequence of relative spans can be returned:

```
>>> import nltk
>>> from nltk.tokenize import WhitespaceTokenizer
>>> from nltk.tokenize.util import spans_to_relative
>>> sent=" She secured 90.56 % in class X \n. She is a meritorious
student\n"
>>>list(spans_to_relative(WhitespaceTokenizer().span_tokenize(sent)))
[(1, 3), (1, 7), (1, 5), (1, 1), (1, 2), (1, 5), (1, 1), (2, 1), (1,
3), (1, 2), (1, 1), (1, 11), (1, 7)]
```

nltk.tokenize.util.string_span_tokenize(sent, separator) will return the offsets
of tokens in sent by splitting at each incidence of the separator:

```
>>> import nltk
>>> from nltk.tokenize.util import string_span_tokenize
>>> sent=" She secured 90.56 % in class X \n. She is a meritorious
student\n"
>>> list(string_span_tokenize(sent, ""))
[(1, 4), (5, 12), (13, 18), (19, 20), (21, 23), (24, 29), (30, 31),
(32, 34), (35, 38), (39, 41), (42, 43), (44, 55), (56, 64)]
```

Normalization

In order to carry out processing on natural language text, we need to perform normalization that mainly involves eliminating punctuation, converting the entire text into lowercase or uppercase, converting numbers into words, expanding abbreviations, canonicalization of text, and so on.

Eliminating punctuation

Sometimes, while tokenizing, it is desirable to remove punctuation. Removal of punctuation is considered one of the primary tasks while doing normalization in NLTK.

Consider the following example:

```
>>> text=[" It is a pleasant evening.","Guests, who came from US
arrived at the venue","Food was tasty."]
>>> from nltk.tokenize import word_tokenize
>>> tokenized_docs=[word_tokenize(doc) for doc in text]
>>> print(tokenized_docs)
[['It', 'is', 'a', 'pleasant', 'evening', '.'], ['Guests', ',',
'who', 'came', 'from', 'US', 'arrived', 'at', 'the', 'venue'],
['Food', 'was', 'tasty', '.']]
```

The preceding code obtains the tokenized text. The following code will remove punctuation from tokenized text:

```
>>> import re
>>> import string
>>> text=[" It is a pleasant evening.", "Guests, who came from US
arrived at the venue", "Food was tasty."]
>>> from nltk.tokenize import word tokenize
>>> tokenized docs=[word tokenize(doc) for doc in text]
>>> x=re.compile('[%s]' % re.escape(string.punctuation))
>>> tokenized docs no punctuation = []
>>> for review in tokenized docs:
    new review = []
    for token in review:
    new token = x.sub(u'', token)
    if not new token == u'':
            new review.append(new token)
    tokenized docs no punctuation.append(new review)
>>> print(tokenized docs no punctuation)
[['It', 'is', 'a', 'pleasant', 'evening'], ['Guests', 'who', 'came',
'from', 'US', 'arrived', 'at', 'the', 'venue'], ['Food', 'was',
'tasty']]
```

Conversion into lowercase and uppercase

A given text can be converted into lowercase or uppercase text entirely using the functions lower() and upper(). The task of converting text into uppercase or lowercase falls under the category of normalization.

Consider the following example of case conversion:

```
>>> text='HARdWork IS KEy to SUCCESS'
>>> print(text.lower())
hardwork is key to success
>>> print(text.upper())
HARDWORK IS KEY TO SUCCESS
```

Dealing with stop words

Stop words are words that need to be filtered out during the task of information retrieval or other natural language tasks, as these words do not contribute much to the overall meaning of the sentence. There are many search engines that work by deleting stop words so as to reduce the search space. Elimination of stopwords is considered one of the normalization tasks that is crucial in NLP.

NLTK has a list of stop words for many languages. We need to unzip datafile so that the list of stop words can be accessed from nltk data/corpora/stopwords/:

```
>>> import nltk
>>> from nltk.corpus import stopwords
>>> stops=set(stopwords.words('english'))
>>> words=["Don't", 'hesitate','to','ask','questions']
>>> [word for word in words if word not in stops]
["Don't", 'hesitate', 'ask', 'questions']
```

The instance of nltk.corpus.reader.WordListCorpusReader is a stopwords corpus. It has the words () function, whose argument is fileid. Here, it is English; this refers to all the stop words present in the English file. If the words () function has no argument, then it will refer to all the stop words of all the languages.

Other languages in which stop word removal can be done, or the number of languages whose file of stop words is present in NLTK can be found using the fileids () function:

```
>>> stopwords.fileids()
['danish', 'dutch', 'english', 'finnish', 'french', 'german',
'hungarian', 'italian', 'norwegian', 'portuguese', 'russian',
'spanish', 'swedish', 'turkish']
```

Any of these previously listed languages can be used as an argument to the words () function so as to get the stop words in that language.

Calculate stopwords in English

Let's see an example of how to calculate stopwords:

```
>>> import nltk
>>> from nltk.corpus import stopwords
>>> stopwords.words('english')
['i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you',
'your', 'yours', 'yourself', 'yourselves', 'he', 'him', 'his',
'himself', 'she', 'her', 'hers', 'herself', 'it', 'its', 'itself',
'they', 'them', 'their', 'theirs', 'themselves', 'what', 'which',
'who', 'whom', 'this', 'that', 'these', 'those', 'am', 'is', 'are',
'was', 'were', 'be', 'been', 'being', 'have', 'has', 'had',
'having', 'do', 'does', 'did', 'doing', 'a', 'an', 'the', 'and',
'but', 'if', 'or', 'because', 'as', 'until', 'while', 'of', 'at',
'by', 'for', 'with', 'about', 'against', 'between', 'into',
'through', 'during', 'before', 'after', 'above', 'below', 'to',
'from', 'up', 'down', 'in', 'out', 'on', 'off', 'over', 'under',
'again', 'further', 'then', 'once', 'here', 'there', 'when',
'where', 'why', 'how', 'all', 'any', 'both', 'each', 'few', 'more',
'most', 'other', 'some', 'such', 'no', 'nor', 'not', 'only', 'own',
'same', 'so', 'than', 'too', 'very', 's', 't', 'can', 'will',
'just', 'don', 'should', 'now']
>>> def para fraction(text):
stopwords = nltk.corpus.stopwords.words('english')
para = [w for w in text if w.lower() not in stopwords]
return len(para) / len(text)
>>> para fraction(nltk.corpus.reuters.words())
0.7364374824583169
>>> para fraction(nltk.corpus.inaugural.words())
0.5229560503653893
```

Normalization may also involve converting numbers into words (for example, 1 can be replaced by one) and expanding abbreviations (for instance, can't can be replaced by cannot). This can be achieved by representing them in replacement patterns. This is discussed in the next section.

Substituting and correcting tokens

In this section, we will discuss the replacement of tokens with other tokens. We will also about how we can correct the spelling of tokens by replacing incorrectly spelled tokens with correctly spelled tokens.

Replacing words using regular expressions

In order to remove errors or perform text normalization, word replacement is done. One way by which text replacement is done is by using regular expressions. Previously, we faced problems while performing tokenization for contractions. Using text replacement, we can replace contractions with their expanded versions. For example, doesn't can be replaced by does not.

We will begin by writing the following code, naming this program replacers.py, and saving it in the nltkdata folder:

```
import re
replacement patterns = [
(r'won\'t', 'will not'),
(r'can\'t', 'cannot'),
(r'i\'m', 'i am'),
(r'ain\'t', 'is not'),
(r'(\w+)\'ll', '\q<1> will'),
(r'(\wedge w+)n\wedge t', \wedge q<1> not'),
(r'(\w+)\'ve', '\g<1> have'),
(r'(\w+)\'s', '\g<1> is'),
(r'(\w+)\'re', '\q<1> are'),
(r'(\w+)\'d', '\q<1> would')
1
class RegexpReplacer(object):
    def init (self, patterns=replacement patterns):
        self.patterns = [(re.compile(regex), repl) for (regex, repl)
in
        patterns]
    def replace(self, text):
        s = text
        for (pattern, repl) in self.patterns:
             (s, count) = re.subn(pattern, repl, s)
        return s
```

Here, replacement patterns are defined in which the first term denotes the pattern to be matched and the second term is its corresponding replacement pattern. The RegexpReplacer class has been defined to perform the task of compiling pattern pairs and it provides a method called replace(), whose function is to perform the replacement of a pattern with another pattern.

Example of the replacement of a text with another text

Let's see an example of how we can substitute a text with another text:

```
>>> import nltk
>>> from replacers import RegexpReplacer
>>> replacer= RegexpReplacer()
>>> replacer.replace("Don't hesitate to ask questions")
'Do not hesitate to ask questions'
>>> replacer.replace("She must've gone to the market but she didn't
go")
'She must have gone to the market but she did not go'
```

The function of RegexpReplacer.replace() is substituting every instance of a replacement pattern with its corresponding substitution pattern. Here, must've is replaced by must have and didn't is replaced by did not, since the replacement pattern in replacers.py has already been defined by tuple pairs, that is, $(r'(\w+)\'ve', '\g<1> have')$ and $(r'(\w+)n\'t', '\g<1> not')$.

We can not only perform the replacement of contractions; we can also substitute a token with any other token.

Performing substitution before tokenization

Tokens substitution can be performed prior to tokenization so as to avoid the problem that occurs during tokenization for contractions:

```
>>> import nltk
>>> from nltk.tokenize import word_tokenize
>>> from replacers import RegexpReplacer
>>> replacer=RegexpReplacer()
>>> word_tokenize("Don't hesitate to ask questions")
['Do', "n't", 'hesitate', 'to', 'ask', 'questions']
>>> word_tokenize(replacer.replace("Don't hesitate to ask
questions"))
['Do', 'not', 'hesitate', 'to', 'ask', 'questions']
```

Dealing with repeating characters

Sometimes, people write words involving repeating characters that cause grammatical errors. For instance consider a sentence, I like it lotttttt. Here, lotttttt refers to lot. So now, we'll eliminate these repeating characters using the backreference approach, in which a character refers to the previous characters in a group in a regular expression. This is also considered one of the normalization tasks.

Firstly, append the following code to the previously created replacers.py:

```
class RepeatReplacer(object):
    def __init__(self):
        self.repeat_regexp = re.compile(r'(\w*)(\w)\2(\w*)')
        self.repl = r'\1\2\3'
    def replace(self, word):
        repl_word = self.repeat_regexp.sub(self.repl, word)
        if repl_word != word:
            return self.replace(repl_word)
        else:
            return repl word
```

Example of deleting repeating characters

Let's see an example of how we can delete repeating characters from a token:

```
>>> import nltk
>>> from replacers import RepeatReplacer
>>> replacer=RepeatReplacer()
>>> replacer.replace('lotttt')
'lot'
>>> replacer.replace('ohhhhh')
'oh'
>>> replacer.replace('ooohhhhh')
'oh'
```

The RepeatReplacer class works by compiling regular expressions and replacement strings and is defined using backreference.Repeat_regexp, which is present in replacers.py. It matches the starting characters that can be zero or many $(\backslash w^*)$, ending characters that can be zero or many $(\backslash w^*)$, or a character $(\backslash w)$ that is followed by same character.

For example, lotttt is split into (lo)(t)t(tt). Here, one t is reduced and the string becomes lottt. The process of splitting continues, and finally, the resultant string obtained is lot.

The problem with RepeatReplacer is that it will convert happy to hapy, which is inappropriate. To avoid this problem, we can embed wordnet along with it.

In the replacers.py program created previously, add the following lines to include wordnet:

```
import re
from nltk.corpus import wordnet
class RepeatReplacer(object):
    def __init__(self):
        self.repeat_regexp = re.compile(r'(\w*)(\w)\2(\w*)')
        self.repl = r'\1\2\3'
    def replace(self, word):
        if wordnet.synsets(word):
            return word
```

```
repl_word = self.repeat_regexp.sub(self.repl, word)
if repl_word != word:
    return self.replace(repl_word)
else:
    return repl word
```

Now, let's take a look at how the previously mentioned problem can be overcome:

```
>>> import nltk
>>> from replacers import RepeatReplacer
>>> replacer=RepeatReplacer()
>>> replacer.replace('happy')
'happy'
```

Replacing a word with its synonym

Now we will see how we can substitute a given word by its synonym. To the already existing replacers.py, we can add a class called WordReplacer that provides mapping between a word and its synonym:

```
class WordReplacer(object):
    def __init__(self, word_map):
        self.word_map = word_map
    def replace(self, word):
        return self.word map.get(word, word)
```

Example of substituting word a with its synonym

Let's have a look at an example of substituting a word with its synonym:

```
>>> import nltk
>>> from replacers import WordReplacer
>>> replacer=WordReplacer({'congrats':'congratulations'})
>>> replacer.replace('congrats')
'congratulations'
>>> replacer.replace('maths')
'maths'
```

In this code, the replace () function looks for the corresponding synonym for a word in word_map. If the synonym is present for a given word, then the word will be replaced by its synonym. If the synonym for a given word is not present, then no replacement will be performed; the same word will be returned.

Applying Zipf's law to text

Zipf's law states that the frequency of a token in a text is directly proportional to its rank or position in the sorted list. This law describes how tokens are distributed in languages: some tokens occur very frequently, some occur with intermediate frequency, and some tokens rarely occur.

Let's see the code for obtaining the log-log plot in NLTK that is based on Zipf's law:

```
>>> import nltk
>>> from nltk.corpus import gutenberg
>>> from nltk.probability import FreqDist
>>> import matplotlib
>>> import matplotlib.pyplot as plt
>>> matplotlib.use('TkAgg')
>>> fd = FreqDist()
>>> for text in gutenberg.fileids():
. . . for word in gutenberg.words(text):
. . . fd.inc(word)
>>> ranks = []
>>> freqs = []
>>> for rank, word in enumerate(fd):
. . . ranks.append(rank+1)
. . . freqs.append(fd[word])
. . .
>>> plt.loglog(ranks, freqs)
>>> plt.xlabel('frequency(f)', fontsize=14, fontweight='bold')
>>> plt.ylabel('rank(r)', fontsize=14, fontweight='bold')
>>> plt.grid(True)
>>> plt.show()
```

The preceding code will obtain a plot of rank versus the frequency of words in a document. So, we can check whether Zipf's law holds for all the documents or not by seeing the proportionality relationship between rank and the frequency of words.

Similarity measures

There are many similarity measures that can be used for performing NLP tasks. The nltk.metrics package in NLTK is used to provide various evaluation or similarity measures, which is conducive to perform various NLP tasks.

In order to test the performance of taggers, chunkers, and so on, in NLP, the standard scores retrieved from information retrieval can be used.

Let's have a look at how the output of named entity recognizer can be analyzed using the standard scores obtained from a training file:

Applying similarity measures using Ethe edit distance algorithm

Edit distance or the Levenshtein edit distance between two strings is used to compute the number of characters that can be inserted, substituted, or deleted in order to make two strings equal.

The operations performed in Edit Distance include the following:

• Copying letters from the first string to the second string (cost 0) and substituting a letter with another (cost 1):

D(i-1,j-1) + d(si,tj)(Substitution / copy)

• Deleting a letter in the first string (cost 1)

D(i,j-1)+1 (deletion)

• Inserting a letter in the second string (cost 1):

D(i,j) = min D(i-1,j)+1 (insertion)

The Python code for Edit Distance that is included in the nltk.metrics package is as follows:

```
from future import print function
def edit dist init(len1, len2):
    lev = []
    for i in range(len1):
        lev.append([0] * len2) # initialize 2D array to zero
    for i in range(len1):
        lev[i][0] = i
                               # column 0: 0,1,2,3,4,...
    for j in range(len2):
                               # row 0: 0,1,2,3,4,...
        lev[0][j] = j
    return lev
def edit dist step(lev,i,j,s1,s2,transpositions=False):
c1 =s1[i-1]
c2 = s2[j-1]
# skipping a character in s1
a =lev[i-1][j] +1
# skipping a character in s2
b =lev[i][j -1]+1
# substitution
c =lev[i-1][j-1]+(c1!=c2)
# transposition
d =c+1 # never picked by default
if transpositions and i>1 and j>1:
if s1[i -2]==c2 and s2[j -2]==c1:
d =lev[i-2][j-2]+1
# pick the cheapest
lev[i][j] =min(a,b,c,d)
def edit distance(s1, s2, transpositions=False):
    # set up a 2-D array
    len1 = len(s1)
    len2 = len(s2)
    lev = edit dist init(len1 + 1, len2 + 1)
    # iterate over the array
    for i in range(len1):
        for j in range(len2):
           edit dist step(lev, i + 1, j + 1, s1, s2,
transpositions=transpositions)
    return lev[len1][len2]
```

Let's have a look at the Edit Distance calculated in NLTK using the nltk.metrics package:

```
>>> import nltk
>>> from nltk.metrics import *
>>> edit_distance("relate","relation")
```
```
3
>>> edit_distance("suggestion","calculation")
7
```

Here, when we calculate the edit distance between relate and relation, three operations (one substitution and two insertions) are performed. While calculating the edit distance between suggestion and calculation, seven operations (six substitutions and one insertion) are performed.

Applying similarity measures using Jaccard's Coefficient

Jaccard's coefficient, or Tanimoto coefficient, may be defined as a measure of the overlap of two sets, X and Y.

It may be defined as follows:

- $Jaccard(X, Y) = |X \cap Y| / |XUY|$
- Jaccard(X,X)=1
- Jaccard(X, Y) = 0 if $X \cap Y = 0$

The code for Jaccard's similarity may be given as follows:

```
def jacc_similarity(query, document):
first=set(query).intersection(set(document))
second=set(query).union(set(document))
return len(first)/len(second)
```

Let's have a look at the implementation of Jaccard's similarity coefficient using NLTK:

```
>>> import nltk
>>> from nltk.metrics import *
>>> X=set([10,20,30,40])
>>> Y=set([20,30,60])
>>> print(jaccard_distance(X,Y))
0.6
```

Applying similarity measures using the Smith Waterman distance

The Smith Waterman distance is similar to edit distance. This similarity metric was developed in order to detect the optical alignments between related protein sequences and DNA. It consists of costs to be assigned to and functions for alphabet mapping to cost values (substitution); cost is also assigned to gap G (insertion or deletion):

- 1. θ //start over
- 2. *D(i-1,j-1) -d(si,tj)* //subst/copy
- 3. D(i,j) = max D(i-1,j)-G //insert
- 4. D(i,j-1)-G //delete

Note

Distance is maximum over all i,j in table of D(i,j)

- 5. G = 1 //example value for gap
- 6. d(c,c) = -2 //context dependent substitution cost
- 7. d(c,d) = +1 //context dependent substitution cost

Similar to Edit distance, the Python code for Smith Waterman can be embedded with the nltk.metrics package to perform string similarity using Smith Waterman in NLTK.

Other string similarity metrics

Binary distance is a string similarity metric. It returns the value 0.0 if two labels are identical; otherwise, it returns the value 1.0.

The Python code for Binary distance metrics is:

```
def binary_distance(label1, label2):
  return 0.0 if label1 == label2 else 1.0
```

Let's see how Binary distance metrics is implemented in NLTK:

```
>>> import nltk
>>> from nltk.metrics import *
>>> X = set([10,20,30,40])
>>> Y= set([30,50,70])
>>> binary_distance(X, Y)
1.0
```

Masi distance is based on partial agreement when multiple labels are present.

The Python code included in nltk.metrics for masi distance is as follows:

```
def masi_distance(label1, label2):
    len_intersection = len(label1.intersection(label2))
    len_union = len(label1.union(label2))
    len_label1 = len(label1)
    len_label2 = len(label2)
    if len_label1 == len_label2 and len_label1 == len_intersection:
        m = 1
    elif len_intersection == min(len_label1, len_label2):
        m = 0.67
    elif len_intersection > 0:
        m = 0.33
    else:
        m = 0
```

return 1 - (len_intersection / float(len_union)) * m

Let's see the implementation of masi distance in NLTK:

```
>>> import nltk
>>> from __future__ import print_function
>>> from nltk.metrics import *
>>> X = set([10,20,30,40])
>>> Y= set([30,50,70])
>>> print(masi_distance(X,Y))
0.945
```

Summary

In this chapter, you have learned various operations that can be performed on a text that is a collection of strings. You have understood the concept of tokenization, substitution, and normalization, and applied various similarity measures to strings using NLTK. We have also discussed Zipf's law, which may be applicable to some of the existing documents.

In the next chapter, we'll discuss various language modeling techniques and different NLP tasks.

Chapter 2. Statistical Language Modeling

Computational linguistics is an emerging field that is widely used in analytics, software applications, and contexts where people communicate with machines. Computational linguistics may be defined as a subfield of artificial intelligence. Applications of computational linguistics include machine translation, speech recognition, intelligent Web searching, information retrieval, and intelligent spelling checkers. It is important to understand the preprocessing tasks or the computations that can be performed on natural language text. In the following chapter, we will discuss ways to calculate word frequencies, the **Maximum Likelihood Estimation** (MLE) model, interpolation on data, and so on. But first, let's go through the various topics that we will cover in this chapter. They are as follows:

- Calculating word frequencies (1-gram, 2-gram, 3-gram)
- Developing MLE for a given text
- Applying smoothing on the MLE model
- Developing a back-off mechanism for MLE
- Applying interpolation on data to get a mix and match
- Evaluating a language model through perplexity
- Applying Metropolis-Hastings in modeling languages
- Applying Gibbs sampling in language processing

Understanding word frequency

Collocations may be defined as the collection of two or more tokens that tend to exist together. For example, the United States, the United Kingdom, Union of Soviet Socialist Republics, and so on.

Unigram represents a single token. The following code will be used for generate unigrams for Alpino Corpus:

```
>>> import nltk
>>> from nltk.util import ngrams
>>> from nltk.corpus import alpino
>>> alpino.words()
['De', 'verzekeringsmaatschappijen', 'verhelen', ...]>>>
unigrams=ngrams(alpino.words(),1)
>>> for i in unigrams:
print(i)
```

Consider another example for generating quadgrams or fourgrams from alpinocorpus:

```
>>> import nltk
>>> from nltk.util import ngrams
>>> from nltk.corpus import alpino
>>> alpino.words()
['De', 'verzekeringsmaatschappijen', 'verhelen', ...]
>>> quadgrams=ngrams(alpino.words(),4)
```

>>> for i in quadgrams:
print(i)

bigram refers to a pair of tokens. To find bigrams in the text, firstly, lowercased words are searched, a list of lowercased words in the text is created, and BigramCollocationFinder is produced. The BigramAssocMeasures found in the nltk.metrics package can be used to find bigrams in the text:

```
>>> import nltk
>>> from nltk.collocations import BigramCollocationFinder
>>> from nltk.corpus import webtext
>>> from nltk.metrics import BigramAssocMeasures
>>> tokens=[t.lower() for t in webtext.words('grail.txt')]
>>> words=BigramCollocationFinder.from_words(tokens)
>>> words.nbest(BigramAssocMeasures.likelihood_ratio, 10)
[("'", 's'), ('arthur', ':'), ('#', '1'), ("'", 't'), ('villager',
'#'), ('#', '2'), (']', '['), ('1', ':'), ('oh', ','), ('black',
'knight')]
```

In the preceding code, we can add a word filter that can be used to eliminate stopwords and punctuation:

```
>>> from nltk.corpus import stopwords
>>> from nltk.corpus import webtext
>>> from nltk.collocations import BigramCollocationFinder
>>> from nltk.metrics import BigramAssocMeasures
>>> set = set(stopwords.words('english'))
>>> stops_filter = lambda w: len(w) < 3 or w in set
>>> tokens=[t.lower() for t in webtext.words('grail.txt')]
>>> words=BigramCollocationFinder.from_words(tokens)
>>> words.apply_word_filter(stops_filter)
>>> words.nbest(BigramAssocMeasures.likelihood_ratio, 10)
[('black', 'knight'), ('clop', 'clop'), ('head', 'knight'),
('mumble', 'mumble'), ('squeak', 'squeak'), ('saw', 'saw'), ('holy',
'grail'), ('run', 'away'), ('french', 'guard'), ('cartoon',
'character')]
```

Here, we can change the frequency of bigrams from 10 to any other number.

Another way of generating bigrams from a text is using collocation finders. This is given in the following code:

```
>>> import nltk
>>> from nltk.collocation import *
>>> text1="Hardwork is the key to success. Never give up!"
>>> word = nltk.wordpunct_tokenize(text1)
>>> finder = BigramCollocationFinder.from_words(word)
```

```
>>> bigram_measures = nltk.collocations.BigramAssocMeasures()
>>> value = finder.score_ngrams(bigram_measures.raw_freq)
>>> sorted(bigram for bigram, score in value)
[('.', 'Never'), ('Hardwork', 'is'), ('Never', 'give'), ('give',
'up'), ('is', 'the'), ('key', 'to'), ('success', '.'), ('the',
'key'), ('to', 'success'), ('up', '!')]
```

We will now see another code for generating bigrams from alpino corpus:

```
>>> import nltk
>>> from nltk.util import ngrams
>>> from nltk.corpus import alpino
>>> alpino.words()
['De', 'verzekeringsmaatschappijen', 'verhelen', ...]
>>> bigrams_tokens=ngrams(alpino.words(),2)
>>> for i in bigrams_tokens:
print(i)
```

This code will generate bigrams from alpino corpus.

We will now see the code for generating trigrams:

```
>>> import nltk
>>> from nltk.util import ngrams
>>> from nltk.corpus import alpino
>>> alpino.words()
['De', 'verzekeringsmaatschappijen', 'verhelen', ...]>>>
trigrams_tokens=ngrams(alpino.words(),3)
>>> for i in trigrams_tokens:
print(i)
```

For generating fourgrams and generating the frequency of fourgrams, the following code is used:

```
>>> import nltk
>>> from nltk.collocations import *
>>> text="Hello how are you doing ? I hope you find the book
interesting"
>>> tokens=nltk.wordpunct_tokenize(text)
>>>
fourgrams=nltk.collocations.QuadgramCollocationFinder.from_words(toke
ns)
>>> for fourgram, freq in fourgrams.ngram_fd.items():
print(fourgram,freq)
('hope', 'you', 'find', 'the') 1
('Hello', 'how', 'are', 'you') 1
```

```
('you', 'doing', '?', 'I') 1
('are', 'you', 'doing', '?') 1
('how', 'are', 'you', 'doing') 1
('?', 'I', 'hope', 'you') 1
('doing', '?', 'I', 'hope') 1
('find', 'the', 'book', 'interesting') 1
('you', 'find', 'the', 'book') 1
('I', 'hope', 'you', 'find') 1
```

We will now see the code for generating ngrams for a given sentence:

```
('Hello', ',', 'please', 'read', 'the')
(',', 'please', 'read', 'the', 'book')
('please', 'read', 'the', 'book', 'thoroughly')
('read', 'the', 'book', 'thoroughly', '.')
('the', 'book', 'thoroughly', '.', 'If')
('book', 'thoroughly', '.', 'If', 'you')
('thoroughly', '.', 'If', 'you', 'have')
('.', 'If', 'you', 'have', 'any')
('If', 'you', 'have', 'any', 'queries')
('you', 'have', 'any', 'queries', ',')
('have', 'any', 'queries', ',', 'then')
('any', 'queries', ',', 'then', "don't")
('queries', ',', 'then', "don't", 'hesitate')
(',', 'then', "don't", 'hesitate', 'to')
('then', "don't", 'hesitate', 'to', 'ask')
("don't", 'hesitate', 'to', 'ask', '.')
('hesitate', 'to', 'ask', '.', 'There')
('to', 'ask', '.', 'There', 'is')
('ask', '.', 'There', 'is', 'no')
('.', 'There', 'is', 'no', 'shortcut')
('There', 'is', 'no', 'shortcut', 'to')
('is', 'no', 'shortcut', 'to', 'success')
('no', 'shortcut', 'to', 'success', '.')
```

Develop MLE for a given text

MLE, also referred to as multinomial logistic regression or a conditional exponential classifier, is an essential task in the field of NLP. It was first introduced in 1996 by Berger and Della Pietra. Maximum Entropy is defined in NLTK in the nltk.classify.maxent module. In this module, all the probability distributions are considered that are in accordance with the training data. This model is used to refer to two features, namely input-feature and joint feature. An input feature may be called the feature of unlabeled words. A joined feature may be called the feature of labeled words. MLE is used to generate freqdist that contains the probability distribution for a given occurrence in a text. param freqdist consists of frequency distribution on which probability distribution is based.

We'll now see the code for the Maximum Entropy Model in NLTK:

```
from future import print function, unicode literals
  docformat ='epytext en'
try:
import numpy
except ImportError:
   pass
import tempfile
import os
from collections import defaultdict
from nltk import compat
from nltk.data import gzip open unicode
from nltk.util import OrderedDict
from nltk.probability import DictionaryProbDist
from nltk.classify.api import ClassifierI
from nltk.classify.util import CutoffChecker, accuracy, log likelihood
from nltk.classify.megam import (call megam,
write megam file, parse megam weights)
from nltk.classify.tadm import
call tadm, write tadm file, parse tadm weights
```

In the preceding code, nltk.probability consists of the FreqDist class that can be used to determine the frequency of the occurrence of individual tokens in a text.

The ProbDistI is used to determine the probability distribution of individual occurrences in a text. There are basically two kinds of probability distributions: Derived Probability Distribution and Analytic Probability Distribution. Distributed Probability Distributions are obtained from frequency distribution. Analytic Probability Distributions are obtained from parameters, such as variance.

In order to obtain the frequency distribution, the maximum likelihood estimate is used. It computes the probability of every occurrence on the basis of its frequency in the frequency distribution:

class MLEProbDist(ProbDistI):

```
def __init__(self, freqdist, bins=None):
        self._freqdist = freqdist
        def freqdist(self):
"""
```

It will find the frequency distribution on the basis of probability distribution:

```
** ** **
    return self. freqdist
    def prob(self, sample):
        return self. freqdist.freq(sample)
    def max(self):
        return self. freqdist.max()
    def samples(self):
        return self. freqdist.keys()
    def repr (self):
** ** **
        It will return string representation of ProbDist
** ** **
        return '<MLEProbDist based on %d samples>' %
self. freqdist.N()
class LidstoneProbDist(ProbDistI):
** ** **
```

It is used to obtain frequency distribution. It is represented by a real number, Gamma, whose range lies between 0 and 1. The LidstoneProbDist calculates the probability of a given observation with count c, outcomes N, and bins B as follows: (c+Gamma)/(N+B*Gamma).

It also means that Gamma is added to the count of each bin and MLE is computed from the given frequency distribution:

```
"""
SUM_TO_ONE = False
    def __init__(self, freqdist, gamma, bins=None):
"""
```

Lidstone is used to compute the probability distribution in order to obtain freqdist.

paramfreqdist may be defined as the frequency distribution on which probability estimates are based.

param bins may be defined as sample values that can be obtained from the probability distribution. The sum of probabilities is equal to one:

..

```
if (bins == 0) or (bins is None and freqdist.N() == 0):
            name = self. class . name [:-8]
            raise ValueError('A %s probability distribution ' % name
+
'must have at least one bin.')
        if (bins is not None) and (bins < freqdist.B()):
            name = self. class . name [:-8]
            raise ValueError('\nThe number of bins in a %s
distribution ' % name +
'(%d) must be greater than or equal to\n' % bins +
'the number of bins in the FreqDist used ' +
'to create it (%d).' % freqdist.B())
        self. freqdist = freqdist
        self. gamma = float(gamma)
        self. N = self. freqdist.N()
        if bins is None:
            bins = freqdist.B()
        self. bins = bins
        self. divisor = self. N + bins * gamma
        if self. divisor == 0.0:
            # In extreme cases we force the probability to be 0,
            # which it will be, since the count will be 0:
            self. gamma = 0
            self. divisor = 1
def freqdist(self):
** ** **
```

It obtains frequency distribution, which is based upon the probability distribution:

```
"""
    return self._freqdist

def prob(self, sample):
c = self._freqdist[sample]
    return (c + self._gamma) / self._divisor

    def max(self):
    # To obtain most probable sample, choose the one
# that occurs very frequently.
```

```
return self._freqdist.max()

def samples(self):
    return self._freqdist.keys()

def discount(self):
    gb = self._gamma * self._bins
    return gb / (self._N + gb)

def __repr__(self):
    String representation of ProbDist is obtained.

return '<LidstoneProbDist based on %d samples>' %
self._freqdist.N()

class LaplaceProbDist(LidstoneProbDist):
"""
```

It is used to obtain frequency distribution. It calculates the probability of a sample with count c, outcomes N, and bins B as follows:

(c+1)/(N+B)

It also means that 1 is added to the count of every bin, and the maximum likelihood is estimated for the resultant frequency distribution:

"""
 def __init__(self, freqdist, bins=None):
"""

LaplaceProbDist is used to obtain the probability distribution for generating freqdist.

param freqdist is used to obtain the frequency distribution, which is based on probability estimates.

Param bins may be defined as the frequency of sample values that can be generated. The sum of probabilities must be 1:

.....

```
LidstoneProbDist.__init__(self, freqdist, 1, bins)
def __repr__(self):
```

·· ·· ··

```
String representation of ProbDist is obtained.
"""
return '<LaplaceProbDist based on %d samples>' %
self._freqdist.N()
class ELEProbDist(LidstoneProbDist):
"""
```

It is used to obtain frequency distribution. It calculates the probability of a sample with count c, outcomes N, and bins B as follows:

(c+0.5)/(N+B/2)

It also means that 0.5 is added to the count of every bin and the maximum likelihood is estimated for the resultant frequency distribution:

```
"""
    def __init__(self, freqdist, bins=None):
"""
```

The expected likelihood estimation is used to obtain the probability distribution for generating freqdist.param.freqdist is used to obtain the frequency distribution, which is based on probability estimates.

param bins may be defined as the frequency of sample values that can be generated. The sum of probabilities must be 1:

```
class WittenBellProbDist(ProbDistI):
"""
```

The WittenBellProbDist is used to obtain the probability distribution. It is used to obtain the uniform probability mass on the basis of the frequency of the sample seen before. The probability mass for the sample is given as follows:

T/(N+T)

Here, T is the number of samples observed and N is total number of events observed. It is equal to the maximum likelihood estimate of a new sample that is occurring. The sum of all the probabilities is equal to 1:

It obtains the probability distribution. This probability is used to provide the uniform probability mass to an unseen sample. The probability mass for the sample is given as follows:

T/(N+T)

Here, T is the number of samples observed and N is the total number of events observed. It is equal to the maximum likelihood estimate of a new sample that is occurring. The sum of all the probabilities is equal to I:

Here, p = T / Z (N + T), if count = 0 p = c / (N + T), otherwise

Z is the normalizing factor that is calculated using these values and a bin value.

Param freqdist is used to estimate the frequency counts from which the probability distribution is obtained.

Param bins may be defined as the number of possible types of samples:

```
"""
    assert bins is None or bins >= freqdist.B(),\
'bins parameter must not be less than %d=freqdist.B()' % freqdist.B()
    if bins is None:
        bins = freqdist.B()
    self._freqdist = freqdist
    self._T = self._freqdist.B()
    self._Z = bins - self._freqdist.B()
    self._N = self._freqdist.N()
    # self._P0 is P(0), precalculated for efficiency:
    if self._N==0:
        # if freqdist is empty, we approximate P(0) by a
UniformProbDist:
        self._P0 = 1.0 / self._Z
    else:
```

```
self. P0 = self. T / float(self. Z * (self._N + self._T))
   def prob(self, sample):
        # inherit docs from ProbDistI
        c = self. freqdist[sample]
        return (c / float(self. N + self. T) if c != 0 else self. P0)
   def max(self):
        return self. freqdist.max()
   def samples(self):
        return self. freqdist.keys()
   def freqdist(self):
        return self. freqdist
   def discount(self):
        raise NotImplementedError()
   def repr (self):
.. .. ..
        String representation of ProbDist is obtained.
11 11 11
        return '<WittenBellProbDist based on %d samples>' %
```

```
self. freqdist.N()
```

We can perform testing using maximum likelihood estimation. Let's consider the following code for MLE in NLTK:

```
>>> import nltk
>>> from nltk.probability import *
>>> train_and_test(mle)
28.76%
>>> train_and_test(LaplaceProbDist)
69.16%
>>> train_and_test(ELEProbDist)
76.38%
>>> def lidstone(gamma):
    return lambda fd, bins: LidstoneProbDist(fd, gamma, bins)
>>> train_and_test(lidstone(0.1))
86.17%
>>> train_and_test(lidstone(0.5))
76.38%
```

>>> train_and_test(lidstone(1.0))
69.16%

Hidden Markov Model estimation

Hidden Markov Model (HMM) comprises of observed states and the latent states that help in determining them. Consider the diagrammatic description of HMM. Here, x represents the latent state and y represents the observed state.



We can perform testing using HMM estimation. Let's consider the Brown Corpus and the code given here:

```
>>> import nltk
>>> corpus =
nltk.corpus.brown.tagged sents(categories='adventure')[:700]
>>> print(len(corpus))
700
>>> from nltk.util import unique list
>>> tag set = unique list(tag for sent in corpus for (word,tag) in
sent)
>>> print(len(tag set))
104
>>> symbols = unique list(word for sent in corpus for (word,tag) in
sent)
>>> print(len(symbols))
1908
>>> print(len(tag set))
104
>>> symbols = unique list(word for sent in corpus for (word, tag) in
sent)
>>> print(len(symbols))
1908
>>> trainer = nltk.tag.HiddenMarkovModelTrainer(tag set, symbols)
```

```
>>> train_corpus = []
>>> test_corpus = []
>>> for i in range(len(corpus)):
if i % 10:
train_corpus += [corpus[i]]
else:
test_corpus += [corpus[i]]
>>> print(len(train_corpus))
630
>>> print(len(test_corpus))
70
>>> def train_and_test(est):
hmm = trainer.train_supervised(train_corpus, estimator=est)
print('%.2f%%' % (100 * hmm.evaluate(test corpus)))
```

In the preceding code, we have created a 90% training and 10% testing file and we have tested the estimator.

Applying smoothing on the MLE model

Smoothing is used to handle the words that have not occurred previously. So, the probability of unknown words is 0. To solve this problem, smoothing is used.

Add-one smoothing

In the 18th century, Laplace invented add-one smoothing. In add-one smoothing, 1 is added to the count of each word. Instead of 1, any other value can also be added to the count of unknown words so that unknown words can be handled and their probability is non-zero. Pseudo count is the value (that is, either 1 or nonzero) that is added to the counts of unknown words to make their probability nonzero.

Let's consider the following code for add-one smoothing in NLTK:

```
>>> import nltk
>>> corpus=u"<s> hello how are you doing ? Hope you find the book
interesting. </s>".split()
>>> sentence=u"<s>how are you doing</s>".split()
>>> vocabulary=set(corpus)
>>> len(vocabulary)
13
>>> cfd = nltk.ConditionalFreqDist(nltk.bigrams(corpus))
>>> # The corpus counts of each bigram in the sentence:
>>> [cfd[a][b] for (a,b) in nltk.bigrams(sentence)]
[0, 1, 0]
>>> # The counts for each word in the sentence:
>>> [cfd[a].N() for (a,b) in nltk.bigrams(sentence)]
[0, 1, 2]
>>> # There is already a FreqDist method for MLE probability:
>>> [cfd[a].freq(b) for (a,b) in nltk.bigrams(sentence)]
[0, 1.0, 0.0]
>>> # Laplace smoothing of each bigram count:
>>> [1 + cfd[a][b] for (a,b) in nltk.bigrams(sentence)]
[1, 2, 1]
>>> # We need to normalise the counts for each word:
>>> [len(vocabulary) + cfd[a].N() for (a,b) in
nltk.bigrams(sentence)]
[13, 14, 15]
>>> # The smoothed Laplace probability for each bigram:
>>> [1.0 * (1+cfd[a][b]) / (len(vocabulary)+cfd[a].N()) for (a,b) in
nltk.bigrams(sentence)]
[0.07692307692307693, 0.14285714285714285, 0.0666666666666666667]
```

Consider another way of performing Add-one smoothing or generating a Laplace probability distribution:

Good Turing

Good Turing was introduced by Alan Turing along with his statistical assistant I.J. Good. It is an efficient smoothing method that increases the performance of statistical techniques performed for linguistic tasks, such as word sense disambiguation (WSD), named entity recognition (NER), spelling correction, machine translation, and so on. This method helps to predict the probability of unseen objects. In this method, binomial distribution is exhibited by our objects of interest. This method is used to compute the mass probability for zero or low count samples on the basis of higher count samples . Simple Good Turing performs approximation from frequency to frequency by linear regression into a linear line in log space. If c is the adjusted count, it will compute the following:

c = (c + 1) N(c + 1) / N(c) for $c \ge 1$

The samples with zero frequency in training = N(1) for c == 0.

Here, c is the original count and N(i) is the number of event types observed with count i.

Bill Gale and Geoffrey Sampson have presented Simple Good Turing:

```
class SimpleGoodTuringProbDist(ProbDistI):
"""
Given a pair (pi, qi), where pi refers to the frequency and
    qi refers to the frequency of frequency, our aim is to minimize
the
    square variation. E(p) and E(q) is the mean of pi and qi.
    - slope, b = sigma ((pi-E(p)(qi-E(q))) / sigma
((pi-E(p))(pi-E(p)))
    - intercept: a = E(q) - b.E(p)
"""
    SUM_TO_ONE = False
    def init (self, freqdist, bins=None):
```

```
param freqdist refers to the count of frequency from which
probability
        distribution is estimated.
        Param bins is used to estimate the possible number of
samples.
.....
        assert bins is None or bins > freqdist.B(), \
'bins parameter must not be less than %d=freqdist.B()+1' %
(freqdist.B()+1)
        if bins is None:
            bins = freqdist.B() + 1
        self. freqdist = freqdist
        self. bins = bins
        r, nr = self. r Nr()
        self.find best fit(r, nr)
        self. switch(r, nr)
        self. renormalize(r, nr)
    def r Nr non zero(self):
        r Nr = self. freqdist.r Nr()
        del r Nr[0]
        return r Nr
    def r Nr(self):
.. .. ..
Split the frequency distribution in two list (r, Nr), where Nr(r) > 0
** ** **
        nonzero = self. r Nr non zero()
        if not nonzero:
            return [], []
        return zip(*sorted(nonzero.items()))
    def find best fit(self, r, nr):
** ** **
        Use simple linear regression to tune parameters self. slope
and
        self. intercept in the log-log space based on count and
Nr (count)
        (Work in log space to avoid floating point underflow.)
** ** **
        # For higher sample frequencies the data points becomes
horizontal
        # along line Nr=1. To create a more evident linear model in
log-log
        # space, we average positive Nr values with the surrounding
```

** ** **

```
zero
        # values. (Church and Gale, 1991)
        if not r or not nr:
            # Empty r or nr?
            return
        zr = []
        for j in range(len(r)):
            i = (r[j-1] if j > 0 else 0)
            k = (2 * r[j] - i if j == len(r) - 1 else r[j+1])
            zr = 2.0 * nr[j] / (k - i)
             zr.append(zr )
        \log r = [math.log(i) for i in r]
        log zr = [math.log(i) for i in zr]
        xy cov = x var = 0.0
        x \text{ mean} = 1.0 * \text{ sum}(\log r) / \text{len}(\log r)
        y mean = 1.0 * sum(log zr) / len(log zr)
        for (x, y) in zip(\log r, \log zr):
            xy cov += (x - x mean) * (y - y mean)
            x var += (x - x mean) **2
        self. slope = (xy cov / x var if x var != 0 else 0.0)
        if self. slope \geq -1:
            warnings.warn('SimpleGoodTuring did not find a proper
best fit '
'line for smoothing probabilities of occurrences. '
'The probability estimates are likely to be '
'unreliable.')
        self._intercept = y_mean - self._slope * x_mean
    def switch(self, r, nr):
** ** **
        Calculate the r frontier where we must switch from Nr to Sr
        when estimating E[Nr].
** ** **
        for i, r in enumerate(r):
            if len(r) == i + 1 or r[i+1] != r + 1:
                 # We are at the end of r, or there is a gap in r
                 self. switch at = r
                break
            Sr = self.smoothedNr
            smooth r star = (r_{+1}) \times Sr(r_{+1}) / Sr(r_{-})
            unsmooth r star = 1.0 * (r + 1) * nr[i+1] / nr[i]
```

```
std = math.sqrt(self._variance(r_, nr[i], nr[i+1]))
if abs(unsmooth_r_star-smooth_r_star) <= 1.96 * std:
        self._switch_at = r_
        break

def _variance(self, r, nr, nr_1):
        r = float(r)
        nr = float(nr)
        nr_1 = float(nr_1)
        return (r + 1.0)**2 * (nr_1 / nr**2) * (1.0 + nr_1 / nr)

        def _renormalize(self, r, nr):
"""</pre>
```

Renormalization is very crucial to ensure that the proper distribution of probability is obtained. It can be obtained by making the probability estimate of an unseen sample N(1)/N and then, renormalizing all the previously seen sample probabilities:

```
** ** **
        prob cov = 0.0
        for r , nr in zip(r, nr):
            prob cov += nr * self. prob measure(r )
        if prob cov:
            self. renormal = (1 - self. prob measure(0)) / prob cov
   def smoothedNr(self, r):
.....
        Return the number of samples with count r.
** ** **
        # Nr = a r^b (with b < -1 to give the appropriate hyperbolic
        # relationship)
        # Estimate a and b by simple linear regression technique on
        # the logarithmic form of the equation: log Nr = a + b*log(r)
        return math.exp(self. intercept + self. slope * math.log(r))
    def prob(self, sample):
** ** **
        Return the sample's probability.
.. .. ..
        count = self. freqdist[sample]
        p = self. prob measure(count)
        if count == 0:
```

```
if self. bins == self. freqdist.B():
                p = 0.0
            else:
                p = p / (1.0 * self. bins - self. freqdist.B())
        else:
            p = p * self. renormal
        return p
    def prob measure(self, count):
        if count == 0 and self. freqdist.N() == 0 :
            return 1.0
        elif count == 0 and self. freqdist.N() != 0:
            return 1.0 * self. freqdist.Nr(1) / self. freqdist.N()
        if self. switch at > count:
            Er_1 = 1.0 * self. freqdist.Nr(count+1)
            Er = 1.0 * self. freqdist.Nr(count)
        else:
            Er 1 = self.smoothedNr(count+1)
            Er = self.smoothedNr(count)
        r star = (count + 1) * Er 1 / Er
        return r star / self. freqdist.N()
    def check(self):
        prob sum = 0.0
        for i in range(0, len(self. Nr)):
            prob sum += self. Nr[i] * self. prob measure(i) /
self. renormal
        print("Probability Sum:", prob sum)
        #assert prob sum != 1.0, "probability sum should be one!"
    def discount(self):
** ** **
        It is used to provide the total probability transfers from
the
        seen events to the unseen events.
11 11 11
        return 1.0 * self.smoothedNr(1) / self. freqdist.N()
    def max(self):
        return self. freqdist.max()
    def samples(self):
        return self. freqdist.keys()
    def freqdist(self):
```

Let's see the code for Simple Good Turing in NLTK:

```
>>> gt = lambda fd, bins: SimpleGoodTuringProbDist(fd, bins=1e5)
>>> train_and_test(gt)
5.17%
```

Kneser Ney estimation

Kneser Ney is used with trigrams. Let's see the following code in NLTK for the Kneser Ney estimation:

```
>>> import nltk
>>> corpus = [[((x[0],y[0],z[0]),(x[1],y[1],z[1]))
   for x, y, z in nltk.trigrams(sent)]
  for sent in corpus[:100]]
>>> tag set = unique list(tag for sent in corpus for (word,tag) in
sent)
>>> len(tag set)
906
>>> symbols = unique list(word for sent in corpus for (word,taq) in
sent)
>>> len(symbols)
1341
>>> trainer = nltk.tag.HiddenMarkovModelTrainer(tag set, symbols)
>>> train corpus = []
>>> test corpus = []
>>> for i in range(len(corpus)):
if i % 10:
train corpus += [corpus[i]]
else:
test corpus += [corpus[i]]
>>> len(train corpus)
90
>>> len(test corpus)
10
>>> kn = lambda fd, bins: KneserNeyProbDist(fd)
>>> train and test(kn)
0.86%
```

Witten Bell estimation

Witten Bell is the smoothing algorithm that was designed to deal with unknown words having zero probability. Let's consider the following code for Witten Bell estimation in NLTK:

```
>>> train_and_test(WittenBellProbDist)
6.90%
```

Develop a back-off mechanism for MLE

Katz back-off may be defined as a generative n gram language model that computes the conditional probability of a given token given its previous information in n gram. According to this model, in training, if n gram is seen more than n times, then the conditional probability of a token, given its previous information, is proportional to the MLE of that n gram. Else, the conditional probability is equivalent to the back-off conditional probability of (n-1) gram.

The following is the code for Katz's back-off model in NLTK:

```
def prob(self, word, context):
"""
Evaluate the probability of this word in this context using Katz
Backoff.
: param word: the word to get the probability of
: type word: str
:param context: the context the word is in
:type context: list(str)
"""
context = tuple(context)
if(context+(word,) in self._ngrams) or (self._n == 1):
return self[context].prob(word)
else:
return self._alpha(context) * self._backoff.prob(word,context[1:])
```

Applying interpolation on data to get mix and match

The limitation of using an additive smoothed bigram is that we back off to a state of ignorance when we deal with rare text. For example, the word captivating occurs five times in a training data: thrice followed by *by* and twice followed by *the*. With additive smoothing, the occurrence of *a* and *new* before captivating is the same. Both the occurrences are plausible, but the former is more probable as compared to latter. This problem can be rectified using unigram probabilities. We can develop an interpolation model in which both the unigram and bigram probabilities can be combined.

In SRILM, we perform interpolation by first training a unigram model with -order 1 and -order 2 used for the bigram model:

ngram - count - text / home / linux / ieng6 / ln165w / public / data / engand hintrain . txt \ - vocab / home / linux / ieng6 / ln165w / public / data / engandhinlexicon . txt \ - order 1 - addsmooth 0.0001 - lm wsj1 . lm

Evaluate a language model through perplexity

The nltk.model.ngram module in NLTK has a submodule, perplexity (text). This submodule evaluates the perplexity of a given text. Perplexity is defined as 2**Cross Entropy for the text. Perplexity defines how a probability model or probability distribution can be useful to predict a text.

The code for evaluating the perplexity of text as present in the nltk.model.ngram module is as follows:

```
def perplexity(self, text):
"""
    Calculates the perplexity of the given text.
    This is simply 2 ** cross-entropy for the text.
    :param text: words to calculate perplexity of
    :type text: list(str)
"""
```

return pow(2.0, self.entropy(text))

Applying metropolis hastings in modeling languages

There are various ways to perform processing on posterior distribution in **Markov Chain Monte Carlo** (**MCMC**). One way is using the Metropolis-Hastings sampler. In order to implement the Metropolis-Hastings algorithm, we require standard uniform distribution, proposal distribution, and target distribution that is proportional to posterior probability. An example of Metropolis-Hastings is discussed in the following topic.

Applying Gibbs sampling in language processing

With the help of Gibbs sampling, Markov chain is built by sampling from the conditional probability. When the iteration over all the parameters is completed, then one cycle of the Gibbs sampler is completed. When it is not possible to sample from conditional distribution, then Metropolis-Hastings can be used. This is referred to as Metropolis within Gibbs. Gibbs sampling may be defined as Metropolis-hastings with special proposal distribution. On each iteration, we draw a proposal for a new value of a specific parameter.

Consider an example of throwing two coins that is characterized by the number of heads and the number of tosses of a coin:

```
def bern(theta, z, N):
"""Bernoulli likelihood with N trials and z successes."""
return np.clip(theta**z*(1-theta)**(N-z),0,1)
def bern2(theta1, theta2, z1, z2, N1, N2):
"""Bernoulli likelihood with N trials and z successes."""
return bern(theta1, z1, N1) *bern(theta2, z2, N2)
def make thetas(xmin, xmax, n):
xs=np.linspace(xmin, xmax, n)
widths=(xs[1:]-xs[:-1])/2.0
thetas=xs[:-1]+widths
returnt hetas
def make plots (X, Y, prior, likelihood, posterior, projection=None):
fig,ax=plt.subplots(1,3,subplot kw=dict(projection=projection,aspect=
'equal'), figsize=(12,3))
ifprojection=='3d':
ax[0].plot surface(X,Y,prior,alpha=0.3,cmap=plt.cm.jet)
ax[1].plot surface(X,Y,likelihood,alpha=0.3,cmap=plt.cm.jet)
ax[2].plot surface(X,Y,posterior,alpha=0.3,cmap=plt.cm.jet)
else:
ax[0].contour(X,Y,prior)
ax[1].contour(X,Y,likelihood)
ax[2].contour(X,Y,posterior)
ax[0].set title('Prior')
ax[1].set title('Likelihood')
ax[2].set title('Posteior')
plt.tight layout()
thetas1=make thetas(0, 1, 101)
thetas2=make thetas(0, 1, 101)
X, Y=np.meshgrid(thetas1, thetas2)
```

For Metropolis, the following values are considered:

a=2 b=3

```
z1=11
N1 = 14
z2=7
N2 = 14
prior=lambdatheta1, theta2:stats.beta(a,b).pdf(theta1)*stats.beta(a,b)
.pdf(theta2)
lik=partial(bern2, z1=z1, z2=z2, N1=N1, N2=N2)
target=lambdatheta1,theta2:prior(theta1,theta2)*lik(theta1,theta2)
theta=np.array([0.5,0.5])
niters=10000
burnin=500
sigma=np.diag([0.2,0.2])
thetas=np.zeros((niters-burnin,2),np.float)
foriinrange(niters):
new theta=stats.multivariate normal(theta, sigma).rvs()
p=min(target(*new theta)/target(*theta),1)
ifnp.random.rand()<p:</pre>
theta=new theta
ifi>=burnin:
thetas[i-burnin]=theta
kde=stats.gaussian kde(thetas.T)
XY=np.vstack([X.ravel(),Y.ravel()])
posterior metroplis=kde(XY).reshape(X.shape)
make plots(X,Y,prior(X,Y),lik(X,Y),posterior metroplis)
make plots(X,Y,prior(X,Y),lik(X,Y),posterior metroplis,projection='3d
1)
```

For Gibbs, the following values are considered:

```
a=2
b=3
z1=11
N1=14
z2=7
N2=14
prior=lambda
theta1,theta2:stats.beta(a,b).pdf(theta1)*stats.beta(a,b).pdf(theta2)
lik=partial(bern2,z1=z1,z2=z2,N1=N1,N2=N2)
target=lambdatheta1,theta2:prior(theta1,theta2)*lik(theta1,theta2)
```

```
theta=np.array([0.5,0.5])
```

```
niters=10000
burnin=500
sigma=np.diag([0.2,0.2])
thetas=np.zeros((niters-burnin,2),np.float)
foriinrange(niters):
theta=[stats.beta(a+z1,b+N1-z1).rvs(),theta[1]]
theta=[theta[0],stats.beta(a+z2,b+N2-z2).rvs()]
ifi>=burnin:
thetas[i-burnin]=theta
kde=stats.gaussian_kde(thetas.T)
XY=np.vstack([X.ravel(),Y.ravel()])
posterior_gibbs=kde(XY).reshape(X.shape)
make_plots(X,Y,prior(X,Y),lik(X,Y),posterior_gibbs)
make_plots(X,Y,prior(X,Y),lik(X,Y),posterior_gibbs,projection='3d')
```

In the preceding codes of Metropolis and Gibbs, 2D and 3D plots of prior, likelihood, and posterior would be obtained.

Summary

In this chapter, we have discussed about word frequencies (unigram, bigram, and trigram). You have studied Maximum Likelihood Estimation and its implementation in NLTK. We have discussed about the interpolation method, the backoff method, Gibbs sampling, and Metropolis-hastings. We have also discussed how we can perform language modeling through perplexity.

In the next chapter, we will discuss about Stemmer and Lemmatizer, and creating the Morphological generator using machine learning tools.

Chapter 3. Morphology – Getting Our Feet Wet

Morphology may be defined as the study of the composition of words using morphemes. A morpheme is the smallest unit of language that has meaning. In this chapter, we will discuss stemming and lemmatizing, stemmer and lemmatizer for non-English languages, developing a morphological analyzer and morphological generator using machine learning tools, search engines, and many such concepts.

In brief, this chapter will include the following topics:

- Introducing morphology
- Understanding stemmer
- Understanding lemmatization
- Developing a stemmer for non-English languages
- Morphological analyzer
- Morphological generator
- Search engine

Introducing morphology

Morphology may be defined as the study of the production of tokens with the help of **morphemes**. A morpheme is the basic unit of language carrying meaning. There are two types of morpheme: stems and affixes (suffixes, prefixes, infixes, and circumfixes).

Stems are also referred to as free morphemes, since they can even exist without adding affixes. Affixes are referred to as bound morphemes, since they cannot exist in a free form and they always exist along with free morphemes. Consider the word unbelievable. Here, believe is a stem or a free morpheme. It can exist on its own. The morphemes un and able are affixes or bound morphemes. They cannot exist in a free form, but they exist together with stem. There are three kinds of language, namely isolating languages, agglutinative languages, and inflecting languages. Morphology has a different meaning in all these languages. Isolating languages are those languages in which words are merely free morphemes and they do not carry any tense (past, present, and future) and number (singular or plural) information. Mandarin Chinese is an example of an isolating language. Agglutinative languages are those in which small words combine together to convey compound information. Turkish is an example of an agglutinative language. Inflecting languages are those in which words are broken down into simpler units, but all these simpler units exhibit different meanings. Latin is an example of an inflecting language. Morphological processes are of the following types: inflection, derivation, semiaffixes and combining forms, and cliticization. Inflection means transforming the word into a form so that it represents person, number, tense, gender, case, aspect, and mood. Here, the syntactic category of a token remains the same. In derivation, the syntactic category of a word is also changed. Semiaffixes are bound morphemes that exhibit words, such as quality, for example, noteworthy, antisocial, anticlockwise, and so on.

Understanding stemmer

Stemming may be defined as the process of obtaining a stem from a word by eliminating the affixes from a word. For example, in the case of the word raining, stemmer would return the root word or stem word rain by removing the affix from raining. In order to increase the accuracy of information retrieval, search engines mostly use stemming to get the stems and store them as indexed words. Search engines call words with the same meaning synonyms, which may be a kind of query expansion known as conflation. *Martin Porter* has designed a well-known stemming algorithm known as the *Porter stemming algorithm*. This algorithm is basically designed to replace and eliminate some well-known suffices present in English words. To perform stemming in NLTK, we can simply do an instantiation of the PorterStemmer class and then perform stemming by calling the stem method.

Let's see the code for stemming using the PorterStemmer class in NLTK:

```
>>> import nltk
>>> from nltk.stem import PorterStemmer
>>> stemmerporter = PorterStemmer()
>>> stemmerporter.stem('working')
'work'
>>> stemmerporter.stem('happiness')
'happi'
```

The PorterStemmer class has been trained and has knowledge of the many stems and word forms of English. The process of stemming takes place in a series of steps and transforms the word into a shorter word or a word that has a similar meaning to the root word. The **Stemmer I** interface defines the stem() method, and all the stemmers are inherited from the **Stemmer I** interface. The inheritance diagram is depicted here:



Another stemming algorithm known as the *Lancaster stemming algorithm* was introduced at Lancaster University. Similar to the PorterStemmer class, the LancasterStemmer class is used in NLTK to implement Lancaster stemming. However, one of the major differences between the two algorithms is that Lancaster stemming involves the use of more words of different sentiments as compared to Porter Stemming.

Let's consider the following code that depicts Lancaster stemming in NLTK:

```
>>> import nltk
>>> from nltk.stem import LancasterStemmer
>>> stemmerlan=LancasterStemmer()
>>> stemmerlan.stem('working')
'work'
>>> stemmerlan.stem('happiness')
'happy'
```

We can also build our own stemmer in NLTK using RegexpStemmer. It works by accepting a string and eliminating the string from the prefix or suffix of a word when a match is found.

Let's consider an example of stemming using RegexpStemmer in NLTK:

```
>>> import nltk
>>> from nltk.stem import RegexpStemmer
>>> stemmerregexp=RegexpStemmer('ing')
>>> stemmerregexp.stem('working')
'work'
>>> stemmerregexp.stem('happiness')
'happiness'
>>> stemmerregexp.stem('pairing')
'pair'
```

We can use RegexpStemmer in the cases in which stemming cannot be performed using PorterStemmer and LancasterStemmer.

SnowballStemmer is used to perform stemming in 13 languages other than English. In order to perform stemming using SnowballStemmer, firstly, an instance is created in the language in which stemming needs to be performed. Then, using the stem() method, stemming is performed.

Consider the following example of performing stemming in Spanish and French in NLTK using SnowballStemmer:

```
>>> import nltk
>>> from nltk.stem import SnowballStemmer
>>> SnowballStemmer.languages
('danish', 'dutch', 'english', 'finnish', 'french', 'german',
'hungarian', 'italian', 'norwegian', 'porter', 'portuguese',
'romanian', 'russian', 'spanish', 'swedish')
```
```
>>> spanishstemmer=SnowballStemmer('spanish')
>>> spanishstemmer.stem('comiendo')
'com'
>>> frenchstemmer=SnowballStemmer('french')
>>> frenchstemmer.stem('manger')
'mang'
```

Nltk.stem.api consists of the Stemmer I class in which the stem function is performed.

Consider the following code present in NLTK that enables us to perform stemming:

```
Class StemmerI(object):
"""
It is an interface that helps to eliminate morphological affixes
from the tokens and the process is known as stemming.
"""
def stem(self, token):
"""
Eliminate affixes from token and stem is returned.
"""
raise NotImplementedError()
```

Let's see the code used to perform stemming using multiple stemmers:

```
>>> import nltk
>>> from nltk.stem.porter import PorterStemmer
>>> from nltk.stem.lancaster import LancasterStemmer
>>> from nltk.stem import SnowballStemmer
>>> def obtain tokens():
With open('/home/p/NLTK/sample1.txt') as stem: tok =
nltk.word tokenize(stem.read())
return tokens
>>> def stemming(filtered):
stem=[]
for x in filtered:
stem.append(PorterStemmer().stem(x))
return stem
>>> if name ==" main ":
tok= obtain tokens()
>>>print("tokens is %s")%(tok)
>>>stem tokens= stemming(tok)
>>>print("After stemming is %s")%stem tokens
>>>res=dict(zip(tok,stem tokens))
>>>print("{tok:stemmed}=%s")%(result)
```

Understanding lemmatization

Lemmatization is the process in which we transform the word into a form with a different word category. The word formed after lemmatization is entirely different. The built-in morphy() function is used for lemmatization in WordNetLemmatizer. The inputted word is left unchanged if it is not found in WordNet. In the argument, pos refers to the part of speech category of the inputted word.

Consider an example of lemmatization in NLTK:

```
>>> import nltk
>>> from nltk.stem import WordNetLemmatizer
>>> lemmatizer_output=WordNetLemmatizer()
>>> lemmatizer_output.lemmatize('working')
'working'
>>> lemmatizer_output.lemmatize('working',pos='v')
'work'
>>> lemmatizer_output.lemmatize('works')
'work'
```

The WordNetLemmatizer library may be defined as a wrapper around the so-called WordNet corpus, and it makes use of the morphy() function present in WordNetCorpusReader to extract a lemma. If no lemma is extracted, then the word is only returned in its original form. For example, for works, the lemma returned is the singular form, work.

Let's consider the following code that illustrates the difference between stemming and lemmatization :

```
>>> import nltk
>>> from nltk.stem import PorterStemmer
>>> stemmer_output=PorterStemmer()
>>> stemmer_output.stem('happiness')
'happi'
>>> from nltk.stem import WordNetLemmatizer
>>> lemmatizer_output=WordNetLemmatizer()
>>> lemmatizer_output.lemmatize('happiness')
```

In the preceding code, happiness is converted to happi by stemming. Lemmatization doesn't find the root word for happiness, so it returns the word happiness.

Developing a stemmer for non-English language

Polyglot is a software that is used to provide models called morfessor models that are used to obtain morphemes from tokens. The Morpho project's goal is to create unsupervised data-driven processes. The main aim of the Morpho project is to focus on the creation of morphemes, which is the smallest unit of syntax. Morphemes play an important role in natural language processing. Morphemes are useful in automatic recognition and the creation of language. With the help of the vocabulary dictionaries of Polyglot, morfessor models on the 50,000 tokens of different languages were used.

Let's see the code for obtaining the language table using polyglot:

```
from polyglot.downloader import downloader
print(downloader.supported_languages_table("morph2"))
```

The output obtained from preceding code is the languages listed here:

1. Piedmontese language	2. Lombard language	3. Gan Chinese
4. Sicilian	5. Scots	6. Kirghiz, Kyrgyz
7. Pashto, Pushto	8. Kurdish	9. Portuguese
10. Kannada	11. Korean	12. Khmer
13. Kazakh	14. liokano	15. Polish
16. Panjabi, Punjabi	17. Georgian	18. Chuvash
19. Alemannic	20. Czech	21. Welsh
22. Chechen	23. Catalan; Valencian	24. Northern Sami
25. Sanskrit (Sa sk ta)	26. Slovene	27. Javanese
28. Slovak	29. Bosnian-Croatian-Serbian	30. Bavarian
31. Swedish	32. Swahili	33. Sundanese
34. Serbian	35. Albanian	36. Japanese
37. Western Frisian	38. French	39. Finnish
40. Upper Sorbian	41. Faroese	42. Persian
43. Sinhala, Sinhalese	44. Italian	45. Amharic
46. Aragonese	47. Volapük	48. Icelandic
49. Sakha	50. Afrikaans	51. Indonesian
52. Interlingua	53. Azerbaijani	54. Ido
55. Arabic	56. Assamese	57. Yoruba
58. Yiddish	59. Waray-Waray	60. Croatian
61. Hungarian	62. Haitian; Haitian Creole	63. Quechua
64. Armenian	65. Hebrew (modern)	66. Silesian
67. Hindi	68. Divehi; Dhivehi; Mald	69. German
70. Danish	71. Occitan	72. Tagalog
73. Turkmen	74. Thai	75. Tajik
76. Greek, Modern	77. Telugu	78. Tamil
79. Oriya	80. Ossetian, Ossetic	81. Tatar
82. Turkish	83. Kapampangan	84. Venetian
85. Manx	86. Gujarati	87. Galician
88. Irish	89. Scottish Gaelic; Gaelic	90. Nepali
91. Cebuano	92. Zazaki	93. Walloon
94. Dutch	95. Norwegian	96. Norwegian Nynorsk
97. West Flemish	98. Chinese	99. Bosnian
100. Breton	101. Belarusian	102. Bulgarian
103. Bashkir	104. Egyptian Arabic	105. Tibetan Standard, Tib
106. Bengali	107. Burmese	108. Romansh
109. Marathi (Mar h)	110. Malay	111. Maltese
112. Russian	113. Macedonian	114. Malayalam
115. Mongolian	116. Malagasy	117. Vietnamese
118. Spanish; Castilian	119. Estonian	120. Basque
121. Bishnupriya Manipuri	122. Asturian	123. English
124. Esperanto	125. Luxembourgish, Letzeb	126. Latin
127. Uighur, Uyghur	128. Ukrainian	129. Limburgish, Limburgan
130. Latvian	131. Urdu	132. Lithuanian
133. Fiji Hindi	134. Uzbek	135. Romanian, Moldavian,

The necessary models can be downloaded using the following code:

```
%%bash
polyglot_data] Downloading package morph2.en to
[polyglot_data] /home/rmyeid/polyglot_data...
[polyglot_data] Package morph2.en is already up-to-date!
[polyglot_data] Downloading package morph2.ar to
[polyglot_data] /home/rmyeid/polyglot_data...
[polyglot_data] Package morph2.ar is already up-to-date!
```

Consider an example that is used to obtain an output from polyglot:

```
from polyglot.text import Text, Word
tokens =["unconditional" ,"precooked", "impossible", "painful",
"entered"]
for s in tokens:
s=Word(s, language="en")
print("{:<20}{}".format(s,s.morphemes))
unconditional['un','conditional']
precooked['pre','cook','ed']
impossible['im','possible']
painful['pain','ful']
entered['enter','ed']
```

If tokenization is not performed properly, then we can perform morphological analysis for the process of splitting the text into the original constituents:

```
sent="Ihopeyoufindthebookinteresting"
para=Text(sent)
para.language="en"
para.morphemes
WordList(['I','hope','you','find','the','book','interesting'])
```

Morphological analyzer

Morphological analysis may be defined as the process of obtaining grammatical information from tokens, given their suffix information. Morphological analysis can be performed in three ways: morpheme-based morphology (or anitem and arrangement approach), lexeme-based morphology (or an item and process approach), and word-based morphology (or a word and paradigm approach). A morphological analyzer may be defined as a program that is responsible for the analysis of the morphology of a given input token. It analyzes a given token and generates morphological information, such as gender, number, class, and so on, as an output.

In order to perform morphological analysis on a given non-whitespace token, the pyEnchant dictionary is used.

Let's consider the following code that performs morphological analysis:

```
>>> import enchant
>>> s = enchant.Dict("en US")
>>> tok=[]
>>> def tokenize(st1):
if not st1:return
for j in xrange(len(st1),-1,-1):
if s.check(st1[0:j]):
tok.append(st1[0:i])
st1=st[j:]
tokenize(st1)
break
>>> tokenize("itismyfavouritebook")
>>> tok
['it', 'is', 'my', 'favourite', 'book']
>>> tok=[ ]
>>> tokenize("ihopeyoufindthebookinteresting")
>>> tok
['i', 'hope', 'you', 'find', 'the', 'book', 'interesting']
```

We can determine the category of the word with the help of the following points:

- **Morphological hints**: The suffix's information helps us detect the category of a word. For example, the -ness and -ment suffixes exist with nouns.
- **Syntactic hints**: Contextual information is conducive to determine the category of a word. For example, if we have found the word that has the noun category, then syntactic hints will be useful for determining whether an adjective would appear before the noun or after the noun category.
- Semantic hints: A semantic hint is also useful for determining the word's category. For example, if we already know that a word represents the name of a location, then it will fall under the noun category.
- **Open class**: This is class of words that are not fixed, and their number keeps on increasing every day, whenever a new word is added to their list. Words in the open class are usually

nouns. Prepositions are mostly in a closed class. For example, there can be an unlimited number of words in the of Persons list. So, it is an open class.

- Morphology captured by the Part of Speech tagset: The Part of Speech tagset captures information that helps us perform morphology. For example, the word plays would appear with the third person and a singular noun.
- **Omorfi:Omorfi (Open morphology of Finnish)** is a package that has been licensed by GNU GPL version 3. It is used for performing numerous tasks, such as language modeling, morphological analysis, rule-based machine translation, information retrieval, statistical machine translation, morphological segmentation, ontologies, and spell checking and correction.

Morphological generator

A morphological generator is a program that performs the task of morphological generation. Morphological generation may be considered an opposite task of morphological analysis. Here, given the description of a word in terms of number, category, stem, and so on, the original word is retrieved. For example, if root = go, part of speech = verb, tense= present, and if it occurs along with a third person and singular subject, then a morphological generator would generate its surface form, goes.

There is a lot of Python-based software that performs morphological analysis and generation. Some of them are as follows:

- **ParaMorfo**: It is used to perform morphological generation and analysis of Spanish and Guarani nouns, adjectives, and verbs.
- HornMorpho: It is used for the morphological generation and analysis of Oromo and Amharic nouns and verbs, as well as Tigrinya verbs.
- AntiMorfo: It is used for the morphological generation and analysis of Quechua adjectives, verbs, and nouns, as well as Spanish verbs.
- MorfoMelayu: It is used for the morphological analysis of Malay words.

Other examples of software that is used to perform morphological analysis and generation are as follows:

- Morph is a morphological generator and analyzer for English for the RASP system
- Morphy is a morphological generator, analyzer, and POS tagger for German
- Morphisto is a morphological generator and analyzer for German
- Morfette performs supervised learning (inflectional morphology) for Spanish and French

Search engine

PyStemmer 1.0.1 consists of Snowball stemming algorithms that are used for performing information retrieval tasks and for constructing a search engine. It consists of the Porter stemming algorithm and many other stemming algorithms that are useful for performing stemming and information retrieval tasks in many languages, including many European languages.

We can construct a vector space search engine by converting the texts into vectors.

The following are the steps involved in constructing a vector space search engine:

1. Consider the following code for the removal of stopwords and tokenization:

A stemmer is a program that accepts words and converts them into stems. Tokens that have the same stem have nearly the same meanings. Stopwords are also eliminated from a text.

```
def eliminatestopwords(self,list):
"""
Eliminate words which occur often and have not much
significance from context point of view.
"""
return[ word for word in list if word not in self.stopwords ]
def tokenize(self,string):
"""
Perform the task of splitting text into stop words and tokens
"""
Str=self.clean(str)
Words=str.split("")
return [self.stemmer.stem(word,0,len(word)-1) for word in words]
```

2. Consider the following code for mapping keywords into vector dimensions:

```
def obtainvectorkeywordindex(self, documentList):
"""
In the document vectors, generate the keyword for the given
position of element
"""
```

```
#Perform mapping of text into strings
vocabstring = "".join(documentList)
```

```
vocablist = self.parser.tokenise(vocabstring)
#Eliminate common words that have no search significance
vocablist = self.parser.eliminatestopwords(vocablist)
uniqueVocablist = util.removeDuplicates(vocablist)
```

```
vectorIndex={}
offset=0
#Attach a position to keywords that performs mapping with
dimension that is used to depict this token
for word in uniqueVocablist:
vectorIndex[word]=offset
offset+=1
return vectorIndex #(keyword:position)
```

3. Here, a simple term count model is used. Consider the following code for the conversion of text strings into vectors:

```
def constructVector(self, wordString):
    # Initialise the vector with 0's
    Vector_val = [0] * len(self.vectorKeywordIndex)
    tokList = self.parser.tokenize(tokString)
    tokList = self.parser.eliminatestopwords(tokList)
    for word in toklist:
        vector[self.vectorKeywordIndex[word]] += 1;
# simple Term Count Model is used
    return vector
```

4. Searching similar documents by finding the cosine of an angle between the vectors of a document, we can prove whether two given documents are similar or not. If the cosine value is 1, then the angle's value is 0 degrees and the vectors are said to be parallel (this means that the documents are said to be related). If the cosine value is 0 and value of the angle is 90 degrees, then the vectors are said to be perpendicular (this means that the documents are not said to be related). Let's see the code for computing the cosine between the text vectors using SciPy:

5. We perform the mapping of keywords to vector space. We construct a temporary text that represents the items to be searched and then compare it with document vectors with the help of cosine measurement. Let's see the following code for searching the vector space:

```
ratings.sort(reverse=True)
return ratings
```

6. We will now consider the following code that can be used for detecting languages from the source text:

```
>>> import nltk
>>> import sys
>>> try:
from nltk import wordpunct tokenize
from nltk.corpus import stopwords
except ImportError:
print( 'Error has occured')
#_____
_____
>>> def calculate languages ratios(text):
.....
Compute probability of given document that can be written in
different languages and give a dictionary that appears like
{'german': 2, 'french': 4, 'english': 1}
.....
languages ratios = {}
1 1 1
nltk.wordpunct tokenize() splits all punctuations into separate
tokens
wordpunct tokenize ("I hope you like the book interesting .")
[' I', ' hope ', 'you ', 'like ', 'the ', 'book' , 'interesting ', '.']
. . .
tok = wordpunct tokenize(text)
wor = [word.lower() for word in tok]
 # Compute occurence of unique stopwords in a text
for language in stopwords.fileids():
stopwords set = set(stopwords.words(language))
words set = set(words)
common elements = words set.intersection(stopwords_set)
languages ratios[language] = len(common elements)
# language "score"
return languages ratios
#_______
```

Compute the probability of given text that is written in different languages and obtain the one that is highest scored. It makes use of stopwords calculation approach, finds out unique stopwords present in a analyzed text. """

ratios = _calculate_languages_ratios(text)
most_rated_language = max(ratios, key=ratios.get)
return most_rated_language

if __name__=='__main__':

text = '''

All over this cosmos, most of the people believe that there is an invisible supreme power that is the creator and the runner of this world. Human being is supposed to be the most intelligent and loved creation by that power and that is being searched by human beings in different ways into different things. As a result people reveal His assumed form as per their own perceptions and beliefs. It has given birth to different religions and people are divided on the name of religion viz. Hindu, Muslim, Sikhs, Christian etc. People do not stop at this. They debate the superiority of one over the other and fight to establish their views. Shrewd people like politicians oppose and support them at their own convenience to divide them and control them. It has intensified to the extent that even parents of a new born baby teach it about religious differences and

recommend their own religion superior to that of others and let the child learn to hate other people just because of religion. Jonathan Swift, an eighteenth century novelist, observes that we have just enough religion to make us hate, but not enough to make us love one another.

The word 'religion' does not have a derogatory meaning - A literal meaning of religion is 'A personal or institutionalized system grounded in belief in a

God or Gods and the activities connected with this'. At its basic level, 'religion is just a set of teachings that tells people how to lead a good life'. It has never been the purpose of religion to divide people into groups of isolated followers that cannot live in harmony together. No religion claims to teach intolerance or even instructs its believers to segregate a certain religious group or even take the fundamental rights of an individual solely based on their religious choices. It is

......

also said that 'Majhab nhi sikhata aaps mai bair krna'.But this very majhab or religion takes a very heinous form when it is misused by the shrewd politicians and the fanatics e.g. in Ayodhya on 6th December, 1992 some right wing political parties and communal organizations incited the Hindus to demolish the 16th century Babri Masjid in the name of religion to polarize Hindus votes. Muslim fanatics in Bangladesh retaliated and destroyed a number of temples, assassinated innocent Hindus and raped Hindu girls who had nothing to do with the demolition of Babri Masjid. This very inhuman act has been presented by Taslima Nasrin, a Bangladeshi Doctor-cum-Writer in her controversial novel 'Lajja' (1993) in which, she seems to utilizes fiction's mass emotional appeal, rather than its potential for nuance and universality. . . . >>> language = detect language(text) >>> print(language)

The preceding code will search for stopwords and detect the language of the text, that is, English.

Summary

The field of computational linguistics has numerous applications. We need to perform preprocessing on our original text in order to implement or build an application. In this chapter, we have discussed stemming, lemmatization, and morphological analysis and generation, and their implementation in NLTK. We have also discussed search engines and their implementation.

In the next chapter, we will discuss parts of speech, tagging, and chunking.

Chapter 4. Parts-of-Speech Tagging – Identifying Words

Parts-of-speech (**POS**) tagging is one of the many tasks in NLP. It is defined as the process of assigning a particular parts-of-speech tag to individual words in a sentence. The parts-of-speech tag identifies whether a word is a noun, verb, adjective, and so on. There are numerous applications of parts-of-speech tagging, such as information retrieval, machine translation, NER, language analysis, and so on.

This chapter will include the following topics:

- Creating POS tagged corpora
- Selecting a machine learning algorithm
- Statistical modeling involving the n-gram approach
- Developing a chunker using POS tagged data

Introducing parts-of-speech tagging

Parts-of-speech tagging is the process of assigning a category (for example, noun, verb, adjective, and so on) tag to individual tokens in a sentence. In NLTK, taggers are present in the nltk.tag package and it is inherited by the TaggerIbase class.

Consider an example to implement POS tagging for a given sentence in NLTK:

```
>>> import nltk
>>> text1=nltk.word_tokenize("It is a pleasant day today")
>>> nltk.pos_tag(text1)
[('It', 'PRP'), ('is', 'VBZ'), ('a', 'DT'), ('pleasant', 'JJ'),
('day', 'NN'), ('today', 'NN')]
```

We can implement the tag() method in all the subclasses of TaggerI. In order to evaluate tagger, TaggerI has provided the evaluate() method. A combination of taggers can be used to form a back-off chain so that the next tagger can be used for tagging if one tagger is not tagging.

Let's see the list of available tags provided by **Penn Treebank** (<u>https://www.ling.upenn.edu/courses/</u><u>Fall_2003/ling001/penn_treebank_pos.html</u>):

```
CC - Coordinating conjunction
CD - Cardinal number
DT - Determiner
EX - Existential there
FW - Foreign word
IN - Preposition or subordinating conjunction
JJ - Adjective
JJR - Adjective, comparative
JJS - Adjective, superlative
LS - List item marker
```

```
MD - Modal
NN - Noun, singular or mass
NNS - Noun, plural
NNP - Proper noun, singular
NNPS - Proper noun, plural
PDT - Predeterminer
POS - Possessive ending
PRP - Personal pronoun
PRP$ - Possessive pronoun (prolog version PRP-S)
RB - Adverb
RBR - Adverb, comparative
RBS - Adverb, superlative
RP - Particle
SYM - Symbol
TO - to
UH - Interjection
VB - Verb, base form
VBD - Verb, past tense
VBG - Verb, gerund or present participle
VBN - Verb, past participle
VBP - Verb, non-3rd person singular present
VBZ - Verb, 3rd person singular present
WDT - Wh-determiner
WP - Wh-pronoun
WP$ - Possessive wh-pronoun (prolog version WP-S)
WRB - Wh-adverb
```

NLTK may provide the information of tags. Consider the following code, which provides information about the NNS tag:

```
>>> nltk.help.upenn_tagset('NNS')
NNS: noun, common, plural
    undergraduates scotches bric-a-brac products bodyguards facets
coasts
    divestitures storehouses designs clubs fragrances averages
    subjectivists apprehensions muses factory-jobs ...
```

Let's see another example in which a regular expression may also be queried:

>>> nltk.help.upenn_tagset('VB.*')
VB: verb, base form
 ask assemble assess assign assume atone attention avoid bake
balkanize
 bank begin behold believe bend benefit bevel beware bless boil
bomb
 boost brace break bring broil brush build ...
VBD: verb, past tense

dipped pleaded swiped regummed soaked tidied convened halted registered cushioned exacted snubbed strode aimed adopted belied figgered speculated wore appreciated contemplated ... VBG: verb, present participle or gerund telegraphing stirring focusing angering judging stalling lactating hankerin' alleging veering capping approaching traveling besieging encrypting interrupting erasing wincing ... VBN: verb, past participle multihulled dilapidated aerosolized chaired languished panelized used experimented flourished imitated reunifed factored condensed sheared unsettled primed dubbed desired ... VBP: verb, present tense, not 3rd person singular predominate wrap resort sue twist spill cure lengthen brush terminate appear tend stray glisten obtain comprise detest tease attract emphasize mold postpone sever return wag ... VBZ: verb, present tense, 3rd person singular bases reconstructs marks mixes displeases seals carps weaves snatches slumps stretches authorizes smolders pictures emerges stockpiles seduces fizzes uses bolsters slaps speaks pleads ... R

The preceding code gives information regarding all the tags of verb phrases.

Let's look at an example that depicts words' sense disambiguation achieved through POS tagging:

```
>>> import nltk
>>> text=nltk.word_tokenize("I cannot bear the pain of bear")
>>> nltk.pos_tag(text)
[('I', 'PRP'), ('can', 'MD'), ('not', 'RB'), ('bear', 'VB'), ('the',
'DT'), ('pain', 'NN'), ('of', 'IN'), ('bear', 'NN')]
```

Here, in the previous sentence, bear is a verb, which means to tolerate, and it also is an animal, which means that it is a noun.

In NLTK, a tagged token is represented as a tuple consisting of a token and its tag. We can create this tuple in NLTK using the str2tuple() function:

```
>>> import nltk
>>> taggedword=nltk.tag.str2tuple('bear/NN')
>>> taggedword
('bear', 'NN')
>>> taggedword[0]
```

'bear'
>>> taggedword[1]
'NN'

Let's consider an example in which sequences of tuples can be generated from the given text:

```
>>> import nltk
>>> sentence='''The/DT sacred/VBN Ganga/NNP flows/VBZ in/IN this/DT
region/NN ./. This/DT is/VBZ a/DT pilgrimage/NN ./. People/NNP from/
IN all/DT over/IN the/DT country/NN visit/NN this/DT place/NN ./. '''
>>> [nltk.tag.str2tuple(t) for t in sentence.split()]
[('The', 'DT'), ('sacred', 'VBN'), ('Ganga', 'NNP'), ('flows',
'VBZ'), ('in', 'IN'), ('this', 'DT'), ('region', 'NN'), ('.', '.'),
('This', 'DT'), ('is', 'VBZ'), ('a', 'DT'), ('pilgrimage', 'NN'),
('.', '.'), ('People', 'NNP'), ('from', 'IN'), ('all', 'DT'),
('over', 'IN'), ('the', 'DT'), ('.', '.')]
```

Now, consider the following code that converts the tuple (word and pos tag) into a word and a tag:

```
>>> import nltk
>>> taggedtok = ('bear', 'NN')
>>> from nltk.tag.util import tuple2str
>>> tuple2str(taggedtok)
'bear/NN'
```

Let's see the occurrence of some common tags in the Treebank corpus:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> treebank_tagged = treebank.tagged_words(tagset='universal')
>>> tag = nltk.FreqDist(tag for (word, tag) in treebank_tagged)
>>> tag.most_common()
[('NOUN', 28867), ('VERB', 13564), ('.', 11715), ('ADP', 9857),
('DET', 8725), ('X', 6613), ('ADJ', 6397), ('NUM', 3546), ('PRT',
3219), ('ADV', 3171), ('PRON', 2737), ('CONJ', 2265)]
```

Consider the following code, which calculates the number of tags occurring before a noun tag:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> treebank_tagged = treebank.tagged_words(tagset='universal')
>>> tagpairs = nltk.bigrams(treebank_tagged)
>>> preceders_noun = [x[1] for (x, y) in tagpairs if y[1] == 'NOUN']
>>> freqdist = nltk.FreqDist(preceders_noun)
>>> [tag for (tag, ) in freqdist.most common()]
```

```
['NOUN', 'DET', 'ADJ', 'ADP', '.', 'VERB', 'NUM', 'PRT', 'CONJ', 'PRON', 'X', 'ADV']
```

We can also provide POS tags to tokens using dictionaries in Python. Let's see the following code that illustrates the creation of a tuple (word:pos tag) using dictionaries in Python:

```
>>> import nltk
>>> tag={}
>>> tag
{}
>>> tag['beautiful']='ADJ'
>>> tag
{'beautiful': 'ADJ'}
>>> tag['boy']='N'
>>> tag['read']='V'
>>> tag['generously']='ADV'
>>> tag
{'boy': 'N', 'beautiful': 'ADJ', 'generously': 'ADV', 'read': 'V'}
```

Default tagging

Default tagging is a kind of tagging that assigns identical parts-of-speech tags to all the tokens. The subclass of SequentialBackoffTagger is DefaultTagger. The choose_tag() method must be implemented by SequentialBackoffTagger. This method includes the following arguments:

- A collection of tokens
- The index of the token that should be tagged
- The previous tags list

The hierarchy of tagger is depicted as follows:



Let's now see the following code, which depicts the working of DefaultTagger:

```
>>> import nltk
>>> from nltk.tag import DefaultTagger
>>> tag = DefaultTagger('NN')
>>> tag.tag(['Beautiful', 'morning'])
[('Beautiful', 'NN'), ('morning', 'NN')]
```

We can convert a tagged sentence into an untagged sentence with the help of nltk.tag.untag(). After calling this function, the tags on individual tokens will be eliminated.

Let's see the code for untagging a sentence:

```
>>> from nltk.tag import untag
>>> untag([('beautiful', 'NN'), ('morning', 'NN')])
['beautiful', 'morning']
```

Creating POS-tagged corpora

A corpus may be known as a collection of documents. A corpora is the collection of multiple corpus.

Let's see the following code, which will generate a data directory inside the home directory:

```
>>> import nltk
>>> import os,os.path
>>> create = os.path.expanduser('~/nltkdoc')
>>> if not os.path.exists(create):
    os.mkdir(create)
>>> os.path.exists(create)
True
>>> import nltk.data
>>> create in nltk.data.path
True
```

This code will create a data directory named ~/nltkdoc inside the home directory. The last line of this code will return True and will ensure that the data directory has been created. If the last line of the code returns False, then it means that the data directory has not been created and we need to create it manually. After creating the data directory manually, we can test the last line and it will then return True. Within this directory, we can create another directory named nltkcorpora that will hold the whole corpus. The path will be ~/nltkdoc/nltkcorpora. Also, we can create a subdirectory named important that will hold all the necessary files.

The path will be ~/nltkdoc/nltkcorpora/important.

Let's see the following code to load a text file into the subdirectory:

```
>>> import nltk.data
>>> nltk.data.load('nltkcorpora/important/firstdoc.txt',format='raw')
'nltk\n'
```

Here, in the previous code, we have mentioned format='raw', since nltk.data.load() cannot interpret .txt files.

There is a word list corpus in NLTK known as the Names corpus. It consists of two files, namely, male.txt and female.txt.

Let's see the code to generate the length of male.txt and female.txt:

>>> import nltk
>>> from nltk.corpus import names
>>> names.fileids()

```
['female.txt', 'male.txt']
>>> len(names.words('male.txt'))
2943
>>> len(names.words('female.txt'))
5001
```

NLTK also consists of a large collection of English words. Let's see the code that describes the number of words present in the English word file:

```
>>> import nltk
>>> from nltk.corpus import words
>>> words.fileids()
['en', 'en-basic']
>>> len(words.words('en'))
235886
>>> len(words.words('en-basic'))
850
```

Consider the following code used in NLTK for defining the Maxent Treebank POS tagger:

def pos_tag(tok):
 """

We can use POS tagger given by NLTK to tag a list of tokens:

```
>>> from nltk.tag import pos tag
>>> from nltk.tokenize import word tokenize
>>> pos tag(word tokenize("Papa's favourite hobby is reading."))
        [('Papa', 'NNP'), ("'s", 'POS'), ('favourite', 'JJ'),
('hobby', 'NN'), ('is',
        'VBZ'), ('reading', 'VB'), ('.', '.')]
    :param tokens: list of tokens that need to be tagged
    :type tok: list(str)
    :return: The tagged tokens
    :rtype: list(tuple(str, str))
    .. .. ..
    tagger = load( POS TAGGER)
    return tagger.tag(tok)
def batch pos tag(sent):
    ** ** **
    We can use part of speech tagger given by NLTK to perform
tagging of list of tokens.
    .. .. ..
    tagger = load( POS TAGGER)
    return tagger.batch tag(sent)
```

Selecting a machine learning algorithm

POS tagging is also referred to as word category disambiguation or grammatical tagging. POS tagging may be of two types: rule-based or stochastic/probabilistic. E. Brill's tagger is based on the rule-based tagging algorithm.

A POS classifier takes a document as input and obtains word features. It trains itself with the help of these word features combined with the already available training labels. This type of classifier is referred to as a second order classifier, and it makes use of the bootstrap classifier in order to generate the tags for words.

A backoff classifier is one in which backoff procedure is performed. The output is obtained in such a manner that the trigram POS tagger relies on the bigram POS tagger, which in turn relies on the unigram POS tagger.

While training a POS classifier, a feature set is generated. This feature set may comprise the following:

- Information about the current word
- Information about the previous word or prefix
- Information about the next word or successor

In NLTK, FastBrillTagger is based on unigram. It makes use of a dictionary of words that are already known and the pos tag information.

Let's see the code for FastBrillTagger used in NLTK:

```
from nltk.tag import UnigramTagger
from nltk.tag import FastBrillTaggerTrainer
from nltk.tag.brill import SymmetricProximateTokensTemplate
from nltk.tag.brill import ProximateTokensTemplate
from nltk.tag.brill import ProximateTagsRule
from nltk.tag.brill import ProximateWordsRule
ctx = [ # Context = surrounding words and tags.
    SymmetricProximateTokensTemplate(ProximateTagsRule, (1, 1)),
    SymmetricProximateTokensTemplate(ProximateTagsRule, (1, 2)),
    SymmetricProximateTokensTemplate(ProximateTagsRule, (1, 3)),
    SymmetricProximateTokensTemplate(ProximateTagsRule, (2, 2)),
    SymmetricProximateTokensTemplate(ProximateWordsRule, (0, 0)),
    SymmetricProximateTokensTemplate(ProximateWordsRule, (1, 1)),
    SymmetricProximateTokensTemplate(ProximateWordsRule, (1, 2)),
    ProximateTokensTemplate(ProximateTagsRule, (-1, -1), (1, 1)),
1
```

tagger = UnigramTagger(sentences)

```
tagger = FastBrillTaggerTrainer(tagger, ctx, trace=0)
tagger = tagger.train(sentences, max_rules=100)
```

Classification may be defined as the process of deciding a POS tag for a given input.



In **supervised classification**, a training corpus is used that comprises a word and its correct tag. In **unsupervised classification**, any pair of words and a correct tag list does not exist:

In supervised classification, during training, a feature extractor accepts the input and labels and generates a set of features. These features set along with the label act as input to machine learning algorithms. During the testing or prediction phase, a feature extractor is used that generates features from unknown inputs, and the output is sent to a classifier model that generates an output in the form of label or pos tag information with the help of machine learning algorithms.

The **maximum entropy** classifier is one in that searches the parameter set in order to maximize the total likelihood of the corpus used for training.

It may be defined as follows:

Statistical modeling involving the n-gram approach

Unigram means a single word. In a unigram tagger, a single token is used to find the particular parts-of-speech tag.

Training of UnigramTagger can be performed by providing it with a list of sentences at the time of initialization.

Let's see the following code in NLTK, which performs UnigramTagger training:

```
>>> import nltk
>>> from nltk.tag import UnigramTagger
>>> from nltk.corpus import treebank
>>> training= treebank.tagged_sents()[:7000]
>>> unitagger=UnigramTagger(training)
>>> treebank.sents()[0]
['Pierre', 'Vinken', ',', '61', 'years', 'old', ',', 'will', 'join',
'the', 'board', 'as', 'a', 'nonexecutive', 'director', 'Nov.', '29',
'.']
>>> unitagger.tag(treebank.sents()[0])
[('Pierre', 'NNP'), ('Vinken', 'NNP'), (',', ','), ('61', 'CD'),
('years', 'NNS'), ('old', 'JJ'), (',', ','), ('will', 'MD'),
('join', 'VB'), ('the', 'DT'), ('board', 'NN'), ('as', 'IN'), ('a',
'DT'), ('nonexecutive', 'JJ'), ('director', 'NN'), ('Nov.', 'NNP'),
('29', 'CD'), ('.', '.')]
```

In the preceding code, we have performed training using the first 7000 sentences of the Treebank corpus.

The hierarchy followed by UnigramTagger is depicted in the following inheritance diagram:



To evaluate UnigramTagger, let's see the following code, which calculates the accuracy:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> from nltk.tag import UnigramTagger
>>> training= treebank.tagged_sents()[:7000]
>>> unitagger=UnigramTagger(training)
>>> testing = treebank.tagged_sents()[2000:]
>>> unitagger.evaluate(testing)
0.963400866227395
```

So, it is 96% accurate in correctly performing pos tagging.

Since UnigramTagger inherits from ContextTagger, we can map the context key with a specific tag.

Consider the following example of tagging using UnigramTagger:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> from nltk.tag import UnigramTagger
>>> unitag = UnigramTagger(model={'Vinken': 'NN'})
>>> unitag.tag(treebank.sents()[0])
[('Pierre', None), ('Vinken', 'NN'), (',', None), ('61', None),
('years', None), ('old', None), (',', None), ('will', None),
('join', None), ('the', None), ('board', None), ('as', None), ('a',
None), ('nonexecutive', None), ('director', None), ('Nov.', None),
('29', None), ('.', None)]
```

Here, in the preceding code, UnigramTagger only tags 'Vinken' with the 'NN' tag and the rest are tagged with the 'None' tag since we have provided the tag for the word 'Vinken' in the context model and no other words are included in the context model.

In a given context, ContextTagger uses the frequency of a given tag to decide the occurrence of the most probable tag. In order to use minimum threshold frequency, we can pass a specific value to the cutoff value. Let's see the code that evaluates UnigramTagger:

```
>>> unitagger = UnigramTagger(training, cutoff=5)
>>> unitagger.evaluate(testing)
0.7974218445306567
```

Backoff tagging may be defined as a feature of SequentialBackoffTagger. All the taggers are chained together so that if one of the taggers is unable to tag a token, then the token may be passed to the next tagger.

Let's see the following code, which uses back-off tagging. Here, DefaultTagger and UnigramTagger are used to tag a token. If any tagger of them is unable to tag a word, then the next tagger may be used to tag it:

```
>>> import nltk
>>> from nltk.tag import UnigramTagger
>>> from nltk.tag import DefaultTagger
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> tag1=DefaultTagger('NN')
>>> tag2=UnigramTagger(training,backoff=tag1)
>>> tag2.evaluate(testing)
0.963400866227395
```

The subclasses of NgramTagger areUnigramTagger, BigramTagger, and TrigramTagger. BigramTagger makes use of the previous tag as contextual information. TrigramTagger uses the previous two tags as contextual information.

Consider the following code, which illustrates the implementation of BigramTagger:

```
>>> import nltk
>>> from nltk.tag import BigramTagger
>>> from nltk.corpus import treebank
>>> training 1= treebank.tagged sents()[:7000]
>>> bigramtagger=BigramTagger(training 1)
>>> treebank.sents()[0]
['Pierre', 'Vinken', ',', '61', 'years', 'old', ',', 'will', 'join',
'the', 'board', 'as', 'a', 'nonexecutive', 'director', 'Nov.', '29',
'.']
>>> bigramtagger.tag(treebank.sents()[0])
[('Pierre', 'NNP'), ('Vinken', 'NNP'), (',', ','), ('61', 'CD'),
('years', 'NNS'), ('old', 'JJ'), (',', ','), ('will', 'MD'),
('join', 'VB'), ('the', 'DT'), ('board', 'NN'), ('as', 'IN'), ('a',
'DT'), ('nonexecutive', 'JJ'), ('director', 'NN'), ('Nov.', 'NNP'),
('29', 'CD'), ('.', '.')]
>>> testing 1 = treebank.tagged sents()[2000:]
>>> bigramtagger.evaluate(testing 1)
0.922942709936983
```

Let's see another code for BigramTagger and TrigramTagger:

```
>>> import nltk
>>> from nltk.tag import BigramTagger, TrigramTagger
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> bigramtag = BigramTagger(training)
>>> bigramtag.evaluate(testing)
0.9190426339881356
>>> trigramtag = TrigramTagger(training)
>>> trigramtag.evaluate(testing)
0.9101956195989079
```

NgramTagger can be used to generate a tagger for *n* greater than three as well. Let's see the following code in NLTK, which develops QuadgramTagger:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> from nltk import NgramTagger
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> quadgramtag = NgramTagger(4, training)
>>> quadgramtag.evaluate(testing)
0.9429767842847466
```

The AffixTagger is also a ContextTagger in that makes use of a prefix or suffix as the contextual information.

Let's see the following code, which uses AffixTagger:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> from nltk.tag import AffixTagger
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> affixtag = AffixTagger(training)
>>> affixtag.evaluate(testing)
0.29043249789601167
```

Let's see the following code, which learns the use of four character prefixes:

```
>>> import nltk
>>> from nltk.tag import AffixTagger
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> prefixtag = AffixTagger(training, affix_length=4)
>>> prefixtag.evaluate(testing)
0.21103516226368618
```

Consider the following code, which learns the use of three character suffixes:

```
>>> import nltk
>>> from nltk.tag import AffixTagger
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> suffixtag = AffixTagger(training, affix_length=-3)
>>> suffixtag.evaluate(testing)
0.29043249789601167
```

Consider the following code in NLTK, which that combines many affix taggers in the back-off chain:

```
>>> import nltk
>>> from nltk.tag import AffixTagger
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> prefixtagger=AffixTagger(training,affix_length=4)
>>> prefixtagger.evaluate(testing)
0.21103516226368618
>>>
prefixtagger3=AffixTagger(training,affix_length=3,backoff=prefixtagger
r)
>>> prefixtagger3.evaluate(testing)
```

```
0.25906767658107027
>>>
suffixtagger3=AffixTagger(training,affix_length=-3,backoff=prefixtagg
er3)
>>> suffixtagger3.evaluate(testing)
0.2939630929654946
>>>
suffixtagger4=AffixTagger(training,affix_length=-4,backoff=suffixtagg
er3)
>>> suffixtagger4.evaluate(testing)
0.3316090892296324
```

The **TnT** is **Trigrams n Tags**. **TnT** is a statistical-based tagger that is based on the second order Markov models.

Let's see the code in NLTK for TnT:

```
>>> import nltk
>>> from nltk.tag import tnt
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> tnt_tagger=tnt.TnT()
>>> tnt_tagger.train(training)
>>> tnt_tagger.evaluate(testing)
0.9882176652913768
```

TnT computes ConditionalFreqDist and internalFreqDist from the training text. These instances are used to compute unigrams, bigrams, and trigrams. In order to choose the best tag, TnT uses the ngram model.

Consider the following code of a DefaultTagger in which, if the value of the unknown tagger is provided explicitly, then TRAINED will be set to TRUE:

```
>>> import nltk
>>> from nltk.tag import DefaultTagger
>>> from nltk.tag import tnt
>>> from nltk.corpus import treebank
>>> testing = treebank.tagged_sents()[2000:]
>>> training= treebank.tagged_sents()[:7000]
>>> tnt_tagger=tnt.TnT()
>>> unknown=DefaultTagger('NN')
>>> tagger_tnt=tnt.TnT(unk=unknown,Trained=True)
>>> tnt_tagger.train(training)
>>> tnt_tagger.evaluate(testing)
0.988238192006897
```

Developing a chunker using pos-tagged corpora

Chunking is the process used to perform entity detection. It is used for the segmentation and labeling of multiple sequences of tokens in a sentence.

To design a chunker, a chunk grammar should be defined. A chunk grammar holds the rules of how chunking should be done.

Let's consider the example that performs Noun Phrase Chunking by forming the chunk rules:

```
>>> import nltk
>>> sent=[("A","DT"),("wise", "JJ"), ("small", "JJ"),("girl", "NN"),
("of", "IN"), ("village", "N"), ("became", "VBD"), ("leader", "NN")]
>>> sent=[("A","DT"),("wise", "JJ"), ("small", "JJ"),("girl", "NN"),
("of", "IN"), ("village", "NN"),
                                 ("became", "VBD"), ("leader",
"NN")]
>>> grammar = "NP: {<DT>?<JJ>*<NN><IN>?<NN>*}"
>>> find = nltk.RegexpParser(grammar)
>>> res = find.parse(sent)
>>> print(res)
(S
  (NP A/DT wise/JJ small/JJ girl/NN of/IN village/NN)
 became/VBD
  (NP leader/NN))
>>> res.draw()
```

The following parse tree is generated:



Here, the chunk rule for **Noun Phrase** is defined by keeping **DT** as optional, any number of **JJ**, followed by **NN**, optional **IN**, and any number of **NN**.

Consider another example in which the Noun Phrase chunk rule is created with any number of nouns:

```
>>> import nltk
>>>
noun1=[("financial","NN"),("year","NN"),("account","NN"),("summary","
NN")]
```

```
>>> gram="NP:{<NN>+}"
>>> find = nltk.RegexpParser(gram)
>>> print(find.parse(noun1))
(S (NP financial/NN year/NN account/NN summary/NN))
>>> x=find.parse(noun1)
>>> x.draw()
```

The output in the form of the parse tree is given here:



Chunking is the process in which some of the parts of a chunk are eliminated. Either an entire chunk may be used, a part of the chunk may be used from the middle and the remaining parts are eliminated, or a part of chunk may be used either from the beginning of the chunk or from the end of the chunk and the remaining part of the chunk is removed.

Consider the code for UnigramChunker in NLTK, which has been developed to perform chunking and parsing:

Consider the following code, which can be used to estimate the accuracy of the chunker after it is trained:

import nltk.corpus, nltk.tag def ubt conll chunk accuracy(train sents, test sents): chunks train =conll tag chunks(training) chunks test =conll tag chunks(testing) chunker1 =nltk.tag.UnigramTagger(chunks train) print 'u:', nltk.tag.accuracy(chunker1, chunks test) chunker2 =nltk.tag.BigramTagger(chunks train, backoff=chunker1) print 'ub:', nltk.tag.accuracy(chunker2, chunks test) chunker3 =nltk.tag.TrigramTagger(chunks train, backoff=chunker2) print 'ubt:', nltk.tag.accuracy(chunker3, chunks test) chunker4 =nltk.tag.TrigramTagger(chunks train, backoff=chunker1) print 'ut:', nltk.tag.accuracy(chunker4, chunks test) chunker5 =nltk.tag.BigramTagger(chunks train, backoff=chunker4) print 'utb:', nltk.tag.accuracy(chunker5, chunks test) # accuracy test for conll chunking conll train =nltk.corpus.conll2000.chunked sents('train.txt') conll test =nltk.corpus.conll2000.chunked sents('test.txt') ubt conll chunk accuracy(conll train, conll test)

```
# accuracy test for treebank chunking
treebank_sents =nltk.corpus.treebank_chunk.chunked_sents()
ubt_conll_chunk_accuracy(treebank_sents[:2000],
treebank_sents[2000:])
```

Summary

In this chapter, we have discussed POS tagging, different POS taggers, and the approaches used for POS tagging. You have also learned about statistical modeling involving the n-gram approach, and have developed a chunker using POS tags information.

In the following chapter, we will discuss Treebank construction, CFG construction, different parsing algorithms, and so on.

Chapter 5. Parsing – Analyzing Training Data

Parsing, also referred to as syntactic analysis, is one of the tasks in NLP. It is defined as the process of finding whether a character sequence, written in natural language, is in accordance with the rules defined in formal grammar. It is the process of breaking the sentences into words or phrase sequences and providing them a particular component category (noun, verb, preposition, and so on).

This chapter will include the following topics:

- Treebank construction
- Extracting Context-free Grammar (CFG) rules from Treebank
- Creating a probabilistic Context-free Grammar from CFG
- CYK chart parsing algorithm
- Earley chart parsing algorithm

Introducing parsing

Parsing is one of the steps involved in NLP. It is defined as the process of determining the part-of-speech category for an individual component in a sentence and analyzing whether a given sentence is in accordance with grammar rules or not. The term parsing has been derived from the Latin word *pars* (oration is) which means part-of-speech.

Consider an example—*Ram bought a book.* This sentence is grammatically correct. But, instead of this sentence, if we have a sentence Book bought a Ram, then by adding the semantic information to the parse tree so constructed, we can conclude that although the sentence is grammatically correct, it is not semantically correct. So, the generation of a parse tree is followed by adding meaning to it as well. A parser is a software that accepts an input text and constructs a parse tree or a syntax tree. Parsing may be divided into two categories Top-down Parsing and Bottom-up Parsing. In Top-down Parsing, we begin from the start symbol and continue till we reach individual components. Some of the Top-down Parsers include the Recursive Descent Parser, LL Parser, and Earley Parser. In Bottom-up Parsing, we start from individual components and continue till we reach the start symbol. Some Bottom-up Parsers include the Operator-precedence parser, Simple precedence parser, Simple LR Parser, LALR Parser, Canonical LR (*LR(1)*) Parser, GLR Parser, CYK or (alternatively CKY) Parser, Recursive ascent parser, and Shiftreduce parser.

The nltk.parse.api.ParserI class is defined in NLTK. This class is used to obtain parses or syntactic structures for a given sentence. Parsers can be used to obtain syntactic structures, discourse structures, and morphological trees.

Chart parsing follows the dynamic programming approach. In this, once some results are obtained, these may be treated as the intermediate results and may be reused to obtain future results. Unlike in Top-down parsing, the same task is not performed again and again.

Treebank construction

The nltk.corpus.package consists of a number of corpus readerclasses that can be used to obtain the contents of various corpora.

Treebank corpus can also be accessed from nltk.corpus. Identifiers for files can be obtained using fileids():

```
>>> import nltk
>>> import nltk.corpus
>>> print(str(nltk.corpus.treebank).replace('\\\\','/'))
<BracketParseCorpusReader in 'C:/nltk data/corpora/treebank/</pre>
combined'>
>>> nltk.corpus.treebank.fileids()
                 'wsj 0002.mrg',
                                   'wsj 0003.mrg',
                                                    'wsj 0004.mrg',
['wsj 0001.mrg',
'wsj 0005.mrg', 'wsj 0006.mrg',
                                  'wsj 0007.mrg',
                                                   'wsj 0008.mrg',
'wsj 0009.mrg', 'wsj 0010.mrg',
                                  'wsj 0011.mrg',
                                                   'wsj 0012.mrg',
'wsj 0013.mrg',
                 'wsj 0014.mrg',
                                  'wsj 0015.mrg',
                                                   'wsj 0016.mrg',
'wsj 0017.mrg',
                'wsj 0018.mrg',
                                  'wsj 0019.mrg',
                                                   'wsj 0020.mrg',
'wsj 0021.mrg',
                'wsj 0022.mrg',
                                  'wsj 0023.mrg',
                                                   'wsj 0024.mrg',
'wsj 0025.mrg',
                 'wsj 0026.mrg',
                                  'wsj 0027.mrg',
                                                   'wsj 0028.mrg',
'wsj 0029.mrg', 'wsj 0030.mrg',
                                  'wsj 0031.mrg',
                                                   'wsj 0032.
mrg', 'wsj 0033.mrg', 'wsj 0034.mrg', 'wsj 0035.mrg',
'wsj 0036.mrg',
                 'wsj 0037.mrg',
                                  'wsj 0038.mrg',
                                                   'wsj 0039.mrg',
'wsj 0040.mrg',
                 'wsj 0041.mrg',
                                  'wsj 0042.mrg',
                                                   'wsj 0043.mrg',
'wsj 0044.mrg',
                 'wsj 0045.mrg',
                                  'wsj 0046.mrg',
                                                   'wsj 0047.mrg',
'wsj 0048.mrg',
                 'wsj 0049.mrg',
                                  'wsj 0050.mrg',
                                                   'wsj 0051.mrg',
'wsj 0052.mrg',
                 'wsj 0053.mrg',
                                  'wsj 0054.mrg',
                                                   'wsj 0055.mrg',
'wsj 0056.mrg',
                 'wsj 0057.mrg',
                                  'wsj 0058.mrg',
                                                   'wsj 0059.mrg',
'wsj 0060.mrg',
                 'wsj 0061.mrg',
                                  'wsj 0062.mrg',
                                                   'wsj 0063.mrg',
'wsj 0064.mrg',
                 'wsj 0065.mrg',
                                  'wsj 0066.mrg',
                                                   'wsj 0067.mrg',
'wsj 0068.mrg',
                 'wsj 0069.mrg',
                                  'wsj 0070.mrg',
                                                   'wsj 0071.mrg',
'wsj 0072.mrg',
                 'wsj 0073.mrg',
                                  'wsj 0074.mrg',
                                                   'wsj 0075.mrg',
'wsj 0076.mrg',
                 'wsj 0077.mrg',
                                  'wsj 0078.mrg',
                                                   'wsj 0079.mrg',
'wsj 0080.mrg',
                 'wsj 0081.mrg',
                                  'wsj 0082.mrg',
                                                   'wsj 0083.mrg',
'wsj 0084.mrg',
                 'wsj 0085.mrg',
                                  'wsj 0086.mrg',
                                                   'wsj 0087.mrg',
'wsj 0088.mrg',
                 'wsj 0089.mrg',
                                  'wsj 0090.mrg',
                                                   'wsj 0091.mrg',
'wsj 0092.mrg',
                 'wsj 0093.mrg',
                                  'wsj 0094.mrg',
                                                   'wsj 0095.mrg',
'wsj 0096.mrg',
                 'wsj 0097.mrg',
                                  'wsj 0098.mrg',
                                                   'wsj 0099.mrg',
'wsj 0100.mrg',
                 'wsj 0101.mrg',
                                  'wsj 0102.mrg',
                                                   'wsj 0103.mrg',
'wsj 0104.mrg',
                 'wsj 0105.mrg',
                                  'wsj 0106.mrg',
                                                   'wsj 0107.mrg',
'wsj 0108.mrg',
                 'wsj 0109.mrg',
                                  'wsj 0110.mrg',
                                                   'wsj 0111.mrg',
'wsj 0112.mrg',
                 'wsj 0113.mrg',
                                  'wsj 0114.mrg',
                                                   'wsj 0115.mrg',
'wsj 0116.mrg',
                 'wsj 0117.mrg',
                                  'wsj 0118.mrg',
                                                   'wsj 0119.mrg',
'wsj 0120.mrg',
                 'wsj 0121.mrg',
                                  'wsj 0122.mrg',
                                                   'wsj 0123.mrg',
'wsj 0124.mrg',
                 'wsj 0125.mrg',
                                  'wsj 0126.mrg',
                                                   'wsj 0127.mrg',
```
```
'wsj 0128.mrg', 'wsj 0129.mrg', 'wsj 0130.mrg', 'wsj 0131.mrg',
'wsj 0132.mrg', 'wsj 0133.mrg', 'wsj 0134.mrg', 'wsj_0135.mrg',
'wsj 0136.mrg', 'wsj 0137.mrg', 'wsj 0138.mrg', 'wsj 0139.mrg',
'wsj_0140.mrg', 'wsj_0141.mrg', 'wsj_0142.mrg', 'wsj_0143.mrg',
'wsj 0144.mrg', 'wsj 0145.mrg', 'wsj 0146.mrg', 'wsj 0147.mrg',
'wsj 0148.mrg', 'wsj 0149.mrg', 'wsj 0150.mrg', 'wsj 0151.mrg',
'wsj_0152.mrg', 'wsj_0153.mrg', 'wsj_0154.mrg', 'wsj_0155.mrg',
'wsj 0156.mrg', 'wsj 0157.mrg', 'wsj 0158.mrg', 'wsj 0159.mrg',
'wsj 0160.mrg', 'wsj 0161.mrg', 'wsj 0162.mrg', 'wsj 0163.mrg',
'wsj 0164.mrg', 'wsj 0165.mrg', 'wsj 0166.mrg', 'wsj 0167.mrg',
'wsj 0168.mrg', 'wsj 0169.mrg', 'wsj 0170.mrg', 'wsj 0171.mrg',
'wsj 0172.mrg', 'wsj 0173.mrg', 'wsj 0174.mrg', 'wsj 0175.mrg',
'wsj 0176.mrg', 'wsj 0177.mrg', 'wsj 0178.mrg', 'wsj 0179.mrg',
'wsj 0180.mrg', 'wsj 0181.mrg', 'wsj 0182.mrg', 'wsj 0183.mrg',
'wsj_0184.mrg', 'wsj_0185.mrg', 'wsj_0186.mrg', 'wsj_0187.mrg',
'wsj 0188.mrg', 'wsj 0189.mrg', 'wsj 0190.mrg', 'wsj 0191.mrg',
'wsj 0192.mrg', 'wsj 0193.mrg', 'wsj 0194.mrg', 'wsj 0195.mrg',
'wsj 0196.mrg', 'wsj 0197.mrg', 'wsj 0198.mrg', 'wsj 0199.mrg']
>>> from nltk.corpus import treebank
>>> print(treebank.words('wsj 0007.mrg'))
['McDermott', 'International', 'Inc.', 'said', '0', ...]
>>> print(treebank.tagged words('wsj 0007.mrg'))
[('McDermott', 'NNP'), ('International', 'NNP'), ...]
```

Let's see the code in NLTK for accessing the Penn Treebank Corpus, which uses the Treebank Corpus Reader contained in the corpus module:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> print(treebank.parsed sents('wsj 0007.mrg')[2])
(S
  (NP-SBJ
    (NP (NNP Bailey) (NNP Controls))
    (, ,)
    (VP
      (VBN based)
      (NP (-NONE- *))
      (PP-LOC-CLR
        (IN in)
        (NP (NP (NNP Wickliffe)) (, ,) (NP (NNP Ohio)))))
    (, ,))
  (VP
    (VBZ makes)
    (NP
      (JJ computerized)
      (JJ industrial)
      (NNS controls)
```

```
(NNS systems)))
(. .))
>>> import nltk
>>> from nltk.corpus import treebank_chunk
>>> treebank_chunk.chunked_sents()[1]
Tree('S', [Tree('NP', [('Mr.', 'NNP'), ('Vinken', 'NNP')]), ('is',
'VBZ'), Tree('NP', [('chairman', 'NN')]), ('of', 'IN'), Tree('NP',
[('Elsevier', 'NNP'), ('N.V.', 'NNP')]), (',', ','), Tree('NP',
[('the', 'DT'), ('Dutch', 'NNP'), ('publishing', 'VBG'), ('group',
'NN')]), ('.', '.')])
>>> treebank chunk.chunked sents()[1].draw()
```

The preceding code obtains the following parse tree:



```
>>> import nltk
>>> from nltk.corpus import treebank chunk
>>> treebank chunk.chunked sents()[1].leaves()
[('Mr.', 'NNP'), ('Vinken', 'NNP'), ('is', 'VBZ'), ('chairman',
'NN'), ('of', 'IN'), ('Elsevier', 'NNP'), ('N.V.', 'NNP'), (',',
','), ('the', 'DT'), ('Dutch', 'NNP'), ('publishing', 'VBG'),
('group', 'NN'), ('.', '.')]
>>> treebank chunk.chunked sents()[1].pos()
[(('Mr.', 'NNP'), 'NP'), (('Vinken', 'NNP'), 'NP'), (('is', 'VBZ'),
'S'), (('chairman', 'NN'), 'NP'), (('of', 'IN'), 'S'), (('Elsevier',
'NNP'), 'NP'), (('N.V.', 'NNP'), 'NP'), ((',', ','), 'S'), (('the',
'DT'), 'NP'), (('Dutch', 'NNP'), 'NP'), (('publishing', 'VBG'),
'NP'), (('group', 'NN'), 'NP'), (('.', '.'), 'S')]
>>> treebank chunk.chunked sents()[1].productions()
[S -> NP ('is', 'VBZ') NP ('of', 'IN') NP (',', ',') NP ('.', '.'),
NP -> ('Mr.', 'NNP') ('Vinken', 'NNP'), NP -> ('chairman', 'NN'), NP
-> ('Elsevier', 'NNP') ('N.V.', 'NNP'), NP -> ('the', 'DT')
('Dutch', 'NNP') ('publishing', 'VBG') ('group', 'NN')]
```

Part of speech annotations are included in the tagged words () method:

```
>>> nltk.corpus.treebank.tagged_words()
[('Pierre', 'NNP'), ('Vinken', 'NNP'), (',', ','), ...]
```

The type of tags and the count of these tags used in the Penn Treebank Corpus are shown here:

#	16
\$	724
,	4,886
-LRB-	120
-NONE-	6,592
-RRB-	126
	384
•	563
``	712
CC	2,265
CD	3,546
DT	8,165
EX	88
FW	4
IN	9,857
JJ	5,834

JJR	381
JJS	182
LS	13
MD	927
NN	13,166
NNP	9,410
NNPS	244
NNS	6,047
PDT	27
POS	824
PRP	1,716
PRP\$	766
RB	2,822
RBR	136
RBS	35
RP	216
SYM	1

ТО	2,179
UH	3
VB	2,554
VBD	3,043
VBG	1,460
VBN	2,134
VBP	1,321
VBZ	2,125
WDT	445
WP	241
WP\$	14

The tags and frequency can be obtained from the following code:

```
>>> import nltk
>>> from nltk.probability import FreqDist
>>> from nltk.corpus import treebank
>>> fd = FreqDist()
>>> fd.items()
dict_items([])
```

The preceding code obtains a list of tags and the frequency of each tag in the Treebank corpus.

Let's see the code in NLTK for accessing the Sinica Treebank Corpus:

```
>>> import nltk
>>> from nltk.corpus import sinica_treebank
>>> print(sinica_treebank.sents())
[['?'], ['??'], ['??', '?', '?', '??', '???', '??'], ...]
```

```
>>> sinica_treebank.parsed_sents()[27]
Tree('S', [Tree('NP', [Tree('N.?', [Tree('Nhaa', ['?']),
Tree('DE', ['?'])]), Tree('Ncb', ['??'])]), Tree('Ncda', ['?'])]),
Tree('Dd', ['??']), Tree('DM', ['??']), Tree('VH11', ['??'])])
```

Extracting Context Free Grammar (CFG) rules from Treebank

CFG was defined for natural languages in 1957 by Noam Chomsky. A CFG consists of the following components:

- A set of non terminal nodes (N)
- A set of terminal nodes (*T*)
- Start symbol (*S*)
- A set of production rules (*P*) of the form:

 $A \rightarrow a$

CFG rules are of two types—Phrase structure rules and Sentence structure rules.

A Phrase Structure Rule can be defined as follows— $A \rightarrow a$, where $A \hat{I} N$ and a consists of Terminals and Non terminals.

In Sentence level Construction of CFG, there are four structures:

- Declarative structure: Deals with declarative sentences (the subject is followed by a predicate).
- **Imperative structure**: Deals with imperative sentences, commands, or suggestions (sentences begin with a verb phrase and do not include a subject).
- Yes-No structure: Deals with question-answering sentences. The answers to these questions are either *yes* or *no*.
- Wh-question structure: Deals with question-answering sentences. Questions that begin following *Wh* words (Who, What, How, When, Where, Why, and Which).

General CFG rules are summarized here:

- $S \rightarrow NP VP$
- $S \rightarrow VP$
- $S \rightarrow Aux NP VP$
- $S \rightarrow Wh NP VP$
- $S \rightarrow Wh NP Aux NP VP$
- $NP \rightarrow (Det) (AP) Nom (PP)$
- $VP \rightarrow Verb$ (NP) (NP) (PP)*
- $VP \rightarrow Verb S$
- $PP \rightarrow Prep$ (NP)
- $AP \rightarrow (Adv) Adj (PP)$

Consider an example that depicts the use of Context-free Grammar rules in NLTK:

```
>>> import nltk
>>> from nltk import Nonterminal, nonterminals, Production, CFG
>>> nonterminal1 = Nonterminal('NP')
>>> nonterminal2 = Nonterminal('VP')
```

```
>>> nonterminal3 = Nonterminal('PP')
>>> nonterminal1.symbol()
'NP'
>>> nonterminal2.symbol()
'VP'
>>> nonterminal3.symbol()
'PP'
>>> nonterminal1==nonterminal2
False
>>> nonterminal2==nonterminal3
False
>>> nonterminal1==nonterminal3
False
>>> S, NP, VP, PP = nonterminals('S, NP, VP, PP')
>>> N, V, P, DT = nonterminals('N, V, P, DT')
>>> production1 = Production(S, [NP, VP])
>>> production2 = Production(NP, [DT, NP])
>>> production3 = Production(VP, [V, NP, NP, PP])
>>> production1.lhs()
S
>>> production1.rhs()
(NP, VP)
>>> production3.lhs()
VP
>>> production3.rhs()
(V, NP, NP, PP)
>>> production3 == Production(VP, [V,NP,NP,PP])
True
>>> production2 == production3
False
```

An example for accessing ATIS grammar in NLTK is as follows:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> gram1
<Grammar with 5517 productions>
```

Extract the testing sentences from ATIS as follows:

```
>>> import nltk
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> len(sent)
98
>>> testingsent=sent[25]
```

```
>>> testingsent[1]
11
>>> testingsent[0]
['list', 'those', 'flights', 'that', 'stop', 'over', 'in', 'salt',
'lake', 'city', '.']
>>> sent=testingsent[0]
```

Bottom-up parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser1 = nltk.parse.BottomUpChartParser(gram1)
>>> chart1 = parser1.chart_parse(sent)
>>> print((chart1.num_edges()))
13454
>>> print((len(list(chart1.parses(gram1.start())))))
11
```

Bottom-up, Left Corner parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser2 = nltk.parse.BottomUpLeftCornerChartParser(gram1)
>>> chart2 = parser2.chart_parse(sent)
>>> print((chart2.num_edges()))
8781
>>> print((len(list(chart2.parses(gram1.start())))))
11
```

Left Corner parsing with a Bottom-up filter:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
```

```
>>> sent=testingsent[0]
>>> parser3 = nltk.parse.LeftCornerChartParser(gram1)
>>> chart3 = parser3.chart_parse(sent)
>>> print((chart3.num_edges()))
1280
>>> print((len(list(chart3.parses(gram1.start())))))
11
```

Top-down parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>>parser4 = nltk.parse.TopDownChartParser(gram1)
>>> chart4 = parser4.chart_parse(sent)
>>> print((chart4.num_edges()))
37763
>>> print((len(list(chart4.parses(gram1.start())))))
11
```

Incremental Bottom-up parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser5 = nltk.parse.IncrementalBottomUpChartParser(gram1)
>>> chart5 = parser5.chart_parse(sent)
>>> print((chart5.num_edges()))
13454
>>> print((len(list(chart5.parses(gram1.start())))))
11
```

Incremental Bottom-up, Left Corner parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract test sentences(sent)
```

```
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser6 =
nltk.parse.IncrementalBottomUpLeftCornerChartParser(gram1)
>>> chart6 = parser6.chart_parse(sent)
>>> print((chart6.num_edges()))
8781
>>> print((len(list(chart6.parses(gram1.start())))))
11
```

Incremental Left Corner parsing with a Bottom-up filter:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser7 = nltk.parse.IncrementalLeftCornerChartParser(gram1)
>>> chart7 = parser7.chart_parse(sent)
>>> print((chart7.num_edges()))
1280
>>> print((len(list(chart7.parses(gram1.start())))))
11
```

Incremental Top-down parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser8 = nltk.parse.IncrementalTopDownChartParser(gram1)
>>> chart8 = parser8.chart_parse(sent)
>>> print((chart8.num_edges()))
37763
>>> print((len(list(chart8.parses(gram1.start())))))
11
```

Earley parsing:

```
>>> import nltk
>>> gram1 = nltk.data.load('grammars/large_grammars/atis.cfg')
>>> sent = nltk.data.load('grammars/large_grammars/
```

```
atis_sentences.txt')
>>> sent = nltk.parse.util.extract_test_sentences(sent)
>>> testingsent=sent[25]
>>> sent=testingsent[0]
>>> parser9 = nltk.parse.EarleyChartParser(gram1)
>>> chart9 = parser9.chart_parse(sent)
>>> print((chart9.num_edges()))
37763
>>> print((len(list(chart9.parses(gram1.start())))))
11
```

Creating a probabilistic Context Free Grammar from CFG

In **Probabilistic Context-free Grammar (PCFG)**, probabilities are attached to all the production rules present in CFG. The sum of these probabilities is 1. It generates the same parse structures as CFG, but it also assigns a probability to each parse tree. The probability of a parsed tree is obtained by taking the product of probabilities of all the production rules used in building the tree.

Let's see the following code in NLTK, that illustrates the formation of rules in PCFG:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> from itertools import islice
>>> from nltk.grammar import PCFG, induce pcfg, toy pcfg1, toy pcfg2
>>> gram2 = PCFG.from string("""
A -> B B [.3] | C B C [.7]
B -> B D [.5] | C [.5]
C -> 'a' [.1] | 'b' [0.9]
D -> 'b' [1.0]
""")
>>> prod1 = gram2.productions()[0]
>>> prod1
A -> B B [0.3]
>>> prod2 = gram2.productions()[1]
>>> prod2
A -> C B C [0.7]
>>> prod2.lhs()
А
>>> prod2.rhs()
(C, B, C)
>>> print((prod2.prob()))
0.7
>>> gram2.start()
Α
>>> gram2.productions()
[A -> B B [0.3], A -> C B C [0.7], B -> B D [0.5], B -> C [0.5], C
-> 'a' [0.1], C -> 'b' [0.9], D -> 'b' [1.0]]
```

Let's see the code in NLTK that illustrates Probabilistic Chart Parsing:

```
>>> import nltk
>>> from nltk.corpus import treebank
>>> from itertools import islice
>>> from nltk.grammar import PCFG, induce_pcfg, toy_pcfg1, toy_pcfg2
>>> tokens = "Jack told Bob to bring my cookie".split()
```

```
>>> grammar = toy pcfg2
>>> print(grammar)
Grammar with 23 productions (start state = S)
    S -> NP VP [1.0]
    VP -> V NP [0.59]
    VP -> V [0.4]
    VP -> VP PP [0.01]
    NP -> Det N [0.41]
    NP -> Name [0.28]
    NP -> NP PP [0.31]
    PP -> P NP [1.0]
    V -> 'saw' [0.21]
    V -> 'ate' [0.51]
    V -> 'ran' [0.28]
    N -> 'boy' [0.11]
    N -> 'cookie' [0.12]
    N -> 'table' [0.13]
    N \rightarrow 'telescope' [0.14]
    N -> 'hill' [0.5]
    Name -> 'Jack' [0.52]
    Name -> 'Bob' [0.48]
    P -> 'with' [0.61]
    P -> 'under' [0.39]
    Det -> 'the' [0.41]
    Det -> 'a' [0.31]
    Det -> 'my' [0.28]
```

CYK chart parsing algorithm

The drawback of Recursive Descent Parsing is that it causes the Left Recursion Problem and is very complex. So, CYK chart parsing was introduced. It uses the Dynamic Programming approach. CYK is one of the simplest chart parsing algorithms. The CYK algorithm is capable of constructing a chart in O(n3) time. Both CYK and Earley are Bottom-up chart parsing algorithms. But, the Earley algorithm also makes use of Top-down predictions when invalid parses are constructed.

Consider the following example of CYK parsing:

```
tok = ["the", "kids", "opened", "the", "box", "on", "the", "floor"]
gram = nltk.parse_cfg("""
S -> NP VP
NP -> Det N | NP PP
VP -> V NP | VP PP
PP -> P NP
Det -> 'the'
N -> 'kids' | 'box' | 'floor'
V -> 'opened' P -> 'on'
""")
```

Consider the following code to construct the initializing table:

```
def init_nfst(tok, gram):
numtokens1 = len(tok)
  # fill w/ dots
nfst = [["." for i in range(numtokens1+1)] !!!!!!! for j in
range(numtokens1+1)]
  # fill in diagonal
for i in range(numtokens1):
prod= gram.productions(rhs=tok[i])
nfst[i][i+1] = prod[0].lhs()
return nfst
```

Consider the following code to fill in the table:

```
def complete_nfst(nfst, tok, trace=False):
index1 = {} for prod in gram.productions():
#make lookup reverse
index1[prod.rhs()] = prod.lhs()
numtokens1 = len(tok) for span in range(2, numtokens1+1):
for start in range(numtokens1+1-span):
#go down towards diagonal
end1 = start1 + span for mid in range(start1+1, end1):
nt1, nt2 = nfst[start1][mid001], nfst[mid001][end1]
if (nt1,nt2) in index1:
```

```
if trace:
print "[%s] %3s [%s] %3s [%s] ==> [%s] %3s [%s]" % \ (start, nt1,
mid001, nt2, end1, start1, index[(nt1,nt2)], end) nfst[start1][end1]
= index[(nt1,nt2)]
return nfst
```

Following is the code in Python for constructing the display table:

```
def display(wfst, tok):
print '\nWFST ' + ' '.join([("%-4d" % i) for i in range(1,
len(wfst))])
for i in range(len(wfst)-1):
print "%d " % i,
for j in range(1, len(wfst)):
print "%-4s" % wfst[i][j],
print
```

The result can be obtained from the following code:

```
tok = ["the", "kids", "opened", "the", "box", "on", "the", "floor"]
res1 = init_wfst(tok, gram)
display(res1, tok)
res2 = complete_wfst(res1,tok)
display(res2, tok)
```

Earley chart parsing algorithm

Earley algorithm was given by Earley in 1970. This algorithm is similar to Top-down parsing. It can handle left-recursion, and it doesn't need CNF. It fills in a chart in the left to right manner.

Consider an example that illustrates parsing using the Earley chart parser:

```
>>> import nltk
>>> nltk.parse.earleychart.demo(print times=False, trace=1,sent='I
saw a dog', numparses=2)
* Sentence:
I saw a dog
['I', 'saw', 'a', 'dog']
    . uog .|
-----] . . .| [0:1] 'I'
[-----] . .| [1:2] 'sa
. [-----] .| [2:3] 'a'
. . .
  I. saw. a. dog.|
|.
| [ ----- ]
|.
                               .| [1:2] 'saw'
|.
               . [-----]| [3:4] 'dog'
|.
              •
                       |>
        •
              .
.
.
.
       •
|>
|>
                               .| [0:0] NP -> * Det Noun
                               .| [0:0] NP -> * 'I'
|> .
|[-----]
                        •
                        •
                             .| [0:1] NP -> 'I' *
              | [---->
                               .| [0:1] S -> NP * VP
| [---->
|. >
       >
|.
      > .
> .
[-----]
|.
|.
|.
       [---->
|.
        [----]
|.
| [ ----- ]
  [---->
|.
        •
|.
|.
       •
|.
        •
                             .| [2:3] Det -> 'a' *
.| [2:3] NP -> Det * Noun
       •
               [-----]
|.
                [---->
|.
                . | [3:3] Noun -> * 'dog'
. [-----]| [3:4] Noun -> 'dog' *
|.
|.
               [-----]| [2:4] NP -> Det Noun *
|.
      [-----]| [1:4] VP -> Verb NP *
|.
                [----->| [2:4] NP -> NP * PP
|.
        •
```

[====================================	=================]	[0:4]	S	->	NP	VP	› *
.	[>	[1:4]	VP	->	VP	*	ΡP

Consider an example that illustrates parsing using the Chart parser in NLTK:

```
>>> import nltk
>>> nltk.parse.chart.demo(2, print times=False, trace=1,sent='John
saw a dog', numparses=1)
* Sentence:
John saw a dog
['John', 'saw', 'a', 'dog']
* Strategy: Bottom-up
    John . saw . a . dog
|.
                                 • |
        --] . .
[-----] .
. [-----]
                                 .| [0:1] 'John'
|[----]
                                 .| [1:2] 'saw'
|.
                                  .| [2:3] 'a'
|.
                     [-----]| [3:4] 'dog'
|.
                                 .| [0:0] NP -> * 'John'
|>
                 •
                          •
                                 .| [0:1] NP -> 'John' *
| [----]
                               .| [0:0] S -> * NP VP
|>
               •
                                 .| [0:0] NP -> * NP PP
|>
                •
                                 .| [0:1] S -> NP * VP
| [----->
                •
                              .| [0:1] NP -> NP * PP
               •
| [---->
                                 .| [1:1] Verb -> * 'saw'
|.
        >
                               .| [1:2] Verb -> 'saw' *
.| [1:1] VP -> * Verb NP
                          •
•
|.
        [-----]
        >
|.
                       .
.
.
        >
                                 .| [1:1] VP -> * Verb
|.
        [---->
                                 .| [1:2] VP -> Verb * NP
|.
        [-----]
                                 .| [1:2] VP -> Verb *
|.
                        .
.
.
                                 .| [1:1] VP -> * VP PP
|.
                                 .| [0:2] S -> NP VP *
| [ -----]
                                 .| [1:2] VP -> VP * PP
|.
        [---->
                > .
[-----]
                                 .| [2:2] Det -> * 'a'
|.
                               .| [2:3] Det -> 'a' *
|.
                               .| [2:2] NP -> * Det Noun
.| [2:3] NP -> Det * Noun
                > .
|.
|.
                 [---->
                         > .| [3:3] Noun -> * 'dog'
|.
                         [-----]| [3:4] Noun -> 'dog' *
|.
               [-----]| [2:4] NP -> Det Noun *
|.
                >
                                 .| [2:2] S -> * NP VP
|.
                >
                              .| [2:2] NP -> * NP PP
|.
        [-----]| [1:4] VP -> Verb NP *
|.
                [----->| [2:4] S -> NP * VP
|.
                 [----->| [2:4] NP -> NP * PP
|[======]| [0:4] S -> NP VP *
```

```
|. [----->| [1:4] VP -> VP * PP
Nr edges in chart: 33
(S (NP John) (VP (Verb saw) (NP (Det a) (Noun dog))))
```

Consider an example that illustrates parsing using the Stepping Chart parser in NLTK:

```
>>> import nltk
>>> nltk.parse.chart.demo(5, print times=False, trace=1,sent='John
saw a dog', numparses=2)
* Sentence:
John saw a dog
['John', 'saw', 'a', 'dog']
* Strategy: Stepping (top-down vs bottom-up)
*** SWITCH TO TOP DOWN
                       . .| [0:1] 'John'
|[----]
       [-----]
                                .| [1:2] 'saw'
|.
           [-----] .| [2:3] 'a'
|.
        •
                       [-----]| [3:4] 'dog'
                •
|.
                        . .| [0:0] S -> * NP VP
|>
        •
                •
                                .| [0:0] NP -> * NP PP
|>
                •
        •
                        •
                                .| [0:0] NP -> * Det Noun
|>
       •
                •
                        •
                                .| [0:0] NP -> * 'John'
|>
                        •
               •
        •
                                .| [0:1] NP -> 'John' *
| [----]
                •
                         •
              •
                                .| [0:1] S -> NP * VP
| [---->
                        •
                                .| [0:1] NP -> NP * PP
| [---->
                        •
|. >
                                .| [1:1] VP -> * VP PP
               •
                        •
               •
                                .| [1:1] VP -> * Verb NP
       >
|.
                        •
       >
                        •
                                .| [1:1] VP -> * Verb
|.
                •
       > .
[-----]
                                .| [1:1] Verb -> * 'saw'
|.
                        •
                       .
.
.
                                .| [1:2] Verb -> 'saw' *
|.
                                .| [1:2] VP -> Verb * NP
|.
        [---->
|.
                                .| [1:2] VP -> Verb *
        [-----]
                      .
.
                                .| [0:2] S -> NP VP *
|[-----]
                                .| [1:2] VP -> VP * PP
|.
        [---->
                                .| [2:2] NP -> * NP PP
                >
                        •
|.
        •
                        . .| [2:2] NP -> * Det Noun
|.
                >
*** SWITCH TO BOTTOM UP
                   . .| [2:2] Det -> * 'a'
> .| [3:3] Noun -> * 'd
       . >
|.
                                .| [3:3] Noun -> * 'dog'
|.
       •
                [-----] .| [2:3] Det -> 'a' *
        •
|.
                       [-----]| [3:4] Noun -> 'dog' *
|.
                [-----> .| [2:3] NP -> Det * Noun
|.
        •
               [-----]| [2:4] NP -> Det Noun *
|.
       [-----]| [1:4] VP -> Verb NP *
|.
                [----->| [2:4] NP -> NP * PP
|.
         •
```

|[======]| [0:4] S -> NP VP * [----->| [1:4] VP -> VP * PP |. . > . .| [2:2] S -> * NP VP |. [----->| [2:4] S -> NP * VP |. *** SWITCH TO TOP DOWN . >| [4:4] VP -> * VP PP . >| [4:4] VP -> * Verb 1 • |. • >| [4:4] VP -> * Verb NP |. • . >| [4:4] VP -> * Verb |. *** SWITCH TO BOTTOM UP *** SWITCH TO TOP DOWN *** SWITCH TO BOTTOM UP *** SWITCH TO TOP DOWN *** SWITCH TO BOTTOM UP *** SWITCH TO TOP DOWN *** SWITCH TO BOTTOM UP Nr edges in chart: 37

Let's see the code for Feature chart parsing in NLTK:

```
>>> import nltk
>>>nltk.parse.featurechart.demo(print times=False,print grammar=True,
parser=nltk.parse.featurechart.FeatureChartParser,sent='I saw a dog')
Grammar with 18 productions (start state = S[])
    S[] -> NP[] VP[]
    PP[] -> Prep[] NP[]
    NP[] -> NP[] PP[]
    VP[] -> VP[] PP[]
   VP[] -> Verb[] NP[]
   VP[] -> Verb[]
    NP[] -> Det[pl=?x] Noun[pl=?x]
   NP[] -> 'John'
    NP[] -> 'I'
    Det[] -> 'the'
    Det[] -> 'my'
    Det[-pl] -> 'a'
    Noun[-pl] -> 'dog'
    Noun[-pl] -> 'cookie'
    Verb[] -> 'ate'
    Verb[] -> 'saw'
    Prep[] -> 'with'
    Prep[] -> 'under'
* FeatureChartParser
Sentence: I saw a dog
|. I .saw. a .dog.|
|[---] . . .| [0:1] 'I'
```

```
|. [---] . .| [1:2] 'saw'
   . [---] .| [2:3] 'a'
|.
       . [---]| [3:4] 'dog'
|.
   •
           . .| [0:1] NP[] -> 'I' *
| [ - - - ]
           . .| [0:1] S[] -> NP[] * VP[] {}
|[---> .
|[---> . .| [0:1] NP[] -> NP[] * PP[] {}
|. [---] . .| [1:2] Verb[] -> 'saw' *
|. [---> . .| [1:2] VP[] -> Verb[] * NP[] {}
   [---] . .| [1:2] VP[] -> Verb[] *
|.
|. [---> . .| [1:2] VP[] -> VP[] * PP[] {}
|[-----] . .| [0:2] S[] -> NP[] VP[] *
|. . [---] .| [2:3] Det[-pl] -> 'a' *
   . [---> .| [2:3] NP[] -> Det[pl=?x] * Noun[pl=?x] {?x:
|.
False}
|. . . [---]| [3:4] Noun[-pl] -> 'dog' *
   . [-----]| [2:4] NP[] -> Det[-pl] Noun[-pl] *
|.
      [----->| [2:4] S[] -> NP[] * VP[] {}
|. .
|. .
      [----->| [2:4] NP[] -> NP[] * PP[] {}
   [-----]| [1:4] VP[] -> Verb[] NP[] *
|.
|. [----->| [1:4] VP[] -> VP[] * PP[] {}
|[=======]| [0:4] S[] -> NP[] VP[] *
(S[]
 (NP[] I)
 (VP[] (Verb[] saw) (NP[] (Det[-pl] a) (Noun[-pl] dog))))
```

The following code is found in NLTK for the implementation of the Earley algorithm:

```
def demo(print times=True, print grammar=False,
         print trees=True, trace=2,
         sent='I saw John with a dog with my cookie', numparses=5):
    .....
    A demonstration of the Earley parsers.
    .....
    import sys, time
    from nltk.parse.chart import demo grammar
    # The grammar for ChartParser and SteppingChartParser:
    grammar = demo grammar()
    if print grammar:
        print("* Grammar")
        print(grammar)
    # Tokenize the sample sentence.
    print("* Sentence:")
    print(sent)
    tokens = sent.split()
    print(tokens)
```

```
# Do the parsing.
    earley = EarleyChartParser(grammar, trace=trace)
    t = time.clock()
    chart = earley.chart parse(tokens)
    parses = list(chart.parses(grammar.start()))
    t = time.clock()-t
    # Print results.
    if numparses:
        assert len(parses) == numparses, 'Not all parses found'
    if print trees:
        for tree in parses: print(tree)
    else:
        print("Nr trees:", len(parses))
    if print times:
       print("Time:", t)
if name == ' main ': demo()
```

print()

Summary

In this chapter, we discussed Parsing, accessing the Treebank Corpus, and the implementation of Context-free Grammar, Probabilistic Context-free Grammar, the CYK algorithm, and the Earley algorithm. Hence, in this chapter, we discussed about the syntactic analysis phase of NLP.

In the next chapter, we will discuss about semantic analysis, which is another phase of NLP. We will discuss about NER using different approaches and obtain ways for performing disambiguation tasks.

Chapter 6. Semantic Analysis – Meaning Matters

Semantic analysis, or meaning generation is one of the tasks in NLP. It is defined as the process of determining the meaning of character sequences or word sequences. It may be used for performing the task of disambiguation.

This chapter will include the following topics:

- NER
- NER system using the HMM
- Training NER using machine learning toolkits
- NER using POS tagging
- Generation of the synset id from Wordnet
- Disambiguating senses using Wordnet

Introducing semantic analysis

NLP means performing computations on natural language. One of the steps performed while processing a natural language is semantic analysis. While analyzing an input sentence, if the syntactic structure of a sentence is built, then the semantic analysis of a sentence will be done. Semantic interpretation means mapping a meaning to a sentence. Contextual interpretation is mapping the logical form to the knowledge representation. The primitive or the basic unit of semantic analysis is referred to as meaning or sense. One of the tools dealing with senses is ELIZA. ELIZA was developed in the sixties by Joseph Weizenbaum. It made use of substitution and pattern matching techniques to analyze the sentence and provide an output to the given input. MARGIE was developed by Robert Schank in the seventies. It could represent all the English verbs using 11 primitives. MARGIE could interpret the sense of a sentence and represent it with the help of primitives. It further gave way to the concept of scripts. From MARGIE, **Script Applier Mechanism (SAM)** was developed. It could translate a sentence from different languages, such as English, Chinese, Russian, Dutch, and Spanish. In order to perform processing on textual data, a Python library or TextBlob is used. TextBlob provides APIs for performing NLP tasks, such as Part-of-Speech tagging, extraction of Noun Phrases, classification, machine translation, sentiment analysis.

Semantic analysis can be used to query a database and retrieve information. Another Python library, Gensim, can be used to perform document indexing, topic modeling, and similarity retrieval. Polyglot is an NLP tool that supports various multilingual applications. It provides NER for 40 different languages, tokenization for 165 different languages, language detection for 196 different languages, sentiment analysis for 136 different languages, POS tagging for 16 different languages, Morphological Analysis for 135 different languages, word embedding for 137 different languages, and transliteration for 69 different languages. MontyLingua is an NLP tool that is used to perform the semantic interpretation of English text. From English sentences, it extracts semantic information, such as verbs, nouns, adjectives, dates, phrases, and so on.

Sentences can be formally represented using logics. The basic expressions or sentences in propositional logic are represented using propositional symbols, such as P,Q, R, and so on. Complex expressions in

propositional logic can be represented using Boolean operators. For example, to represent the sentence *If it is raining, I'll wear a raincoat* using propositional logic:

- **P**: It is raining.
- Q: I'll wear raincoat.
- $\mathbf{P} \rightarrow \mathbf{Q}$: If it is raining, I'll wear a raincoat.

Consider the following code to represent operators used in NLTK:

```
>>> import nltk
>>> nltk.boolean_ops()
negation -
conjunction &
disjunction |
implication ->
equivalence <->
```

Well-formed Formulas (WFF) are formed using propositional symbols or using a combination of propositional symbols and Boolean operators.

Let's see the following code in NLTK, that categorizes logical expressions into different subclasses:

```
>>> import nltk
>>> input_expr = nltk.sem.Expression.from string
>>> input_expr('X | (Y -> Z)')
<OrExpression (X | (Y -> Z))>
>>> input_expr('-(X & Y)')
<NegatedExpression -(X & Y)>
>>> input_expr('X & Y')
<AndExpression (X & Y)>
>>> input_expr('X <-> -- X')
<IffExpression (X <-> --X)>
```

For mapping True or False values to logical expressions, the Valuation function is used in NLTK:

```
>>> import nltk
>>> value = nltk.Valuation([('X', True), ('Y', False), ('Z', True)])
>>> value['Z']
True
>>> domain = set()
>>> v = nltk.Assignment(domain)
>>> u = nltk.Model(domain, value)
>>> print(u.evaluate('(X & Y)', v))
False
>>> print(u.evaluate('-(X & Y)', v))
True
>>> print(u.evaluate('(X & Z)', v))
```

```
True
>>> print(u.evaluate('(X | Y)', v))
True
```

First order predicate logic involving constants and predicates in NLTK are depicted in the following code:

```
>>> import nltk
>>> input_expr = nltk.sem.Expression.from string
>>> expression = input_expr('run(marcus)', type_check=True)
>>> expression.argument
<ConstantExpressionmarcus>
>>> expression.argument.type
e
>>> expression.function
<ConstantExpression run>
>>> expression.function.type
<e,?>
>>> sign = {'run': '<e, t>'}
>>> expression = input_expr('run(marcus)', signature=sign)
>>> expression.function.type
e
```

The signature is used in NLTK to map associated types and non-logical constants. Consider the following code in NLTK that helps to generate a query and retrieve data from the database:

```
>>> import nltk
>>> nltk.data.show cfg('grammars/book grammars/sql1.fcfg')
% start S
S[SEM=(?np + WHERE + ?vp)] -> NP[SEM=?np] VP[SEM=?vp]
VP[SEM=(?v + ?pp)] -> IV[SEM=?v] PP[SEM=?pp]
VP[SEM=(?v + ?ap)] \rightarrow IV[SEM=?v] AP[SEM=?ap]
VP[SEM=(?v + ?np)] \rightarrow TV[SEM=?v] NP[SEM=?np]
VP[SEM=(?vp1 + ?c + ?vp2)] -> VP[SEM=?vp1] Conj[SEM=?c] VP[SEM=?vp2]
NP[SEM=(?det + ?n)] ->Det[SEM=?det] N[SEM=?n]
NP[SEM=(?n + ?pp)] -> N[SEM=?n] PP[SEM=?pp]
NP[SEM=?n] -> N[SEM=?n] | CardN[SEM=?n]
CardN[SEM='1000'] -> '1,000,000'
PP[SEM=(?p + ?np)] -> P[SEM=?p] NP[SEM=?np]
AP[SEM=?pp] -> A[SEM=?a] PP[SEM=?pp]
NP[SEM='Country="greece"'] -> 'Greece'
NP[SEM='Country="china"'] -> 'China'
Det[SEM='SELECT'] -> 'Which' | 'What'
Conj[SEM='AND'] -> 'and'
N[SEM='City FROM city table'] -> 'cities'
N[SEM='Population'] -> 'populations'
IV[SEM=''] -> 'are'
```

```
TV[SEM=''] -> 'have'
A -> 'located'
P[SEM=''] -> 'in'
P[SEM='>'] -> 'above'
>>> from nltk import load parser
>>> test = load parser('grammars/book grammars/sql1.fcfg')
>>> q=" What cities are in Greece"
>>> t = list(test.parse(q.split()))
>>> ans = t[0].label()['SEM']
>>> ans = [s for s in ans if s]
>>> q = ' '.join(ans)
>>> print(q)
SELECT City FROM city table WHERE Country="greece"
>>> from nltk.sem import chat80
>>> r = chat80.sql query('corpora/city database/city.db', q)
>>> for p in r:
print(p[0], end=" ")
```

athens

Introducing NER

Named entity recognition (NER) is the process in which proper nouns or named entities are located in a document. Then, these Named Entities are classified into different categories, such as Name of Person, Location, Organization, and so on.

There are 12 NER tagsets defined by IIIT-Hyderabad IJCNLP 2008. These are described here:

SNO.	Named entity tag	Meaning
1	NEP	Name of Person
2	NED	Name of Designation
3	NEO	Name of Organization
4	NEA	Name of Abbreviation
5	NEB	Name of Brand
6	NETP	Title of Person

SNO.	Named entity tag	Meaning
7	NETO	Title of Object
8	NEL	Name of Location
9	NETI	Time
10	NEN	Number
11	NEM	Measure
12	NETE	Terms

One of the applications of NER is information extraction. In NLTK, we can perform the task of information extraction by storing the tuple (entity, relation, entity), and then, the entity value can be retrieved.

Consider an example in NLTK that shows how information extraction is performed:

```
>>> import nltk
>>> locations=[('Jaipur', 'IN', 'Rajasthan'),('Ajmer', 'IN',
'Rajasthan'),('Udaipur', 'IN', 'Rajasthan'),('Mumbai', 'IN',
'Maharashtra'),('Ahmedabad', 'IN', 'Gujrat')]
>>> q = [x1 for (x1, relation, x2) in locations if x2=='Rajasthan']
>>> print(q)
['Jaipur', 'Ajmer', 'Udaipur']
```

The nltk.tag.stanford module is used that makes use of stanford taggers to perform NER. We can download tagger models from <u>http://nlp.stanford.edu/software</u>.

Let's see the following example in NLTK that can be used to perform NER using the Stanford tagger:

```
>>> from nltk.tag import StanfordNERTagger
>>> sentence =
StanfordNERTagger('english.all.3class.distsim.crf.ser.gz')
>>> sentence.tag('John goes to NY'.split())
[('John', 'PERSON'), ('goes', 'O'), ('to', 'O'),('NY', 'LOCATION')]
```

A classifier has been trained in NLTK to detect Named Entities. Using the function nltk.ne.chunk(), named entities can be identified from a text. If the parameter binary is set to

true, then the named entities are detected and tagged with the NE tag; otherwise the named entities are tagged with tags such as PERSON, GPE, and ORGANIZATION.

Let's see the following code, that detects Named Entities, if they exist, and tags them with the NE tag:

```
>>> import nltk
>>> sentences1 = nltk.corpus.treebank.tagged sents()[17]
>>> print(nltk.ne chunk(sentences1, binary=True))
(S
  The/DT
total/NN
of/IN
  18/CD
deaths/NNS
from/IN
malignant/JJ
mesothelioma/NN
  ,/,
lung/NN
cancer/NN
and/CC
asbestosis/NN
was/VBD
far/RB
higher/JJR
than/IN
  */-NONE-
expected/VBN
  *?*/-NONE-
  ,/,
the/DT
researchers/NNS
said/VBD
  0/-NONE-
  *T*-1/-NONE-
  ./.)
>>> sentences2 = nltk.corpus.treebank.tagged sents()[7]
>>> print(nltk.ne chunk(sentences2, binary=True))
(S
  A/DT
  (NE Lorillard/NNP)
spokewoman/NN
said/VBD
  ,/,
  · · / · · ·
  This/DT
is/VBZ
```

```
an/DT
old/JJ
story/NN
  ./.)
>>> print(nltk.ne chunk(sentences2))
(S
 A/DT
  (ORGANIZATION Lorillard/NNP)
spokewoman/NN
said/VBD
  ,/,
  This/DT
is/VBZ
an/DT
old/JJ
story/NN
  ./.)
```

Consider another example in NLTK that can be used to detect named entities:

```
>>> import nltk
>>> from nltk.corpus import conll2002
>>> for documents in conll2002.chunked sents('ned.train')[25]:
print(documents)
(PER Vandenbussche/Adj)
('zelf', 'Pron')
('besloot', 'V')
('dat', 'Conj')
('het', 'Art')
('hof', 'N')
('"', 'Punc')
('de', 'Art')
('politieke', 'Adj')
('zeden', 'N')
('uit', 'Prep')
('het', 'Art')
('verleden', 'N')
('"', 'Punc')
('heeft', 'V')
('willen', 'V')
('veroordelen', 'V')
('.', 'Punc')
```

A chunker is a program that is used to partition plain text into a sequence of semantically related words. To perform NER in NLTK, default chunkers are used. Default chunkers are chunkers based on classifiers that have been trained on the ACE corpus. Other chunkers have been trained on parsed or chunked NLTK corpora. The languages covered by these NLTK chunkers are as follows:

- Dutch
- Spanish
- Portuguese
- English

Consider another example in NLTK that identifies named entities and categorizes into different named entity classes:

```
>>> import nltk
>>> sentence = "I went to Greece to meet John";
>>> tok=nltk.word_tokenize(sentence)
>>> pos_tag=nltk.pos_tag(tok)
>>> print(nltk.ne_chunk(pos_tag))
(S
    I/PRP
went/VBD
to/TO
    (GPE Greece/NNP)
to/TO
meet/VB
    (PERSON John/NNP))
```

A NER system using Hidden Markov Model

HMM is one of the popular statistical approaches of NER. An HMM is defined as a **Stochastic Finite State Automaton** (**SFSA**) consisting of a finite set of states that are associated with the definite probability distribution. States are unobserved or hidden. HMM generates optimal state sequences as an output. HMM is based on the Markov Chain property. According to the Markov Chain property, the probability of the occurrence of the next state is dependent on the previous tag. It is the simplest approach to implement. The drawback of HMM is that it requires a large amount of training and it cannot be used for large dependencies. HMM consists of the following:

- Set of states, S, where |S|=N. Here, N is the total number of states.
- Start state, S0.
- Output alphabet, O; |O| = k. k is the total number of output alphabets.
- Transition probability, A.
- Emission probability, B.
- Initial state probabilities, π .

HMM is represented by the following tuple— $\lambda = (A, B, \pi)$.

Start probability or initial state probability may be defined as the probability that a particular tag occurs first in a sentence.

Transition probability (A=aij) may be defined as the probability of the occurrence of the next tag j in a sentence given the occurrence of the particular tag i at present.

A=aij= the number of transitions from state si to sj /the number of transitions from state si

Emission probability (B=bj(O)) may be defined as the probability of the occurrence of an output sequence given a state *j*.

B=bj(k) = the number of times in state *j* and observing the symbol *k* /the expected number of times in state *j*.

The Baum Welch algorithm is used to find the maximum likelihood and the posterior mode estimates for HMM parameters. The forward-backward algorithm is used to find the posterior marginals of all the hidden state variables given a sequence of emissions or observations.

There are three steps involved in performing NER using HMM—Annotation, HMM train, and HMM test. The Annotation module converts raw text into annotated or trainable data. During HMM train, we compute HMM parameters—start probability, transition probability, and emission probability. During HMM test, the Viterbi algorithm is used. that finds out the optimal tag sequence.

Consider an example of chunking using the HMM in NLTK. Using chunking, the NP and VP chunks can be obtained. NP chunks can further be processed to obtain proper nouns or named entities:

>>> import nltk >>> nltk.tag.hmm.demo pos() HMM POS tagging demo Training HMM... Testing... Test: the/AT fulton/NP county/NN grand/JJ jury/NN said/VBD friday/NR an/AT investigation/NN of/IN atlanta's/NP\$ recent/JJ primary/NN election/NN produced/VBD ``/`` no/AT evidence/NN ''/'' that/CS any/ DTI irregularities/NNS took/VBD place/NN ./. Untagged: the fulton county grand jury said friday an investigation of atlanta's recent primary election produced `` no evidence '' that any irregularities took place . HMM-tagged: the/AT fulton/NP county/NN grand/JJ jury/NN said/VBD friday/NR an/AT investigation/NN of/IN atlanta's/NP\$ recent/JJ primary/NN election/NN produced/VBD ``/`` no/AT evidence/NN ''/'' that/CS any/DTI irregularities/NNS took/VBD place/NN ./. Entropy: 18.7331739705

Test: the/AT jury/NN further/RBR said/VBD in/IN term-end/NN presentments/NNS that/CS the/AT city/NN executive/JJ committee/NN ,/, which/WDT had/HVD over-all/JJ charge/NN of/IN the/AT election/NN ,/, ``/`` deserves/VBZ the/AT praise/NN and/CC thanks/NNS of/IN the/AT city/NN of/IN atlanta/NP ''/'' for/IN the/AT manner/NN in/IN which/WDT the/AT election/NN was/BEDZ conducted/VBN ./.

Untagged: the jury further said in term-end presentments that the city executive committee , which had over-all charge of the election , `` deserves the praise and thanks of the city of atlanta '' for the manner in which the election was conducted .

HMM-tagged: the/AT jury/NN further/RBR said/VBD in/IN term-end/AT presentments/NN that/CS the/AT city/NN executive/NN committee/NN ,/, which/WDT had/HVD over-all/VBN charge/NN of/IN the/AT election/NN ,/, ``/`` deserves/VBZ the/AT praise/NN and/CC thanks/NNS of/IN the/AT city/NN of/IN atlanta/NP ''/'' for/IN the/AT manner/NN in/IN which/WDT the/AT election/NN was/BEDZ conducted/VBN ./.

Entropy: 27.0708725519

Test: the/AT september-october/NP term/NN jury/NN had/HVD been/BEN charged/VBN by/IN fulton/NP superior/JJ court/NN judge/NN durwood/NP pye/NP to/TO investigate/VB reports/NNS of/IN possible/JJ ``/`` irregularities/NNS ''/'' in/IN the/AT hard-fought/JJ primary/NN which/WDT was/BEDZ won/VBN by/IN mayor-nominate/NN ivan/NP allen/NP jr./NP ./.

Untagged: the september-october term jury had been charged by fulton superior court judge durwoodpye to investigate reports of possible `` irregularities '' in the hard-fought primary which was won by mayor-nominate ivanallenjr. .

HMM-tagged: the/AT september-october/JJ term/NN jury/NN had/HVD been/ BEN charged/VBN by/IN fulton/NP superior/JJ court/NN judge/NN durwood/TO pye/VB to/TO investigate/VB reports/NNS of/IN possible/JJ ``/`` irregularities/NNS ''/'' in/IN the/AT hard-fought/JJ primary/ NN which/WDT was/BEDZ won/VBN by/IN mayor-nominate/NP ivan/NP allen/ NP jr./NP ./.

Entropy: 33.8281874237

Test: ``/`` only/RB a/AT relative/JJ handful/NN of/IN such/JJ reports/NNS was/BEDZ received/VBN ''/'' ,/, the/AT jury/NN said/VBD ,/, ``/`` considering/IN the/AT widespread/JJ interest/NN in/IN the/

AT election/NN ,/, the/AT number/NN of/IN voters/NNS and/CC the/AT size/NN of/IN this/DT city/NN ''/'' ./.

Untagged: `` only a relative handful of such reports was received '', the jury said , `` considering the widespread interest in the election , the number of voters and the size of this city '' .

HMM-tagged: ``/`` only/RB a/AT relative/JJ handful/NN of/IN such/JJ reports/NNS was/BEDZ received/VBN ''/'' ,/, the/AT jury/NN said/VBD ,/, ``/`` considering/IN the/AT widespread/JJ interest/NN in/IN the/AT election/NN ,/, the/AT number/NN of/IN voters/NNS and/CC the/AT size/NN of/IN this/DT city/NN ''/'' ./.

Entropy: 11.4378198596

Test: the/AT jury/NN said/VBD it/PPS did/DOD find/VB that/CS many/AP of/IN georgia's/NP\$ registration/NN and/CC election/NN laws/NNS ``/`` are/BER outmoded/JJ or/CC inadequate/JJ and/CC often/RB ambiguous/JJ ''/'' ./.

Untagged: the jury said it did find that many of georgia's registration and election laws `` are outmoded or inadequate and often ambiguous '' .

HMM-tagged: the/AT jury/NN said/VBD it/PPS did/DOD find/VB that/CS many/AP of/IN georgia's/NP\$ registration/NN and/CC election/NN laws/ NNS ``/`` are/BER outmoded/VBG or/CC inadequate/JJ and/CC often/RB ambiguous/VB ''/'' ./. Entropy: 20.8163623192

Test: it/PPS recommended/VBD that/CS fulton/NP legislators/NNS act/ VB ``/`` to/TO have/HV these/DTS laws/NNS studied/VBN and/CC revised/ VBN to/IN the/AT end/NN of/IN modernizing/VBG and/CC improving/VBG them/PPO ''/'' ./.

Untagged: it recommended that fulton legislators act $\hat{\}$ to have these laws studied and revised to the end of modernizing and improving them '' .

HMM-tagged: it/PPS recommended/VBD that/CS fulton/NP legislators/NNS act/VB ``/`` to/TO have/HV these/DTS laws/NNS studied/VBD and/CC revised/VBD to/IN the/AT end/NN of/IN modernizing/NP and/CC improving/VBG them/PPO ''/'' ./.

Entropy: 20.3244921203

Test: the/AT grand/JJ jury/NN commented/VBD on/IN a/AT number/NN of/ IN other/AP topics/NNS ,/, among/IN them/PPO the/AT atlanta/NP and/ CC fulton/NP county/NN purchasing/VBG departments/NNS which/WDT it/ PPS said/VBD ``/`` are/BER well/QL operated/VBN and/CC follow/VB generally/RB accepted/VBN practices/NNS which/WDT inure/VB to/IN the/ AT best/JJT interest/NN of/IN both/ABX governments/NNS ''/'' ./.

Untagged: the grand jury commented on a number of other topics , among them the atlanta and fulton county purchasing departments which it said `` are well operated and follow generally accepted practices which inure to the best interest of both governments ''.

HMM-tagged: the/AT grand/JJ jury/NN commented/VBD on/IN a/AT number/ NN of/IN other/AP topics/NNS ,/, among/IN them/PPO the/AT atlanta/NP and/CC fulton/NP county/NN purchasing/NN departments/NNS which/WDT it/PPS said/VBD ``/`` are/BER well/RB operated/VBN and/CC follow/VB generally/RB accepted/VBN practices/NNS which/WDT inure/VBZ to/IN the/AT best/JJT interest/NN of/IN both/ABX governments/NNS ''/'' ./.

Entropy: 31.3834231469

Test: merger/NN proposed/VBN

Untagged: merger proposed

HMM-tagged: merger/PPS proposed/VBD

Entropy: 5.6718203946

Test: however/WRB ,/, the/AT jury/NN said/VBD it/PPS believes/VBZ ``/`` these/DTS two/CD offices/NNS should/MD be/BE combined/VBN to/ TO achieve/VB greater/JJR efficiency/NN and/CC reduce/VB the/AT cost/ NN of/IN administration/NN ''/'' ./.

Untagged: however , the jury said it believes `` these two offices should be combined to achieve greater efficiency and reduce the cost of administration '' .

HMM-tagged: however/WRB ,/, the/AT jury/NN said/VBD it/PPS believes/ VBZ ``/`` these/DTS two/CD offices/NNS should/MD be/BE combined/VBN to/TO achieve/VB greater/JJR efficiency/NN and/CC reduce/VB the/AT cost/NN of/IN administration/NN ''/'' ./. Entropy: 8.27545943909

Test: the/AT city/NN purchasing/VBG department/NN ,/, the/AT jury/NN said/VBD ,/, ``/`` is/BEZ lacking/VBG in/IN experienced/VBN clerical/ JJ personnel/NNS as/CS a/AT result/NN of/IN city/NN personnel/NNS policies/NNS ''/'' ./.

Untagged: the city purchasing department , the jury said , $\hat{}$ is lacking in experienced clerical personnel as a result of city personnel policies '' .

HMM-tagged: the/AT city/NN purchasing/NN department/NN ,/, the/AT jury/NN said/VBD ,/, ``/`` is/BEZ lacking/VBG in/IN experienced/AT clerical/JJ personnel/NNS as/CS a/AT result/NN of/IN city/NN personnel/NNS policies/NNS ''/'' ./.

Entropy: 16.7622537278

accuracy over 284 tokens: 92.96

The outcome of an NER tagger may be defined as a *response* and an interpretation of human beings as *answer key*. So, we provide the following definitions:

- **Correct**: If the response is exactly the same as answer key
- **Incorrect**: If the response is not same as answer key
- Missing: If answer key is found tagged, but response is not tagged
- Spurious: If response is found tagged, but answer key is not tagged

Performance of an NER-based system can be judged by using the following parameters:

• **Precision (P)**: It is defined as follows:

P=Correct/(Correct+Incorrect+Missing)

• Recall (R): It is defined as follows:

R=*Correct*/(*Correct*+*Incorrect*+*Spurious*)

• **F-Measure**: It is defined as follows:

F-Measure = (2*PREC*REC)/(PRE+REC)

Training NER using Machine Learning Toolkits

NER can be performed using the following approaches:

- Rule-based or Handcrafted approach:
 - List Lookup approach
 - Linguistic approach
- Machine Learning-based approach or Automated approach:
 - Hidden Markov Model
 - Maximum Entropy Markov Model
 - Conditional Random Fields
 - Support Vector Machine
 - Decision Trees

It has been proved experimentally that Machine learning-based approaches outperform Rule-based approaches. Also, if a combination of Rule-based approaches and Machine Learning-based approaches is used, then the performance of NER will increase.

NER using POS tagging

Using POS tagging, NER can be performed. The POS tags that can be used are as follows (they are available at <u>https://www.ling.upenn.edu/courses/Fall_2003/ling001/penn_treebank_pos.html</u>):

Tag	Description
СС	Coordinating conjunction
CD	Cardinal number
DT	Determiner
EX	Existential there
FW	Foreign word
IN	Preposition or subordinating conjunction
JJ	Adjective
JJR	Adjective, comparative
JJS	Adjective, superlative
LS	List item marker

Tag	Description
MD	Modal
NN	Noun, singular or mass
NNS	Noun, plural
NNP	Proper noun, singular
NNPS	Proper noun, plural
PDT	Predeterminer
POS	Possessive ending
PRP	Personal pronoun
PRP\$	Possessive pronoun
RB	Adverb
RBR	Adverb, comparative
RBS	Adverb, superlative
RP	Particle
SYM	Symbol
ТО	То
UH	Interjection

Tag	Description
VB	Verb, base form
VBD	Verb, past tense
VBG	Verb, gerund or present participle
VBN	Verb, past participle
VBP	Verb, non-3rd person singular present
VBZ	Verb, 3rd person singular present
WDT	Wh-determiner
WP	Wh-pronoun
WP\$	Possessive wh-pronoun
WRB	Wh-adverb

If POS tagging is performed, then using POS information, named entities can be identified. The tokens tagged with the NNP tag are Named Entities.

Consider the following example in NLTK in which POS tagging is used to perform NER:

```
>>> import nltk
>>> from nltk import pos_tag, word_tokenize
>>> pos_tag(word_tokenize("John and Smith are going to NY and
Germany"))
[('John', 'NNP'), ('and', 'CC'), ('Smith', 'NNP'), ('are', 'VBP'),
('going', 'VBG'), ('to', 'TO'), ('NY', 'NNP'), ('and', 'CC'),
('Germany', 'NNP')]
```

Here, the named entities are—John, Smith, NY, and Germany since they are tagged with the NNP tag.

Let's see another example in which POS tagging is performed in NLTK and the POS tag information is used to detect Named Entities:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> from nltk.tag import UnigramTagger
>>> tagger =
UnigramTagger(brown.tagged sents(categories='news')[:700])
>>> sentence =
['John', 'and', 'Smith', 'went', 'to', 'NY', 'and', 'Germany']
>>> for word, tag in tagger.tag(sentence):
print(word, '->', tag)
John -> NP
and -> CC
Smith -> None
went -> VBD
to -> TO
NY -> None
and -> CC
Germany -> None
```

Here, John has been tagged with the NP tag, so it is identified as a named entity. Some of the tokens here are tagged with the None tag because these tokens have not been trained.

Generation of the synset id from Wordnet

Wordnet may be defined as an English lexical database. The conceptual dependency between words, such as hypernym, synonym, antonym, and hyponym, can be found using synsets.

Consider the following code in NLTK for the generation of synsets:

```
def all synsets(self, pos=None):
        """Iterate over all synsets with a given part of speech tag.
        If no pos is specified, all synsets for all parts of speech
        will be loaded.
        .....
        if pos is None:
            pos tags = self. FILEMAP.keys()
        else:
            pos tags = [pos]
        cache = self. synset offset cache
        from pos and line = self. synset from pos and line
        # generate all synsets for each part of speech
        for pos tag in pos tags:
            # Open the file for reading. Note that we can not re-use
            # the file poitners from self. data file map here,
because
            # we're defining an iterator, and those file pointers
might
            # be moved while we're not looking.
            if pos tag == ADJ SAT:
                pos tag = ADJ
            fileid = 'data.%s' % self. FILEMAP[pos tag]
            data file = self.open(fileid)
            try:
                # generate synsets for each line in the POS file
                offset = data file.tell()
                line = data file.readline()
                while line:
                    if not line[0].isspace():
                        if offset in cache [pos tag]:
                             # See if the synset is cached
                            synset = cache[pos tag][offset]
                        else:
                            # Otherwise, parse the line
                            synset = from pos and line(pos_tag, line)
                            cache[pos tag][offset] = synset
```

```
# adjective satellites are in the same file
as
                         # adjectives so only yield the synset if
it's actually
                         # a satellite
                         if synset. pos == ADJ SAT:
                             yield synset
                         # for all other POS tags, yield all synsets
(this means
                         # that adjectives also include adjective
satellites)
                         else:
                             yield synset
                    offset = data file.tell()
                    line = data file.readline()
            # close the extra file handle we opened
            except:
                data file.close()
                raise
            else:
                data file.close()
```

Let's see the following code in NLTK, that is used to look up a word using synsets:

```
>>> import nltk
>>> from nltk.corpus import wordnet
>>> wn.synsets('cat')
[Synset('cat.n.01'), Synset('guy.n.01'), Synset('cat.n.03'),
Synset('kat.n.01'), Synset('guy.n.01'), Synset('cat.n.01'),
Synset('caterpillar.n.02'), Synset('big_cat.n.01'),
Synset('computerized_tomography.n.01'), Synset('cat.v.01'),
Synset('vomit.v.01')]
>>> wn.synsets('cat', pos=wn.VERB)
[Synset('cat.v.01'), Synset('vomit.v.01')]
>>> wn.synset('cat.n.01')
```

Here, cat.n.01 means that cat is of the noun category and only one meaning of cat exists:

```
>>> print(wn.synset('cat.n.01').definition())
feline mammal usually having thick soft fur and no ability to roar:
domestic cats; wildcats
```

```
>>> len(wn.synset('cat.n.01').examples())
0
>>> wn.synset('cat.n.01').lemmas()
[Lemma('cat.n.01.cat'), Lemma('cat.n.01.true_cat')]
>>> [str(lemma.name()) for lemma in wn.synset('cat.n.01').lemmas()]
['cat', 'true_cat']
>>> wn.lemma('cat.n.01.cat').synset()
Synset('cat.n.01')
```

Let's see the following example in NLTK, that depicts the use of Synsets and Open Multilingual Wordnet using ISO 639 language codes:

```
>>> import nltk
>>> from nltk.corpus import wordnet
>>> from nltk.corpus import wordnet as wn
>>> sorted(wn.langs())
['als', 'arb', 'cat', 'cmn', 'dan', 'eng', 'eus', 'fas', 'fin',
'fra', 'fre', 'glg', 'heb', 'ind', 'ita', 'jpn', 'nno', 'nob',
'pol', 'por', 'spa', 'tha', 'zsm']
>>> wn.synset('cat.n.01').lemma names('ita')
['gatto']
>>> sorted(wn.synset('cat.n.01').lemmas('dan'))
[Lemma('cat.n.01.kat'), Lemma('cat.n.01.mis'),
Lemma('cat.n.01.missekat')]
>>> sorted(wn.synset('cat.n.01').lemmas('por'))
[Lemma('cat.n.01.Gato-doméstico'), Lemma('cat.n.01.Gato doméstico'),
Lemma('cat.n.01.gato'), Lemma('cat.n.01.gato')]
>>> len(wordnet.all lemma names(pos='n', lang='jpn'))
66027
>>> cat = wn.synset('cat.n.01')
>>> cat.hypernyms()
[Synset('feline.n.01')]
>>> cat.hyponyms()
[Synset('domestic cat.n.01'), Synset('wildcat.n.03')]
>>> cat.member holonyms()
[]
>>> cat.root hypernyms()
[Synset('entity.n.01')]
>>>
wn.synset('cat.n.01').lowest common hypernyms(wn.synset('dog.n.01'))
[Synset('carnivore.n.01')]
```

Disambiguating senses using Wordnet

Disambiguation is the task of distinguishing two or more of the same spellings or the same sounding words on the basis of their sense or meaning.

Following are the implementations of disambiguation or the WSD task using Python technologies:

- Lesk algorithms:
 - Original Lesk
 - Cosine Lesk (use cosines to calculate overlaps instead of using raw counts)
 - Simple Lesk (with definitions, example(s), and hyper+hyponyms)
 - Adapted/extended Lesk
 - Enhanced Lesk
- Maximizing similarity:
 - Information content
 - Path similarity
- Supervised WSD:
 - It Makes Sense (IMS)
 - SVM WSD
- Vector Space models:
 - Topic Models, LDA
 - LSI/LSA
 - NMF
- Graph-based models:
 - Babelfly
 - UKB
- Baselines:
 - Random sense
 - Highest lemma counts
 - First NLTK sense

Wordnet sense similarity in NLTK involves the following algorithms:

- **Resnik Score**: On comparing two tokens, a score (Least Common Subsumer) is returned that decides the similarity of two tokens
- **Wu-Palmer Similarity**: Defines the similarity between two tokens on the basis of the depth of two senses and Least Common Subsumer
- **Path Distance Similarity**: The similarity of two tokens is determined on the basis of the shortest distance that is computed in the is-a taxonomy
- Leacock Chodorow Similarity: A similarity score is returned on the basis of the shortest path and the depth (maximum) in which the senses exist in the taxonomy
- Lin Similarity: A similarity score is returned on the basis of the information content of the Least Common Subsumer and two input Synsets
- Jiang-Conrath Similarity: A similarity score is returned on the basis of the content information of Least Common Subsumer and two input Synsets

Consider the following example in NLTK, which depicts path similarity:

```
>>> import nltk
>>> from nltk.corpus import wordnet
>>> from nltk.corpus import wordnet as wn
>>> lion = wn.synset('lion.n.01')
>>> cat = wn.synset('cat.n.01')
>>> lion.path_similarity(cat)
0.25
```

Consider the following example in NLTK that depicts Leacock Chodorow Similarity:

```
>>> import nltk
>>> from nltk.corpus import wordnet
>>> from nltk.corpus import wordnet as wn
>>> lion = wn.synset('lion.n.01')
>>> cat = wn.synset('cat.n.01')
>>> lion.lch_similarity(cat)
2.2512917986064953
```

Consider the following example in NLTK that depicts Wu-Palmer Similarity:

```
>>> import nltk
>>> from nltk.corpus import wordnet
>>> from nltk.corpus import wordnet as wn
>>> lion = wn.synset('lion.n.01')
>>> cat = wn.synset('cat.n.01')
>>> lion.wup_similarity(cat)
0.896551724137931
```

Consider the following example in NLTK that depicts Resnik Similarity, Lin Similarity, and Jiang-Conrath Similarity:

```
>>> import nltk
>>> from nltk.corpus import wordnet
>>> from nltk.corpus import wordnet as wn
>>> from nltk.corpus import wordnet ic
>>> brown ic = wordnet ic.ic('ic-brown.dat')
>>> semcor ic = wordnet ic.ic('ic-semcor.dat')
>>> from nltk.corpus import genesis
>>> genesis ic = wn.ic(genesis, False, 0.0)
>>> lion = wn.synset('lion.n.01')
>>> cat = wn.synset('cat.n.01')
>>> lion.res similarity(cat, brown ic)
8.663481537685325
>>> lion.res similarity(cat, genesis ic)
7.339696591781995
>>> lion.jcn similarity(cat, brown ic)
0.36425897775957294
```

```
>>> lion.jcn_similarity(cat, genesis_ic)
0.3057800856788946
>>> lion.lin_similarity(cat, semcor_ic)
0.8560734335071154
```

Let's see the following code in NLTK based on Wu-Palmer Similarity and Path Distance Similarity:

```
from nltk.corpus import wordnet as wn
def getSenseSimilarity(worda,wordb):
.. .. ..
find similarity betwwn word senses of two words
** ** **
wordasynsets = wn.synsets(worda)
wordbsynsets = wn.synsets(wordb)
synsetnamea = [wn.synset(str(syns.name)) for syns in wordasynsets]
        synsetnameb = [wn.synset(str(syns.name)) for syns in
wordbsynsets]
for sseta, ssetb in [(sseta,ssetb) for sseta in synsetnamea\
for ssetb in synsetnameb]:
pathsim = sseta.path similarity(ssetb)
wupsim = sseta.wup similarity(ssetb)
if pathsim != None:
print "Path Sim Score: ",pathsim," WUP Sim Score: ",wupsim, \
"\t", sseta.definition, "\t", ssetb.definition
if name == " main ":
#getSenseSimilarity('walk','dog')
getSenseSimilarity('cricket', 'ball')
```

Consider the following code of a Lesk algorithm in NLTK, which is used to perform the disambiguation task:

from nltk.corpus import wordnet

def lesk(context_sentence, ambiguous_word, pos=None, synsets=None):
 """Return a synset for an ambiguous word in a context.

:param iter context_sentence: The context sentence where the ambiguous word

occurs, passed as an iterable of words.

:param str ambiguous_word: The ambiguous word that requires WSD. :param str pos: A specified Part-of-Speech (POS).

:param iter synsets: Possible synsets of the ambiguous word. :return: ``lesk_sense`` The Synset() object with the highest signature overlaps.

```
//
    This function is an implementation of the original Lesk
algorithm (1986) [1].
    Usage example::
>>> lesk(['I', 'went', 'to', 'the', 'bank', 'to', 'deposit',
'money', '.'], 'bank', 'n')
        Synset('savings bank.n.02')
    context = set(context sentence)
    if synsets is None:
        synsets = wordnet.synsets(ambiguous word)
    if pos:
        synsets = [ss for ss in synsets if str(ss.pos()) == pos]
    if not synsets:
        return None
    _, sense = max(
        (len(context.intersection(ss.definition().split())), ss) for
ss in synsets
    )
    return sense
```

Summary

In this chapter, we have discussed Semantic Analysis, which is also one of the phase of Natural Language Processing. We have discussed NER, NER using HMM, NER using Machine Learning Toolkits, Performance Metrics of NER, NER using POS tagging, and WSD using Wordnet and the Generation of Synsets.

In the next chapter, we will discuss sentiment analysis using NER and machine learning approaches. We will also discuss the evaluation of the NER system.

Chapter 7. Sentiment Analysis – I Am Happy

Sentiment analysis or sentiment generation is one of the tasks in NLP. It is defined as the process of determining the sentiments behind a character sequence. It may be used to determine whether the speaker or the person expressing the textual thoughts is in a happy or sad mood, or it represents a neutral expression.

This chapter will include the following topics:

- Introducing sentiment analysis
- Sentiment analysis using NER
- Sentiment analysis using machine learning
- Evaluation of the NER system

Introducing sentiment analysis

Sentiment analysis may be defined as a task performed on natural languages. Here, computations are performed on the sentences or words expressed in natural language to determine whether they express a positive, negative, or a neutral sentiment. Sentiment analysis is a subjective task, since it provides the information about the text being expressed. Sentiment analysis may be defined as a classification problem in which classification may be of two types—binary categorization (positive or negative) and multi-class categorization (positive, negative, or neutral). Sentiment analysis is also referred to as text sentiment analysis. It is a text mining approach in which we determine the sentiments or the emotions behind the text. When we combine sentiment analysis with topic mining, then it is referred to as topic-sentiment analysis. Sentiment analysis can be performed using a lexicon. The lexicon could be domain-specific or of a general purpose nature. Lexicon may contain a list of positive expressions, negative expressions, and stop words. When a testing sentence appears, then a simple look up operation can be performed through this lexicon.

One example of the word list is—Affective Norms for English Words (ANEW). It is an English word list found at the University of Florida. It consists of 1034 words for dominance, valence, and arousal. It was formed by Bradley and Lang. This word list was constructed for academic purposes and not for research purposes. Other variants are DANEW (Dutch ANEW) and SPANEW (Spanish ANEW).

AFINN consists of 2477 words (earlier 1468 words). This word list was formed by Finn Arup Nielson. The main purpose for creating this word list was to perform sentiment analysis for Twitter texts. A valence value ranging from -5 to +5 is allotted to each word.

The **Balance Affective** word list consists of 277 English words. The valence code ranges from 1 to 4. 1 means positive, 2 means negative, 3 means anxious, and 4 means neutral.

Berlin Affective Word List (BAWL) consists of 2,200 words in German. Another version of BAWL is **Berlin Affective Word List Reloaded (BAWL-R)** that comprises of additional arousal for words.

Bilingual Finnish Affective Norms comprises 210 British English as well as Finnish nouns. It also comprises taboo words.

Compass DeRose Guide to Emotion Words consists of emotional words in English. This was formed by Steve J. DeRose. Words were classified, but there was no valence and arousal.

Dictionary of Affect in Language (DAL) comprises emotional words that can be used for sentiment analysis. It was formed by Cynthia M. Whissell. So, it is also referred to as **Whissell's Dictionary of Affect in Language (WDAL)**.

General Inquirer consists of many dictionaries. In this, the positive list comprises 1915 words and the negative list comprises 2291 words.

Hu-Liu opinion Lexicon (HL) comprises a list of 6800 words (positive and negative).

Leipzig Affective Norms for German (LANG) is a list that consists of 1000 nouns in German, and the rating has been done based on valence, concreteness, and arousal.

Loughran and McDonald Financial Sentiment Dictionaries were created by Tim Loughran and Bill McDonald. These dictionaries consist of words for financial documents, which are positive, negative, or modal words.

Moors consist of a list of words in Dutch related to dominance, arousal, and valence.

NRC Emotion Lexicon comprises of a list of words developed through Amazon Mechanical Turk by Saif M. Mohammad.

OpinionFinder's Subjectivity Lexicon comprises a list of 8221 words (positive or negative).

SentiSense comprises 2,190 synsets and 5,496 words based on 14 emotional categories.

Warringer comprises 13,915 words in English collected from Amazon Mechanical Turk that are related to dominance, arousal, and valence.

labMT is a word list consisting of 10,000 words.

Let's consider the following example in NLTK, which performs sentiment analysis for movie reviews:

```
'this', 'film', 'i', 'he', 'but', 'on', 'are', 't', 'by', 'be',
'one', 'movie', 'an', 'who', 'not', 'you', 'from', 'at', 'was',
'have', 'they', 'has', 'her', 'all', '?', 'there', 'like', 'so',
'out', 'about', 'up', 'more', 'what', 'when', 'which', 'or', 'she',
'their', ':', 'some', 'just', 'can', 'if', 'we', 'him', 'into',
'even', 'only', 'than', 'no', 'good', 'time', 'most', 'its', 'will',
'story', 'would', 'been', 'much', 'character', 'also', 'get',
'other', 'do', 'two', 'well', 'them', 'very', 'characters', ';',
'first', '--', 'after', 'see', '!', 'way', 'because', 'make', 'life']
def doc features (doc):
   doc words = set(doc)
   features = \{\}
   for word in token features:
        features['contains(%s)' % word] = (word in doc words)
   return features
print doc features (movie reviews.words('pos/cv957 8737.txt
feature sets = [(doc features(d), c) for (d,c) in doc]
train sets, test sets = feature sets[100:], feature sets[:100]
classifiers = nltk.NaiveBayesClassifier.train(train sets)
print nltk.classify.accuracy(classifiers, test sets)
    0.86
classifier.show most informative features (5)
    Most Informative Features
contains(damon) = True
                                                      11.2 : 1.0
                                   pos:neg =
contains(outstanding) = True
                                   pos : neg
                                                      10.6 : 1.0
                                               =
                                                      8.8 : 1.0
contains(mulan) = True
                                   pos : neg
                                               =
                                                       8.4 : 1.0
contains(seagal) = True
                                   neg : pos
                                               =
contains(wonderfully) = True
                                   pos:neg =
                                                       7.4 : 1.0
```

Here, it is checked whether the informative features are present in the document or not.

Consider another example of semantic analysis. First, the preprocessing of text is performed. In this, individual sentences are identified in a given text. Then, tokens are identified in the sentences. Each token further comprises three entities, namely, word, lemma, and tag.

Let's see the following code in NLTK for the preprocessing of text:

```
importnltk
class Splitter(object):
def __init__(self):
self.nltk splitter = nltk.data.load('tokenizers/punkt/
```

```
english.pickle')
self.nltk_tokenizer = nltk.tokenize.TreebankWordTokenizer()

def split(self, text):
sentences = self.nltk_splitter.tokenize(text)
tokenized_sentences = [self.nltk_tokenizer.tokenize(sent) for sent
in sentences]
return tokenized_sentences
classPOSTagger(object):
def __init__(self):
pass

def pos_tag(self, sentences):
pos = [nltk.pos_tag(sentence) for sentence in sentences]
pos = [[(word, word, [postag]) for (word, postag) in sentence] for
sentence in pos]
returnpos
```

The lemmas generated will be same as the word forms. Tags are the POS tags. Consider the following code, which generates three tuples for each token, that is, word, lemma, and the POS tag:

```
text = """Why are you looking disappointed. We will go to restaurant
for dinner."""
splitter = Splitter()
postagger = POSTagger()
splitted_sentences = splitter.split(text)
print splitted_sentences
[['Why','are','you','looking','disappointed','.'],
['We','will','go','to','restaurant','for','dinner','.']]
pos_tagged_sentences = postagger.pos_tag(splitted_sentences)
print pos_tagged_sentences
[[('Why','Why',['WP']),('are','are',['VBZ']),('you','you',['PRP']),('
looking','looking',['VB']),('disappointed','disappointed',['VB']),('.
','.',['.'])],[('We','We',['PRP']),('will','will',['VBZ']),('go','go','go','for',['IN']),('to','to',['TO']),('restaurant','restaurant',['NN']),('for','for',['IN']),('dinner','dinner',['NN']),('.','.',['.'])]]
```

We can construct two kinds of dictionary consisting of positive and negative expressions. We can then perform tagging on our processed text using dictionaries.

Let's consider the following NLTK code for tagging using dictionaries:

```
classDictionaryTagger(object):
def init (self, dictionary paths):
```

```
files = [open(path, 'r') for path in dictionary paths]
dictionaries = [yaml.load(dict file) for dict file in files]
map(lambda x: x.close(), files)
self.dictionary = {}
self.max key size = 0
forcurr dict in dictionaries:
for key in curr dict:
if key in self.dictionary:
self.dictionary[key].extend(curr dict[key])
else:
self.dictionary[key] = curr dict[key]
self.max key size = max(self.max key size, len(key))
def tag(self, postagged sentences):
return [self.tag sentence(sentence) for sentence in
postagged sentences]
def tag sentence(self, sentence, tag with lemmas=False):
tag sentence = []
        N = len(sentence)
ifself.max key size == 0:
self.max key size = N
i = 0
while (i< N):
j = min(i + self.max key size, N) #avoid overflow
taqqed = False
while (j > i):
expression form = ' '.join([word[0] for word in
sentence[i:j]]).lower()
expression lemma = ' '.join([word[1] for word in
sentence[i:j]]).lower()
iftag with lemmas:
literal = expression lemma
else:
literal = expression form
if literal in self.dictionary:
    is single token = j - i == 1
original position = i
i = j
taggings = [tag for tag in self.dictionary[literal]]
tagged expression = (expression form, expression lemma, taggings)
if is single token: #if the tagged literal is a single token,
conserve its previous taggings:
original token tagging = sentence[original position][2]
tagged expression[2].extend(original token tagging)
tag sentence.append(tagged expression)
tagged = True
```

Here, words in the preprocessed text are tagged as positive or negative with the help of dictionaries.

Let's see the following code in NLTK, which can be used to compute the number of positive expressions and negative expressions:

```
def value_of(sentiment):
if sentiment == 'positive': return 1
if sentiment == 'negative': return -1
return 0
def sentiment_score(review):
return sum ([value_of(tag) for sentence in dict_tagged_sentences for
token in sentence for tag in token[2]])
```

The nltk.sentiment.util module is used in NLTK to perform sentiment analysis using Hu-Liu lexicon. This module counts the number of positive, negative, and neutral expressions, with the help of the lexicon, and then decides on the basis of majority counts whether the text consist of a positive, negative, or neutral sentiment. The words which are not available in the lexicon are considered neutral.

Sentiment analysis using NER

NER is the process of finding named entities and then categorizing named entities into different named entity classes. NER can be performed using different techniques, such as the Rule-based approach, List look up approach, and Statistical approaches (Hidden Markov Model, Maximum Entropy Markov Model, Support Vector Machine, Conditional Random Fields, and Decision Trees).

If named entities are identified in the list, then they may be removed or filtered out from the sentences. Similarly, stop words may also be removed. Now, sentiment analysis may be performed on the remaining words, since named entities are words that do not contribute to sentiment analysis.

Sentiment analysis using machine learning

The nltk.sentiment.sentiment_analyzer module in NLTK is used to perform sentiment analysis. It is based on machine learning techniques.

Let's see the following code of the nltk.sentiment.sentiment analyzer module in NLTK:

```
from __future__ import print_function
from collections import defaultdict
from nltk.classify.util import apply_features, accuracy as
```

```
eval_accuracy
from nltk.collocations import BigramCollocationFinder
from nltk.metrics import (BigramAssocMeasures, precision as
eval_precision,
    recall as eval_recall, f_measure as eval_f_measure)
from nltk.probability import FreqDist
from nltk.sentiment.util import save_file, timer
class SentimentAnalyzer(object):
    """
    A tool for Sentiment Analysis which is based on machine learning
techniques.
    """
    def __init__(self, classifier=None):
        self.feat_extractors = defaultdict(list)
        self.classifier = classifier
```

Consider the following code, which will return all the words (duplicates) from a text:

```
def all_words(self, documents, labeled=None):
    all_words = []
    if labeled is None:
        labeled = documents and isinstance(documents[0], tuple)
    if labeled == True:
        for words, sentiment in documents:
            all_words.extend(words)
    elif labeled == False:
        for words in documents:
            all_words.extend(words)
    return all_words
```

Consider the following code, which will apply the feature extraction function to the text:

Consider the following code, which will return the word's features:

The following code returns the bigram features:

```
def bigram_collocation_feats(self, documents, top_n=None, min_freq=3,
assoc_measure=BigramAssocMeasures.pmi):
    finder = BigramCollocationFinder.from_documents(documents)
    finder.apply_freq_filter(min_freq)
    return finder.nbest(assoc measure, top n)
```

Let's see the following code, which can be used to classify a given instance using the available feature set:

Let's see the following code, which can be used for the extraction of features from the text:

```
def add_feat_extractor(self, function, **kwargs):
    self.feat_extractors[function].append(kwargs)

def extract_features(self, document):
    all_features = {}
    for extractor in self.feat_extractors:
        for param_set in self.feat_extractors[extractor]:
            feats = extractor(document, **param_set)
            all_features.update(feats)
        return all_features
```

Let's see the following code that can be used to perform training on the training file. Save classifier is used to save the output in a file:

```
def train(self, trainer, training_set, save_classifier=None,
**kwargs):
    print("Training classifier")
    self.classifier = trainer(training_set, **kwargs)
    if save_classifier:
        save_file(self.classifier, save_classifier)
    return self.classifier
```

Let's see the following code that can be used to perform testing and performance evaluation of our classifier using test data:

```
classifier = self.classifier
        print("Evaluating {0}
results...".format(type(classifier). name ))
        metrics results = {}
        if accuracy == True:
            accuracy score = eval accuracy(classifier, test set)
            metrics_results['Accuracy'] = accuracy_score
        gold results = defaultdict(set)
        test results = defaultdict(set)
        labels = set()
        for i, (feats, label) in enumerate(test_set):
            labels.add(label)
            gold results[label].add(i)
            observed = classifier.classify(feats)
            test results[observed].add(i)
        for label in labels:
            if precision == True:
                precision score = eval precision(gold results[label],
                    test results[label])
                metrics results['Precision [{0}]'.format(label)] =
precision score
            if recall == True:
                recall score = eval recall(gold results[label],
                    test results[label])
                metrics results['Recall [{0}]'.format(label)] =
recall score
            if f measure == True:
                f measure score = eval f measure(gold results[label],
                    test results[label])
                metrics results['F-measure [{0}]'.format(label)] =
f measure score
        if verbose == True:
            for result in sorted(metrics_results):
                print('{0}: {1}'.format(result,
metrics results[result]))
        return metrics results
```

Twitter can be considered as one of the most popular blogging services that is used to create messages referred to as *tweets*. These tweets comprise words that are either related to positive, negative, or neutral sentiments.

For performing sentiment analysis, we can use machine learning classifiers, statistical classifiers, or automated classifiers, such as the Naive Bayes Classifier, Maximum Entropy Classifier, Support Vector Machine Classifier, and so on.

These machine learning classifiers or automated classifiers are used to perform supervised classification, since they require training data for classification.

Let's see the following code in NLTK for feature extraction:

```
stopWords = []
#If there is occurrence of two or more same character, then replace
it with the character itself.
def replaceTwoOrMore(s):
    pattern = re.compile(r"(.)1{1,}", re.DOTALL)
    return pattern.sub(r"11", s)
def getStopWordList(stopWordListFileName):
    # This function will read the stopwords from a file and builds a
list.
    stopWords = []
    stopWords.append('AT USER')
    stopWords.append('URL')
    fp = open(stopWordListFileName, 'r')
    line = fp.readline()
    while line:
        word = line.strip()
        stopWords.append(word)
        line = fp.readline()
    fp.close()
    return stopWords
def getFeatureVector(tweet):
    featureVector = []
    #Tweets are firstly split into words
    words = tweet.split()
    for w in words:
        #replace two or more with two occurrences
        w = replaceTwoOrMore(w)
        #strip punctuation
        w = w.strip('\'"?,.')
        #Words begin with alphabet is checked.
        val = re.search(r"^[a-zA-Z][a-zA-Z0-9]*$", w)
        #If there is a stop word, then it is ignored.
        if (w in stopWords or val is None):
            continue
        else:
```

```
featureVector.append(w.lower())
    return featureVector
#end
#Tweets are read one by one and then processed.
fp = open('data/sampleTweets.txt', 'r')
line = fp.readline()
st = open('data/feature list/stopwords.txt', 'r')
stopWords = getStopWordList('data/feature list/stopwords.txt')
while line:
    processedTweet = processTweet(line)
    featureVector = getFeatureVector(processedTweet)
    print featureVector
    line = fp.readline()
#end loop
fp.close()
#Tweets are read one by one and then processed.
inpTweets = csv.reader(open('data/sampleTweets.csv', 'rb'),
delimiter=',', quotechar='|')
tweets = []
for row in inpTweets:
    sentiment = row[0]
    tweet = row[1]
    processedTweet = processTweet(tweet)
    featureVector = getFeatureVector(processedTweet, stopWords)
    tweets.append((featureVector, sentiment));
#Features Extraction takes place using following method
def extract features(tweet):
    tweet words = set(tweet)
    features = \{\}
    for word in featureList:
        features['contains(%s)' % word] = (word in tweet words)
    return features
```

During the training of a classifier, the input to the machine learning algorithm is a label and features. Features are obtained from the feature extractor when the input is given to the feature extractor. During prediction, a label is provided as an output of a classifier model and the input of the classifier model is the features that are obtained using the feature extractor. Let's have a look at a diagram explaining the same process:



Now, let's see the following code that can be used to perform sentiment analysis using the Naive Bayes Classifier:

```
NaiveBClassifier = nltk.NaiveBayesClassifier.train(training_set)
# Testing the classifiertestTweet = 'I liked this book on Sentiment
Analysis a lot.'
processedTestTweet = processTweet(testTweet)
print
NaiveBClassifier.classify(extract_features(getFeatureVector(processed
TestTweet)))
testTweet = 'I am so badly hurt'
processedTestTweet = processTweet(testTweet)
print
NBClassifier.classify(extract_features(getFeatureVector(processedTest
Tweet)))
```

Let's see the following code on sentiment analysis using maximum entropy:

```
TestTweet)))
print MaxEntClassifier.show_most_informative_features(10)
```

Evaluation of the NER system

Performance metrics or evaluation helps to show the performance of an NER system. The outcome of an NER tagger may be defined as the *response* and the interpretation of human beings as the *answer key*. So, we will provide the following definitions:

- Correct: If the response is exactly the same as the answer key
- **Incorrect**: If the response is not the same as the answer key
- Missing: If the answer key is found tagged, but the response is not tagged
- Spurious: If the response is found tagged, but the answer key is not tagged

The performance of an NER-based system can be judged by using the following parameters:

- **Precision (P)**: *P*=*Correct*/(*Correct*+*Incorrect*+*Missing*)
- **Recall (R)**: *R*=*Correct*/(*Correct*+*Incorrect*+*Spurious*)
- **F-Measure**: F-Measure = (2*P*R)/(P+R)

Let's see the code for NER using the HMM:

```
Function to find all tags in corpus *********
#******
def find tag set(tra lines):
global tag set
tag set = [ ]
for line in tra lines:
tok = line.split()
for t in tok:
wd = t.split("/")
if not wd[1] in tag set:
tag set.append(wd[1])
return
#****** Function to find frequency of each tag in tagged corpus
*******
defcnt tag(tr ln):
global start li
qlobal li
global tag set
global c
global line cnt
global lines
```

```
lines = tr ln
start li = [ ] # list of starting tags
find tag set(tr_ln)
line cnt = 0
for line in lines:
tok = line.split()
x = tok[0].split("/")
if not x[1] in start li:
start li.append(x[1])
line cnt = line cnt + 1
find freq tag()
find freq srttag()
return
def find freq tag():
global tag cnt
global tag set
tag cnt={}
i = 0
for w in tag set:
cal freq tag(tag set[i])
i = i + 1
tag cnt.update({w:freq tg})
return
defcal freq tag(tg):
global freq tg
global lines
freq tg = 0
for line in lines:
freq tg = freq tg + line.count(tg)
return
#******
           Function to find frequency of each starting tag in tagged
corpus ********
```

```
def find freq srttag():
global lst
lst = {}
           # start probability
i = 0
for w in start_li:
        cc = freq srt tag(start li[i])
prob = cc / line cnt
lst.update({start li[i]:prob})
i = i + 1
return
def freq srt tag(stg):
global lines
freq srt tg = 0
for line in lines:
tok = line.split()
ifstg in tok[0]:
freq srt tg = freq srt tg + 1
return(freq srt tg)
import tkinter as tk
import vit
import random
import cal start p
import calle prob
import trans mat
import time
import trans
import dict5
from tkinter import *
from tkinter import ttk
from tkinter.filedialog import askopenfilename
from tkinter.messagebox import showerror
import languagedetect1
import languagedetect3
e dict = dict()
t dict = dict()
def calculate1(*args):
import listbox1
def calculate2(*args):
import listbox2
def calculate3(*args):
```

```
import listbox3
def dispdlg():
global file name
root = tk.Tk()
root.withdraw()
file name = askopenfilename()
return
def tranhmm():
ttk.Style().configure("TButton", padding=6,
relief="flat", background="Pink", foreground="Red")
ttk.Button(mainframe, text="BROWSE",
command=find train corpus).grid(column=7, row=5, sticky=W)
# The following code will be used to display or accept the testing
corpus from the user.
def testhmm():
ttk.Button(mainframe, text="Develop a new testing Corpus",
command=calculate3).grid(column=9, row=5, sticky=E)
ttk.Button(mainframe, text="BROWSE",
command=find obs).grid(column=9, row=7, sticky=E)
#In HMM, We require parameters such as Start Probability, Transition
Probability and Emission Probability. The following code is used to
calculate emission probability matrix
def cal emit mat():
global emission probability
global corpus
global tlines
calle prob.m prg(e dict, corpus, tlines)
emission probability = e dict
return
# to calculate states
def cal states():
global states
global tlines
```

```
cal_start_p.cnt_tag(tlines)
states = cal start p.tag set
return
# to take observations
def find obs():
global observations
global test lines
global tra
global w4
global co
global tra
global wol
global wo2
global testl
global wo3
global te
global definitionText
global definitionScroll
global dt2
global ds2
global dt11
global ds11
wo3=[ ]
woo=[]
wo1=[ ]
wo2=[]
   co=0
w4=[]
if(flag2!=0):
definitionText11.pack forget()
definitionScroll11.pack forget()
dtl.pack forget()
ds1.pack forget()
dispdlg()
f = open(file name, "r+", encoding = 'utf-8')
test lines = f.readlines()
f.close()
fname="C:/Python32/file name1"
```

```
for x in states:
if not x in start probability:
start probability.update({x:0.0})
for line in test lines:
ob = line.split()
observations = ( ob )
fe=open("C:\Python32\output3 file","w+",encoding = 'utf-8')
fe.write("")
fe.close()
ff=open("C:\Python32\output4 file", "w+", encoding = 'utf-8')
ff.write("")
ff.close()
ff7=open("C:\Python32\output5 file","w+",encoding = 'utf-8')
ff7.write("")
ff7.close()
ff8=open("C:\Python32\output6 file","w+",encoding = 'utf-8')
ff8.write("")
ff8.close()
ff81=open("C:\Python32\output7 file", "w+", encoding = 'utf-8')
ff81.write("")
ff81.close()
dict5.search obs train corpus(file1, fname, tlines, test lines, observati
ons, states, start probability, transition probability,
emission probability)
f20 = open("C:\Python32\output5 file", "r+", encoding = 'utf-8')
te = f20.readlines()
tee=f20.read()
f = open(fname, "r+", encoding = 'utf-8')
train llines = f.readlines()
ds11 = Scrollbar(root)
dt11 = Text(root, width=10,
height=20,fg='black',bg='pink',yscrollcommand=ds11.set)
ds11.config(command=dt11.yview)
dt11.insert("1.0",train llines)
dt11.insert("1.0","\n")
```

```
dt11.insert("1.0","*****TRAINING SENTENCES*****")
     # an example of how to add new text to the text area
dt11.pack(padx=10,pady=150)
ds11.pack(padx=10,pady=150)
ds11.pack(side=LEFT, fill=BOTH)
dt11.pack(side=LEFT, fill=BOTH, expand=True)
ds2 = Scrollbar(root)
dt2 = Text(root, width=10,
height=10,fg='black',bg='pink',yscrollcommand=ds2.set)
ds2.config(command=dt2.yview)
dt2.insert("1.0",test lines)
dt2.insert("1.0","\n")
dt2.insert("1.0","\n")
dt2.insert("1.0","******TESTING SENTENCES*******")
     # an example of how to add new text to the text area
dt2.pack(padx=10,pady=150)
ds2.pack(padx=10,pady=150)
ds2.pack(side=LEFT, fill=BOTH)
dt2.pack(side=LEFT, fill=BOTH, expand=True)
definitionScroll = Scrollbar(root)
definitionText = Text(root, width=10,
```

dt11.insert("1.0","\n")

```
# an example of how to add new text to the text area
definitionText.pack(padx=10,pady=150)
definitionScroll.pack(padx=10,pady=150)
```

```
definitionScroll.pack(side=LEFT, fill=BOTH)
definitionText.pack(side=LEFT, fill=BOTH, expand=True)
```

```
l = tk.Label(root, text="NOTE:****The Entities which are not tagged
in Output are not Named Entities*****" , fg='black', bg='pink')
1.place(x = 500, y = 650, width=500, height=25)
    #ttk.Button(mainframe, text="View Parameters",
command=parame).grid(column=11, row=10, sticky=E)
    #definitionText.place(x= 19, y = 200,height=25)
f20.close()
f14 = open("C:\Python32\output2 file", "r+", encoding = 'utf-8')
testl = f14.readlines()
for lines in testl:
toke = lines.split()
for t in toke:
w4.append(t)
f14.close()
f12 = open("C:\Python32\output file","w+",encoding = 'utf-8')
f12.write("")
f12.close()
ttk.Button(mainframe, text="SAVE OUTPUT",
command=save output).grid(column=11, row=7, sticky=E)
ttk.Button (mainframe, text="NER EVALUATION",
command=evaluate).grid(column=13, row=7, sticky=E)
ttk.Button(mainframe, text="REFRESH", command=ref).grid(column=15,
row=7, sticky=E)
return
def ref():
root.destroy()
import new1
return
```

Let's see the following code in Python, which will be used to evaluate the output produced by NER using HMM:

```
def evaluate():
global wDict
global woe
global woe1
global woe2
woe1=[ ]
```

```
woe=[]
woe2=[]
ws=[ ]
wDict = \{\}
i=0
    j=0
    k=0
sp=0
f141 = open("C:\Python32\output1 file", "r+", encoding = 'utf-8')
tesl = f141.readlines()
for lines in tesl:
toke = lines.split()
for t in toke:
ws.append(t)
if t in wDict: wDict[t] += 1
else: wDict[t] = 1
for line in tlines:
tok = line.split()
for t in tok:
wd = t.split("/")
if(wd[1]!='OTHER'):
if t in wDict: wDict[t] += 1
else: wDict[t] = 1
print ("words in train corpus ",wDict)
for key in wDict:
i=i+1
print("total words in Dictionary are:",i)
for line in train lines:
toe=line.split()
for t1 in toe:
if '/' not in t1:
sp=sp+1
woe2.append(t1)
print("Spurious words are")
for w in woe2:
print(w)
print("Total spurious words are:",sp)
for 1 in te:
to=l.split()
for t1 in to:
if '/' in t1:
                #print(t1)
if t1 in ws or t1 in wDict:
woe.append(t1)
                     j=j+1
if t1 not in wDict:
```

```
wdd=t1.split("/")
ifwdd[0] not in woe2:
woel.append(t1)
                         k=k+1
print("Word found in Dict are:")
for w in woe:
print(w)
print("Word not found in Dict are:")
for w in woel:
print(w)
print("Total correctly tagged words are:",j)
print("Total incorrectly tagged words are:",k)
pr = (j) / (j+k)
re=(j)/(j+k+sp)
f141.close()
root=Tk()
root.title("NER EVALUATION")
root.geometry("1000x1000")
ds21 = Scrollbar(root)
dt21 = Text(root, width=10,
height=10,fg='black',bg='pink',yscrollcommand=ds21.set)
ds21.config(command=dt21.yview)
dt21.insert("1.0", (2*pr*re)/(pr+re))
dt21.insert("1.0","\n")
dt21.insert("1.0", "F-MEASURE=")
dt21.insert("1.0","\n")
dt21.insert("1.0", "F-MEASURE=(2*PRECISION*RECALL)/(PRECISION+RECALL)"
)
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
dt21.insert("1.0",re)
dt21.insert("1.0", "RECALL=")
dt21.insert("1.0","\n")
dt21.insert("1.0", "RECALL= CORRECT/(CORRECT +INCORRECT +SPURIOUS)")
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
dt21.insert("1.0",pr)
dt21.insert("1.0", "PRECISION=")
dt21.insert("1.0","\n")
dt21.insert("1.0", "PRECISION= CORRECT/(CORRECT +INCORRECT +MISSING)")
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
dt21.insert("1.0", "Total No. of Missing words are: 0")
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
dt21.insert("1.0", sp)
```

```
dt21.insert("1.0", "Total No. of Spurious Words are:")
dt21.insert("1.0","\n")
for w in woe2:
dt21.insert("1.0",w)
dt21.insert("1.0"," ")
dt21.insert("1.0", "Total Spurious Words are:")
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
dt21.insert("1.0",k)
dt21.insert("1.0", "Total No. of Incorrectly tagged words are:")
dt21.insert("1.0","\n")
for w in woel:
dt21.insert("1.0",w)
dt21.insert("1.0"," ")
dt21.insert("1.0","Total Incorrectly tagged words are:")
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
dt21.insert("1.0",j)
dt21.insert("1.0", "Total No. of Correctly tagged words are:")
dt21.insert("1.0","\n")
for w in woe:
dt21.insert("1.0",w)
dt21.insert("1.0"," ")
dt21.insert("1.0", "Total Correctly tagged words are:")
dt21.insert("1.0","\n")
dt21.insert("1.0","\n")
# an example of how to add new text to the text area
dt21.pack(padx=5,pady=5)
ds21.pack(padx=5,pady=5)
ds21.pack(side=LEFT, fill=BOTH)
```

```
dt21.pack(side=LEFT, fill=BOTH, expand=True)
dt21.pack(side=LEFT, fill=BOTH, expand=True)
root.mainloop()
return
def save_output():
    #dispdlg()
f = open("C:\Python32\save","w+",encoding = 'utf-8')
f20 = open("C:\Python32\output5_file","r+",encoding = 'utf-8')
te = f20.readlines()
for t in te:
f.write(t)
f.close()
```

```
f20.close()
# to calculate start probability matrix
def cal srt prob():
global start probability
start probability = cal start p.lst
return
# to print vitarbi parameter if required
def pr param():
11 = tk.Label(root, text="HMM Training is going on....Don't Click
any Button!!",fg='black',bg='pink')
11.place(x = 300, y = 150, height=25)
print("states")
print(states)
print(" ")
print(" ")
print("start probability")
print(start probability)
print(" ")
print(" ")
print("transition probability")
print(transition probability)
print(" ")
print(" ")
print("emission probability")
print(emission probability)
11 = tk.Label(root,
text="
                                            ")
11.place(x = 300, y = 150, height=25)
global flag1
    flag1=0
global flag2
    flag2=0
ttk.Button (mainframe, text="View Parameters",
command=parame).grid(column=7, row=5, sticky=W)
return
def parame():
global flag2
    flag2=flag1+1
```
```
global definitionText11
global definitionScroll11
definitionScroll11 = Scrollbar(root)
definitionText11 = Text(root, width=10,
height=10,fg='black',bg='pink',yscrollcommand=definitionScroll11.set)
    #definitionText.place(x= 19, y = 200, height=25)
definitionScroll11.config(command=definitionText11.yview)
definitionText11.delete("1.0", END) # an example of how to delete
all current text
definitionText11.insert("1.0", emission probability )
definitionText11.insert("1.0","\n")
definitionText11.insert("1.0", "Emission Probability")
definitionText11.insert("1.0","\n")
definitionText11.insert("1.0", transition probability)
definitionText11.insert("1.0", "Transition Probability")
definitionText11.insert("1.0","\n")
definitionText11.insert("1.0", start probability)
definitionText11.insert("1.0", "Start Probability")
     # an example of how to add new text to the text area
definitionText11.pack(padx=10,pady=175)
definitionScroll11.pack(padx=10,pady=175)
definitionScroll11.pack(side=LEFT, fill=BOTH)
definitionText11.pack(side=LEFT, fill=BOTH, expand=True)
return
# to calculate transition probability matrix
def cat trans prob():
global transition probability
global corpus
global tlines
trans mat.main prg(t dict, corpus, tlines)
transition probability = t dict
return
def find train corpus():
global train lines
global tlines
```

```
global c
global corpus
global words1
global w1
global train1
global fname
global file1
global ds1
global dt1
global w21
words1=[ ]
    c=0
w1=[ ]
w21=[]
f11 = open("C:\Python32\output1 file", "w+", encoding='utf-8')
f11.write("")
f11.close()
fr = open("C:\Python32\output file", "w+", encoding='utf-8')
fr.write("")
fr.close()
fgl=open("C:\Python32\ladetect1","w+",encoding = 'utf-8')
fgl.write("")
fgl.close()
fgl=open("C:\Python32\ladetect", "w+", encoding = 'utf-8')
fgl.write("")
fql.close()
dispdlq()
f = open(file name, "r+", encoding = 'utf-8')
train lines = f.readlines()
ds1 = Scrollbar(root)
dt1 = Text(root, width=10,
height=10,fg='black',bg='pink',yscrollcommand=ds1.set)
ds1.config(command=dt1.yview)
dt1.insert("1.0", train lines)
dt1.insert("1.0","\n")
dt1.insert("1.0","\n")
dt1.insert("1.0","******TRAINING SENTENCES*******")
     # an example of how to add new text to the text area
dt1.pack(padx=10,pady=175)
ds1.pack(padx=10,pady=175)
ds1.pack(side=LEFT, fill=BOTH)
dt1.pack(side=LEFT, fill=BOTH, expand=True)
```

```
fname="C:/Python32/file name1"
f = open(file name, "r+", encoding = 'utf-8')
    file1=file name
p = open(fname, "w+", encoding = 'utf-8')
corpus = f.read()
for line in train lines:
tok = line.split()
for t in tok:
n=t.split()
le=len(t)
i=0
             j=0
for n1 in n:
while(j<le):</pre>
if(n1[j]!='/'):
i=i+1
                         j=j+1
else:
                         j=j+1
if(i==le):
p.write(t)
p.write("/OTHER ")
                              #Handling Spurious words
else:
p.write(t)
p.write(" ")
p.write("\n")
p.close()
fname="C:/Python32/file name1"
f00 = open(fname, "r+", encoding = 'utf-8')
tlines = f00.readlines()
for line in tlines:
tok = line.split()
for t in tok:
wd = t.split("/")
if(wd[1]!='OTHER'):
if not wd[0] in words1:
words1.append(wd[0])
w1.append(wd[1])
f00.close()
```

```
f157 = open("C:\Python32\input file", "w+", encoding='utf-8')
f157.write("")
f157.close()
f1 = open("C:\Python32\input file", "w+", encoding='utf-8')
#input file has list of Named Entities of training file
for w in words1:
f1.write(w)
f1.write("\n")
fl.close()
fr=open("C:\Python32\detect", "w+", encoding = 'utf-8')
fr.write("")
fr.close()
f.close()
f.close()
cal states()
cal emit mat()
cal srt prob()
cat trans prob()
pr param()
return
root=Tk()
root.title("NAMED ENTITY RECOGNITION IN NATURAL LANGUAGES USING
HIDDEN MARKOV MODEL")
root.geometry("1000x1000")
mainframe = ttk.Frame(root, padding="20 20 12 12")
mainframe.grid(column=0, row=0, sticky=(N, W, E, S))
b=StringVar()
a=StringVar()
ttk.Style().configure("TButton", padding=6,
relief="flat",background="Pink", foreground="Red")
ttk.Button(mainframe, text="ANNOTATION",
command=calculate1).grid(column=5, row=3, sticky=W)
ttk.Button(mainframe, text="TRAIN HMM",
command=tranhmm).grid(column=7, row=3, sticky=E)
ttk.Button (mainframe, text="TEST HMM",
```

```
command=testhmm).grid(column=9, row=3, sticky=E)
ttk.Button(mainframe, text="HELP", command=hmmhelp).grid(column=11,
row=3, sticky=E)
# To call viterbi for particular observations find in find_obs
def call vitar():
global test lines
global train lines
global corpus
global observations
global states
global start probability
global transition probability
global emission probability
find train corpus()
cal states()
find obs()
cal emit mat()
cal srt prob()
cat trans prob()
   # print("Vitarbi Parameters are for selected corpus")
   # pr param()
    # -----To add all states not in start probability
_____
for x in states:
if not x in start probability:
start probability.update({x:0.0})
for line in test lines:
ob = line.split()
observations = ( ob )
print(" ")
print(" ")
print(line)
print("*******************************")
print (vit.viterbi (observations, states, start probability,
transition probability, emission probability),bg='Pink',fg='Red')
```

return

root.mainloop()

The preceding code in Python shows how NER is performed using the HMM, and how an NER system is evaluated using performance metrics (Precision, Recall and F-Measure).

Summary

In this chapter, we have discussed sentiment analysis using NER and machine learning techniques. We have also discussed the evaluation of an NER-based system..

In the next chapter, we'll discuss information retrieval, text summarization, stop word removal, questionanswering system, and more.

Chapter 8. Information Retrieval – Accessing Information

Information retrieval is one of the many applications of natural language processing. Information retrieval may be defined as the process of retrieving information (for example, the number of times the word *Ganga* has appeared in the document) corresponding to a query that has been made by the user.

This chapter will include the following topics:

- Introducing information retrieval
- Stop word removal
- Information retrieval using a vector space model
- Vector space scoring and query operator interactions
- Developing an IR system using latent semantic indexing
- Text summarization
- Question-answering system

Introducing information retrieval

Information retrieval may be defined as the process of retrieving the most suitable information as a response to the query being made by the user. In information retrieval, the search is performed based on metadata or context-based indexing. One example of information retrieval is Google Search in which, corresponding to each user query, a response is provided on the basis of the information retrieval algorithm being used. An indexing mechanism is used by the information retrieval algorithm. The indexing mechanism used is known as an inverted index. An IR system builds an index postlist to perform the information retrieval task.

Boolean retrieval is an information retrieval task in which a Boolean operation is applied to the postlist in order to retrieve relevant information.

The accuracy of an information retrieval task is measured in terms of precision and recall.

Suppose that a given IR system returns X documents when a query is fired. But the actual or gold set of documents that needs to be returned is Y.

Recall may be defined as the fraction of gold documents that a system finds. It may be defined as the ratio of true positives to the combination of true positives and false negatives.

Recall (R) = $(X \cap Y) / Y$

Precision may be defined as the fraction of documents that an IR system detects and are correct.

Precision (P) = $(X \cap Y) / X$

F-Measure may be defined as the harmonic mean of precision and recall.

 $F\text{-}Measure = 2 * (X \cap Y) / (X + Y)$

Stop word removal

While performing information retrieval, it is important to detect the stop words in a document and eliminate them.

Let's see the following code that can be used to provide the collection of stop words that can be detected in the English text in NLTK:

```
>>> import nltk
>>> fromnltk.corpus import stopwords
>>> stopwords.words('english')
['i', 'me', 'my', 'myself', 'we', 'our', 'ours', 'ourselves', 'you',
'your', 'yours', 'yourself', 'yourselves', 'he', 'him', 'his',
'himself', 'she', 'her', 'hers', 'herself', 'it', 'its', 'itself',
'they', 'them', 'their', 'theirs', 'themselves', 'what', 'which',
'who', 'whom', 'this', 'that', 'these', 'those', 'am', 'is', 'are',
'was', 'were', 'be', 'been', 'being', 'have', 'has', 'had',
'having', 'do', 'does', 'did', 'doing', 'a', 'an', 'the', 'and',
'but', 'if', 'or', 'because', 'as', 'until', 'while', 'of', 'at',
'by', 'for', 'with', 'about', 'against', 'between', 'into',
'through', 'during', 'before', 'after', 'above', 'below', 'to',
'from', 'up', 'down', 'in', 'out', 'on', 'off', 'over', 'under',
'again', 'further', 'then', 'once', 'here', 'there', 'when',
'where', 'why', 'how', 'all', 'any',
'both', 'each', 'few', 'more', 'most', 'other', 'some', 'such',
'no', 'nor', 'not', 'only', 'own', 'same', 'so', 'than', 'too',
'very', 's', 't', 'can', 'will', 'just', 'don', 'should', 'now']
```

NLTK consists of stop word corpus that comprises of 2,400 stop words from 11 different languages.

Let's see the following code in NLTK that can be used to find the fraction of words in a text that are not stop words:

```
>>> def not_stopwords(text):
    stopwords = nltk.corpus.stopwords.words('english')
    content = [w for w in text if w.lower() not in stopwords]
    return len(content) / len(text)
>>> not_stopwords(nltk.corpus.reuters.words())
0.7364374824583169
```

Let's see the following code in NLTK that can be used to remove the stop words from a given text. Here, the lower() function is used prior to the elimination of stop words so that the stop words in capital letters, such as A, are first converted into lower case letters and then eliminated:

```
import nltk
from collections import Counter
import string
fromnltk.corpus import stopwords
def get tokens():
    with open('/home/d/TRY/NLTK/STOP.txt') as stopl:
        tokens =
nltk.word tokenize(stopl.read().lower().translate(None,
string.punctuation))
    return tokens
if name == " main ":
    tokens = get tokens()
    print("tokens[:20]=%s") %(tokens[:20])
    count1 = Counter(tokens)
    print("before: len(count1) = %s") %(len(count1))
    filtered1 = [w for w in tokens if not w in
stopwords.words('english')]
    print("filtered1 tokens[:20]=%s") %(filtered1[:20])
    count1 = Counter(filtered1)
    print("after: len(count1) = %s") %(len(count1))
    print("most common = %s") %(count.most common(10))
    tagged1 = nltk.pos tag(filtered1)
    print("tagged1[:20]=%s") %(tagged1[:20])
```

Information retrieval using a vector space model

In a vector space model, documents are represented as vectors. One of the methods of representing documents as vectors is using **TF-IDF** (**Term Frequency-Inverse Document Frequency**).

Term frequency may be defined as the total number of times a given token exists in a document divided by the total number of tokens. It may also be defined as the frequency of the occurrence of certain terms in a given document.

The formula for term frequency (TF) is given as follows:

 $TF(t,d) = 0.5 + (0.5 * f(t,d)) / max \{f(w,d) : w \in d\}$

IDF may be defined as the inverse of document frequency. It is also defined as the document count that lies in the corpus in which a given term coexists.

IDF can be computed by finding the logarithm of the total number of documents present in a given corpus divided by the number of documents in which a particular token exists.

The formula for IDF(t,d) may be stated as follows:

 $IDF(t,D) = log(N/\{d\epsilon D : t\epsilon d\})$

The TF-IDF score can be obtained by multiplying both scores. This is written as follows:

TF-IDF(t, d, D) = TF(t, d) * IDF(t, D)

TF-IDF provides the estimate of the frequency of a term as present in the given document and how much it is being spread across the corpus.

In order to compute TF-IDF for a given document, the following steps are required:

- Tokenization of documents
- Computation of vector space model
- Computation of TF-IDF for each document

The process of tokenization involves tokenizing the text into sentences first. The individual sentences are then tokenized into words. The words, which are of no significance during information retrieval, also known as stop words, can then be removed.

Let's see the following code that can be used for performing tokenization on each document in a corpus:

```
authen = OAuthHandler(CLIENT_ID, CLIENT_SECRET, CALLBACK)
authen.set_access_token(ACCESS_TOKEN)
ap = API(authen)
venue = ap.venues(id='4bd47eeb5631c9b69672a230')
stopwords = nltk.corpus.stopwords.words('english')
tokenizer = RegexpTokenizer("[\w']+", flags=re.UNICODE)
def freq(word, tokens):
return tokens.count(word)
#Compute the frequency for each term.
vocabulary = []
docs = {}
all_tips = []
for tip in (venue.tips()):
```

```
tokens = tokenizer.tokenize(tip.text)
bitokens = bigrams(tokens)
tritokens = trigrams(tokens)
tokens = [token.lower() for token in tokens if len(token) > 2]
tokens = [token for token in tokens if token not in stopwords]
bitokens = [' '.join(token).lower() for token in bitokens]
bitokens = [token for token in bitokens if token not in stopwords]
tritokens = [' '.join(token).lower() for token in tritokens]
tritokens = [token for token in tritokens if token not in stopwords]
ftokens = []
ftokens.extend(tokens)
ftokens.extend(bitokens)
ftokens.extend(tritokens)
docs[tip.text] = {'freq': {}}
for token in ftokens:
docs[tip.text]['freq'][token] = freq(token, ftokens)
print docs
```

The next step performed after tokenization is the normalization of the tf vector. Let's see the following code that performs the normalization of the tf vector:

```
authen = OAuthHandler(CLIENT_ID, CLIENT_SECRET, CALLBACK)
authen.set_access_token(ACCESS_TOKEN)
ap = API(auth)
venue = ap.venues(id='4bd47eeb5631c9b69672a230')
stopwords = nltk.corpus.stopwords.words('english')
tokenizer = RegexpTokenizer("[\w']+", flags=re.UNICODE)
def freq(word, tokens):
return tokens.count(word)
def word_count(tokens):
return len(tokens)
def tf(word, tokens):
return (freq(word, tokens) / float(word count(tokens)))
```

```
#Compute the frequency for each term.
vocabulary = []
docs = \{\}
all tips = []
for tip in (venue.tips()):
tokens = tokenizer.tokenize(tip.text)
bitokens = bigrams(tokens)
tritokens = trigrams(tokens)
tokens = [token.lower() for token in tokens if len(token) > 2]
tokens = [token for token in tokens if token not in stopwords]
bitokens = [' '.join(token).lower() for token in bitokens]
bitokens = [token for token in bitokens if token not in stopwords]
tritokens = [' '.join(token).lower() for token in tritokens]
tritokens = [token for token in tritokens if token not in stopwords]
ftokens = []
ftokens.extend(tokens)
ftokens.extend(bitokens)
ftokens.extend(tritokens)
docs[tip.text] = {'freq': {}, 'tf': {}}
for token in ftokens:
        #The Computed Frequency
docs[tip.text]['freq'][token] = freq(token, ftokens)
        # Normalized Frequency
docs[tip.text]['tf'][token] = tf(token, ftokens)
```

print docs

Let's see the following code for computing the TF-IDF:

```
authen = OAuthHandler(CLIENT_ID, CLIENT_SECRET, CALLBACK)
authen.set_access_token(ACCESS_TOKEN)
ap = API(authen)
```

```
venue = ap.venues(id='4bd47eeb5631c9b69672a230')
stopwords = nltk.corpus.stopwords.words('english')
tokenizer = RegexpTokenizer("[\w']+", flags=re.UNICODE)
```

def freq(word, doc):

```
return doc.count(word)
def word count(doc):
return len(doc)
def tf(word, doc):
return (freq(word, doc) / float(word count(doc)))
def num docs containing (word, list of docs):
count = 0
for document in list of docs:
if freq(word, document) > 0:
count += 1
return 1 + count
def idf(word, list of docs):
return math.log(len(list of docs) /
float(num docs containing(word, list of docs)))
#Compute the frequency for each term.
vocabulary = []
docs = \{\}
all tips = []
for tip in (venue.tips()):
tokens = tokenizer.tokenize(tip.text)
bitokens = bigrams(tokens)
tritokens = trigrams(tokens)
tokens = [token.lower() for token in tokens if len(token) > 2]
tokens = [token for token in tokens if token not in stopwords]
bitokens = [' '.join(token).lower() for token in bitokens]
bitokens = [token for token in bitokens if token not in stopwords]
tritokens = [' '.join(token).lower() for token in tritokens]
tritokens = [token for token in tritokens if token not in stopwords]
ftokens = []
ftokens.extend(tokens)
ftokens.extend(bitokens)
ftokens.extend(tritokens)
docs[tip.text] = {'freq': {}, 'tf': {}, 'idf': {}}
```

```
for token in ftokens:
    #The frequency computed for each tip
docs[tip.text]['freq'][token] = freq(token, ftokens)
    #The term-frequency (Normalized Frequency)
docs[tip.text]['tf'][token] = tf(token, ftokens)
vocabulary.append(ftokens)
for doc in docs:
for token in docs[doc]['tf']:
    #The Inverse-Document-Frequency
docs[doc]['idf'][token] = idf(token, vocabulary)
```

print docs

TF-IDF is computed by finding the product of TF and IDF. The large value of TF-IDF is computed when there is an occurrence of high term frequency and low document frequency.

Let's see the following code for computing the TF-IDF for each term in a document:

```
authen = OAuthHandler(CLIENT ID, CLIENT SECRET, CALLBACK)
authen.set access token (ACCESS TOKEN)
ap = API (authen)
venue = ap.venues(id='4bd47eeb5631c9b69672a230')
stopwords = nltk.corpus.stopwords.words('english')
tokenizer = RegexpTokenizer("[\w']+", flags=re.UNICODE)
def freq(word, doc):
return doc.count(word)
def word count (doc):
return len(doc)
def tf(word, doc):
return (freq(word, doc) / float(word count(doc)))
def num docs containing(word, list_of_docs):
count = 0
for document in list of docs:
if freq(word, document) > 0:
```

```
count += 1
return 1 + count
def idf(word, list of docs):
return math.log(len(list of docs) /
float(num docs containing(word, list of docs)))
def tf idf(word, doc, list of docs):
return (tf(word, doc) * idf(word, list_of_docs))
#Compute the frequency for each term.
vocabulary = []
docs = \{\}
all tips = []
for tip in (venue.tips()):
tokens = tokenizer.tokenize(tip.text)
bitokens = bigrams(tokens)
tritokens = trigrams(tokens)
tokens = [token.lower() for token in tokens if len(token) > 2]
tokens = [token for token in tokens if token not in stopwords]
bitokens = [' '.join(token).lower() for token in bitokens]
bitokens = [token for token in bitokens if token not in stopwords]
tritokens = [' '.join(token).lower() for token in tritokens]
tritokens = [token for token in tritokens if token not in stopwords]
ftokens = []
ftokens.extend(tokens)
ftokens.extend(bitokens)
ftokens.extend(tritokens)
docs[tip.text] = {'freq': {}, 'tf': {}, 'idf': {},
                        'tf-idf': {}, 'tokens': []}
for token in ftokens:
        #The frequency computed for each tip
docs[tip.text]['freq'][token] = freq(token, ftokens)
        #The term-frequency (Normalized Frequency)
docs[tip.text]['tf'][token] = tf(token, ftokens)
docs[tip.text]['tokens'] = ftokens
vocabulary.append(ftokens)
for doc in docs:
```

```
for token in docs[doc]['tf']:
        #The Inverse-Document-Frequency
docs[doc]['idf'][token] = idf(token, vocabulary)
        #The tf-idf
docs[doc]['tf-idf'][token] = tf idf(token, docs[doc]['tokens'],
vocabulary)
#Now let's find out the most relevant words by tf-idf.
words = \{\}
for doc in docs:
for token in docs[doc]['tf-idf']:
if token not in words:
words[token] = docs[doc]['tf-idf'][token]
else:
if docs[doc]['tf-idf'][token] > words[token]:
words[token] = docs[doc]['tf-idf'][token]
for item in sorted(words.items(), key=lambda x: x[1], reverse=True):
print "%f <= %s" % (item[1], item[0])</pre>
```

Let's see the following code for mapping keywords to the vector's dimension:

```
>>> def getVectkeyIndex(self,documentList):
    vocabString=" ".join(documentList)
    vocabList=self.parser.tokenise(vocabString)
    vocabList=self.parser.removeStopWords(vocabList)
    uniquevocabList=util.removeDuplicates(vocabList)
    vectorIndex={}
    offset=0
```

```
for word in uniquevocabList:
        vectorIndex[word]=offset
        offset+=1
return vectorIndex
```

Let's see the following code for mapping document strings to vectors:

```
>>> def makeVect(self,wordString):
    vector=[0]*len(self.vectorkeywordIndex)
    wordList=self.parser.tokenise(wordString)
    wordList=self.parser.removeStopWords(wordList)
    for word in wordList:
        vector[self.vectorkeywordIndex[word]]+=1;
    return vector
```

Vector space scoring and query operator interaction

Vector space model is used for the representation of meanings in the form of vectors of lexical items. A vector space model can easily be modeled using linear algebra. So the similarity between vectors can be computed easily.

Vector size is used to represent the size of the vector being used that represents a particular context. The window-based method and dependency-based method are used for the modeling context. In the window-based method, the context is determined using the occurrence of words within the window of a particular size. In a dependency-based method, the context is determined when there is an occurrence of a word in a particular syntactic relation with the corresponding target word. Features or contextual words are stemmed and lemmatized. Similarity metrics can be used to compute the similarity between the two vectors.

Let's see the following list of similarity metrics:

Measure	Definition
Euclidean	$\frac{1}{1+\sqrt{\sum_{i=1}^{n}(u_{i}-v_{i})^{2}}}$
Cityblock	$\frac{1}{1+\sum_{i=1}^{n} u_i-v_i }$
Chebyshev	$\frac{1}{1 + \max_i u_i - v_i }$
Cosine	$\frac{u.v}{ u v }$
Correlation	$\frac{(u-\mu_u).(v-\mu_v)}{ u v }$
Dice	$\frac{2\sum_{i=0}^{n}\min(u_i, v_i)}{\sum_{i=0}^{n}u_i + v_i}$
Jaccard	$\frac{u.v}{\sum_{i=0}^{n} u_i + v_i}$
Jaccard2	$\frac{\sum_{i=0}^{n} min(u_i, v_i)}{\sum_{i=0}^{n} max(u_i, v_i)}$
Lin	$\frac{\sum_{i=0}^{n} u_i + v_i}{ u + v }$
Tanimoto	$\frac{u.v}{ u + v -u.v}$
Jensen-Shannon Div	$1 - \frac{\frac{1}{2} \left(D\left(u \left\ \frac{u+v}{2} \right) + D\left(v \left\ \frac{u+v}{2} \right) \right)}{\sqrt{2\log 2}} \right)}{\sqrt{2\log 2}}$
α -skew	$1 - \frac{D\left(u \ \alpha v + (1 - \alpha)u\right)}{\sqrt{2\log 2}}$

Weighting scheme is another term that is very important as it provides information that the given context is more related to the target word.

Scheme	Definition
None	$w_{ij} = f_{ij}$
TF-IDF	$w_{ij} = \log(f_{ij}) \times \log\left(\frac{N}{n_j}\right)$
TF-ICF	$w_{ij} = \log(f_{ij}) \times \log\left(\frac{N}{f_j}\right)$
Okapi BM25	$w_{ij} = \frac{f_{\bar{e}}}{0.5 + 1.5 \times \frac{f_j}{\frac{f_j}{j}} + f_{ij}} \log \frac{N - n_j + 0.5}{f_{\bar{e}} + 0.5}$
ATC	$w_{ij} = \frac{\left(0.5 + 0.5 \times \frac{f_{ij}}{\max_{f}}\right) \log\left(\frac{N}{n_{j}}\right)}{\sqrt{\sum_{i=1}^{N} \left[\left(0.5 + 0.5 \times \frac{f_{ij}}{\max_{f}}\right) \log\left(\frac{N}{n_{j}}\right)\right]^{2}}}$
נדט	$w_{ij} = \frac{\left(\log\left(f_{ij}\right) + 1.0\right)\log\left(\frac{N}{n_{j}}\right)}{0.8 + 0.2 \times f_{j} \times \frac{j}{f_{j}}}$
MI	$w_{ij} = \log \frac{P\left(t_{ij} \mid c_j\right)}{P\left(t_{ij}\right)P\left(c_j\right)}$
PosMI	$\max(0, MI)$
T-Test	$w_{ij} = \frac{P(t_{ij} \mid c_j) - P(t_{ij})P(c_j)}{\sqrt{P(t_{ij})P(c_j)}}$
χ^2	see(Curran, 2004, p.83)
Lin98a	$w_{ij} = \frac{f_{ij} \times f}{f_i \times f_j}$
Lin98b	$w_{ij} = -1 \times \log \frac{n_j}{N}$
Gref94	$w_{ij} = \frac{\log f_{ij} + 1}{\log n_i + 1}$

Let's see the list of weighting schemes that can be considered:

Developing an IR system using latent semantic indexing

Latent semantic indexing can be used for performing categorization with the help of minimum training.

Latent semantic indexing is a technique that can be used for processing text. It can perform the following:

- Automatic categorization of text
- Conceptual information retrieval
- Cross-lingual information retrieval

Latent semantic method may be defined as an information retrieval and indexing method. It makes use of a mathematical technique known as **Singular Value Decomposition** (**SVD**). SVD is used for the detection of patterns having a certain relation with the concepts contained in a given unstructured text.

Some of the applications of latent semantic indexing include the following:

- Information discovery
- Automated document classification text summarization[20] (eDiscovery, Publishing)
- Relationship discovery
- Automatic generation of the link charts of individuals and organizations
- Matching technical papers and grants with reviewers
- Online customer support
- Determining document authorship
- Automatic keyword annotation of images
- Understanding software source code
- Filtering spam
- Information visualization
- Essay scoring
- Literature-based discovery

Text summarization

Text summarization is the process of generating summaries from a given long text. Based on the Luhn work, *The Automatic Creation of Literature Abstracts* (1958), a naïve summarization approach known as NaiveSumm is developed. It makes use of a word's frequencies for the computation and extraction of sentences that consist of the most frequent words. Using this approach, text summarization can be performed by extracting a few specific sentences.

Let's see the following code in NLTK that can be used for performing text summarization:

```
from nltk.tokenize import sent tokenize, word tokenize
from nltk.corpus import stopwords
from collections import defaultdict
from string import punctuation
from heapq import nlargest
class Summarize Frequency:
  def __init__(self, cut_min=0.2, cut_max=0.8):
     Initilize the text summarizer.
    Words that have a frequency term lower than cut min
     or higer than cut max will be ignored.
    .....
    self. cut min = cut min
    self. cut max = cut max
    self. stopwords = set(stopwords.words('english') +
list(punctuation))
  def _compute_frequencies(self, word_sent):
      Compute the frequency of each of word.
      Input:
       word sent, a list of sentences already tokenized.
      Output:
       freq, a dictionary where freq[w] is the frequency of w.
    .....
    freq = defaultdict(int)
    for s in word sent:
      for word in s:
        if word not in self. stopwords:
          freq[word] += 1
    # frequencies normalization and fitering
    m = float(max(freq.values()))
    for w in freq.keys():
      freq[w] = freq[w]/m
      if freq[w] >= self. cut max or freq[w] <= self. cut min:
```

```
del freq[w]
    return freq
  def summarize(self, text, n):
    ** ** **
list of (n) sentences are returned.
summary of text is returned.
    .....
    sents = sent tokenize(text)
    assert n <= len(sents)</pre>
    word sent = [word tokenize(s.lower()) for s in sents]
    self. freq = self. compute frequencies(word sent)
    ranking = defaultdict(int)
    for i,sent in enumerate(word sent):
      for w in sent:
        if w in self. freq:
          ranking[i] += self. freq[w]
    sents idx = self. rank(ranking, n)
    return [sents[j] for j in sents idx]
  def rank(self, ranking, n):
    """ return the first n sentences with highest ranking """
    return nlargest(n, ranking, key=ranking.get)
```

The preceding code computes the term frequency for each word and then the most frequent words, such as determiners, may be eliminated as they are not of much use while performing information retrieval tasks.

Question-answering system

Question-answering systems are referred to as intelligent systems that can be used to provide responses for the questions being asked by the user based on certain facts or rules stored in the knowledge base. So the accuracy of a question-answering system to provide a correct response depends on the rules or facts stored in the knowledge base.

One of the many issues involved in a question-answering system is how the responses and questions would be represented in the system. Responses may be retrieved and then represented using text summarization or parsing. Another issue involved in the question-answering system is how the questions and the corresponding answers are represented in a knowledge base.

To build a question-answering system, various approaches, such as the named entity recognition, information retrieval, information extraction, and so on, can be applied.

A question-answering system involves three phases:

- Extraction of facts
- Understanding of questions
- Generation of answers

Extraction of facts is performed in order to understand domain-specific data and generate a response for a given query.

Extraction of facts can be performed in two ways using: extraction of entity and extraction of relation. The process of extraction of entity or extraction of proper nouns is referred to as NER. The process of extraction of relation is based on the extraction of semantic information from the text.

Understanding of questions involves the generation of a parse tree from a given text.

The generation of answers involves obtaining the most likely response for a given query that can be understood by the user.

Let's see the following code in NLTK that can be used to accept a query from a user user. This query can be processed by removing stop words from it so that information retrieval can be performed post processing:

```
import nltk
from nltk import *
import string
print "Enter your question"
ques=raw input()
ques=ques.lower()
stopwords=nltk.corpus.stopwords.words('english')
cont=nltk.word_tokenize(question)
analysis keywords=list( set(cont) -set(stopwords) )
```

Summary

In this chapter, we have discussed information retrieval. We have mainly learned about stop words removal. Stop words are eliminated so that information retrieval and text summarization tasks become faster. We have also discussed the implementation of text summarization, question-answering systems, and vector space models.

In the next chapter, we'll study the concepts of discourse analysis and anaphora resolution.

Chapter 9. Discourse Analysis – Knowing Is Believing

Discourse analysis is another one of the applications of Natural Language Processing. Discourse analysis may be defined as the process of determining contextual information that is useful for performing other tasks, such as **anaphora resolution (AR)** (we will cover this section later in this chapter), NER, and so on.

This chapter will include the following topics:

- Introducing discourse analysis
- Discourse analysis using Centering Theory
- Anaphora resolution

Introducing discourse analysis

The word *discourse* in linguistic terms means language in use. Discourse analysis may be defined as the process of performing text or language analysis, which involves text interpretation and knowing the social interactions. Discourse analysis may involve dealing with morphemes, n-grams, tenses, verbal aspects, page layouts, and so on. Discourse may be defined as the sequential set of sentences.

In most cases, we can interpret the meaning of the sentence on the basis of the preceding sentences.

Consider a discourse John went to the club on Saturday. He met Sam." Here, He refers to John.

Discourse Representation Theory (DRT) has been developed to provide a means for performing AR. A **Discourse Representation Structure (DRS)** has been developed that provides the meaning of discourse with the help of discourse referents and conditions. Discourse referents refer to variables used in first-order logic and things under consideration in a discourse. A discourse representation structure's conditions refer to the atomic formulas used in first-order predicate logic.

First Order Predicate Logic (FOPL) was developed to extend the idea of propositional logic. FOPL involves the use of functions, arguments, and quantifiers. Two types of quantifiers are used to represent the general sentences, namely, universal quantifiers and existential quantifiers. In FOPL, connectives, constants, and variables are also used. For instance, Robin is a bird can be represented in FOPL as bird (robin).

Let's see an example of the discourse representation structure:



The preceding diagram is a representation of the following sentences:

- 1. John went to a club
- 2. John went to a club. He met Sam.

Here, the discourse consists of two sentences. Discourse Structure Representation may represent the entire text. For computationally processing DRS, it needs to be converted into a linear format.

The NLTK module that can be used to provide first order predicate logic implementation is nltk.sem.logic. Its UML diagram is shown here:



The nltk.sem.logic module is used to define the expressions of first order predicate logic. Its UML diagram is comprised of various classes that are required for the representation of objects in first order predicate logic as well as their methods. The methods that are included are as follows:

- substitute_bindings(bindings): Here, binding represents variable-to-expression mapping. It replaces variables present in the expression with a specific value.
- Variables (): This comprises a set of all the variables that need to be replaced. It consists of constants as well as free variables.
- replace (variable, expression, replace_bound): This is used for substituting the expression for a variable instance; replace_bound is used to specify whether we need to replace bound variables or not.
- Normalize (): This is used to rename the autogenerated unique variables.
- Visit (self, function, combinatory, default): This is used to visit subexpression calling functions; results are passed to the combinator that begins with a default value. Results of the combination are returned.
- free (indvar_only): This is used to return the set of all the free variables of the object. Individual variables are returned if indvar_only is set to True.
- Simplify(): This is used to simplify the expression that represents an object.

The NLTK module that provides a base for the discourse representation theory is nltk.sem.drt. It is built on top of nltk.sem.logic. Its UML class diagram comprises classes that are inherited from the nltk.sem.logic module. The following are the methods described in this module:

- The get refs (recursive): This method obtains the referents for the current discourse.
- The fol(): This method is used for the conversion of DRS into first order predicate logic.
- The draw(): This method is used for drawing DRS with the help of the Tkinter graphics library.

Let's see the UML class diagram of the nltk.sem.drt module:



The NLTK module that provides access to WordNet 3.0 is nltk.corpus.reader.wordnet.

Linear format comprises discourse referents and DRS conditions, for example:

([x], [John(x), Went(x)])

Let's see the following code in NLTK, which can be used for the implementation of DRS:

```
>>> import nltk
>>> expr read = nltk.sem.DrtExpression.from string
```

```
>>> expr1 = expr_read('([x], [John(x), Went(x)])')
>>> print(expr1)
([x],[John(x), Went(x)])
>>> expr1.draw()
>>> print(expr1.fol())
exists x.(John(x) & Went(x))
```

The preceding code of NLTK will draw the following image:



Here, the expression is converted into FOPL using the fol() method.

Let's see the following code in NLTK for the other expression:

```
>>> import nltk
>>> expr_read = nltk.sem.DrtExpression.from string
>>> expr2 = expr_read('([x,y], [John(x), Went(x),Sam(y),Meet(x,y)])')
>>> print(expr2)
([x,y],[John(x), Went(x), Sam(y), Meet(x,y)])
>>> expr2.draw()
>>> print(expr2.fol())
exists x y.(John(x) & Went(x) & Sam(y) & Meet(x,y))
```

The fol() function is used to obtain the first order predicate logic equivalent of the expression. The preceding code displays the following image:

Ø	
Γ	xv
	John(x)
	Went(x)
	Sam(y)
	Meet(x, y)

We can perform the concatenation of two DRS using the DRS concatenation operator (+). Let's see the following code in NLTK that can be used to perform the concatenation of two DRS:

```
>>> import nltk
>>> expr_read = nltk.sem.DrtExpression.from string
>>> expr3 = expr_read('([x], [John(x), eats(x)])+
([y],[Sam(y),eats(y)])')
>>> print(expr3)
(([x],[John(x), eats(x)]) + ([y],[Sam(y), eats(y)]))
>>> print(expr3.simplify())
([x,y],[John(x), eats(x), Sam(y), eats(y)])
>>> expr3.draw()
```

The preceding code draws the following image:



Here, simplify () is used to simplify the expression.

Let's see the following code in NLTK, which can be used to embed one DRS into another:

```
>>> import nltk
>>> expr_read = nltk.sem.DrtExpression.from string
>>> expr4 =
expr_read('([],[(([x],[student(x)])->([y],[book(y),read(x,y)]))])')
>>> print(expr4.fol())
all x.(student(x) -> exists y.(book(y) & read(x,y)))
```

Let's see another example that can be used to combine two sentences. Here, PRO has been used and resolve anaphora () is used to perform AR:

```
>>> import nltk
>>> expr_read = nltk.sem.DrtExpression.from string
>>> expr5 = expr_read('([x,y],[ram(x),food(y),eats(x,y)])')
>>> expr6 = expr_read('([u,z],[PRO(u),coffee(z),drinks(u,z)])')
>>> expr7=expr5+expr6
>>> print(expr7.simplify())
([u,x,y,z],[ram(x), food(y), eats(x,y), PRO(u), coffee(z),
drinks(u,z)])
```

>>> print(expr7.simplify().resolve_anaphora())
([u,x,y,z],[ram(x), food(y), eats(x,y), (u = [x,y,z]), coffee(z),
drinks(u,z)])

Discourse analysis using Centering Theory

Discourse analysis using Centering Theory is the first step toward corpus annotation. It also involves the task of AR. In Centering Theory, we perform the task of segmenting discourse into various units for analysis.

Centering Theory involves the following:

- Interaction between purposes or intentions of discourse participants and discourse
- Attention of participants
- Discourse structure

Centering is related to participants attention and how the local as well as global structures affect expressions and the coherence of discourse.

Anaphora resolution

AR may be defined as the process by which a pronoun or a noun phrase used in the sentence is resolved and refers to a specific entity on the basis of discourse knowledge.

For example:

John helped Sara. He was kind.

Here, He refers to John.

AR is of three types, namely:

- **Pronominal**: Here, the referent is referred to by a pronoun. For example, Sam found the love of his life. Here, 'his' refers to 'Sam'.
- **Definite noun phrase**: Here, the antecedent may be referred to by the phrase of the form, <the><noun phrase>. For example, The relationship could not last long. Here, The relationship refers to the love in the previous sentence.
- Quantifier/ordinal: The quantifier, such as one, and the ordinal, such as first, are also examples of AR. For example, He began a new one. Here, one refers to the relationship.

In cataphora, the referent precedes the antecedent. For example, After his class, Sam will go home. Here, his refers to Sam.

For integrating some extensions in a NLTK architecture, a new module is developed on top of the existing modules, nltk.sem.logic and nltk.sem.drt. The new module acts like a replacement for the nltk.sem.drt module. There is a replacement of all the classes with the enhanced classes.

A method called resolve() can be called indirectly and directly from a class called AbstractDRS(). It then provides a list consisting of resolved copies of a particular object. An object that needs to be resolved must override the readings() method. The resolve() method is used to generate readings using the traverse() function. The traverse() function is used to perform sorting on the list of operations. A priority order list includes the following:

- Binding operations
- Local accommodation operations
- Intermediate accommodation operations
- Global accommodation operations

Let's see the flow diagram of the traverse () function:


After the priority order of operations is generated, the following takes place:

- Readings are generated from the operation with the help of the deepcopy () method. The current operation is taken as an argument.
- When the readings () method runs, a list of operations are performed.
- Till the list of operations is not empty, run is performed on those operations.
- If there are no operations left to be performed, admissibility check will be run on the final reading; if the check is successful, it will be stored.

In AbstractDRS(), the resolve() method is defined. It is defined as follows:

def resolve(self, verbose=False)

The PresuppositionDRS class includes the following methods:

- find_bindings(drs_list, collect_event_data): Bindings are found from the list of DRS instances using the is_possible_binding method. Collection of participation information is done if collect event data is set to True.
- is_possible_binding (cond): This finds out whether the condition is a binding candidate and makes sure that it is an unary predicate with the features that match the trigger conditions.
- is_presupposition.cond(cond): This is used to identify a trigger condition among all the conditions.
- presupposition_readings(trail): This is like readings in the subclasses of PresuppositionDRS.

Let's see the classes that are inherited from AbstractDRS:



Let's see the classes that are inherited in DRTAbstractVariableExpression:



Let's see the classes inherited from DrtBooleanExpression:



Let's see the classes inherited from DrtApplicationExpression:



Let's see the classes inherited from DRS:



Summary

In this chapter, we have discussed discourse analysis, discourse analysis using Centering Theory, and anaphora resolution. We have discussed the discourse representation structure that is built using first order predicate logic. We have also discussed how NLTK can be used to implement first order predicate logic using UML diagrams.

In the next chapter, we will discuss the evaluation of NLP Tools. We will also discuss various metrics for error identification, lexical matching, syntactic matching, and shallow semantic matching.

Chapter 10. Evaluation of NLP Systems – Analyzing Performance

The evaluation of NLP systems is performed so that we can analyze whether a given NLP system produces the desired result or not and the desired performance is achieved or not. Evaluation may be performed automatically using predefined metrics, or it may be performed manually by comparing human output with the output obtained by an NLP system.

This chapter will include the following topics:

- The need for the evaluation of NLP systems
- Evaluation of NLP tools (POS Taggers, Stemmers, and Morphological Analyzers)
- Parser evaluation using gold data
- The evaluation of an IR system
- Metrics for error identification
- Metrics based on lexical matching
- Metrics based on syntactic matching
- Metrics using shallow semantic matching

The need for evaluation of NLP systems

Evaluation of NLP systems is done so as to analyze whether the output given by the NLP systems is similar to the one expected from the human output. If errors in the module are identified at an early stage, then the cost of correcting the NLP system is reduced to quite an extent.

Suppose we want to evaluate a tagger. We can do this by comparing the output of the tagger with the human output. Many a times, we do not have access to an impartial or expert human. So we can construct a gold standard test data to perform the evaluation of our tagger. This is a corpus, which has been tagged manually and is considered as a standard corpus that can be used for the evaluation of our tagger. The tagger is considered as correct if the output in the form of a tag given by the tagger is the same as that provided by the gold standard test data.

Creation of a gold standard annotated corpus is a major task and is also very expensive. It is performed by manually tagging a given test data. The tags chosen in this manner are taken as standard tags that can be used to represent a wide range of information.

Evaluation of NLP tools (POS taggers, stemmers, and morphological analyzers)

We can perform the evaluation of NLP systems, such as POS taggers, stemmers, morphological analyzers, NER-based systems, machine translators, and so on. Consider the following code in NLTK that can be used to train a unigram tagger. Sentence tagging is performed and then an evaluation is done to check whether the output given by the tagger is the same as the gold standard test data:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> sentences=brown.tagged_sents(categories='news')
>>> sent=brown.sents(categories='news')
>>> unigram_sent=nltk.UnigramTagger(sentences)
>>> unigram_sent.tag(sent[2008])
[('Others', 'NNS'), (',', ','), ('which', 'WDT'), ('are', 'BER'),
('reached', 'VBN'), ('by', 'IN'), ('walking', 'VBG'), ('up', 'RP'),
('a', 'AT'), ('single', 'AP'), ('flight', 'NN'), ('of', 'IN'),
('stairs', 'NNS'), (',', ','), ('have', 'HV'), ('balconies', 'NNS'),
('.', '.')]
>>> unigram_sent.evaluate(sentences)
0.9349006503968017
```

Consider the following code in NLTK in which the training and testing of Unigram tagger is performed on separate data. A given data is split into 80% training data and 20% testing data:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> sentences=brown.tagged_sents(categories='news')
>>> sz=int(len(sentences)*0.8)
>>> sz
3698
>>> training_sents = sentences[:sz]
>>> testing_sents=sentences[sz:]
>>> unigram_tagger=nltk.UnigramTagger(training_sents)
>>> unigram_tagger.evaluate(testing_sents)
0.8028325063827737
```

Consider the following code in NLTK that demonstrates the use of N-Gram tagger. Here, Training corpus consists of tagged data. Also, in the following example, we have used a special case of n-gram tagger, that is, bigram tagger:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> sentences=brown.tagged_sents(categories='news')
>>> sz=int(len(sentences)*0.8)
>>> training_sents = sentences[:sz]
>>> testing_sents=sentences[sz:]
>>> bigram_tagger=nltk.UnigramTagger(training_sents)
>>> bigram_tagger=nltk.BigramTagger(training_sents)
>>> bigram_tagger.tag(sentences[2008])
[(('Others', 'NNS'), None), ((',', ','), None), (('which', 'WDT'),
None), (('are', 'BER'), None), (('reached', 'VBN'), None), (('by',
'IN'), None), (('walking', 'VBG'), None), (('up', 'IN'), None),
(('a', 'AT'), None), (('single', 'AP'), None), (('flight', 'NN'),
None), (('of', 'IN'), None), (('stairs', 'NNS'), None), ((',', ','))
```

```
None), (('have', 'HV'), None), (('balconies', 'NNS'), None), (('.',
'.'), None)]
>>> un sent=sentences[4203]
>>> bigram tagger.tag(un sent)
[(('The', 'AT'), None), (('population', 'NN'), None), (('of', 'IN'),
None), (('the', 'AT'), None), (('Congo', 'NP'), None), (('is',
'BEZ'), None), (('13.5', 'CD'), None), (('million', 'CD'), None),
((',', ','), None), (('divided', 'VBN'), None), (('into', 'IN'),
None), (('at', 'IN'), None), (('least', 'AP'), None), (('seven',
'CD'), None), (('major', 'JJ'), None), (('``', '``'), None),
(('culture', 'NN'), None), (('clusters', 'NNS'), None), (("''",
"''"), None), (('and', 'CC'), None), (('innumerable', 'JJ'), None),
(('tribes', 'NNS'), None), (('speaking', 'VBG'), None), (('400',
'CD'), None), (('separate', 'JJ'), None), (('dialects', 'NNS'),
None), (('.', '.'), None)]
>>> bigram tagger.evaluate(testing sents)
0.09181559805385615
```

Another way of tagging can be performed by means of bootstrapping different methods. In this approach, tagging can be performed using a bigram Tagger. If the tag is not found using the bigram Tagger, then a back-off method involving a unigram Tagger can be used. Also, if a tag is not found using a unigram Tagger, then a back-off method involving a default tagger can be used.

Let's see the following code in NLTK that implements combined Tagger:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> sentences=brown.tagged_sents(categories='news')
>>> sz=int(len(sentences)*0.8)
>>> training_sents = sentences[:sz]
>>> testing_sents=sentences[sz:]
>>> s0=nltk.DefaultTagger('NNP')
>>> s1=nltk.UnigramTagger(training_sents,backoff=s0)
>>> s2=nltk.BigramTagger(training_sents,backoff=s1)
>>> s2.evaluate(testing_sents)
0.8122260224480948
```

The linguists use the following clues to determine the category of a word:

- Morphological clues
- Syntactic clues
- Semantic clues

Morphological clues are those in which prefix, suffix, infix, and affix information are used to determine the category of a word. For example, *ment* is a suffix that combines with a verb to form a noun, such as establish + ment = establishment and achieve + ment = achievement.

Syntactic clues can be useful in determining the category of a word. For example, let's assume that nouns are already known. Now, adjectives can be determined. Adjectives can occur either after a noun or after a word, such as very, in a sentence.

Semantic information can also be used to determine the category of a word. If the meaning of a word is known, then its category can easily be known.

Let's see the following code in NLTK that can be used for the evaluation of a chunk parser:

```
>>> import nltk
>>> chunkparser = nltk.RegexpParser("")
>>> print(nltk.chunk.accuracy(chunkparser,
nltk.corpus.conll2000.chunked_sents('train.txt',
chunk_types=('NP',))))
0.44084599507856814
```

Let's see another code in NLTK that is based on the evaluation of a naïve chunk parser that looks for tags, such as CD, JJ, and so on:

```
>>> import nltk
>>> grammar = r"NP: {<[CDJNP].*>+}"
>>> cp = nltk.RegexpParser(grammar)
>>> print(nltk.chunk.accuracy(cp,
nltk.corpus.conll2000.chunked_sents('train.txt',
chunk_types=('NP',))))
0.8744798726662164
```

The following code in NLTK is used to compute the conditional frequency distribution for chunked data:

```
def chunk tags(train):
    """Generate a following tags list that appears inside chunks"""
    cfreqdist = nltk.ConditionalFreqDist()
    for t in train:
        for word, tag, chunktag in nltk.chunk.tree2conlltags(t):
            if chtag == "O":
                cfreqdist[tag].inc(False)
            else:
                cfreqdist[tag].inc(True)
    return [tag for tag in cfreqdist.conditions() if
cfreqdist[tag].max() == True]
>>> training sents =
nltk.corpus.conll2000.chunked sents('train.txt', chunk types=('NP',))
>>> print chunked tags(train sents)
['PRP$', 'WDT', 'JJ', 'WP', 'DT', '#', '$', 'NN', 'FW', 'POS',
'PRP', 'NNS', 'NNP', 'PDT', 'RBS', 'EX', 'WP$', 'CD', 'NNPS', 'JJS',
'JJR'l
```

Let's see the following code for performing the evaluation of chunker in NLTK. Here, two entities, namely guessed and correct, are used. Guessed entities are those that are returned by a chunk parser. Correct entities are those set of chunks that are defined in the test corpus:

```
>>> import nltk
>>> correct = nltk.chunk.tagstr2tree(
"[ the/DT little/JJ cat/NN ] sat/VBD on/IN [ the/DT mat/NN ]")
>>> print(correct.flatten())
(S the/DT little/JJ cat/NN sat/VBD on/IN the/DT mat/NN)
>>> grammar = r"NP: {<[CDJNP].*>+}"
>>> cp = nltk.RegexpParser(grammar)
>>> grammar = r"NP: {<PRP|DT|POS|JJ|CD|N.*>+}"
>>> chunk parser = nltk.RegexpParser(grammar)
>>> tagged tok = [("the", "DT"), ("little", "JJ"), ("cat",
"NN"),("sat", "VBD"), ("on", "IN"), ("the", "DT"), ("mat", "NN")]
>>> chunkscore = nltk.chunk.ChunkScore()
>>> guessed = cp.parse(correct.flatten())
>>> chunkscore.score(correct, guessed)
>>> print(chunkscore)
ChunkParse score:
   IOB Accuracy: 100.0%
   Precision: 100.0%
   Recall:
                100.0%
   F-Measure: 100.0%
```

Let's see the following code in NLTK that can be used for the evaluation of unigram chunker and bigram chunker:

```
>>>chunker_data = [[(t,c) for w,t,c in
nltk.chunk.tree2conlltags(chtree)]
>>> for chtree in
nltk.corpus.conll2000.chunked_sents('train.txt')]
>>> unigram_chunk = nltk.UnigramTagger(chunker_data)
>>> print nltk.tag.accuracy(unigram_chunk, chunker_data)
0.781378851068
>>> bigram_chunk = nltk.BigramTagger(chunker_data,
backoff=unigram_chunker)
>>> print nltk.tag.accuracy(bigram_chunk, chunker_data)
0.893220987404
```

Consider the following code in which the suffix of a word is used to determine the part of a speech tag. A classifier is trained to provide a list of informative suffixes. A feature extractor function has been used that checks the suffixes that are present in a given word:

```
>>> from nltk.corpus import brown
>>> suffix_freqdist = nltk.FreqDist()
>>> for wrd in brown.words():
```

```
wrd = wrd.lower()
        suffix freqdist[wrd[-1:]] += 1
. . .
        suffix fdist[wrd[-2:]] += 1
. . .
        suffix fdist[wrd[-3:]] += 1
. . .
>>> common suffixes = [suffix for (suffix, count) in
suffix freqdist.most common(100)]
>>> print(common suffixes)
['e', ',', '.', 's', 'd', 't', 'he', 'n', 'a', 'of', 'the',
 'y', 'r', 'to', 'in', 'f', 'o', 'ed', 'nd', 'is', 'on', 'l',
 'g', 'and', 'ng', 'er', 'as', 'ing', 'h', 'at', 'es', 'or',
 're', 'it', '``', 'an', "''", 'm', ';', 'i', 'ly', 'ion', ...]
>>> def pos feature(wrd):
       feature = \{\}
. . .
        for suffix in common suffixes:
. . .
            feature['endswith({})'.format(suffix)] =
. . .
wrd.lower().endswith(suffix)
        return feature
. . .
>>> tagged wrds = brown.tagged wrds(categories='news')
>>> featureset = [(pos feature(n), g) for (n,g) in tagged wrds]
>>> size = int(len(featureset) * 0.1)
>>> train set, test set = featureset[size:], featureset[:size]
>>> classifier1 = nltk.DecisionTreeClassifier.train(train set)
>>> nltk.classify.accuracy(classifier1, test set)
0.62705121829935351
>>> classifier.classify(pos features('cats'))
'NNS'
>>> print(classifier.pseudocode(depth=4))
if endswith(,) == True: return ','
if endswith(,) == False:
  if endswith(the) == True: return 'AT'
  if endswith(the) == False:
    if endswith(s) == True:
      if endswith(is) == True: return 'BEZ'
      if endswith(is) == False: return 'VBZ'
    if endswith(s) == False:
      if endswith(.) == True: return '.'
      if endswith(.) == False: return 'NN'
```

Consider the following code in NLTK for building a regular expression tagger. Here, tags are assigned on the basis of matching patterns:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> sentences = brown.tagged sents(categories='news')
>>> sent = brown.sents(categories='news')
>>> pattern = [
(r'.*ing$', 'VBG'),
                                 # for gerunds
(r'.*ed$', 'VBD'),
                                 # for simple past
(r'.*es$', 'VBZ'),
                                 # for 3rd singular present
(r'.*ould$', 'MD'),
                                 # for modals
(r'.*\'s$', 'NN$'),
                                 # for possessive nouns
(r'.*s$', 'NNS'),
                                 # for plural nouns
(r'^-?[0-9]+(.[0-9]+)?$', 'CD'), # for cardinal numbers
 (r'.*', 'NN')
                                  # for nouns (default)
]
>>> regexpr tagger = nltk.RegexpTagger(pattern)
>>> regexpr tagger.tag(sent[3])
 [('``', 'NN'), ('Only', 'NN'), ('a', 'NN'), ('relative', 'NN'),
('handful', 'NN'), ('of', 'NN'), ('such', 'NN'), ('reports', 'NNS'),
('was', 'NNS'), ('received', 'VBD'), ("''", 'NN'), (',', 'NN'),
('the', 'NN'), ('jury', 'NN'), ('said', 'NN'), (',', 'NN'), ('``',
'NN'), ('considering', 'VBG'), ('the', 'NN'), ('widespread', 'NN'),
('interest', 'NN'), ('in', 'NN'), ('the', 'NN'), ('election', 'NN'),
(',', 'NN'), ('the', 'NN'), ('number', 'NN'), ('of', 'NN'),
('voters', 'NNS'), ('and', 'NN'), ('the', 'NN'), ('size', 'NN'),
('of', 'NN'), ('this', 'NNS'), ('city', 'NN'), ("''", 'NN'), ('.',
'NN')]
>>> regexp tagger.evaluate(sentences)
0.20326391789486245
```

Consider the following code to build a lookup tagger. In building up a lookup tagger, a list of frequently used words is maintained along with their tag information. Some of the words have been assigned the None tag because they do not exist among the list of the most frequently occurring words:

```
>>> import nltk
>>> from nltk.corpus import brown
>>> freqd = nltk.FreqDist(brown.words(categories='news'))
>>> cfreqd =
nltk.ConditionalFreqDist(brown.tagged_words(categories='news'))
>>> mostfreq_words = freqd.most_common(100)
>>> likelytags = dict((word, cfreqd[word].max()) for (word, _) in
mostfreq_words)
>>> baselinetagger = nltk.UnigramTagger(model=likelytags)
>>> baselinetagger.evaluate(brown_tagged_sents)
0.45578495136941344
>>> sent = brown.sents(categories='news')[3]
>>> baselinetagger.tag(sent)
[('``', '``'), ('Only', None), ('a', 'AT'), ('relative', None),
```

```
('handful', None), ('of', 'IN'), ('such', None), ('reports', None),
('was', 'BEDZ'), ('received', None), ("''", "''"), (',', ','),
('the', 'AT'), ('jury', None), ('said', 'VBD'), (',', ','),
('``', '``'), ('considering', None), ('the', 'AT'), ('widespread',
None),
('interest', None), ('in', 'IN'), ('the', 'AT'), ('election', None),
(',', ','), ('the', 'AT'), ('number', None), ('of', 'IN'),
('voters', None), ('and', 'CC'), ('the', 'AT'), ('size', None),
('of', 'IN'), ('this', 'DT'), ('city', None), ("''", "''"), ('.',
'.')]
>>> baselinetagger = nltk.UnigramTagger(model=likely tags,
backoff=nltk.DefaultTagger('NN'))
def performance(cfreqd, wordlist):
    lt = dict((word, cfreqd[word].max()) for word in wordlist)
    baseline tagger = nltk.UnigramTagger(model=lt,
backoff=nltk.DefaultTagger('NN'))
    return
baseline tagger.evaluate(brown.tagged sents(categories='news'))
def display():
    import pylab
    word freqs =
nltk.FreqDist(brown.words(categories='news')).most common()
    words by freq = [w for (w, ) in word freqs]
    cfd =
nltk.ConditionalFreqDist(brown.tagged words(categories='news'))
    sizes = 2 ** pylab.arange(15)
    perfs = [performance(cfd, words by freq[:size]) for size in
sizesl
    pylab.plot(sizes, perfs, '-bo')
    pylab.title('Lookup Tagger Performance with Varying Model Size')
    pylab.xlabel('Model Size')
    pylab.ylabel('Performance')
   pylab.show()
display()
```

Let's see the following stemming code in NLTK using lancasterstemmer. The evaluation of such a stemmer can be done using gold test data:

```
>>> import nltk
>>> from nltk.stem.lancaster import LancasterStemmer
>>> stri=LancasterStemmer()
>>> stri.stem('achievement')
'achiev'
```

Consider the following code in NLTK that can be used for designing a classifier-based chunker. It makes use of the Maximum Entropy classifier:

```
class ConseNPChunkTagger(nltk.TaggerI):
    def init (self, train sents):
        train set = []
        for tagsent in train sents:
            untagsent = nltk.tag.untag(tagsent)
            history = []
            for i, (word, tag) in enumerate(tagsent):
                featureset = npchunk features(untagsent, i, history)
                train set.append( (featureset, tag) )
                history.append(tag)
        self.classifier = nltk.MaxentClassifier.train(
            train set, algorithm='megam', trace=0)
    def tag(self, sentence):
        history = []
        for i, word in enumerate (sentence):
            featureset = npchunk features(sentence, i, history)
            tag = self.classifier.classify(featureset)
            history.append(tag)
        return zip(sentence, history)
class ConseNPChunker(nltk.ChunkParserI): [4]
    def init (self, train sents):
        tagsent = [[((w,t),c) for (w,t,c) in]
                         nltk.chunk.tree2conlltags(sent)]
                        for sent in train sents]
       self.tagger = ConseNPChunkTagger(tagsent)
    def parse(self, sentence):
        tagsent = self.tagger.tag(sentence)
        conlltags = [(w,t,c) for ((w,t),c) in tagsent]
        return nltk.chunk.conlltags2tree(conlltags)
```

In the following code, the evaluation of chunker is performed with the use of a feature extractor. The resultant chunker is similar to the unigram chunker:

```
>>> def npchunk_features(sentence, i, history):
... word, pos = sentence[i]
... return {"pos": pos}
>>> chunker = ConseNPChunker(train_sents)
>>> print(chunker.evaluate(test_sents))
ChunkParse score:
IOB Accuracy: 92.9%
```

 Precision:
 79.9%

 Recall:
 86.7%

 F-Measure:
 83.2%

In the following code, the features of the previous part of the speech tag are also added. This involves the interaction between tags. So the resultant chunker is similar to the bigram chunker:

```
>>> def npchunk features (sentence, i, history):
        word, pos = sentence[i]
. . .
        if i == 0:
. . .
            previword, previpos = "<START>", "<START>"
        else:
. . .
            previword, previpos = sentence[i-1]
. . .
        return {"pos": pos, "previpos": previpos}
. . .
>>> chunker = ConseNPChunker(train sents)
>>> print(chunker.evaluate(test sents))
ChunkParse score:
    IOB Accuracy: 93.6%
    Precision:
                  81.9%
    Recall:
                    87.2%
                   84.5%
    F-Measure:
```

Consider the following code for chunker in which features for the current word are added to improve the performance of a chunker:

```
>>> def npchunk features (sentence, i, history):
        word, pos = sentence[i]
. . .
        if i == 0:
. . .
            previword, previpos = "<START>", "<START>"
. . .
        else:
. . .
            previword, previpos = sentence[i-1]
. . .
        return {"pos": pos, "word": word, "previpos": previpos}
. . .
>>> chunker = ConseNPChunker(train sents)
>>> print(chunker.evaluate(test sents))
ChunkParse score:
    IOB Accuracy:
                   94.5%
                    84.2%
    Precision:
    Recall:
                    89.4%
                    86.7%
    F-Measure:
```

Let's consider the code in NLTK in which the collection of features, such as paired features, lookahead features, complex contextual features, and so on, are added to enhance the performance of a chunker:

```
>>> def npchunk_features(sentence, i, history):
... word, pos = sentence[i]
... if i == 0:
... previword, previpos = "<START>", "<START>"
```

```
else:
. . .
             previword, previpos = sentence[i-1]
. . .
         if i == len(sentence)-1:
. . .
             nextword, nextpos = "<END>", "<END>"
. . .
         else:
. . .
             nextword, nextpos = sentence[i+1]
. . .
         return {"pos": pos,
. . .
                  "word": word,
. . .
                  "previpos": previpos,
. . .
                  "nextpos": nextpos,
. . .
                  "previpos+pos": "%s+%s" % (previpos, pos),
. . .
                  "pos+nextpos": "%s+%s" % (pos, nextpos),
. . .
                  "tags-since-dt": tags since dt(sentence, i)}
. . .
>>> def tags since dt(sentence, i):
        tags = set()
. . .
         for word, pos in sentence[:i]:
. . .
             if pos == 'DT':
. . .
                  tags = set()
. . .
             else:
                  tags.add(pos)
. . .
        return '+'.join(sorted(tags))
. . .
>>> chunker = ConsecutiveNPChunker(train sents)
>>> print(chunker.evaluate(test sents))
ChunkParse score:
    IOB Accuracy:
                     96.0%
    Precision:
                     88.6%
                     91.0%
    Recall:
    F-Measure:
                     89.8%
```

The evaluation of Morphological Analyzer can also be performed using gold data. The human expected output is already stored to form a gold set and then the output of the morphological analyzer is compared with the gold data.

Parser evaluation using gold data

Parser evaluation can be done using the gold data or the standard data against which the output of the parser is matched.

Firstly, training of parser model is performed on the training data. Then parsing is done on the unseen data or testing data.

The following two measures can be used to evaluate the performance of a parser:

- Labelled Attachment Score (LAS)
- Labelled Exact Match (LEM)

In both cases, parser's output is compared with testing data. A good parsing algorithm is one that gives the highest LAS and LEM scores. The training and testing data that we use for parsing may consist of parts of speech tags that are gold standard tags, since they have been assigned manually. Parser evaluation can be done using metrics, such as Recall, Precision, and F-Measure.

Here, precision may be defined as the number of correct entities produced by parser divided by the total number of entities produced by parser.

Recall may be defined as the number of correct entities produced by parser divided by the total number of entities in the gold standard parse trees.

F-Score may be defined as the harmonic mean of recall and precision.

Evaluation of IR system

IR is also one of the applications of Natural Language Processing.

Following are the aspects that can be considered while performing the evaluation of the IR system:

- Resources required
- Presentation of documents
- Market evaluation or appealing to the user
- Retrieval speed
- Assistance in constituting queries
- Ability to find required documents

Evaluation is usually done by comparing one system with another.

IR systems can be compared on the basis of a set of documents, set of queries, techniques used, and so on. Metrics used for performance evaluation are Precision, Recall, and F-Measure. Let's learn a bit more about them:

• **Precision**: It is defined as the proportion of a retrieved set that is relevant.

 $Precision = |relevant \cap retrieved| \div |retrieved| = P(relevant | retrieved)$

• **Recall**: It is defined as the proportion of all the relevant documents in the collection included in the retrieved set.

 $Recall = |relevant \cap retrieved| \div |relevant| = P(retrieved | relevant)$ • **F-Measure**: It can be obtained using Precision and Recall as follows:

F-Measure = (2*Precision*Recall) / (Precision + Recall)

Metrics for error identification

Error identification is a very important aspect that affects the performance of an NLP system. Searching tasks may involve the following terminologies:

- **True Positive** (**TP**): This may be defined as the set of relevant documents that is correctly identified as the relevant document.
- **True Negative** (**TN**): This may be defined as the set of irrelevant documents that is correctly identified as the irrelevant document.
- False Positive (FP): This is also referred to as Type I error and is the set of irrelevant documents that is incorrectly identified as the relevant document.
- False Negative (FN): This is also referred to as Type II error and is the set of relevant documents that is incorrectly identified as the irrelevant document.

On the basis of the previously mentioned terminologies, we have the following metrics:

- Precision (P) TP/(TP+FP)
- *Recall (R) TP/(TP+FN)*
- F-Measure 2*P*R/(P+R)

Metrics based on lexical matching

We can also perform the analysis of performance at word level or lexical level.

Consider the following code in NLTK in which movie reviews have been taken and marked as either positive or negative. A feature extractor is constructed that checks whether a given word is present in a document or not:

```
>>> from nltk.corpus import movie reviews
>>> docs = [(list(movie reviews.words(fileid)), category)
                 for category in movie reviews.categories()
. . .
                 for fileid in movie reviews.fileids(category)]
. . .
>>> random.shuffle(docs)
all wrds = nltk.FreqDist(w.lower() for w in movie reviews.words())
word features = list(all wrds)[:2000]
def doc features (doc):
    doc words = set(doc)
    features = {}
    for word in word features:
        features['contains({})'.format(word)] = (word in doc words)
    return features
>>> print(doc features(movie reviews.words('pos/cv957 8737.txt')))
{'contains(waste)': False, 'contains(lot)': False, ...}
featuresets = [(doc features(d), c) for (d, c) in docs]
train set, test set = featuresets[100:], featuresets[:100]
classifier = nltk.NaiveBayesClassifier.train(train set)
>>> print(nltk.classify.accuracy(classifier, test set))
0.81
>>> classifier.show most informative features(5)
Most Informative Features
   contains(outstanding) = True
                                             pos:neq =
                                                                11.1
: 1.0
        contains(seagal) = True
                                             neg : pos
                                                                  7.7
                                                          =
: 1.0
   contains (wonderfully) = True
                                             pos:neg =
                                                                  6.8
: 1.0
        contains(damon) = True
                                             pos:neg =
                                                                  5.9
: 1.0
        contains(wasted) = True
                                             neg : pos
                                                                  5.8
                                                          =
: 1.0
```

Consider the following code in NLTK that describes nltk.metrics.distance, which provides metrics to determine whether a given output is the same as the expected output:

```
from __future__ import print_function
from ___future___ import division
def edit dist init(len1, len2):
    lev = []
    for i in range(len1):
        lev.append([0] * len2) # initialization of 2D array to zero
    for i in range(len1):
        lev[i][0] = i
                                # column 0: 0,1,2,3,4,...
    for j in range(len2):
                               # row 0: 0,1,2,3,4,...
        lev[0][j] = j
    return lev
def edit dist step(lev, i, j, s1, s2, transpositions=False):
    c1 = s1[i - 1]
    c2 = s2[j - 1]
    # skipping a character in s1
   a = lev[i - 1][j] + 1
    # skipping a character in s2
   b = lev[i][j - 1] + 1
    # substitution
    c = lev[i - 1][j - 1] + (c1 != c2)
    # transposition
    d = c + 1 # never picked by default
    if transpositions and i > 1 and j > 1:
        if s1[i - 2] == c2 and s2[j - 2] == c1:
            d = lev[i - 2][j - 2] + 1
    # pick the cheapest
    lev[i][j] = min(a, b, c, d)
def edit distance(s1, s2, transpositions=False):
    # set up a 2-D array
    len1 = len(s1)
    len2 = len(s2)
    lev = edit dist init(len1 + 1, len2 + 1)
    # iterate over the array
    for i in range(len1):
        for j in range(len2):
            _edit_dist_step(lev, i + 1, j + 1, s1, s2,
transpositions=transpositions)
    return lev[len1][len2]
```

```
def binary distance(label1, label2):
    """Simple equality test.
    0.0 if the labels are identical, 1.0 if they are different.
>>> from nltk.metrics import binary distance
>>> binary distance(1,1)
    0.0
>>> binary distance(1,3)
    1.0
    .. .. ..
    return 0.0 if label1 == label2 else 1.0
def jaccard distance(label1, label2):
    """Distance metric comparing set-similarity.
    11 11 11
    return (len(label1.union(label2)) -
len(label1.intersection(label2)))/len(label1.union(label2))
def masi distance(label1, label2)
    len intersection = len(label1.intersection(label2))
    len union = len(label1.union(label2))
    len label1 = len(label1)
    len label2 = len(label2)
    if len label1 == len label2 and len label1 == len intersection:
        m = 1
    elif len intersection == min(len label1, len label2):
        m = 0.67
    elif len intersection > 0:
       m = 0.33
    else:
        m = 0
    return 1 - (len intersection / len union) * m
def interval distance(label1,label2):
    try:
        return pow(label1 - label2, 2)
#
         return pow(list(label1)[0]-list(label2)[0],2)
    except:
        print ("non-numeric labels not supported with interval
```

```
distance")
```

```
def presence(label):
    return lambda x, y: 1.0 * ((label in x) == (label in y))
def fractional presence(label):
    return lambda x, y:\
        abs(((1.0 / len(x)) - (1.0 / len(y)))) * (label in x and
label in y) \
        or 0.0 * (label not in x and label not in y) \setminus
        or abs((1.0 / len(x))) * (label in x and label not in y) \setminus
        or ((1.0 / len(y))) * (label not in x and label in y)
def custom distance(file):
    data = \{\}
    with open(file, 'r') as infile:
        for 1 in infile:
            labelA, labelB, dist = l.strip().split("\t")
            labelA = frozenset([labelA])
            labelB = frozenset([labelB])
            data[frozenset([labelA,labelB])] = float(dist)
    return lambda x,y:data[frozenset([x,y])]
def demo():
    edit distance examples = [
        ("rain", "shine"), ("abcdef", "acbdef"), ("language",
"lnaguaeg"),
        ("language", "lnaugage"), ("language", "lngauage")]
    for s1, s2 in edit distance examples:
        print("Edit distance between '%s' and '%s':" % (s1, s2),
edit distance(s1, s2))
    for s1, s2 in edit distance examples:
        print("Edit distance with transpositions between '%s' and
'%s':" % (s1, s2), edit distance(s1, s2, transpositions=True))
    s1 = set([1, 2, 3, 4])
    s2 = set([3, 4, 5])
    print("s1:", s1)
    print("s2:", s2)
    print("Binary distance:", binary distance(s1, s2))
    print("Jaccard distance:", jaccard distance(s1, s2))
    print("MASI distance:", masi distance(s1, s2))
```

if __name__ == '__main__':
 demo()

Metrics based on syntactic matching

Syntactic matching can be done by performing the task of chunking. In NLTK, a module called nltk.chunk.api is provided that helps to identify chunks and returns a parse tree for a given chunk sequence.

The module called nltk.chunk.named_entity is used to identify a list of named entities and also to generate a parse structure. Consider the following code in NLTK based on syntactic matching:

```
>>> import nltk
>>> from nltk.tree import Tree
>>> print(Tree(1,[2,Tree(3,[4]),5]))
(1 \ 2 \ (3 \ 4) \ 5)
>>> ct=Tree('VP',[Tree('V',['gave']),Tree('NP',['her'])])
>>> sent=Tree('S',[Tree('NP',['I']),ct])
>>> print(sent)
(S (NP I) (VP (V gave) (NP her)))
>>> print(sent[1])
(VP (V gave) (NP her))
>>> print(sent[1,1])
(NP her)
>>> t1=Tree.from string("(S(NP I) (VP (V gave) (NP her)))")
>>> sent==t1
True
>>> t1[1][1].set label('X')
>>> t1[1][1].label()
'X'
>>> print(t1)
(S (NP I) (VP (V gave) (X her)))
>>> t1[0],t1[1,1]=t1[1,1],t1[0]
>>> print(t1)
(S (X her) (VP (V gave) (NP I)))
>>> len(t1)
2
```

Metrics using shallow semantic matching

WordNet Similarity is used to perform semantic matching. In this, a similarity of a given text is computed against the hypothesis. The Natural Language Toolkit can be used to compute: path distance, Leacock-Chodorow Similarity, Wu-Palmer Similarity, Resnik Similarity, Jiang-Conrath Similarity, and Lin Similarity between words present in the text and the hypothesis. In these metrics, we compare the similarity between word senses rather than words.

During Shallow Semantic analysis, NER and coreference resolution are also performed.

Consider the following code in NLTK that computes wordnet similarity:

```
>>> wordnet.N['dog'][0].path_similarity(wordnet.N['cat'][0])
0.200000000000000
>>> wordnet.V['run'][0].path_similarity(wordnet.V['walk'][0])
0.25
```

Summary

In this chapter, we discussed the evaluation of NLP systems (POS tagger, stemmer, and morphological analyzer). You learned about various metrics used for performing the evaluation of NLP systems based on error identification, lexical matching, syntactic matching, and shallow semantic matching. We also discussed parser evaluation performed using gold data. Evaluation can be done using three metrics, namely Precision, Recall, and F-Measure. You also learned about the evaluation of IR system.

Appendix B. Bibliography

This course is a blend of text and quizzes, all packaged up keeping your journey in mind. It includes content from the following Packt products:

- NLTK Essentials, Nitin Hardeniya
- Python 3 Text Processing with NLTK 3 Cookbook, Jacob Perkins
- Mastering Natural Language Processing with Python, Deepti Chopra, Nisheeth Joshi, Iti Mathur

Index

A

- AbiWord
 - about / Getting ready
- above_score(score_fn, min_score) function / Scoring ngrams
- absolute link / <u>There's more...</u>
- AbstractLazySequence class / <u>How it works...</u>
- access token, Facebook
 - URL / <u>Facebook</u>
- accuracy
 - evaluating, of tagger / Evaluating accuracy
- a ClassiferBasedTagger class
 - training / <u>How to do it...</u>
- Add-one smoothing
 - about / <u>Add-one smoothing</u>
- Affective Norms for English Words (ANEW) / Introducing sentiment analysis
- AffixTagger class / <u>Affix tagging</u>
 - min_stem_length keyword / <u>Working with min_stem_length</u>
- affix tagging
 - about / How to do it ..., How it works ...
- agglutinative languages
 - about / Introducing morphology
- Anaphora Resolution (AR)
 - about / Discourse analysis using Centering Theory, Anaphora resolution
 - pronominal / <u>Anaphora resolution</u>
 - definite noun phrase / <u>Anaphora resolution</u>
 - Quantifier/Ordinal / <u>Anaphora resolution</u>
- anchor tag / How it works...
- AntiMorfo
 - about / Morphological generator
- antonym replacement
 - about / Replacing negations with antonyms
- AntonymReplacer class
 - about / <u>How it works...</u>
- antonyms
 - about / <u>Antonyms</u>, <u>Replacing negations with antonyms</u>
 - negations, replacing with / Replacing negations with antonyms, How it works...
- antonyms() method / <u>Antonyms</u>
- append_line() function / <u>How to do it...</u>, <u>How it works...</u>
- ASCII
 - converting / <u>Converting to ASCII</u>
- Aspell
 - about / <u>Getting ready</u>
 - URL / <u>Getting ready</u>

- associative arrays/memories
 - about / <u>Dictionaries</u>
- astimezone() method / <u>How it works...</u>
- atomic, Redis operations
 - about / Storing a frequency distribution in Redis
- Automatic Content Extraction / <u>How to do it...</u>

B

- Back-off mechanism
 - developing, for MLE / <u>Develop a back-off mechanism for MLE</u>
- backoff classifier
 - about / Selecting a machine learning algorithm
- backoff tagging
 - \circ about / <u>See also</u>
 - taggers, combining with / Combining taggers with backoff tagging, How it works...
- backoff_tagger function / How it works..., There's more...
- backreference
 - about / Getting ready
- Bag of word (BOW) representation
 - about / <u>Text classification</u>
- Bag of words model
 - · about / Bag of words feature extraction
- bag_of_bigrams_words() function / <u>Including significant bigrams</u>
- bag_of_words() function / <u>How to do it...</u>, <u>How it works...</u>
- bar plot
 - about / <u>A bar plot</u>
- base name
 - about / <u>How to do it...</u>
- Bayes theorem / Training a Naive Bayes classifier
- BeautifulSoup
 - about / Introduction
 - HTML entities, converting with / <u>Converting HTML entities with BeautifulSoup</u>, <u>How</u> to do it...
 - URL, for installation / Getting ready
 - URL, for usage / There's more...
 - used, for extracting URLs / Extracting URLs with BeautifulSoup
- Berlin Affective Word List (BAWL) / Introducing sentiment analysis
- Berlin Affective Word List Reloaded (BAWL-R) / Introducing sentiment analysis
- BigramCollocationFinder / How it works...
- BigramTagger class / <u>Training and combining ngram taggers</u>
- binary classifier
 - about / Introduction, How to do it ...

/ Getting ready

- binary classifiers / Classifying with multiple binary classifiers
- · binary named entity extraction / Binary named entity extraction
- block readers functions, nltk.corpus.reader.util
 - read_whitespace_block() / <u>Block reader functions</u>

- o read_wordpunct_block() / <u>Block reader functions</u>
- read_line_block() / <u>Block reader functions</u>
- read_blankline_block() / <u>Block reader functions</u>
- o read_regexp_block() / <u>Block reader functions</u>
- Boolean retrieval
 - about / Boolean retrieval
- BOW (Bag of Word) representation
 - about / <u>Sampling</u>
- Brill tagger
 - about / Brill tagger
 - training / Training a Brill tagger, How it works...
- BrillTagger class
 - about / Training a Brill tagger
- BrillTaggerTrainer class
 - about / <u>How it works...</u>
 - trace parameter, passing / Tracing

С

- cardinal
 - about / Swapping noun cardinals
- Cardinal number (CD) / Tagging with regular expressions
- CART
 - about / Decision trees
- · categorized chunk corpus read
 - creating / <u>Getting ready</u>, <u>How it works...</u>, <u>There's more...</u>
- categorized chunk corpus reader
 - creating / <u>Creating a categorized chunk corpus reader</u>
- CategorizedChunkedCorpusReader class / <u>How it works...</u>
- categorized Conll chunk corpus reader
 - about / Categorized CoNLL chunk corpus reader
- categorized corpora
 - about / Categorized corpora
- CategorizedCorpusReader class
 - about / <u>How to do it...</u>
- CategorizedPlaintextCorpusReader
 - about / <u>How it works...</u>
- CategorizedPlaintextCorpusReader class
 - about / <u>How to do it...</u>
- categorized tagged corpus reader
 - about / Categorized tagged corpus reader
- categorized text corpus
 - creating / Creating a categorized text corpus, How to do it..., How it works...
- category file
 - about / Category file
- cess_cat corpora / <u>The cess_esp and cess_cat treebank</u>
- cess_esp corpora / The cess_esp and cess_cat treebank
- channel

- about / Distributed tagging with execnet
- character encoding
 - detecting / Detecting and converting character encodings, How to do it...
 - converting / Detecting and converting character encodings, How to do it ...
 - UnicodeDammit / UnicodeDammit conversion
- charade
 - about / Introduction, Getting ready
 - URL / <u>Getting ready</u>
- chart parser
 - about / <u>A chart parser</u>
- ChinkRule class
 - about / Chunking and chinking with regular expressions
 - / How it works...
- chinks
 - about / Chunking and chinking with regular expressions
- chi_sq() function / <u>There's more...</u>
- choose_tag() method / <u>How it works...</u>
- Chrome / <u>The Scrapy shell</u>
- chunk
 - about / Creating a chunked phrase corpus, Introduction
- chunked corpus
 - analyzing / <u>Analyzing a chunked corpus</u>
- ChunkedCorpusReader class / <u>How to do it..., How it works...</u>
- chunked phrase corpus
 - about / <u>See also</u>
 - creating / <u>Getting ready</u>, <u>How it works...</u>
- chunker
 - training, with NLTK-Trainer / <u>Training a chunker with NLTK-Trainer</u>, <u>How to do it...</u>, <u>How it works...</u>
 - analyzing, against chunked corpus / <u>Analyzing a chunker against a chunked corpus</u>
 - developing, pos-tagged corpora used / <u>Developing a chunker using pos-tagged corpora</u>
- chunk extraction
 - about / Introduction
- chunking
 - about / Chunking, Developing a chunker using pos-tagged corpora
- chunk patterns
 - about / Chunking and chinking with regular expressions
 - defining, with regular expressions / <u>Getting ready</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>There's more...</u>
 - alternative patterns, parsing / <u>Parsing alternative patterns</u>
- ChunkRule class
 - about / Chunking and chinking with regular expressions

/ How it works...

- ChunkRule pattern / <u>How to do it...</u>
- chunk rules
 - creating, with context / Chunk rule with context
 - looping / <u>Looping and tracing chunk rules</u>

- tracing / Looping and tracing chunk rules
- chunks
 - about / Introduction
 - merging, with regular expressions / <u>Merging and splitting chunks with regular</u> <u>expressions, How to do it..., How it works...</u>
 - splitting, with regular expressions / <u>Merging and splitting chunks with regular</u> expressions, <u>How to do it...</u>, <u>How it works...</u>
 - rule descriptions, specifying / Specifying rule descriptions
 - expanding, with regular expressions / <u>Expanding and removing chunks with regular</u> expressions, <u>How it works...</u>, <u>There's more...</u>
 - removing, with regular expressions / <u>Expanding and removing chunks with regular</u> expressions, <u>How it works...</u>, <u>There's more...</u>
- ChunkScore metrics
 - about / <u>The ChunkScore metrics</u>
- ChunkString / <u>How it works...</u>
- chunk transformations
 - chaining / Chaining chunk transformations, How it works...
- chunk transforms
 - about / Introduction
- chunk tree
 - converting, to text / <u>Converting a chunk tree to text</u>, <u>How it works...</u>
- chunk types
 - parsing / Parsing different chunk types
- chunk_tree_to_sent() function / <u>How it works...</u>
- class-imbalance problem / There's more...
- classification
 - about / Machine learning
- classification-based chunking
 - about / <u>Classification-based chunking</u>
 - performing / <u>How to do it...</u>
- classification probability
 - about / <u>Classification probability</u>
- classifier-based tagging
 - about / <u>Classifier-based tagging</u>, <u>There's more...</u>
 - features, detecting with custom feature detector / <u>Detecting features with a custom</u> <u>feature detector</u>
 - cutoff probability, setting / <u>Setting a cutoff probability</u>
 - pre-trained classifier, using / <u>Using a pre-trained classifier</u>
- ClassifierBasedPOSTagger class / <u>Classifier-based tagging</u>
- ClassifierBasedTagger class / <u>Classifier-based tagging</u>, <u>How it works...</u>
- ClassifierChunker class
 - creating / <u>Classification-based chunking</u>
- classifiers
 - combining, with voting / <u>Combining classifiers with voting</u>, <u>How to do it...</u>, <u>How it</u> <u>works...</u>
 - training, with NLTK-Trainer / Training a classifier with NLTK-Trainer, How it works...
- classify() method / <u>How to do it...</u>
- Cleaner class
 - about / There's more...
 - URL / <u>There's more...</u>
- clean_html() function / <u>How to do it...</u>
- clear() method / <u>How it works...</u>, <u>How it works...</u>
- collocations
 - about / Discovering word collocations
- complex matrix operations, NumPy
 - performing / <u>Complex matrix operations</u>
 - reshaping / <u>Reshaping and stacking</u>
 - stacking / <u>Reshaping and stacking</u>
 - random numbers, generating / <u>Random numbers</u>
- concatenated corpus view
 - about / Concatenated corpus view
- conditional exponential classifier
 - about / Training a maximum entropy classifier
- conditional frequency distribution
 - storing, in Redis / <u>Storing a conditional frequency distribution in Redis</u>, <u>How to do it...</u>, <u>How it works...</u>
- Conditional Random Field (CRF)
 - about / <u>Machine learning based tagger</u>
- CoNLL
 - about / <u>CoNLL2000 corpus</u>
- CoNLL2000
 - about / <u>Introduction</u>
- CoNLL2000 corpus
 - about / <u>CoNLL2000 corpus</u>
 - $\circ \ URL \, / \, \underline{CoNLL2000 \ corpus}$
- Context Free Grammar (CFG) rules
 - extracting, from Treebank / <u>Extracting Context Free Grammar (CFG) rules from</u> <u>Treebank</u>
 - phrase structure rules / <u>Extracting Context Free Grammar (CFG) rules from Treebank</u>
 - sentence structure rules / Extracting Context Free Grammar (CFG) rules from Treebank
- ContextTagger
 - context model, overrding / <u>Overriding the context model</u>
 - minimum frequency cutoff / Minimum frequency cutoff
- convert() function / <u>How it works...</u>
- convert_tree_labels() function / <u>How to do it..., How it works...</u>
- corpora
 - about / <u>Setting up a custom corpus</u>
 - / Creating POS-tagged corpora
- corpus
 - about / Introduction, Setting up a custom corpus
 - editing, with file locking / Corpus editing with file locking, How to do it..., How it works...
 - / Creating POS-tagged corpora
- CorpusReader class / How to do it...

- corpus view
 - about / Creating a custom corpus view
- corpus views / There's more...
- correct_verbs() function / <u>How to do it..., How it works...</u>
- cross-fold validation
 - about / Cross-fold validation
- css() method
 - about / <u>The Scrapy shell</u>
- CSV synonym replacement
 - about / <u>CSV synonym replacement</u>
- CsvWordReplacer class
 - about / <u>CSV synonym replacement</u>
- custom corpus
 - about / <u>Setting up a custom corpus</u>
 - setting up / <u>How to do it...</u>
 - YAML file, loading / Loading a YAML file
 - training / <u>Training on a custom corpus</u>
- custom corpus view
 - creating / <u>Creating a custom corpus view</u>, <u>How to do it...</u>, <u>How it works...</u>
- custom feature detector
 - features, detecting with / Detecting features with a custom feature detector
- CustomSpellingReplacer class / <u>Personal word lists</u>
- CYK chart parsing algorithm
 - about / CYK chart parsing algorithm

D

- 3D plot
 - about / <u>3D plots</u>
- D3
- about / <u>Geovisualization</u>
- DANEW (Dutch ANEW) / Introducing sentiment analysis
- data collection
 - about / Data collection
 - Twitter / <u>Twitter</u>
- data extraction
 - about / <u>Data extraction</u>
 - trending topics, searching in Twitter / Trending topics
- data flow, Scrapy
 - about / Data flow in Scrapy
 - Scrapy shell / The Scrapy shell
 - items / <u>Items</u>
- data munging
 - about / What is text wrangling?
- data skewness
 - about / <u>Sampling</u>
- data structure server
 - about / Storing a frequency distribution in Redis

- dates
 - parsing, with dateutil / Parsing dates and times with dateutil, How it works...
- dateutil
 - about / <u>Introduction</u>
 - times, parsing with / Parsing dates and times with dateutil, How it works...
 - dates, parsing with / Parsing dates and times with dateutil, How it works...
 - installing / <u>Getting ready</u>
 - URL, for documentation / Getting ready
- decision tree classifier
 - training / Training a decision tree classifier, How to do it..., How it works...
 - uncertainty, controlling with entropy cutoff / <u>Controlling uncertainty with</u> <u>entropy_cutoff</u>
 - tree depth, controlling with depth cutoff / <u>Controlling tree depth with depth_cutoff</u>
 - decisions, controlling with support cutoff / <u>Controlling decisions with support_cutoff</u>
- DecisionTreeClassifier.train()
- about / <u>There's more...</u>
- DecisionTreeClassifier class
 - about / Training a decision tree classifier, How to do it..., How it works...
 - evaluating, with high information words / <u>The DecisionTreeClassifier class with high</u> <u>information words</u>
- decision trees
 - about / <u>Decision trees</u>
- deep parsing
 - versus shallow parsing / Shallow versus deep parsing
- deep tree
 - flattening / Flattening a deep tree, How to do it ..., How it works ..., There's more
- DefaultTagger class / Default tagging, How it works...
- default tagging
 - about / Default tagging, How to do it ..., How it works ...
- delete command / <u>How it works...</u>
- dependencies
 - about / <u>Dependency parsing</u>
- dependency parser
 - about / <u>Stemming</u>
- dependency parsing (DP)
 - about / <u>Dependency parsing</u>
- depth_cutoff value
 - about / Controlling tree depth with depth_cutoff
- detect() function / <u>How it works...</u>
- dialog systems
 - about / <u>Dialog systems</u>
- dictionaries
 - \circ about / <u>Dictionaries</u>
- Dictionary of Affect in Language (DAL) / Introducing sentiment analysis
- dict style feature / <u>Bag of words feature extraction</u>
- DictVectorizer object / <u>How it works...</u>
- different classifier builder

- using / <u>Using a different classifier builder</u>
- different tagger classes
 - using / <u>Using different taggers</u>
- dir() function
 - about / <u>Helping yourself</u>
- direct translation
 - about / Machine translation
- Discourse Analysis
 - about / Introducing discourse analysis
 - discourse representation structure / Introducing discourse analysis
- Discourse Representation Structure (DRS) / Introducing discourse analysis
- Discourse Representation Theory (DRT) / <u>Introducing discourse analysis</u>
- distributed chunking
 - used, with execnet / <u>Distributed chunking with execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>There's more...</u>
 - Python subprocesses / Python subprocesses
- distributed tagging
 - used, with execnet / <u>Distributed tagging with execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>Creating multiple channels</u>, <u>Local versus remote gateways</u>
 - multiple channels, creating / <u>Creating multiple channels</u>
 - local gateway versus remote gateway / <u>Local versus remote gateways</u>
- distributed word scoring
 - used, with Redis / <u>Distributed word scoring with Redis and execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>See also</u>
 - used, with execnet / <u>Distributed word scoring with Redis and execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>See also</u>
- dist_featx.py module
 - about / <u>How it works...</u>
- done message
 - about / <u>How it works...</u>

E

- Earley chart parsing algorithm
 - about / Earley chart parsing algorithm
- eigenvalues
 - about / eigenvalues and eigenvectors
- eigenvectors
 - about / <u>eigenvalues and eigenvectors</u>
- ELE (Expected Likelihood Estimate)
 - about / <u>Training estimator</u>
- ELEProbDist parameter
 - about / <u>Training estimator</u>
- Enchant
 - about / <u>Spelling correction with Enchant</u>
 - spelling issues, correcting with / Getting ready, How it works...
 - URL / Getting ready
- enchant.list_languages() method / There's more...

- English words corpus / English words corpus
- entropy
 - about / Controlling uncertainty with entropy_cutoff
- entropy_cutoff value
 - about / Controlling uncertainty with entropy_cutoff
- en_GB dictionary
 - about / The en_GB dictionary
- error identification
 - about / Metrics for error identification
 - metrics / <u>Metrics for error identification</u>
- estimator
 - training / <u>Training estimator</u>
 - about / <u>Training estimator</u>
- evaluate() method / Evaluating accuracy
- execnet
 - distributed tagging, used with / <u>Distributed tagging with execnet</u>, <u>How to do it...</u>, <u>How it</u> works..., <u>Creating multiple channels</u>, <u>Local versus remote gateways</u>
 - about / Distributed tagging with execnet
 - URL / Getting ready
 - distributed chunking, used with / <u>Distributed chunking with execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>There's more...</u>
 - parallel list processing, used with / <u>Parallel list processing with execnet</u>, <u>How it</u> works..., <u>There's more...</u>
 - distributed word scoring, used with / <u>Distributed word scoring with Redis and execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>See also</u>
- ExpandLeftRule / <u>How to do it...</u>
- ExpandRightRule / <u>How to do it...</u>
- exploratory data analysis (EDA)
 - about / <u>Diving into NLTK</u>
- extract() method
 - about / The Scrapy shell

F

- F-Measure / Evaluation of IR system
- F-measure
 - about / <u>F-measure</u>
- Facebook
 - about / Facebook
 - URL, for graph API / Facebook
 - geo visualization / Facebook
- Facebook SDK
 - installing / <u>Facebook</u>
 - URL / <u>Facebook</u>
- False Negative (FN) / Metrics for error identification
- false negatives
 - about / Measuring precision and recall of a classifier
- False Positive (FP) / <u>Metrics for error identification</u>

- false positives
 - about / Measuring precision and recall of a classifier
- FastBrillTagger
 - about / <u>Selecting a machine learning algorithm</u>
- features
 - detecting, with custom feature detector / <u>Detecting features with a custom feature</u> detector
- feature set
 - about / Introduction
- feature_probdist constructor / <u>How it works...</u>
- feature_probdist variable
 - about / <u>Manual training</u>
- file locking
 - corpus, editing with / Corpus editing with file locking, How to do it..., How it works...
- filter_insignificant() function / <u>How it works...</u>
- Firebug / The Scrapy shell
- First Order Predicate Logic (FOPL) / Introducing discourse analysis
- first_chunk_index() function / How to do it..., How to do it..., How it works..., How it works...
- flatten_childtrees() function / How to do it..., How it works...
- flatten_deeptree() function / <u>How it works...</u>, <u>How it works...</u>
- frequency analysis
 - URL, for details / <u>Replacing synonyms</u>
- frequency distribution
 - storing, in Redis / <u>Storing a frequency distribution in Redis</u>, <u>How to do it...</u>, <u>How it</u> works..., <u>There's more...</u>
- fromstring() function / How to do it ..., Parsing HTML from URLs or files

G

- gateway
 - about / Distributed tagging with execnet
- gateways, API documentation
 - URL / Local versus remote gateways
- gensim
 - installing / <u>Installing gensim</u>
 - URL / Installing gensim
- geomap
 - about / Influencers detection
- geo visualization
 - about / Geovisualization
 - influencers detection, in Twitter / Influencers detection
 - Facebook / Facebook
 - influencer friends, searching in social media / Influencer friends
- Gibbs sampling
 - applying, in language processing / Applying Gibbs sampling in language processing
- GIS (General Iterative Scaling) / How it works...
- gis algorithm / <u>How to do it...</u>
- Good Turing

- about / <u>Good Turing</u>
- Google news
 - URL / <u>The Scrapy shell</u>

Η

- Hadoop
 - scikit-learn / Scikit-learn on Hadoop
- hash maps
 - about / Storing a frequency distribution in Redis
- help() function
 - about / <u>Helping yourself</u>
- Hidden Markov Model (HMM)
 - about / Machine learning based tagger, A NER system using Hidden Markov Model
- Hidden Markov Model Estimation
 - about / Hidden Markov Model estimation
 - using / Hidden Markov Model estimation
- higher order function / <u>How to do it...</u>
- high information words
 - calculating / Calculating high information words, How to do it..., How it works...
 - about / Calculating high information words
 - used, for evaluating MaxentClassifier class / <u>The MaxentClassifier class with high</u> <u>information words</u>
 - used, for evaluating DecisionTreeClassifier class / <u>The DecisionTreeClassifier class</u> with high information words
 - used, for evaluating SklearnClassifier class / <u>The SklearnClassifier class with high</u> <u>information words</u>
- high_information_words() function
 - about / <u>How it works...</u>
- Hindi stemmer
 - reference link / <u>Stemming</u>
- Hive/Pig UDF
 - about / <u>Hive/Pig UDF</u>
- Hive UDF
 - $\circ~$ used, for running NLTK on Hadoop / $\underline{A~UDF}$
- HornMorpho
 - about / <u>Morphological generator</u>
- HTML
 - URLs extracting, lxml used / Extracting URLs from HTML with lxml, How it works...
 - parsing, from URLs / Parsing HTML from URLs or files
 - cleaning / <u>Cleaning and stripping HTML</u>, <u>How it works...</u>
 - stripping / <u>Cleaning and stripping HTML</u>, <u>How it works...</u>
- HTML entities
 - converting, with BeautifulSoup / <u>Converting HTML entities with BeautifulSoup</u>, <u>How</u> to do it...
- Hu-Liu opinion Lexicon (HL) / Introducing sentiment analysis
- hypernyms
 - working with / Working with hypernyms

- hypernym tree / Calculating WordNet Synset similarity
- hypernym_paths() method / <u>Working with hypernyms</u>
- hyponyms
 - about / <u>Working with hypernyms</u>
- IE engine

I

- about / Information extraction
- ieer corpus / <u>Training a named entity chunker</u>
- IgnoreHeadingCorpusView class
 - about / <u>How it works...</u>
- IIS (Improved Iterative Scaling) / How it works...
- importance score
 - calculating / Building your first NLP application
- infinitive phrases
 - about / <u>Swapping infinitive phrases</u>
 - swapping / <u>How to do it...</u>, <u>How it works...</u>
- inflecting languages
 - about / Introducing morphology
- information extraction
 - about / Information extraction
 - named-entity recognition (NER) / <u>Named-entity recognition (NER)</u>
- information extraction (IE)
 - about / Information extraction
 - rule-based extraction / <u>Information extraction</u>
 - machine learning based / Information extraction
- Information Extraction* Entity Recognition / Training a named entity chunker
- information retrieval
 - about / Introducing information retrieval
 - stop word removal / Stop word removal
 - vector space model, using / Information retrieval using a vector space model
 - Vector Space Model, using / Information retrieval using a vector space model
- information retrieval (IR)
 - about / Information retrieval
 - Boolean retrieval / Boolean retrieval
 - vector space model (VSM) / <u>Vector space model</u>
 - probabilistic model / <u>The probabilistic model</u>
 - reference link / The probabilistic model
- insignificant words
 - filtering, from sentence / Getting ready, How to do it...
- instance
 - about / Introduction
- International Standards Organization (ISO) / Timezone lookup and conversion
- interpolation
 - applying, on data / <u>Applying interpolation on data to get mix and match</u>
- inverse document frequency (IDF)
 - about / <u>Vector space model</u>

- inverted index
 - about / Information retrieval
- IOB tags
 - about / There's more...
- IR System
 - evaluation, performing / Evaluation of IR system
- IR system
 - developing, with latent semantic indexing / <u>Developing an IR system using latent</u> semantic indexing
- isolating languages
 - about / Introducing morphology
- item pipeline
 - building / The item pipeline
- items
 - about / <u>Items</u>
 - rule method / <u>Items</u>
- items() method / How it works..., How it works...
- iterlinks() method / <u>How to do it...</u>

J

- jaccard() function / There's more...
- Jiang-Conrath Similarity / Disambiguating senses using Wordnet
- Json Parser
 - URL / Data extraction

K

- K-means clustering
 - about / <u>K-means</u>
- keys() method / <u>How it works...</u>, <u>How it works...</u>
- KLOUT
 - URL / Influencers detection
- Kneser Ney Estimation
 - about / Kneser Ney estimation

L

- labeled feature set
 - about / Introduction
- labeled feature sets
 - about / Introduction
- LabelEncoder object / How it works...
- Labelled Exact Match(LEM) / <u>Parser evaluation using gold data</u>
- label_feats_from_corpus() function / How to do it..., How it works...
- label_probdist constructor / <u>How it works...</u>
- label_probdist variable
 - about / Manual training
- LancasterStemmer class

- about / There's more..., The LancasterStemmer class
- Lancaster stemming algorithm
 - about / <u>There's more...</u>
- language detection
 - about / <u>Language detection</u>
- Language Model Through Perplexity
 - evaluating / Evaluate a language model through perplexity
- languages
 - sentences, tokenizing in / Tokenizing sentences in other languages
- Latent Dirichlet allocation (LDA)
 - about / Topic modeling in text
- latent dirichlet allocation (LDA)
 - about / Topic modeling
- latent semantic indexing
 - about / Developing an IR system using latent semantic indexing
 - applications / Developing an IR system using latent semantic indexing
- latent semantics indexing (LSI)
 - about / Topic modeling
- LazyCorpusLoader class / <u>Lazy corpus loading</u>
 - about / <u>How to do it...</u>
- lazy corpus loading
 - about / Lazy corpus loading, How to do it ...
- Leacock Chodorow Similarity / Disambiguating senses using Wordnet
- leaves() method / <u>Tree leaves</u>
- Leipzig Affective Norms for German (LANG) / Introducing sentiment analysis
- lemmas
 - about / Looking up lemmas and synonyms in WordNet
 - looking up for / <u>How to do it...</u>, <u>How it works...</u>
 - finding, with WordNetLemmatizer class / <u>How to do it...</u>
- lemmas() method / <u>How to do it...</u>
- lemmatization
 - about / <u>What is text wrangling?</u>, <u>Lemmatization</u>, <u>Lemmatizing words with WordNet</u>, <u>Understanding lemmatization</u>
 - versus stemming / <u>There's more...</u>
 - stemming, combining with / Combining stemming with lemmatization
- less informative features
 - about / <u>Most informative features</u>
- linear algebra
 - about / <u>Linear algebra</u>
 - reference link / <u>Linear algebra</u>
- LinearSVC
 - training with / <u>Training with LinearSVC</u>
 - about / Training with LinearSVC
- Linguistic Data Consortium (LDC)
 - about / <u>Diving deep into a tagger</u>
 - URL / Diving deep into a tagger
- Lin Similarity / Disambiguating senses using Wordnet

- lists
 - about / <u>Lists</u>
- local gateway
 - versus remote gateway / Local versus remote gateways
- LocationChunker class / How to do it..., How it works...
- location chunks
 - extracting / Extracting location chunks, How to do it ...
- lockfile library / Getting ready
 - URL, for documentation / Getting ready
- logistic regression
 - about / Logistic regression, Training with logistic regression
 - training with / <u>Training with logistic regression</u>
- logistic regression classifier
 - about / Training a maximum entropy classifier
- log likelihood / <u>How it works...</u>
- low information words
 - about / Calculating high information words
- lxml
- about / <u>Introduction</u>, <u>Getting ready</u>
- used, for extracting URLs from HTML / <u>Extracting URLs from HTML with lxml</u>, <u>How</u> <u>it works...</u>
- URL, for installation / <u>Getting ready</u>, <u>Getting ready</u>
- URL, for tutorial / <u>How it works...</u>

Μ

- machine learning
 - about / <u>Machine learning</u>
 - supervised learning / Machine learning
 - unsupervised learning / Machine learning
 - semi-supervised learning / Machine learning
 - reinforcement learning / Machine learning
 - used, for sentiment analysis / Sentiment analysis using machine learning
- machine learning algorithm
 - selecting / <u>Selecting a machine learning algorithm</u>
- machine learning based extraction
 - about / Information extraction
- machine learning based tagger
 - about / Machine learning based tagger
- machine translation
 - about / <u>Machine translation</u>
 - direct translation / <u>Machine translation</u>
 - syntactic transfer / <u>Machine translation</u>
- MapReduce
 - reference link / <u>Python streaming</u>
- Markov Chain Monte Carlo (MCMC) / <u>Applying metropolis hastings in modeling languages</u>
- masi distance / <u>How to do it...</u>
- matplotlib

- about / <u>matplotlib</u>
- subplot / <u>Subplot</u>
- axis, adding / Adding an axis
- scatter plot / <u>A scatter plot</u>
- bar plot / <u>A bar plot</u>
- 3D plot / <u>3D plots</u>
- URL / External references
- MaxentClassifier class
 - about / Training a maximum entropy classifier
 - evaluating, with high information words / <u>The MaxentClassifier class with high</u> <u>information words</u>
- maximum entropy (MaxEnt)
 - about / Stochastic gradient descent
- maximum entropy classifier
 - training / <u>Training a maximum entropy classifier</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>There's more...</u>
 - about / Training a maximum entropy classifier, Selecting a machine learning algorithm
 - URL / Training a maximum entropy classifier
- Maximum Entropy Classifier (MEC)
 - about / <u>Machine learning based tagger</u>
- max_iter variable / <u>How it works...</u>
- megam algorithm
 - about / <u>Megam algorithm</u>
 - URL / <u>Megam algorithm</u>
- MergeRule class
 - about / Merging and splitting chunks with regular expressions
- Message Passing Interface (MPI)
 - about / Distributed tagging with execnet
- metrics, based on lexical matching
 - about / Metrics based on lexical matching
- metrics, based on shallow semantic matching
 - about / Metrics using shallow semantic matching
- metrics, based on syntactic matching
 - about / Metrics based on syntactic matching
- metropolis hastings
 - applying, in modeling languages / Applying metropolis hastings in modeling languages
- min_lldelta variable / <u>How it works...</u>
- min_stem_length keyword
 - working with / <u>Working with min_stem_length</u>
- ML (Machine learning)
 - about / Text classification
- MLE model
 - smoothing, applying / <u>Applying smoothing on the MLE model</u>
 - Add-one smoothing / <u>Add-one smoothing</u>
 - Good Turing / <u>Good Turing</u>
 - Kneser Ney Estimation / Kneser Ney estimation
 - Witten Bell Estimation / <u>Witten Bell estimation</u>

- Back-off mechanism, developing / <u>Develop a back-off mechanism for MLE</u>
- model
 - creating, of likely word tags / How to do it..., How it works...
- MongoDB
 - about / <u>Getting ready</u>
 - URL, for installation / <u>Getting ready</u>
- MongoDB-backed corpus reader
 - creating / <u>Creating a MongoDB-backed corpus reader</u>, <u>How it works...</u>
- MongoDBCorpusReader class / <u>How it works...</u>
 - creating / <u>There's more...</u>
- more informative features
 - about / Most informative features
- MorfoMelayu
 - about / <u>Morphological generator</u>
- morphemes
 - about / Introducing morphology
- morphological analyzer
 - about / Morphological analyzer
 - morphological hints / Morphological analyzer
 - syntactic hints / Morphological analyzer
 - semantic hints / Morphological analyzer
 - open class / Morphological analyzer
 - morphology captured by Part of Speech tagset / Morphological analyzer
 - Omorfi / <u>Morphological analyzer</u>
- morphology
 - about / Introducing morphology
- most informative features
 - about / Most informative features
- most_informative_features() method
 - about / Most informative features
- movie_reviews corpus / <u>Getting ready</u>
- multi-label classifier
 - about / Introduction
- multilabel classifier / <u>Classifying with multiple binary classifiers</u>
 - creating / <u>Classifying with multiple binary classifiers</u>
- MultinomialNB / How it works...
- multiple binary classifiers
 - classifying with / Classifying with multiple binary classifiers, How to do it ...
- multiple channels
 - creating / Creating multiple channels
- multi_metrics() function / <u>How to do it...</u>

N

- N-gram tagger
 - about / <u>N-gram tagger</u>
- Naive Bayes
 - about / <u>Naive Bayes</u>

- reference link / <u>Naive Bayes</u>
- Naive Bayes algorithms
 - comparing / Comparing Naive Bayes algorithms
- Naive Bayes classifier
 - training / Training a Naive Bayes classifier, Getting ready, How to do it ...
- NaiveBayesClassifier.train() method / How it works...
- NaiveBayesClassifier class / <u>Training a Naive Bayes classifier</u>
- NaiveBayesClassifier constructor / <u>How it works...</u>
- NAME chunker / <u>How it works...</u>
- named-entity recognition (NER)
 - about / Named-entity recognition (NER)
- named entities
 - extracting / Extracting named entities, How it works ...
- named entity chunker
 - training / <u>Training a named entity chunker</u>, <u>How to do it...</u>, <u>Training a named entity chunker</u>
- named entity recognition
 - about / Extracting named entities
- Named Entity Recognition (NER)
 - about / Introducing NER
- NamesTagger class / How to do it...
- names wordlist corpus / <u>Names wordlist corpus</u>
- National Institute of Standards and Technology (NIST) / How to do it ...
- Natural Language Toolkit (NLTK) / <u>Understanding stemmer</u>
- ndarray
 - about / <u>ndarray</u>
 - indexing / Indexing
 - data, extracting / Extracting data from an array
- negations
 - replacing, with antonyms / Replacing negations with antonyms, How it works...
- negative feature sets / <u>How it works...</u>
- NER
 - about / <u>Stemming</u>, <u>Named Entity Recognition (NER)</u>
 - used, for sentiment analysis / Sentiment analysis using NER
- NER system
 - evaluating / Evaluation of the NER system
- NER tagger
 - about / <u>NER tagger</u>
 - reference link / <u>NER tagger</u>
- NetworkX
 - about / Influencer friends
 - URL / Influencer friends
- ngram
 - about / Training and combining ngram taggers
- NgramTagger class / <u>Quadgram tagger</u>
- ngram taggers
 - training / Training and combining ngram taggers, How it works...

- combining / Training and combining ngram taggers, How it works...
- NLP
 - need for / Why learn NLP?
 - tools / <u>Why learn NLP?</u>
- NLP application
 - building / Building your first NLP application
 - other applications / <u>Other NLP applications</u>
 - machine translation / <u>Machine translation</u>
 - statistical machine translation (SMT) / Statistical machine translation
 - information retrieval (IR) / Information retrieval
 - speech recognition / <u>Speech recognition</u>
 - text classification / Text classification
 - information extraction (IE) / Information extraction
 - question answering (QA) systems / <u>Question answering systems</u>
 - dialog systems / <u>Dialog systems</u>
 - word sense disambiguation (WSD) / <u>Word sense disambiguation</u>
 - topic modeling / <u>Topic modeling</u>
 - language detection / <u>Language detection</u>
 - optical character recognition (OCR) / Optical character recognition
- NLP Systems
 - evaluation, need for / The need for evaluation of NLP systems
- NLP tools
 - evaluation, performing / <u>Evaluation of NLP tools (POS taggers, stemmers, and morphological analyzers)</u>
 - POS Taggers / Evaluation of NLP tools (POS taggers, stemmers, and morphological analyzers)
 - Stemmers / Evaluation of NLP tools (POS taggers, stemmers, and morphological analyzers)
 - Morphological Analyzers / <u>Evaluation of NLP tools (POS taggers, stemmers, and morphological analyzers)</u>
- NLTK
 - about / Why learn NLP?, Diving into NLTK, Introduction, Introduction
 - URL / <u>Why learn NLP?</u>
 - example / Diving into NLTK
 - URL, for installation instructions / Getting ready
 - URL, for data installation / Getting ready
 - URL, for starting Python console / Getting ready
- NLTK, on Hadoop
 - using / <u>NLTK on Hadoop</u>
 - Hive UDF, using / <u>A UDF</u>
 - Python, streaming / Python streaming
- NLTK-Trainer
 - about / Training a tagger with NLTK-Trainer
 - URL, for documentation / Training a tagger with NLTK-Trainer
 - tagger, training with / <u>Training a tagger with NLTK-Trainer</u>, <u>How to do it...</u>, <u>How it</u> works...
 - URL, for installation instructions / <u>Training a tagger with NLTK-Trainer</u>

- pickled tagger, saving / Saving a pickled tagger
- training, on custom corpus / Training on a custom corpus
- used, for training chunker / <u>Training a chunker with NLTK-Trainer</u>, <u>How to do it...</u>, <u>How it works...</u>
- used, for training classifier / Training a classifier with NLTK-Trainer, How it works...
- pickled classifier, saving / <u>Saving a pickled classifier</u>
- training instances, using / Using different training instances
- most informative features / The most informative features
- Maxent classifier / The Maxent and LogisticRegression classifiers
- LogisticRegression classifier / The Maxent and LogisticRegression classifiers
- SVM classifiers / <u>SVMs</u>
- classifiers, combining / Combining classifiers
- high information words / High information words and bigrams
- cross-fold validation / Cross-fold validation
- classifier, analyzing / <u>Analyzing a classifier</u>
- nltk.chunk functions / <u>How it works...</u>
- nltk.corpus
 - treebank corpora, defining / There's more...
- nltk.corpus.treebank_chunk corpus / <u>Treebank chunk corpus</u>
- nltk.data.load() function / <u>How it works...</u>
- nltk.metrics module / <u>See also</u>
- nltk.metrics package
 - about / <u>How it works...</u>
- nltk.sem.logic module
 - substitute_bindings(bindings) method / <u>Introducing discourse analysis</u>
 - replace(variable, expression, replace_bound) method / Introducing discourse analysis
 - Normalize() method / <u>Introducing discourse analysis</u>
 - Visit(self,function,combinatory,default) method / Introducing discourse analysis
 - free(indvar_only) method / Introducing discourse analysis
 - Simplify() method / Introducing discourse analysis
 - get_refs(recursive) method / Introducing discourse analysis
 - fol() method / <u>Introducing discourse analysis</u>
 - draw() method / Introducing discourse analysis
- nltk.tag.untag() function / <u>There's more...</u>
- NLTK functionality
 - URL, for demos / Introduction
- normalization
 - about / Normalization
 - punctuations, eliminating / Eliminating punctuation
 - conversion, into lowercase and uppercase / Conversion into lowercase and uppercase
 - stop words, dealing with / <u>Dealing with stop words</u>
 - stopwords, calculating / Calculate stopwords in English
- noun cardinals
 - swapping / Swapping noun cardinals, How it works...
- Noun Phrase (NP)
 - about / Creating a chunked phrase corpus
- noun phrase (NP)

- about / Chunking
- Noun Phrase chunk rule / Developing a chunker using pos-tagged corpora
- Noun Phrases (NP)
 - about / <u>CoNLL2000 corpus</u>
- NumPy
 - about / <u>NumPy</u>
 - ndarray / <u>ndarray</u>
 - basic operations / <u>Basic operations</u>
 - complex matrix operations / <u>Complex matrix operations</u>
 - URL / External references
- NumPy array
 - about / <u>Decision trees</u>
- NumPy package
 - URL / Getting ready
- n_ii parameter / <u>How it works...</u>
- n_ix parameter / <u>How it works...</u>
- n_xi parameter / <u>How it works...</u>
- n_xx parameter / <u>How it works...</u>

0

- optical character recognition (OCR)
 - about / Optical character recognition
- ordered dictionary
 - storing, in Redis / <u>Storing an ordered dictionary in Redis</u>, <u>Getting ready</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>See also</u>

P

- P(features) parameter / Training a Naive Bayes classifier
- P(features | label) parameter / Training a Naive Bayes classifier
- P(label) parameter / Training a Naive Bayes classifier
- P(label | features) parameter / Training a Naive Bayes classifier
- pandas
 - about / pandas
 - data, reading / <u>Reading data</u>
 - series data / <u>Series data</u>
 - column transformation / Column transformation
 - noisy data / Noisy data
 - URL / External references
- paragraph block reader
 - customizing / Customizing the paragraph block reader
- parallel list processing
 - used, with execnet / Parallel list processing with execnet, How it works..., There's
 - <u>more...</u>
- ParaMorfo
 - about / Morphological generator
- parsed_docs() method / <u>How it works...</u>

- parser evaluation
 - about / <u>Parser evaluation using gold data</u>
 - performing, gold data used / Parser evaluation using gold data
- parsers
 - about / <u>Different types of parsers</u>
 - recursive descent parser / <u>A recursive descent parser</u>
 - shift-reduce parser / <u>A shift-reduce parser</u>
 - chart parser / <u>A chart parser</u>
 - regex parser / <u>A regex parser</u>
- parse trees
 - training / <u>Training on parse trees</u>
- parsing
 - rule-based approach / The two approaches in parsing
 - probabilistic approach / The two approaches in parsing
 - need for / <u>Why we need parsing</u>
 - dependency parsing (DP) / <u>Dependency parsing</u>
 - about / Introducing parsing
 - Treebank construction / <u>Treebank construction</u>
- part-of-speech tagged word corpus
 - creating / <u>Getting ready</u>, <u>How it works...</u>
- part-of-speech tagging
 - about / Introduction
- partial parsing
 - about / Introduction
 - performing, with regular expressions / <u>Partial parsing with regular expressions</u>, <u>How it</u> works...
- part of speech (POS) tagging
 - about / What is Part of speech tagging, Diving deep into a tagger
 - reference link / What is Part of speech tagging, Machine learning based tagger
 - Stanford tagger / <u>Stanford tagger</u>
 - sequential tagger / <u>Sequential tagger</u>
 - Brill tagger / Brill tagger
 - machine learning based tagger / Machine learning based tagger
- Part of Speech tagger (POS)
 - about / <u>Stemming</u>
- part of speech tagging
 - about / Creating a part-of-speech tagged word corpus
- parts-of-speech tagging
 - about / Introducing parts-of-speech tagging
 - default tagging / <u>Default tagging</u>
- Path and Leacock Chordorow (LCH) similarity / Path and Leacock Chordorow (LCH) similarity
- Path Distance Similarity / Disambiguating senses using Wordnet
- pattern creation
 - about / Parsing alternative patterns
- Penn Treebank
 - about / Introduction
- Penn Treebank corpus

- URL / <u>See also</u>
- Penn Treebank Project
 - URL / <u>Treebank chunk corpus</u>
- personal word lists / Personal word lists
- PersonChunker class / There's more...
- petabytes
 - about / Why learn NLP?
- phi_sq() function
 - about / <u>How it works...</u>
 - / There's more...
- phonemes
 - about / Speech recognition
- phrases
 - about / <u>Introduction</u>
- phrase structure parsing
 - about / Dependency parsing
- pickle corpus view
 - about / <u>Pickle corpus view</u>
- pickled chunker
 - saving / Saving a pickled chunker
- pickled tagger
 - trained tagger, loading with / Saving and loading a trained tagger with pickle
 - saving / <u>Saving a pickled tagger</u>
- pivot point
 - about / <u>How to do it...</u>
- PlaintextCorpusReader class
 - about / <u>How to do it...</u>
 - / <u>How it works...</u>
- plural nouns
 - singularizing / Singularizing plural nouns, How it works...
- pmi() function / <u>There's more...</u>
- Polyglotis
 - about / Developing a stemmer for non-English language
- Porter stemmer
 - about / <u>Stemming</u>
- PorterStemmer class
 - about / <u>How it works...</u>
- Porter stemming algorithm
 - about / <u>Stemming words</u>
- pos-tagged corpora
 - used, for developing chunker / <u>Developing a chunker using pos-tagged corpora</u>
- positive feature sets / <u>How it works...</u>
- POS tag
 - about / Part of speech (POS)
- pos tagged corpora
 - creating / <u>Creating POS-tagged corpora</u>
- pre-trained classifier

- using / Using a pre-trained classifier
- Precision / Evaluation of IR system
- precision
 - about / <u>The ChunkScore metrics</u>, <u>Measuring precision and recall of a classifier</u>, <u>How it</u> <u>works...</u>
- precision and recall, MaxentClassifier class
 - calculating / <u>There's more...</u>
- precision and recall, NaiveBayesClassifier class
 calculating / How to do it...
- precision recall() function
 - about / How to do it..., How it works...
- Prepositional Phrases (PP)
 - about / <u>CoNLL2000 corpus</u>
- PresuppositionDRS class
 - o find_bindings(drs_list, collect_event_data) method / <u>Anaphora resolution</u>
 - is_possible_binding(cond) method / <u>Anaphora resolution</u>
 - is_presupposition.cond(cond) method / <u>Anaphora resolution</u>
 - presupposition_readings(trail) method / <u>Anaphora resolution</u>
- probabilistic approach, parsing
 - about / The two approaches in parsing
- Probabilistic Context-free Grammar (PCFG)
 - creating, from CFG / Creating a probabilistic Context Free Grammar from CFG
- probabilistic context-free grammar (PCFG)
 - about / <u>Shallow versus deep parsing</u>
- probabilistic dependency parser
 - about / <u>Dependency parsing</u>
- probabilistic model
 - about / The probabilistic model
- projective dependency parser
 - about / <u>Dependency parsing</u>
- proper names
 - tagging / Tagging proper names, How it works...
- proper noun chunks
 - extracting / Extracting proper noun chunks, There's more...
- PunktSentenceTokenizer class / How it works..., There's more...
- PunktWordTokenizer
 - about / PunktWordTokenizer
- pure function
 - about / <u>How it works...</u>
- pure module
 - about / How it works...
- PyEnchant library
 - about / <u>Getting ready</u>
 - URL / <u>Getting ready</u>
- PyMongo documentation
 - URL / <u>Getting ready</u>
- PySpark

- about / PySpark
- reference link / <u>PySpark</u>
- example / <u>PySpark</u>
- Python
 - URL / Why learn NLP?, Let's start playing with Python!
 - using / Let's start playing with Python!
 - lists / Lists
 - help() function / <u>Helping yourself</u>
 - dir() function / <u>Helping yourself</u>
 - regular expression / <u>Regular expressions</u>
 - dictionaries / Dictionaries
 - reference link / Writing functions
 - streaming, for running NLTK on Hadoop / Python streaming
- Python, on Hadoop
 - using / Different ways of using Python on Hadoop
 - Python, streaming / Python streaming
 - Hive/Pig UDF / Hive/Pig UDF
 - wrappers, streaming / Streaming wrappers
 - reference link / Streaming wrappers
- Python subprocesses, distributed chunking / Python subprocesses
- PyYAML
 - URL, for downloading / YAML synonym replacement

Q

- Quadgram tagger
 - about / <u>Quadgram tagger</u>
- question answering (QA) systems
 - about / <u>Question answering systems</u>
- question answering system
 - about / <u>Question-answering system</u>
 - issues / <u>Question-answering system</u>
 - building / <u>Question-answering system</u>

R

- random forest
 - about / The Random forest algorithm
- rare word
 - removing / <u>Rare word removal</u>
- re() method
 - about / <u>The Scrapy shell</u>
- recall
 - about / <u>The ChunkScore metrics</u>, <u>Measuring precision and recall of a classifier</u>, <u>How it</u> <u>works...</u>
- Recall / Evaluation of IR system
- recursive descent parser
 - about / <u>A recursive descent parser</u>

- Redis
 - frequency distribution, storing / <u>Storing a frequency distribution in Redis</u>, <u>How to do</u> it..., <u>How it works...</u>, <u>There's more...</u>
 - URL / <u>Getting ready</u>
 - conditional frequency distribution, storing / <u>Storing a conditional frequency distribution</u> <u>in Redis, How to do it..., How it works...</u>
 - ordered dictionary, storing / <u>Storing an ordered dictionary in Redis</u>, <u>How to do it...</u>, <u>There's more...</u>, <u>See also</u>
 - distributed word scoring, used with / <u>Distributed word scoring with Redis and execnet</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>See also</u>
- redis-py homepage
 - URL / Getting ready
- Redis commands
 - URL / <u>How it works...</u>
- reference set
 - about / <u>How it works...</u>
- regex parser
 - about / <u>A regex parser</u>
- RegexpParser class / <u>How it works...</u>
 - about / <u>How it works...</u>
- RegexpReplacer class
 - about / <u>Replacement before tokenization</u>
 - / How to do it...
- RegexpStemmer class
 - about / <u>The RegexpStemmer class</u>
- RegexpTagger class / How to do it...
- RegexpTokenizer class / How it works...
- regex tagger
 - about / <u>Regex tagger</u>
- regression
 - about / Machine learning
- regular expression
 - about / <u>Regular expressions</u>
- Regular Expressions
 - using / <u>Tokenization using regular expressions</u>
- regular expressions
 - used, for tokenizing sentences / <u>Tokenizing sentences using regular expressions</u>, <u>There's</u> <u>more...</u>
 - words, tagging with / Tagging with regular expressions, How it works...
 - used, for defining chunk patterns / <u>Chunking and chinking with regular expressions</u>, <u>How to do it...</u>, <u>How it works...</u>, <u>There's more...</u>
 - used, for merging chunks / <u>Merging and splitting chunks with regular expressions</u>, <u>How</u> to do it..., <u>How it works...</u>
 - used, for splitting chunks / <u>How to do it...</u>, <u>How it works...</u>
 - used, for expanding chunks / <u>Expanding and removing chunks with regular expressions</u>, <u>How it works..., There's more...</u>

- used, for removing chunks / <u>Expanding and removing chunks with regular expressions</u>, <u>How it works...</u>, <u>There's more...</u>
- used, for partial parsing / Partial parsing with regular expressions, How it works...
- reinforcement learning
 - about / <u>Machine learning</u>
- relative link / There's more...
- remote gateway
 - versus local gateway / <u>Local versus remote gateways</u>
- remove_line() function / <u>How to do it...</u>, <u>How it works...</u>
- repeating characters
 - removing / Removing repeating characters, How it works..., There's more...
- RepeatReplacer class
 - about / <u>How it works...</u>
- replace() method / How to do it..., How it works..., How it works...
- replacement technique
 - before tokenization / Replacement before tokenization
- replace_negations() method / <u>How it works...</u>
- Resnik Score / <u>Disambiguating senses using Wordnet</u>
- reuters_high_info_words() function / <u>How it works...</u>
- reuters_train_test_feats() function / <u>How it works...</u>
- rule-based approach, parsing
 - about / The two approaches in parsing
- rule-based extraction
 - about / Information extraction

S

- sampling
 - about / <u>Sampling</u>
 - reference link / <u>Sampling</u>
 - example / <u>Sampling</u>
 - Naive Bayes / <u>Naive Bayes</u>
 - decision trees / Decision trees
 - stochastic gradient descent (SGD) / Stochastic gradient descent
 - logistic regression / Logistic regression
 - support vector machines (SVM) / Support vector machines
- scatter plot
 - about / <u>A scatter plot</u>
- scikit-learn
 - URL, for scikit classes / <u>Naive Bayes</u>
 - on Hadoop / <u>Scikit-learn on Hadoop</u>
 - about / <u>Training scikit-learn classifiers</u>
- scikit-learn classifiers
 - training / Training scikit-learn classifiers, Getting ready, How it works...
- scikit-learn model / There's more...
- SciPy
 - about / <u>SciPy</u>
 - linear algebra / Linear algebra

- eigenvalues / eigenvalues and eigenvectors
- eigenvectors / eigenvalues and eigenvectors
- sparse matrix / The sparse matrix
- optimization / <u>Optimization</u>
- URL / <u>External references</u>
- score_ngrams(score_fn) function / <u>Scoring ngrams</u>
- score_words() function
 - about / <u>How it works...</u>
- Scrapy
 - installing / <u>Writing your first crawler</u>
 - URL / <u>Writing your first crawler</u>
 - data flow / Data flow in Scrapy
 - external references / External references
- Scrapy shell
 - about / The Scrapy shell
 - using / The Scrapy shell
- Script Applier Mechanism(SAM)
 - about / Introducing semantic analysis
- semantic analysis
 - about / Introducing semantic analysis
 - Named Entity Recognition (NER) / Introducing NER
 - NER System, using Hidden Markov Model / <u>A NER system using Hidden Markov</u> <u>Model</u>
 - NER, training with Machine Learning toolkits / <u>Training NER using Machine Learning</u> <u>Toolkits</u>
 - NER, using POS tagging / <u>NER using POS tagging</u>
- semi-supervised learning
 - about / Machine learning
- sense disambiguation
 - URL, for details / Introduction
- senses
 - disambiguating, Wordnet used / <u>Disambiguating senses using Wordnet</u>
- sentence
 - insignificant words, filtering from / Getting ready, How to do it...
- Sentence level Construction, CFG
 - declarative structure / Extracting Context Free Grammar (CFG) rules from Treebank
 - imperative structure / Extracting Context Free Grammar (CFG) rules from Treebank
 - Yes-No structure / Extracting Context Free Grammar (CFG) rules from Treebank
 - Wh-question structure / Extracting Context Free Grammar (CFG) rules from Treebank
- sentences
 - text, tokenizing into / Getting ready, How to do it ...
 - tokenizing, in other languages / Tokenizing sentences in other languages
 - tokenizing, into words / Tokenizing sentences into words, There's more
 - tokenizing, regular expressions used / <u>Tokenizing sentences using regular expressions</u>, <u>There's more...</u>
 - tagging / <u>Tagging sentences</u>
- sentences, tokenizing into words

- contractions, separating / Separating contractions
- PunktWordTokenizer / <u>PunktWordTokenizer</u>
- WordPunctTokenizer / <u>WordPunctTokenizer</u>
- sentence splitter
 - about / <u>Sentence splitter</u>
- sentence tokenizer
 - training / Training a sentence tokenizer, How to do it..., How it works...
 - customizing / Customizing the sentence tokenizer
- sentiment analysis
 - about / Introducing sentiment analysis
 - text sentiment analysis / Introducing sentiment analysis
 - topic-sentiment analysis / Introducing sentiment analysis
 - NER, used / <u>Sentiment analysis using NER</u>
 - machine learning, used / Sentiment analysis using machine learning
 - NER system, evaluation / Evaluation of the NER system
- sent_tokenize function / <u>How it works...</u>
- SequentialBackoffTagger class / How it works..., How to do it..., How to do it...
- sequential taggers
 - about / <u>Sequential tagger</u>
 - N-grams tagger / <u>N-gram tagger</u>
 - regex tagger / <u>Regex tagger</u>
- shallow parsing
 - versus deep parsing / <u>Shallow versus deep parsing</u>
- shallow tree
 - creating / <u>Creating a shallow tree</u>, <u>How to do it...</u>
- shallow_tree() function / <u>How to do it..., How it works...</u>
- shift-reduce parser
 - about / <u>A shift-reduce parser</u>
- show_most_informative_features() method
 - about / Most informative features
- significant bigrams
 - including / <u>Including significant bigrams</u>
- significant words
 - about / Filtering insignificant words from a sentence
- similarity measures
 - about / <u>Similarity measures</u>
 - applying, Edit Distance Algorithm used / <u>Applying similarity measures using Ethe edit</u> <u>distance algorithm</u>
 - string similarity metrics / Other string similarity metrics
- singularize_plural_noun() function / <u>How to do it...</u>
- singular value decomposition (SVD)
 - about / eigenvalues and eigenvectors
- Singular Value Decomposition (SVD)
 - about / Developing an IR system using latent semantic indexing
- Sitemap spider
 - about / <u>The Sitemap spider</u>
- SklearnClassifier class

- using / <u>Getting ready</u>
- training / <u>How to do it...</u>
- working / <u>How it works...</u>
- evaluating, with high information words / <u>The SklearnClassifier class with high</u> <u>information words</u>
- smoothing
 - about / Applying smoothing on the MLE model
 - applying, on MLE model / <u>Applying smoothing on the MLE model</u>
- SnowballStemmer class
 - about / <u>The SnowballStemmer class</u>
- Snowball stemmers
 - about / <u>Stemming</u>
- SPANEW (Spanish ANEW) / Introducing sentiment analysis
- sparse matrix
 - about / <u>The sparse matrix</u>
 - DOK (Dictionary of keys) / The sparse matrix
 - LOL (list of list) / <u>The sparse matrix</u>
 - COL (Coordinate list) / The sparse matrix
 - CRS/CSR (Compressed row Storage) / The sparse matrix
 - URL / <u>The sparse matrix</u>
 - CSC (sparse column) / The sparse matrix
- specific preprocessing
 - about / <u>What is text wrangling?</u>
- speech recognition
 - about / Speech recognition
- spell correction
 - with spellchecker / Spell correction
- spelling issues
 - correcting, with Enchant / Getting ready, How it works...
- SpellingReplacer class

• about / <u>How it works...</u>

- / Personal word lists
- SplitRule class
 - about / <u>How to do it...</u>
- split_label_feats() function / <u>How to do it...</u>, <u>How it works...</u>
- squared Pearson correlation coefficient
 - reference link / <u>How it works...</u>
- Stanford parser
 - URL / Dependency parsing
- Stanford tagger
 - about / <u>Stanford tagger</u>
- Stanford tools
 - about / <u>Stanford tagger</u>
 - reference link / <u>Stanford tagger</u>
- statistical machine translation (SMT)
 - about / Statistical machine translation
- statistical modeling

- with n-gram approach / Statistical modeling involving the n-gram approach
- stem() method / <u>How to do it...</u>
- stemmer
 - about / <u>Understanding stemmer</u>
 - developing, for nonenglish language / Developing a stemmer for non-English language
- Stemmer I interface
 - inheritance diagram / <u>Understanding stemmer</u>
- stemming
 - about / What is text wrangling?, Stemming, Stemming words
 - reference link / <u>Stemming</u>
 - versus lemmatization / There's more...
 - combining, with lemmatization / Combining stemming with lemmatization
- Stochastic Finite State Automaton (SFSA)
 - about / A NER system using Hidden Markov Model
- stochastic gradient descent (SGD)
 - about / Stochastic gradient descent
- stop word removal
 - about / What is text wrangling?, Stop word removal
 - implementing / <u>Stop word removal</u>
- stopwords
 - about / Filtering stopwords in a tokenized sentence
 - filtering, in tokenized sentence / Filtering stopwords in a tokenized sentence
 - filtering / <u>Filtering stopwords</u>
- stopwords corpus / <u>How it works..., See also</u>
 - about / There's more...
- StreamBackedCorpusView class / Creating a custom corpus view
- string functions
 - split / <u>Helping yourself</u>
 - strip / <u>Helping yourself</u>
 - upper/lower / <u>Helping yourself</u>
 - replace / <u>Helping yourself</u>
 - reference link / <u>Helping yourself</u>
- subplot
 - about / Subplot
- subtrees
 - about / Creating a chunked phrase corpus
- sub_leaves() method / <u>See also</u>
- summarization
 - about / <u>Building your first NLP application</u>
- supervised classification
 - about / Selecting a machine learning algorithm
- supervised learning
 - about / Machine learning
 - classification / <u>Machine learning</u>
 - regression / <u>Machine learning</u>
- Support Vector Machines (SVM)
 - about / Training with LinearSVC

- URL / Training with LinearSVC
- support vector machines (SVM)
 - about / <u>Support vector machines</u>
- support_cutoff value
 - about / <u>Controlling decisions with support_cutoff</u>
- swap_infinitive_phrase() function / <u>How to do it...</u>
- swap_noun_cardinal() function / <u>How to do it...</u>
- swap_verb_phrase() function / How to do it..., There's more..., How it works...
- synonyms
 - looking up for / <u>How to do it..., How it works...</u>
 - about / <u>All possible synonyms</u>
 - words, replacing with / <u>Replacing synonyms</u>, <u>How it works...</u>
- Synset
 - about / Looking up Synsets for a word in WordNet, Calculating WordNet Synset similarity
 - looking up / Looking up Synsets for a word in WordNet, How it works...
- synset id
 - generation, from Wordnet / Generation of the synset id from Wordnet
- syntactic matching
 - about / Metrics based on syntactic matching
- syntactic parser
 - about / Why we need parsing
- syntactic transfer
 - about / Machine translation

Т

- tag
- about / Introduction
- tag() method / <u>How to do it...</u>
- tagged corpus
 - tagger, analyzing against / <u>Analyzing a tagger against a tagged corpus</u>
 - analyzing / <u>Analyzing a tagged corpus</u>
- TaggedCorpusReader class / <u>How to do it...</u>, <u>How it works...</u>, <u>Creating a custom corpus view</u>
- tagged sentence
 - untagging / <u>Untagging a tagged sentence</u>
- tagger
 - accuracy, evaluating of / Evaluating accuracy
 - training, with NLTK-Trainer / <u>Training a tagger with NLTK-Trainer</u>, <u>How to do it...</u>, <u>How it works...</u>
 - training, with universal tags / Training with universal tags
 - analyzing, against tagged corpus / <u>Analyzing a tagger against a tagged corpus</u>
- tagger-based chunker
 - training / Training a tagger-based chunker, How to do it..., How it works...
- taggers
 - combining, with backoff tagging / <u>Combining taggers with backoff tagging</u>, <u>How it</u> <u>works...</u>
- tagging

- WordNet, using for / Using WordNet for tagging, How to do it..., How it works...
- tags
- converting, to universal tagset / Converting tags to a universal tagset
- tags, for treebank corpus
 - URL / <u>There's more...</u>
- tag separator
 - customizing / <u>Customizing the tag separator</u>
- tagset
 - about / Converting tags to a universal tagset
- tag suffixes
 - passing / <u>There's more...</u>
- tag_equals() function / <u>How to do it...</u>
- tag_pattern2re_pattern() function
 - about / Getting ready
- tag_sents() method / <u>Tagging sentences</u>
- tag_startswith() function / <u>How to do it...</u>, <u>How to do it...</u>
- term-document matrix
 - about / <u>Sampling</u>
- term doc matrix (TDM)
 - about / <u>Text classification</u>
- term frequencies (tf)
 - about / <u>Sampling</u>
- term frequency (TF)
 - about / <u>Vector space model</u>
- term frequency-inverse document frequency (tf-idf)
 - about / Building your first NLP application, Sampling
- test set
 - about / <u>How it works...</u>
- text
- tokenizing, into sentences / How to do it...
- chunk tree, converting to / Converting a chunk tree to text, How it works...
- text-processing
 - reference link / <u>Tokenization</u>
- text classification
 - about / Text classification, Text classification, Introduction
- text cleansing
 - about / What is text wrangling?, Text cleansing
- text clustering
 - about / <u>Text clustering</u>
 - K-means clustering / <u>Text clustering</u>, <u>K-means</u>
 - hierarchical clustering / <u>Text clustering</u>
- text feature extraction
 - about / Bag of words feature extraction
 - working / <u>How it works...</u>
- text indexing
 - URL, for details / <u>Replacing synonyms</u>
- text sentiment analysis / Introducing sentiment analysis

- text summarization
 - about / <u>Text summarization</u>
- text wrangling
 - about / <u>What is text wrangling?</u>
- TF-IDF (Term Frequency-Inverse Document Frequency) / <u>Information retrieval using a vector</u> <u>space model</u>
- TF-IDF corpus
 - about / Installing gensim
- times
 - parsing, with dateutil / Parsing dates and times with dateutil, How it works...
- timezone
 - obtaining / <u>Timezone lookup and conversion</u>, <u>How to do it...</u>, <u>How it works...</u>
 - converting / Timezone lookup and conversion, How to do it..., How it works...
 - local timezone, searching / <u>Local timezone</u>
 - custom offset, creating / <u>Custom offsets</u>
- TnT (Trigrams n Tags)
 - about / Statistical modeling involving the n-gram approach
- TnT tagger
 - about / <u>Training the TnT tagger</u>
 - training / <u>How to do it..., How it works...</u>
 - optional keyword arguments / There's more...
 - beam search, controlling / Controlling the beam search
 - capitalization, significance / Significance of capitalization
- token
 - about / Tokenizing text into sentences
- tokenization
 - about / <u>What is text wrangling?</u>, <u>Tokenization</u>, <u>Introduction</u>, <u>Tokenizing text into</u> <u>sentences</u>, <u>Tokenization</u>
 - text, into sentences / Tokenization of text into sentences
 - text, in other languages / Tokenization of text in other languages
 - sentences, into words / Tokenization of sentences into words
 - TreebankWordTokenizer, using / <u>Tokenization using TreebankWordTokenizer</u>
 - Regular Expressions, using / <u>Tokenization using regular expressions</u>
- tokenized sentence
 - stopwords, filtering in / Filtering stopwords in a tokenized sentence
- tokens, replacement
 - words, replacing with regular expressions / <u>Replacing words using regular expressions</u>
 - text, replacing with another text / Example of the replacement of a text with another text
 - substitution, performing before tokenization / <u>Performing substitution before</u> tokenization
 - $\circ~$ repeating characters, dealing with / $\underline{Dealing~with~repeating~characters}$
 - repeating characters, deleting / <u>Example of deleting repeating characters</u>
 - word, replacing with synonym / <u>Replacing a word with its synonym</u>, <u>Example of</u> <u>substituting word a with its synonym</u>
- topic-sentiment analysis / Introducing sentiment analysis
- topic modeling
 - about / Topic modeling, Topic modeling in text

- gensim, installing / Installing gensim
- train() class method
 - about / <u>How it works...</u>
- trained tagger
 - saving / Saving and loading a trained tagger with pickle
 - loading, with pickle / Saving and loading a trained tagger with pickle
- train_binary_classifiers() function / <u>How it works...</u>
- train_chunker.py script / There's more...
- train_classifier.py script
 - about / How it works..., There's more...
- transform_chunk() function / How to do it..., How it works...
- traverse() function
 - flow diagram / <u>Anaphora resolution</u>
- Treebank chunk corpus / <u>Treebank chunk corpus</u>
- Treebank construction
 - about / Treebank construction
- TreebankWordTokenizer
 - using / Tokenization using TreebankWordTokenizer
- TreebankWordTokenizer class / <u>Separating contractions</u>
- treebank_chunk corpus
 - using / <u>How to do it...</u>
- tree labels
 - converting / Converting tree labels, Getting ready, How to do it ...
- tree leaves
 - about / <u>Tree leaves</u>
- tree transforms
 - about / <u>Introduction</u>
- TrigramTagger class / Training and combining ngram taggers
- true negative
 - about / Measuring precision and recall of a classifier
- True Negative (TN) / Metrics for error identification
- true positive
 - about / Measuring precision and recall of a classifier
- True Positive(TP) / Metrics for error identification
- tuple
 - about / What is Part of speech tagging
- Tweepy
 - installing / <u>Twitter</u>
 - URL / <u>Twitter</u>
- Twitter
 - about / <u>Twitter</u>
 - \circ data, gathering / <u>Twitter</u>
 - trending topics, searching / <u>Trending topics</u>
 - influencers, detecting / Influencers detection
- Twitter libraries
 - URL / <u>Twitter</u>

- U
- Udacity
 - URL / <u>Web crawlers</u>
- unambiguous antonyms / There's more...
- UnChunkRule pattern / How to do it...
- UnicodeDammit
 - about / Introduction, UnicodeDammit conversion
- unigram
 - about / <u>Training a unigram part-of-speech tagger</u>
- unigram part-of-speech tagger
 - training / How to do it..., How it works...
- UnigramTagger
 - about / <u>How to do it...</u>
- UnigramTagger class
 - model, constructing for / There's more...
- universal tags
 - tagger, training with / Training with universal tags
- universal tagset
 - tags, converting to / Converting tags to a universal tagset
 - about / Converting tags to a universal tagset
- unlabeled feature set
 - about / <u>Introduction</u>
- unsupervised classification
 - about / Selecting a machine learning algorithm
- unsupervised learning
 - about / Machine learning
- URLs
 - extracting, from HTML with lxml / <u>Extracting URLs from HTML with lxml</u>, <u>How it</u> works...
 - extracting, directly / Extracting links directly
 - HTML, parsing from / Parsing HTML from URLs or files
 - extracting, with xpath() method / Extracting links with XPaths
 - extracting, BeautifulSoup used / Extracting URLs with BeautifulSoup
- user defined function (UDF)
 - about / <u>Hive/Pig UDF</u>

\mathbf{V}

- values() method / <u>How it works...</u>, <u>How it works...</u>
- vector space model / Information retrieval using a vector space model
- vector space model (VSM)
 - about / <u>Vector space model</u>
- vector space scoring
 - about / Vector space scoring and query operator interaction
 - and query operator interaction / Vector space scoring and query operator interaction
- vector space search engine
 - constructing / <u>Search engine</u>

- verb forms
 - correcting / <u>Getting ready</u>, <u>How to do it...</u>, <u>How it works...</u>
- verb phrase (VP)
 - about / <u>Chunking</u>
- verb phrases
 - swapping / <u>How to do it...</u>, <u>How it works...</u>
- Verb Phrases (VP)
 - about / <u>CoNLL2000 corpus</u>

W

- web crawler
 - about / <u>Web crawlers</u>
 - writing / Writing your first crawler
- Well-formed Formulas (WFF)
 - about / Introducing semantic analysis
- Whissell's Dictionary of Affect in Language (WDAL) / Introducing sentiment analysis
- whitespace tokenizer / <u>Simple whitespace tokenizer</u>
- Witten Bell Estimation
 - about / Witten Bell estimation
- word collocations
 - discovering / Discovering word collocations, How to do it ...
- word collocations, discovering
 - functions, scoring / <u>Scoring functions</u>
 - ngrams, scoring / <u>Scoring ngrams</u>
- word frequency
 - about / <u>Understanding word frequency</u>
 - maximum likelihood estimation, developing for text / Develop MLE for a given text
 - Hidden Markov Model Estimation / <u>Hidden Markov Model estimation</u>
 - Hidden Markov Model Estimation, using / Hidden Markov Model estimation
- wordlist corpus
 - creating / Getting ready, How it works...
- WordListCorpusReader class / Creating a wordlist corpus, How to do it ...
- Wordnet
 - about / Generation of the synset id from Wordnet
 - synset id, generating from / Generation of the synset id from Wordnet
 - used, for disambiguating senses / Disambiguating senses using Wordnet
- WordNet
 - about / Introduction, Looking up Synsets for a word in WordNet
 - use cases / Introduction
 - looking up for Synset / Looking up Synsets for a word in WordNet, How it works...
 - looking up for lemmas / <u>How to do it..., There's more...</u>
 - looking up for synonyms / How to do it..., How it works...
 - words, lemmatizing with / <u>Getting ready</u>, <u>How it works...</u>
 - using, for tagging / Using WordNet for tagging, How to do it..., How it works...
- WordNetLemmatizer class
 - used, for finding lemmas / How to do it...
 - about / <u>How it works...</u>

- WordNet Synset similarity
 - calculating / <u>How to do it...</u>, <u>How it works...</u>
 - verbs, comparing / <u>Comparing verbs</u>
 - Path and Leacock Chordorow (LCH) similarity / <u>Path and Leacock Chordorow (LCH)</u> <u>similarity</u>
- WordNetTagger class / How it works...
- WordPunctTokenizer
 - about / <u>WordPunctTokenizer</u>
- WordReplacer class / <u>How it works...</u>
- words
 - sentences, tokenizing into / Tokenizing sentences into words, There's more...
 - stemming / Stemming words, How to do it ...
 - lemmatizing, with WordNet / Getting ready, How it works...
 - replacing, with synonyms / <u>Replacing synonyms</u>, <u>How it works...</u>
 - tagging, with regular expressions / Tagging with regular expressions, How it works...
- word sense disambiguation (WSD)
 - about / Word sense disambiguation
- Word Sense Disambiguation (WSD) task / Disambiguating senses using Wordnet
- words matching regular expressions
 - replacing / <u>Replacing words matching regular expressions</u>, <u>How to do it...</u>, <u>How it</u> <u>works...</u>
- word tokenizer
 - customizing / Customizing the word tokenizer
- word_tag_model() function / <u>How it works...</u>
- word_tokenize() function / <u>How to do it..., How it works...</u>
- World Wide Web (WWW)
 - about / <u>Web crawlers</u>
- wrappers
 - streaming / <u>Streaming wrappers</u>
- Wu-Palmer Similarity
 - about / <u>How it works...</u>
 - / Disambiguating senses using Wordnet
- wup_similarity method / <u>How it works...</u>

X

- XPath
 - about / The Scrapy shell
- xpath() method
 - about / The Scrapy shell
 - used, for extracting URLs / Extracting links with XPaths
 - reference link / Extracting links with XPaths

Y

- YAML file
 - loading / Loading a YAML file
- YAML synonym replacement

• about / <u>YAML synonym replacement</u>

- Z
- zadd command / <u>How it works...</u>
- zcard command / <u>How it works...</u>
- Zipf's law
 - applying on text / <u>Applying Zipf's law to text</u>
- zrem command / <u>How it works...</u>
- zrevrange command / <u>How it works...</u>
- zscore command / <u>How it works...</u>
- Zset
 - about / <u>How to do it...</u>